

JONIESIAY® PROFESSIONAL TOOL SERIES

CATALOGUE 2017/18 EDITION 6

NEN

an

LUKOIL



JONNESWAY[®] with over 34 years of experience in the field of hand tools, air tools, automotive and repair tools has again advanced to the next level of excellence. Our products not only meet strict quality requirements by professional markets, but also received patents on many new advanced designs. We have established strong distribution networks around the world.

Currently there are more than 4000 JONNESWAY® dealers in 102 countries, including U.S.A., Russia & C.I.S., Poland, Portugal, South, Africa Norway, Demark, Sweden, Finland, Middle East, Asia...etc. Jonnesway has five advantages to achieve ultimate goal as:

COMPLETE RANGE OF JONNESWAY PROFESSIONAL TOOLS

- 1. Jonnesway Professional Hand Tools
- 2. Jonnesway Professional Pneumatic Tools
- 3. Jonnesway Professional Spray Gun and Sander Series
- 4. Jonnesway Professional Automotive Repair and Garage Equipment
- 5. Jonnesway Professional Tool Trolleys with Mechanic Tool Sets

PROMISED HIGH QUALITY

All of Jonnesway tools meet the international standard, many even exceeds the Germany DIN and American ANSI

PROVIDE EXPERIENCED SUPPORT AND TECHNICAL SERVICES

Jonnesway provides support with experience and technical know-how to facilitate our distributors to establish loyal customers and to attract new customers by providing excellent after-market service.

GUARANTEED HIGH-QUALITY AND SUPERB INNOVATION

With higher quality and greater function, Jonnesway R&D aims to achieve industrial safety, environmental friendly and user friendly design, to ensure our distributors' leading position in the market, as well as to stimulate new demands and increase turnover.

OFFER COMPETITIVE PRICE

Jonnesway offers the same or even better qualities as compared to other internationally famous brands, but at a ompetitive price in order to create more profits for our distributors.















Kami selaku Jaguar - Land Rover Authorized Workshop PT. Wahana Auto Ekamarga menerangkan bahwa terhitung dari tahun 2006 telah menggunakan General Tools, Pneumatic Tools, Repair Tools dan Automotive Tools merek "JONNESWAY" yaitu untuk Technical Training maupun di Workshop Jaguar - Land Rover.

Untuk seluruh Jaguar - Land Rover Authorized Workshop kami juga merekomendasikan untuk menggunakan produk "JONNESWAY" sebagai Supporting Tools utama workshop.

Pilihan kami menggunakan produk "JONNESWAY" dikarenakan kualitas yang baik, harga yang kompetitif, serta didukung dengan long life warranty dan layanan purna jual yang memuaskan.

hingga saat ini.

Demikian surat keterangan ini kami buat untuk dapat digunakan sebagaimana mestinya.

Jakarta, September 2015

Hormat Kami,

Harivante **GM** Aftersales

Recommendation JONNESWAY received the Recommendation Letter from JAGUAR Indonesia in 2015

JONNESVAY

SURAT KETERANGAN No: 20/ASS/WAE/SK/IX/2015

Berkat dukungan pelayanan purna jual dari PT. Prima Teknik Mandiri selaku Distributor Tunggal produk tools merek "JONNESWAY" yang kami gunakan masih berfungsi dengan baik





Citroën S.A. Technical Training Department 47 New Market Drive Northriding Johannesburg South Africa 011 462 4200

03 June 2008

Herewith I would like to confirm that Citroën S.A. has been utilizing the Jonnesway products for the past 3 years in our Training Centre. We are more than satisfied with the quality of tools and the outstanding back up service we have received to date.

We recommend them as our tool supplier of choice.

Should you require any further information please do not hesitate to contact me?

Mas

Kind Regards Steven Terblans Technical Training Manager

Peugeot Motors South Africa PO Box 389 Kelvin 2054

To whom this may concern.

Re : Jonnesway Tools supplied by Gondolier



Up to now we have always received exceptional service from both Jonnesway and Gondolier and we are totally satisfied with the quality of Jonnesway tools. It is only a pleasure to recommend both Jonnesway and Gondolier as a preferred supplier of tools.

For an on behalf of PMSA Training Centre,

Hereby I would like to confirm that Peugeot Motors South Africa has been utilizing Jonnesway Tools for the passed 2 years in both our Technical Training Centre and Peugeot Assist Vehicles.

/--

Jaco Mare Training Centre Manager

Recommendation JONNESWAY received the Recommendation Letter from PEUGEOT South Africa in 2008



20 June 2008







SUZUKI SOUTH AFRICA (PTY) LTD

Co. Reg. number 1998/14138/07 PO. Box 823 Isando 1600 South Africa

> June 302008 Ref: 2271/08/JM

JONNESWAY TOOLS

To Whom It May Concern:

Suzuki South Africa is proud to have Jonnesway Tools as our supplier of professional hand tools for use in our Technical Training centre and Workshops.

This has been an ideal opportunity for Suzuki South Africa to be associated with a leading brand like Jonnesway, who's product range and quality are second to none.

Jonnesway Tools are also sponsors and suppliers to the Brad Anassis - Suzuki National Road Racing and Drag Racing Teams.

Yours truly,

Errol Quan Cha **Technical Manager**

Directors: D VAN VUUREN DX MOORKENS* (Managing) (Belgium)*



SURAT KETERANGAN No: RMK-SRV/Ext/I/2016/001

Bersama ini kami selaku Suzuki Authorized Dealer PT. Restu Mahkota Karya - Group menerangkan bahwa terhitung sejak tahun 2013 telah menggunakan General Tools, Repair Automotive Tools merek "JONNESWAY" sebagai Supporting Tools di Workshop kami.

Kami memilih menggunakan Tools produk "JONNESWAY" karena kwalitasnya baik, harga kompetitif dan dukungan purna jual yang terjamin serta ada jaminan long life

warranty dan pengajuan claimnya mudah.

Berkat dukungan pelayanan yang baik dari PT. Prima Teknik Mandiri selaku Distributor Tunggal produk tools merek "JONNESWAY" operasional di workshop kami tidak mengalami kendala hingga saat ini.

Demikian surat keterangan ini kami buat untuk dapat digunakan sebagaimana mestinya.

Jakarta, 14 Januari 2016 Hormat kami

RESTU MANKOTA KARYA **Budiono P** GM After Sales

We, PT. Restu Mahkota Karya - Group, as Suzuki Authorized Dealer, would hereby like to state that as of year 2013, we have been using General Tools, Repair Tools and Automotive Tools "JONNESWAY" Brand as a Supporting Tools for our Workshop.

The reason we choose "JONNESWAY" is because its Good Quality, Competitive Pricing and also backed with Long Life Warranty, satisfactory After Sales service, and easy procedure for claim.

Because of the After Sales service provided by PT Prima Teknik Mandiri, as the Sole Distributor for "JONNESWAY" in Indonesia, the tools we have been using are still functional and are in good condition until now. With this leter, we hope that is has been used for as it is intended for.

Jakarta, January 14th, 2016 Best Regards.

Budiono P

GM After Sales

Head Office 🕴 JL. Panjang No. 12 Kebon Jeruk, Jakarta Barat Telp : (021) 533 2020 (Hunting) Fax : (021) 533 2142, 533 2143 Email : operational@rmk.co.id

Head Office : JL Panjang No. 12 Kebon Jeruk, Jakarta Barat Telp : (021) 533 2020 (Hunting) Fax : (021) 533 2142, 534 2142, 533 2142, 534 2142, 533 2142, 534 2142, 544 2142, 544 2142, 544 2142, 544 2142, 544 2142, 544 2142, 544 2142, 544 2142, 544 2142, 544 2142, 544 2142, 544 2142, 544 2142, 544 2142, 544 2142, 544 2142, 544 2142, 544 2144, 544

Recommendation JONNESWAY received the Recommendation Letter from Indonesia in 2016









Certificate ISO 9001: 2008 Certificate

SG

Verification Report No. : RA/2015/30009C : JAI-1108, JAI-1056 Representative Model Series Model(s) Product Name Air Impact Wrench Address of Applicant JONNESWAY-20150301-V1 TCF Number June 19, 2015 Date of Issue Date of Expiry Applicable Standard(s) Conclusion

Machinery Directive 2006/42/EC

Applicant

with the technical data detailed above.

Authorized Signatory:

SGS TAIWAN LTD. Jason Lin **Technical Manager**

This document is issued by the Company subject to its General Conditions of Service printed over and, for electronic foremat documents, subject to Terms and Conditions for Electronic Documents at the lemitation of Isability, indemnification and jurisdiction issues defined therein. Any holder of the document, of its intervention only and writen the limits of Clienty's astroctions, if any. The Company's sole reg- servicesing all their rights and collipations under the transaction documents. This document carries to alteration, forgency or Balanciation of the content or appearance of this document is unlawful and offs alteration, forgency or shall cation of the sample(s) tabled.

Certificate **CE** Certificate

JONNESWAY.





VDE Prüf- und Zertifizierungsinstitut

ZEICHENGENEHMIGUNG MARKS APPROVAL

Jonnesway Enterprise Co. Ltd. 6F-9, No.51, Sec.2, Keelung Rd. 110 TAIPEI TAIWAN

ist berechtigt, für ihr Produkt / is authorized to use for their product

Zange, isoliert Pliers, insulated

die hier abgebildeten markenrechtlich geschützten Zeichen für die ab Blatt 2 aufgeführten Typen zu benutzen / the legally protected Marks as shown below for the types referred to on page 2 ff.



Geprüft und zertifiziert nach / Tested and certified according to

DIN EN 60900 (VDE 0682-201):2013-04; EN 60900:2012

Das Produkt entspricht den Anforderungen des deutschen Produktsicherheitsgesetzes (ProdSG) hinsichtlich der Gewährleistung von Sicherheit und Gesundheit. The product covers the requirements of the German Act "Produktsicherheitsgesetz (ProdSG)* regarding the ensurance of safety and health.

Befristet zum / valid until: 2019-04-30

VDE Prüf- und Zertifizierungsinstitut GmbH VDE Testing and Certification Institute Zertifizierungsstelle / Certification

VDE Zertifikate sind nur gültig bei Veröffentlichung unter VDE certificates are valid only when published on

Ausweis-Nr. 40040800 Biatt 1 Certificate No. Page

Aktenzeichen: 5010169-3940-0011 / 199851

http://www.vde.com/zert/fikat http://www.vde.com/certificate

Offenbach, 2014-09-26 (letzte Änderung / updated 2014-12-05)

DE

File ref .:

Certificate **VDE** Certificate

HAND TOOLS SERIES

- Chrome Vanadium Steel
- Anti-Slip Grip Patent-Design
- Standard & Stubby Types



Professional Quality ANSI / DIN Standard

JONNESWAY.

CONTENTS	PAGES
TOOL TROLLEY & MECHANIC TOOLS SET	1 - 34
TORQUE WRENCH & RATCHET HANDLE	35 - 41
WRENCH SERIES	42 - 58
SUPER TECH SERIES	59 - 64
SOCKETS SERIES	65 - 95
PLIERS SERIES	96 - 110
SCREWDRIVER SERIES	111 - 118
ΗΕΧ ΚΕΥ	119 - 124
HAMMER, CHISEL & PUNCH	125 - 127
CALIPER	128 - 129
MEASURING TAPE & HACKSAW	130
AIR IMPACT WRENCH SERIES	132 - 140
AIR RATCHET, DRILL & SCREWDRIVER SERIES	141 - 146
AIR DIE GRINDER SERIES	147 - 152
AIR SANDER SERIES	153 - 157
AIR SAW & HYDRAULIC RIVETER	158 - 159
AIR BLOW GUN, AIR GREASE GUN & AIR CONTROL UNIT	160 - 161
AUTO AIR HOSE WINDER	162
AIR TOOL ACCESSORIES	163 - 164
SPRAY GUN SERIES	165 - 168
AUTOMOTIVE TOOLS	169 - 214
MERCEDES BENZ REPAIR TOOLS	215 - 222
BMW REPAIR TOOLS	223 - 230
VOLKSWAGEN & AUDI REPAIR TOOLS	231 - 235
VOLVO REPAIR TOOLS	236 - 237
TRUCK SERVICE TOOLS	238 - 239



TOOL TROLLEY & MECHANIC TOOLS SET

- Heavy Duty Work Table With Anti-Vibration Top.

- 5" x 2" Caster Loading Over 200 lbs Apiece.
- Various Mechanic Tools Sets Design to Satisfy Your Market Demand.



• Specially-Design Side Handle For Holding Tools, Beverages, Fasteners And More. • Long-Life Drawers With Ball Bearing Slides & A Weight Capacity Of 50 KGS Each.

JONNESWAY

MECHANIC TOOLS SET FOR EUROPEAN CARS (RECOMMENDED FOR PORSCHE, AUDI & VOLKSWAGEN)

C-8DW389V

First Drawer

389PCS PROFESSIONAL MECHANIC

TOOL SET W/8-DRAWER TOOL TROLLEY

BALL BEARING SLIDES



- Steel thickness: Cabinet-1.0mm drawer, 1.0mm body, 1.2mm top and bottom covers.
- Ball bearing designed for smooth slicling.
- Safe designed Aluminum end to prevent scratches.
- Internal locking system for extra security.
- One piece steel of Cabinet Body to add more strength.
- 5"x2" Casters

TOOL TROLLEY & MECHANIC TOOLS SET

2

• 200 Lbs loading capacity for each caster



Tray : EVA Form

Easy to organize for more efficient management

Provide complete protection for tools



S04H3	145SV 145PCS 1/4" & 3/8" SOCKET & TORQUE WRENCH SET		
Contents			
S04H2	10PCS-1/4"DR. 6PT SOCKETS: 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13MM		
S04HD2	10PCS-1/4"DR. 6PT DEEP SOCKETS: 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13MM		
R3702	1PC-1/4"DR. RATCHET HANDLE 48 TEETH		
S24H2	2PCS-1/4"DR. EXTENSION BAR		
S15H240	1PC-1/4"DR. UNIVERSAL JOINT		
S16H1438	1PC-ADAPTER: 1/4"(F) x 3/8"(M)		
S26H2120	1PC-1/4"DR. SPINNER HANDLE		
S11H2	3PCS-1/4"DR. PHILLIPS BIT SOCKETS: PH.0, PH.1, PH.2		
S09H2	5PCS-1/4"DR. HEX BIT SOCKETS: 3, 4, 5, 6, 7MM		
S07H2	7PCS-1/4"DR. STAR BIT SOCKETS: T6, T7, T8, T9, T10, T15, T20		
S08H2	9PCS-1/4"DR. STAR BIT SOCKETS (TAMPERPROOF): T8H, T9H, T10H		
	T15H, T20H, T25H, T27H, T30H, T40H		
S04H3	16PCS-3/8"DR. 6PT SOCKETS: 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19		
	20, 21, 22, 24MM		
S04HD3	15PCS-3/8"DR. 6PT DEEP SOCKETS: 8, 9, 10, 11, 12, 13, 14, 15, 16, 17,		
	18, 19, 20, 21, 22MM		
S06H	12PCS-STAR SOCKETS: 1/4"DR E6, E7, E8, E10		
	3/8"DR E11, E12, E14, E16, E18		
	1/2"DR E20, E22, E24		
S06HD	10PCS-STAR DEEP SOCKETS: 1/4"DR E4, E5, E6, E7, E8		
	3/8"DR E10, E11, E12, E14, E16		
R3703B	1PC-3/8"DR. STUBBY RATCHET HANDLE 48TEETH		
R3703	1PC-3/8"DR. RATCHET HANDLE 48 TEETH		
R4103	1PC-3/8"DR. FLEXIBLE HANDLE 48 TEETH		
T21050N	1PC-3/8"DR. MICROMETER TORQUE WRENCH 10-50 N.M.		
S24H3	3PCS-3/8"DR. EXTENSION BAR, L: 75, 150, 250MM		
S15H356	1PC-3/8"DR. UNIVERSAL JOINT		
S16H403	1PC-ADAPTER 1/2"(F) x 3/8"(M)		
S17H3	3PCS-3/8"DR. SPARK SOCKETS: 16, 18, 21 MM		
S11H3	2PCS-3/8"DR. PHILLIPS BIT SOCKETS: PH.1, PH.2		
S09H3	8PCS-3/8"DR. HEX BIT SOCKETS: 5, 5.5, 6, 7, 8, 9, 10, 12 MM		
S07H3	7PCS-3/8"DR. STAR BIT SOCKETS: T20, T25, T27, T30, T40, T45, T50		
S08H3	7PCS-3/8"DR. STAR BIT SOCKETS (TAMPERPROOF): T20, T25, T27,		
	T30, T40, T45, T50		
S64H3	6PCS-3/8"DR. SPLINE BIT SOCKETS: M5, M6, M8, M9, M10, M12		



Tray : EVA Form

· Easy to organize for more efficient management Provide complete protection for tools



S04

Cor
 S04


S09 S07

S08H

S64

S09 S07 S64 R37 T21 S24H S15H S16H S17H







Second Drawer

4H4()75SV	75PCS 1/2"DR. SOCKET & TORQUE WRENCH SET	
ntents:			
4H4	22PCS-1/2	"DR. 6PT SOCKETS : 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18,	
	19, 20, 21,	22, 23, 24, 26, 27, 28, 30, 32 MM	
9H4	8PCS-1/2"[DR. HEX BIT SOCKETS : 4, 5, 6, 7, 8, 9, 10, 12 MM (55MML)	
7H4	8PCS-1/2"[DR. STAR BIT SOCKETS : T27, T30, T40, T45, T50, T55, T60,	
	T70 (55MM	IL)	
3H4	8PCS-1/2"[DR. STAR BIT SOCKETS (TAMPERPROOF) : T27, T30, T40,	
	T45, T50, T	55, T60, T70 (55MML)	
4H4	8PCS-1/2"DR. SPLINE BIT SOCKETS : M5, M6, M8, M9, M10, M12, M14,		
	M16 (55MN	/L)	
9H4	4PCS-1/2"[DR. HEX BIT SOCKETS: 6, 7, 8, 10, MM (100MML)	
7H4	4PCS-1/2"[DR. STAR BIT SOCKETS : T40, T45, T50, T55 (100MML)	
4H4	4PCS-1/2"[DR. SPLINE BIT SOCKETS : M6, M8, M10, M12 (100MML)	
704	1PC-1/2"DI	R. RATCHET HANDLE 48 TEETH	
1200N	1PC-1/2"DR. MICROMETER TORQUE WRENCH 20-200 N.M.		
4H4	2PCS-1/2"DR. EXTENSION BAR : 125, 250 MML		
5H472	1PC-1/2"DR. UNIVERSAL JOINT		
6H304	ADAPTOR FOR EXTENSION BAR 3/8" (F) x 1/2" (M)		
7H4	3PCS-1/2"DR. SPARK PLUG SOCKETS : 16, 18, 21 MM		

Third Drawer

D71P1	24SV	24PCS SCREWDRIVER SET			
Contents:	Contents:				
D71P	4PCS-PHI	4PCS-PHILLIPS SCREWDRIVER : PH.1 x 80, PH.2 x 38, PH.2 x 100,			
	PH.3 x 125	PH.3 x 125			
D71S	5PCS-SLC	5PCS-SLOTTED SCREWDRIVER : 4 x 100, 5.5 x 38, 5.5 x 125, 6.5 x 150,			
	8 x 175 MM	8 x 175 MM			
D71T	12PCS-ST	12PCS-STAR SCREWDRIVER : T6, T7, T8, T9, T10, T15, T20, T25, T27, T30,			
	T40, T45				
D70	3PCS-GO-THRU IMPACT SCREWDRIVER : 6.5 x 125, 8 x 150 MM, PH.2 x 100				

Fourth Drawer

23136SV		36PCS WRENCH SET			
ntents:	ntents:				
4106S	6PCS-FLARE NUT WRENCH : 8 x 9, 10 x 11, 10 x 12, 13 x 14, 16 x 17, 1				
	7 x 19 MM				
6	22PCS-COMBINATION WRENCH : 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18,				
	19, 20, 21, 22, 23, 24, 27, 30, 32 MM				
3	8PCS-75° OFFSET RING WRENCH : 6 x 7, 8 x 9, 10 x 11, 12 x 13, 14 x 15,				
	16 x 17, 18	8 x 19, 20 x 22 MM			







TOOL TROLLEY & MECHANIC TOOLS SET

4

- Tray : EVA Form Easy to organize for more efficient management
 Provide complete protection for tools



8			4.0
			2
-30	-	* 1	
•	$\odot \odot \odot$		
	THE PURCH		
		?	

P0822	23SV	23PCS PLIERS, HAMMER, FILE & CHISEL SET	
Contents:			
P0817	7" COME	SINATION PLIERS	
P1116	8" LONG	NOSE PLIERS	
P1218	8" BENT	LONG NOSE PLIERS	
P1017	7" DIAGO	DNAL PLIERS	
P2810	10" WAT	ERPUMP PLIERS	
P32M10A	10" LOC	10" LOCKING PLIERS	
M61H	2PCS-CHISEL 18X190, 24X220MML		
M63H	4PCS-PIN PUNCH 13X150, 4X180, 5X200, 6X210MML		
M62H	3PCS-TAPER PUNCH 2X185, 3X185, 4X185MML		
M09400	MACHIN	MACHINIST HAMMER 400G	
M06025	STONING	STONING HAMMER 1000G	
MT0701	MEASUR	MEASURING TAPE: 3MX19MM	
MK2080	UTILITY	UTILITY KNIFE(18MM BLADE)	
MF05A	8" FLAT FILE		
MF05B	8" ROUND FILE		
MF05C	8" HALF ROUND FILE		
MF05E	8" TRIANGLE FILE		

Sixth Drawer

Fifth Drawer

S09H4152SV		52PCS INTERNAL & EXTERNAL PLIERS, HAMMER, SOCKET & WRENCH SET	
Contents:			
S09H4317	1/2"DR. H	EX BIT SOCKET: 17MMX100MML	
S09H4806	1/2"DR. H	EX BIT SOCKET: 6MMX200MML	
S09H4808	1/2"DR. H	EX BIT SOCKET: 8MMX200MML	
W29	3PCS-STAR WRENCH: E6 X E8, E10 X E12, E14 X E18		
RD01032S	32PCS 1/4" HEX MINI RATCHET BIT SET		
AG010002SP	4PCS - 7"	4PCS - 7" INTERNAL & EXTERNAL PLIERS SET	
S18A4103S	3PCS-1/2	3PCS-1/2" DR. WHEEL NUT IMPACT DEEP SOCKETS: 17, 19, 21MM	
M11045	45MM Ø D	DEAD BLOW HAMMER WEIGHT: 520G	
AI050066	3PCS - OI	3PCS - OIL FILTER CAP WRENCH SET: 27, 32, 36MM	
AR060003	SWIVEL JAW HOSE CLAMP PLIERS		
AG010188	MAGNETIC PICK-UP TOOL		
AI050085A	OIL FILTER WRENCH: 74.4MM X 14 FLUTES		



Seventh Drawer

W2513	34SV 34PCS WRENCH, HEX KEY & HOOK S		
Contents:			
AI030007-A	11" MUL1	TIPURPOSE SCRAPER	
AI030007-E	9" COTTI	ER PIN PULLER	
AB030045	DOOR U	DOOR UPHOLSTERY REMOVER	
AI030007-C	7" RADIATOR HOSE REMOVER		
AB030043	9" DOOR UPHOLSTERY REMOVER		
W25	10PCS - DOUBLE OPEN WRENCH: 6X7, 8X9, 10X11,12X13,14X15,		
	16X17, 18	16X17, 18X19, 20X22, 24X27, 30X32MM	
H06SA109S	9PCS - ANTI-SLIP EXTRA LONG ARM BALL POINT HEX KEY SET:		
	1.5, 2, 2.5, 3, 4, 5, 6, 8, 10 MM		
H12S110S	10PCS - EXTRAL LONG STAR ARM HEX KEY SET: T9, T10, T15, T2		
	T25, T27,	T25, T27, T30, T40, T45, T50	



- Steel thickness: Cabinet-1.0mm drawer, 1.0mm body, 1.2mm top and bottom covers.Ball bearing designed for smooth slicling.
- Safe designed Aluminum end to prevent scratches.
- Internal locking system for extra security.
- One piece steel of Cabinet Body to add more strength. • 5"x2" Casters
- 200 Lbs loading capacity for each caster



260PCS PROFESSIONAL MECHANIC TOOL SET W/7-DRAWER TOOL TROLLEY C-7DW244V



C-7DW1

7-DRAWER TOOL TROLLEY W/KNOCKABLE WORKING TABLE

	w	D	н	
OVERALL	26	18	31-7/8	Inch
OVERALL	670	460	812	mm
OVERALL	26	18	37-11/16	Inch
(W / CASTERS)	670	460	960	mm
	22-5/8	15	2-15/16	Inch
5 DRAWERS	576	380	75	mm
	22-5/8	15	6	Inch
2 DRAWERS	576	380	154	mm
	N.W	G.W	CUFT	
	74.5KGS	82.5KGS	12.32'	

First Drawer

W23135V		35PCS OFFSET RING WRENCH SET	
Contents:			
W23	11PCS - 75° OFFSET RING WRENCH, 6x7 , 8x9, 10x11 , 12x13 ,		
	14x15 , 16x17, 18x19, 19x21, 19x22, 24x27 , 30x32MM		
W621	9PCS - DOUBLE RING WRENCH, 06x07, 08x09, 10x11, 12x13, 14x15,		
	16x17, 18x19, 20x22, 22x24MM		
W241	2PCS - FLARE NUT WRENCH, 10x11, 12x14MM		
W29	4PCS - STAR WRENCH, E6xE8, E10xE12, 14xE18, E20xE24		
H06SA109S	9PCS - ANTI-SLIP EXTRA LONG ARM BALL POINT HEX KEY SET (MM)		



MECHANIC TOOLS SET


ø

TOOL TROLLEY

6

Tray : EVA Form

Easy to organize for more efficient management
Provide complete protection for tools



Second Drawer

	94SV 94PCS 1/4", 3/8" & 1/2"DR. SOCKET SET	
Contents:		
S04H21	11PCS - 1/4"DR. 6PT FLANK SOCKETS: 5, 5.5, 6, 7, 8, 9, 10, 11, 12,	
	13, 14MM	
S10H2	3PCS - 1/4"DR. SLOTTED BIT SOCKETS: 3.5, 5.5, 7MM	
S09H2	5PCS - 1/4"DR. HEX BIT SOCKETS: H3, H4, H5, H6, H7	
S11H2	3PCS - 1/4" DR. PHILLIPS BIT SOCKETS: PH1, PH2, PH3	
S06H2	5PCS - 1/4"DR. STAR SOCKETS: E4, E5, E6, E7, E8	
S07H2	7PCS - 1/4"DR. STAR BIT SOCKETS: T10, T15, T20, T25, T30, T30, T4	
S26H2280	1PC - 1/4" SPINNER HANDLE	
S23H21115	1PC - 1/4" SLIDING BARS 115MM	
S24H2150	1PC - 1/4" ETENSION BARS 150MM	
S15H240	1PC - 1/4" UNIVERSAL JOINTS	
S44H2206	1PC - 1/4"DR. BIT HOLDER	
S08H2ST8S	8PCS - 1/4" DR. BIT SET	
D125TT	11PCS - 1/4" HEX SHANK TAMPERPROOF INSERT BITS: T6, T7, T8,	
	T9, T10, T15, T20, T25, T27, T30, T40	
S08H355	1PC - 3/8"DR. STAR BIT SOCKET T55 (TAMPERPROOF)	
D125P	3PCS - 1/4' HEX SHANK PHILLIPS INSERT BITS: PH1, PH2, PH3	
R2902	1PC - 1/4" ANTI SLIP GRIP RATCHET HANDLE-36 TEETH	
S16H3814	1PC - ADAPTERS (3/8"x1/4")	
S04H31	16PCS - 3/8"DR. 6PT FLANK SOCKETS: 7, 8, 9, 10, 11, 12, 13, 14,	
	15, 16, 17, 18, 19, 20, 21, 22MM	
S06H31	3PCS - 3/8"DR. STAR SOCKETS: E10, E12, E14	
S07H340	1PC - 3/8"DR. STAR BIT SOCKETS T40	
S64H31	3PCS - 3/8"DR. SPLINE INSERT BIT SOCKET: M6, M8, M10	
S24H3	3PCS - 3/8"DR. EXTENSION BARS: 75, 150MML	
R2903	1PC - 3/8"DR. ANTI SLIP GRIP RATCHET HANDLE-36 TEETH	
R4103	1PC - 3/8"DR. FLEXIBLE RATCHET HANDLE - 36 TEETH	
S15H356	1PC - 3/8"DR. UNIVERSAL JOINTS	
S16H	2PCS - ADAPTERS: 1/4"(F) x 3/8"(M), 1/2"(F) x 3/8"(M)	

Third Drawer

S04H41	145V	45PCS 1/2"DR. SOCKET SET
• Contents:		
S04H41	17PCS -	1/2"DR. 6PT FLANK SOCKETS: 10, 11, 12, 13, 14, 15, 16,
	17, 18, 1	9, 20, 21, 22, 24, 27, 30, 32MM
S09H43	5PCS - 7	1/2"DR. HEX BIT SOCKETS: H8, H10, H12, H14, H17
S24H4	3PCS - 7	1/2"DR. EXTENSION BARS: 50, 130, 250MML
S23H41300	1PC - 1/	2"DR. SLIDING BARS 300MM
S15H472	1PC - 1/	2"DR. UNIVERSAL JOINT
R2904	1PC - 1/	2"DR. ANTI SLIP GRIP RATCHET HANDLE-36 TEETH
S16H3	2PCS -	ADAPTERS: 3/8"(F) x 1/2"(M), 3/4"(F) x 1/2"(M)
S03AD43	2PCS - 7	1/2"DR. 6PT FLANK THIN WALL DEEP IMPACT SOCKETS:
	17, 19M	М
S06H4	5PCS -	1/2"DR. STAR SOCKETS: E11, E16, E18, E20, E24
S07H4	8PCS - 1	1/2"DR. STAR BIT SOCKETS: T45, T50, T55, T60 (55MML)
	T30, T40), T45, T50 (100MML)



- Tray : EVA Form
 Easy to organize for more efficient management
 Provide complete protection for tools



D7 • Cont D71T D71S D71P D71N

P Con
 P088
 P118
 P32M P2810 P098 AG01 AG01 AG01 AG01

Con
 M611
 M60⁻
 M63⁻

MF05

Cont
 W25
 W26



W

H08S





Fourth Drawer

1P12	22SV	22PCS ANTI-SLIP GRIP SCREWDRIVER SET
ntents:		
т	10PCS -	ANTI - SLIP GRIP STAR SCREWDRIVERS: T06, T07, T08,
	T09, T10	, T15, T20, T25, T27, T30
S	7PCS - A	NTI - SLIP GRIP SCREWDRIVER - SLOTTED: 5.5 x 75,
	5.5 x 125	, 5.5 x 200, 6.5 x 38, 6.5 x 100, 6.5 x 150, 6.5 x 250MM
Р	3PCS - A	NTI - SLIP GRIP SCREWDRIVER - PHILLIPS: PH0 x 60,
	PH1 x 38	, PH1 x 150MM
N	1/4" ANT	I - SLIP GRIP NUT DRIVERS: 6, 7MM

Fifth Drawer

0809	sv	9PCS PLIERS SET
ntents:		
8	8" COME	BINATION PLIERS
3	8" LONG	NOSE PLIERS
M10A	10" CUR	VED JAW LOCKING PLIERS WITH WIRE CUTTERS
10	10" BOX	JOINT PLIERS
8	8" HEAV	Y DUTY DIAGONAL CUTTING PLIERS
10009	9" (230M	M) STRAIGHT NOSE, EXTERNAL PLIERS
10012	9" (220M	M) BENT NOSE, EXTERNAL PLIERS
10003	9" (230M	M) STRAIGHT NOSE, INTERNAL PLIERS
10006	9" (220M	M) BENT NOSE, INTERNAL PLIERS

Sixth Drawer

10917	7SV	17PCS PUNCH & PRY BAR TOOL SET
ntents:		
112	COLD CI	HISEL 130MM
103	CENTER	PUNCH 100MM
106S	6PCS PI	N PUNCH SET: 2x8x115, 3x8x125, 4x9.5x150, 5x9.5x165,
	6x12.7x1	80, 8x12.7x180MM
)5A	8" FLAT	FILE
'016	SOFT FA	CE HAMMER
500	ENGINE	ER'S HAMMER 500g
0026	12PCS S	PRAY GUN CLEANING KIT
010035	3 IN 1 LI	GHTED MAGNETIC MIRROR
50024	4PCS PF	RY BAR SET

Seventh Drawer

25138SV		38PCS COMBINATION & OPEN END WRENCH SET
ntents:		
;	4PCS - 0	DPEN END WRENCH, SIZE: 16x17, 19x22, 24x27, 30x32mm
5	19PCS -	COMBINATION WRENCH, SIZE: 6, 7, 8, 9, 10, 11, 12, 13,
	14, 15, 1	6, 17, 18, 19, 21, 22, 24, 34, 36mm
S110S	10PCS E	XTRA LONG ARM STAR TAMPERPROOF KEY SET

TOOL TROLLEY WITH MECHANIC TOOLS SET (RECOMMENDED FOR JAPANESE, KOREAN & MALAYSIAN CARS)

TOOL TROLLEY & MECHANIC TOOLS SET

8

BALL BEARING SLIDES



Steel thickness : Cabinet-1.0mm drawer,1.0mm body, 1.2mm top and bottom covers.
Ball-bearing design for smooth slicling.
Safe-designed Aluminum end to prevent scratches.
Internal locking system for extra security.
One piece steel of Cabinet Body to add more strength.
5" x 2" Casters
200 Lbs loading capacity for each caster

- Tray : EVA Form
- Easy to organize for more efficient management
 Provide complete protection for tools





191PCS PROFESSIONAL MECHANICS TOOLS C-7DW191V SET W/7-DRAWER TOOL TROLLEY

First Drawer

- S04H45121SV 81PCS 1/4",3/8",1/2"DR. SOCKET SET AND
- 40PCS POWER BIT SET
- CONTENTS:

S29H4140SP	
	14PCS - 10MM HEX BITS:
	30MML: 4, 5, 6, 7, 8, 10, 12 75MML: 4, 5, 6, 7, 8, 10, 12
	14PCS - 10MM STAR BIT:
	30MML: T20, T25, T30, T40, T45, T50, T55 75MML: T20, T25,
	T30, T40, T45, T50, T55
	10PCS - 10MM SPLINE BITS:
	30MML: M5, M6, M8, M10, M12
	75MML: M5, M6, M8, M10, M12
	2PCS - BIT HOLDERS: 3/8" DR. X 10 MM, 1/2" DR. X 10MM
S04H3457SP	
S04H2	12PCS-1/4" DR. SOCKETS : 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11,
	12, 13MM
S04HD2	4PCS-1/4" DR.DEEP SOCKETS : 8, 10, 12, 13MM
	16PCS-1/4" DR. SOCKET BITS :
	HEX : 3, 4, 5, 6MM, STAR : T10, T20, T25, T27, T30
	SLOTTED : 4.5, 5, 7MM PHILLIPS : PH1, PH2, PH3
R3502	1PC-1/4" DR. 72TEETH QUICK RELEASE RATCHET HANDLE
S24H2	2PCS-1/4" DR. EXTENSION BARS 2" & 6"
S16H302	1PC-ADAPTOR FOR EXTENSION 1/4" (M) X 3/8" (F)
S15H2	1PC-1/4" DR. UNIVERSAL JOINT
S28H1	1PC-1/4" DR. SPINNER HANDLE
S04H3	8PCS- 3/8" DR. SOCKETS : 14, 15, 17, 18, 19, 20, 22, 24MM
S04HD3	3PCS- 3/8" DR. DEEP SOCKETS : 14, 15, 17MM
R3503	1PC-3/8" DR. 72TEETH QUICK RELEASE RATCHET HANDLE
S17H3	2PCS-3/8" DR. SPARK PLUG SOCKETS : 16, 21MM
S15H356	1PC-3/8" DR. UNIVERSAL JOINT
S16H403	1PC-ADAPTOR FOR EXTENSION 3/8" (M) X 1/2" (F)
S24H3	2PCS-3/8" DR. EXTENSION BARS 3" & 10"
S04H4125SP	
	18PCS-1/2" DR. SOCKETS : 10, 11, 12, 13, 14, 15, 16, 17, 18, 19,
S04H4	20, 21, 22, 23, 24, 27, 30, 32MM
S17H4	2PCS-1/2" DR. SPARK PLUG SOCKETS : 16 & 21MM
S24H4	2PCS-1/2" DR. EXTENSION BARS : 5" & 10"
S23H4125	1PC-1/2" DR. SLIDING T BAR
S15H472	1PC-1/2" DR. UNIVERSAL JOINT
R3504	1PC-12" DR. 72TEETH QUICK RELEASE RATCHET HANDLE



 Tray : EVA Form Easy to organize for more efficient management · Provide complete protection for tools







191PCS PROFESSIONAL MECHANICS TOOLS C-7DW191V SET W/7-DRAWER TOOL TROLLEY

Second Drawer

W60246139SV

39PCS PCS WRENCH SET

CONTENTS:

11/00/11/50	15PCS 72TEETH REV. RATCHETING COMBINATION WRENCH
W60115S	SET : 8,10,11,12,13,14,15,16,17,18,19MM
	3PCS ADPTER QUICK RELEASE : 1/4"DR., 3/8"DR., 1/2"DR.
	1PC 10MM BIT HOLDER
W24108SV	8PCS FLARE NUT SET : 8X9, 10X11, 10X12, 13X14, 16X17,
VV241003V	17X19, 22X24, 24X27 MM
W26116S	16PCS COMBINATION WRENCH SET : 6,7,8,9,10.11.12,13,14,15,
W201100	16,17,18,19,22,24MM
	EVATRAY

Third Drawer

JA-C231SV

1/2" HEAVY DUTY AIR IMPACT WRENCH KIT

CONTENTS:

JAI-1044	1/2" HEAVY DUTY IMPACT WRENCH
JAR-6309A	1/2" HEAVY DUTY AIR RATCHET WRENCH
JAG-0906RM	6MM HEAVY DUTY MEDIUM AIR DIE GRINDER
0004540	3PCS - 1/2" DR. 6PT FLANK THIN WALL IMPACT SOCKETS :
S03AD43	17, 19, 21 MM
00044	11PCS - 1/2" DR. 6PT FLANK IMPACT SOCKETS :
S03A4	10, 11, 12, 13, 14, 16, 17, 19, 21, 22, 24 MM
S03AD4	7PCS - 1/2" DR. 6PT FLANK DEEP IMPACT SOCKETS :
303AD4	10, 11, 13, 14, 17, 19, 21 MM
S03A3A	1PC - 3/8" F DR. ADAPTOR : 1/2" M
S03A4A	2PCS - 1/2" F DR. ADAPTOR : 3/8" M, 3/4" M
S03A4U	1PC - 1/2" DR. UNIVERSAL JOINT
S03A4E	3PCS - 1/2" DR. EXTENSION BAR : 3", 5", 10"

Tray : EVA Form

TOOL TROLLEY & MECHANIC TOOLS SET

10

 Easy to organize for more efficient management Provide complete protection for tools



AN500001SV	19PCS TIRE REPAIR AND SERVICE TOOL SET

1.	T21340N	1/2"DR. MICROMETER TORQUE WRENCH 60~340NM
2.	AG010206	PULL UP WRENCH, L:435~620MM MAX CAPACITY IS UP TO
		500NM
3.	AN010188A	TIRE LEVER WRENCH L:500MM
4.	AN010085A	SNAP IN TIRE VALVE INSTALLER, L:335MM
5.	AN010190	VALVE CORE TORQUE TOOL, TORQUE LIMIT 45NM
6.	AN010191	VALVE CORE TORQUE TOOL, TORQUE LIMIT 25NM
7.	AN010030	WHEEL WEIGHT BALLANCE PLIERS
8.	W26124	COMBINATION WRENCH 24MM
9.	P0917	7" DIAGONAL CUTTING PLIERS (HEAVY DUTY)
10.	AN010269	4PCS-TIRE REPAIR TOOL SET
11.	AI050125-C	25.4MM SUPER SCRAPER, L: 270MM
12.	AG010215	5PCS-REVERSE ACTION WHEEL STUD THREAD
		RESTORER KIT M12X1.5, M12X1.25, M14X1.5

JONNESWAY -----



A	N500002	SV 28PCS WHEEL ALIGNMENT SERVICE TOOL
1.	JAI-1044	1/2"DR. HEAVY DUTY IMPACT WRENCH
2.	AE310015N	20PCS-FRONT & REAR HUB INSTALLER REMOVER
3.	W27AS12	12" ADJUSTABLE ANGLE WRENCH
4.	AN010091B	DELUXE INNER TIE ROD TOOL
5.	AN010092	MULTI PURPOSE INNER TIE ROD TOOL
6.	S03AD4	1/2"DR. 6PT FLANK THIN WALL DEEP IMPACT SOCKET: 17, 19,
		21MM, 13/16"

JONNESWAY



AN300001SV			CS SUSPENSION & UNDERCAR RVICE TOOL SET
1.	AE320042	3PCS HEA	VY DUTY COIL SPRING COMPRESSOR W/JAWS &
		HOLDER	
2.	AN010045	BALL JOINT SEPARATOR OPEN JAW:24MM,L:300MM	
3.	AN010046	BALL JOINT SEPARATOR OPEN JAW:17MM,L:405MM	
4.	AE310021	OUTER TIE ROD REMOVER	
5.	AE310087	UNIVERSAL BALL JOINT SEPARATOR 24MM	
6.	AE310115	UNIVERS	AL BALL JOINT SEPARATOR 20MM
7.	AI020043	BANDING	TOOL WITH CUTTER
8.	R3704	1/2"DR. Al	NTI-SLIP GRIP RATCHET HANDLE 48 TEETH
9.	S04H4	1/2"DR. 6F	PT FLANK SOCKETS: 16, 17, 19MM





Tray : EVA Form

Easy to organize for more efficient management
 Provide complete protection for tools



1.
2.
3.
4.
5.
6.





JONNESWAY -----

JONNESWAY ----



1. 2. 3. 4. 5.

22PCS GO-THRU IMPACT SCREWDRIVER AND FILE SET D71FL20SV

JAT-460B	4PCS - LEVER TYPE HAND GREASE GUN W/9" NYLON HOSE &		
	6" BEND SPOUT		
D70S	3PCS - SL8x150, SL6.5x125, SL5.5x100		
D70P	3PCS - PH3x150, PH2x100, PH1x75		
MF05C	8" HALF ROUND FILE		
MFM06S	6PCS - 4" MINI FILE SET		
M63106S	6PCS - PIN PUNCH SET: 2x8.0x105, 3x8.0x125, 4x9.5x150,		
	5x9.5x165, 6x12.7x180, 8x12.7x180 MM		

P081FL10SV 14PCS PLIERS AND FILE SET


AE310036	5PCS-6" 3-JAWS CR-V GEAR PULLERS
P2712	12" MACHINED TONGUE & GROOVE WATER PUMP PLIERS
P32M10A	10" CURVED JAW LOCKING PLIERS WITH WIRE CUTTERS
AG010002	7"(175mm) STRAIGHT NOSE, INTERNAL PLIERS
AG010005	7"(165mm) BENT NOSE, INTERNAL PLIERS
AG010008	7"(175mm) STRAIGHT NOSE, EXTERNAL PLIERS
AG010011	7"(165mm) BENT NOSE, EXTERNAL PLIERS
P0817	7" COMBINATION PLIERS (EUROPEAN TYPE)
P1118	8" LONG NOSE PLIERS
P0917	7" DIAGONAL CUTTING PLIERS (HEAVY DUTY)

14PCS 1/2"DR. IMPACT SOCKET AND PULLER SET S03A4FL14SV

AE310008	5PCS-INTERNAL & EXERNAL PULLER SET
S23H6450	3/4"DR. SLIDING BAR L:450MM
M09500	500G ENGINEER'S HAMMER
S03AD6	6PCS-3/4"DR 6PT FLANK DEEP IMPACT SOCKET SET: 18, 19,
	22, 24, 27,32MM
MT0302	5m(16ftx3/4") MEASURING TAPES

TOOL TROLLEY & MECHANIC TOOLS SET

 Easy to organize for more efficient management Provide complete protection for tools



/26FL34SV	34PCS COMBINATION WRENCH AND HEX KEY SET

1.	AI050077	25~160MM STRAP WRENCH	
2.	AG010034	580MM MAGNETIC PICK-UP TOOL	
3.	W26	19PCS-COMBINATION WRENCH, SIZE: 6, 7, 8, 10, 11, 12,	
		13, 14, 15, 16, 17, 19, 20, 21, 22, 24, 27, 30, 32MM	
4.	H03SM109S	9PCS-EXTRA LONG ARM HEX KEY SET, SIZE: 1.5,	
		2, 2.5, 3, 4, 5, 6, 8, 10MM	
5.	H02M1	4PCS-LONG ARM HEX KEY, SIZE: 12,14,17,19MM	


JONNESWAY -



1.	AR020016	5PCS-DIGITAL AUTOMOTIVE ANALYZER & MULTI METER
2.	R2904	1/2"DR. 36 TEETH RATCHET HANDLE
3.	S22H41375	1/2"DR. FLEXIBLE HANDLE L:375MM
4.	S23H41300	1/2"DR. SLIDING BAR L:300MM
5.	S24H4250	1/2"DR. EXTENSION BAR L:250MM
6.	S24H4125	1/2"DR. EXTENSION BAR L:125MM
7.	S17H4121	1/2"DR. SPARK PLUG SOCKET 21MM
8.	S04HD4127	1/2"DR. 6PT FLANK DEEP SOCKET
9.	S15H472	1/2"DR. UNIVERSAL JOINT
10.	S04H4	18PCS-1/2"DR 6PT SOCKETS: 10, 11, 12, 13, 14, 15, 16, 17,
		18, 19, 20, 21, 22, 23, 24, 27, 30, 32MM
11.	S05A4	8PCS 1/2"DR HEX BITS IMPACT SOCKETS: H5, H6, H8,
		H10, H12, H14, H17, H19
12.	S64H4212	1/2"DR. SPLINE INSERT BIT SOCKET M12







-01 -00

Tray : EVA Form
Easy to organize for more efficient management
Provide complete protection for tools

.....



S04 Cont
 R2802
 S04H2



JONNESWAY.

C-8DW1162V

217PCS PROFESSIONAL MECHANIC TOOL SET W/8-DRAWER TOOL TROLLEY



First Drawer

P01809SV		9PCS PLIERS SET
Contents:		
P018	8" SIDE C	UTTING PLIERS
P038	8" DIAGO	NAL CUTTER PLIERS
P068	8" LONG	NOSE PLIERS
P2010SA	10" AVIAT	ION TIN SNIPS, STRAIGHT CUT
P256	SNAP RING PLIERS	
P2712	12" MACHINED TONGUE & GROOVE WATER PUMP PLIERS	
P2810	10" BOX JOINT WATER PUMP	
P5603	5" SIDE C	UTTER PLIERS
P7719	9" WIRE 1	WISTING PLIERS

Second Drawer

S04H21	84SV 74PCS 1/4"DR. SOCKET TOOL SET			
Contents:				
R2802Q	1/4"DR. QUICK RELEASE RATCHET HANDLE			
S04H2	13PCS-1/4"DR 6PT FLANK SOCKET : 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11,			
	12, 13, 14MM			
S09H2	6PCS-1/4"DR. HEX BIT SOCKET : H2, H2.5, H3, H4, H5, H6			
S16H3814	ADAPTER: 3/8"(F) x 1/4"(M)			
S16H302	ADAPTER FOR SLIDING T-BAR: 1/4"(M) x 3/8"(F)			
S15H240	1/4"DR. UNIVERSAL JOINT			
S24H2	2PCS-1/4"DR. EXTENSION BAR, L: 100 & 150MM			
S22H21150	1/4"DR. FLEXIBLE HANDLE, L:150MM			
S23H21130	1/4"DR. SLIDING T BAR, L:130MM			
S26H2150	1/4"DR. SPINDER HANDLE			
S26H2280	1/4"DR. UNIVERSAL SPINNER, L: 280MM			
S27H2	1/4"DR. FLEXIBLE EXTENSION BAR, L: 145MM			
S41H216	1/4"DR. SPEEDER HANDLE			
DBT31B	31PCS-SCREWDRIVER BIT SET			
	PHILLIPS: PH1, 2, 3			
	SLOTTED: 4x0.8, 5.5x1, 6.5x1.2			
	POZIDRIV: 2PCS-PZ1, 2, 3			
	HEXAGON: 4, 5, 6MM			
	STAR: 2PCS-T10, T20, T40, 3PCS-T15, T25, T30			
	QUICK RELEASE BIT HOLDER L: 51MM			
D3765P08S	8PCS-PRECISION SCREWDRIVER SET			
	5PCS SLOTTED: 2, 2.4, 3, 3.5, 4.0MM			
	3PCS-PHILLIPS: 00, 0, 1			
D70S	2PCS - GO THRU IMPACT SCREWDRIVER: SL#9.5x200, SL#9.5x300			
D71SA5150	ANTI-SLIP GRIP SCREWDRIVER: SLOTTED 5x150			
DV13S5125	1000V INSULATED SCREWDRIVER: 5.5X125MM			

8 8

 Tray : EVA Form · Easy to organize for more efficient management Provide complete protection for tools



Third Drawer S04H4941SV 41PCS 1/2"DR. SOCKET WRENCH SET

Contents:				
R2804Q	1/2" DR. RATCHET HANDLE-48 TEETH			
S05H4	20PCS- 1/2"DR.12PT SOCKETS: 10, 12, 13, 14, 15, 16, 17, 18, 19, 20,			
	21, 22, 23, 24, 25, 26, 27, 28, 30, 36MM			
S09H4	7PCS-1/2"DR. HEX BIT SOCKETS: H8, H10, H12, H14, H16, H17, H19			
S15H472	1/2" DR. UNIVERSAL JOINT			
S16H1034	ADAPTER: 1"(F) x 3/4"(M)			
S16H1234	ADAPTER: 1/2"(F) x 3/4"(M)			
S16H1438	ADAPTER: 1/4"(F) x 3/8"(M)			
S16H304	ADAPTER FOR SLIDING T-BAR:1/2"(M) x 3/8"(F)			
S16H3410	ADAPTER: 3/4"(F) x 1"(M)			
S16H3412	ADAPTER: 3/4"(F) x 1/2"(M)			
S16H403	ADAPTER FOR SLIDING T-BAR: 3/8"(M) X 1/2"(F)			
S22H41450	1/2"DR. FLEXIBLE HANDLE, L: 450MM			
S24H4	2PCS - 1/2"DR. EXTENSION BAR, L: 125 & 250MM			
S23H41300	1/2"DR. SLIDING T BAR, L:300MM			
S41H41	1/2"DR. SPEED HANDLE, L: 16-1/4"(412MM)			

Fourth Drawer

R19H3126SV		26PCS 3/8"DR. CROWFOOT WRENCH SET
Contents:		
AG010033	TELESCO	PING INSPECTION MIRROR, SIZE: 50 X 92 MM
AG010034	MAGNETIC	C PICK-UP TOOL, CAPACITY: 3.5 LBS
H06S109S	9PCS EXT	RA LONG BALL POINT HEX KEY SET, SIZE: 1.5, 2, 2.5, 3,
	4, 5, 6, 8, 10 MM	
AI050057	OIL FILTER WRENCH	
Al060020 BLADES METRIC GAUGE: 0.05, 0.1		IETRIC GAUGE: 0.05, 0.10, 0.15, 0.20, 0.25, 0.30, 0.35, 0.40
	0.45, 0.50, 0.55, 0.60, 0.65, 0.70, 0.75, 0.80, 0.85, 0.90, 0.95, 1.00MM	
AI030022-3	STRAIGHT PICK TOOL	
R19H310S	10PCS 3/8"DR. CROWFOOT WRENCH	
P2208A	8" STRAIGHT PATTERN SNIPS	
MK2040	UTILITY KNIFE	


Fifth Drawer

MF051	6SV	20PCS FILE TOOL SET				
Contents:	Contents:					
MF05S	5PCS - F	ILE SET, L: 8"				
MF17A	FLAT FIL	E, L: 160MM				
MF17B	HALF RC	DUND FILE, L: 160MM				
MF17C	TRIANG	ULAR FILE, L: 160MM				
MF17D	SQUARE	FILE, L: 160MM				
MF17E	ROUND FILE, L: 160MM					
MF17F	FLAT-POINT FILE, L: 160MM					
MF17G	KNIFE TEPY FILE, L: 160MM					
MF17H	BARRET	TE FILE, L: 160MM				
MF17J	CROSSI	NG FILE, L: 160MM				
F17K	OVAL FIL	LE, L: 160MM				
MF17L	FEATHE	R EDGE FILE, L: 160MM				
MF17M	ROUND	EDGE FLAT FILE, L: 160MM				
MT0703	MEASURING TAPE 8MX25MM					
MTC156	STAINLE	SS STEEL RULER: 12"(300MM)				
V1501	HEAVY D	OUTY EASY STRIPPER, L: 205MM				





- Easy to organize for more efficient management
 Provide complete protection for tools



W Con
 M0400
 M6010
 M6310
 M6310
 M6310
 M6310
 MHS1
 W24
 W5311







• Con W26 AG010



666666666

MF055	5PUS - FILE SEI, L: 8
MF17A	FLAT FILE, L: 160MM
MF17B	HALF ROUND FILE, L: 160MM
MF17C	TRIANGULAR FILE, L: 160MM
MF17D	SQUARE FILE, L: 160MM
MF17E	ROUND FILE, L: 160MM
MF17F	FLAT-POINT FILE, L: 160MM
MF17G	KNIFE TEPY FILE, L: 160MM
MF17H	BARRETTE FILE, L: 160MM
MF17J	CROSSING FILE, L: 160MM
F17K	OVAL FILE, L: 160MM
MF17L	FEATHER EDGE FILE, L: 160MM
MF17M	ROUND EDGE FLAT FILE, L: 160MM
MT0703	MEASURING TAPE 8MX25MM
MTC156	STAINLESS STEEL RULER: 12"(300MM)
V1501	HEAVY DUTY EASY STRIPPER, L: 205MM



JONNESWAY.

TOOL TROLLEY & MECHANIC TOOLS SET

Sixth Drawer

241 [·]	13SV	13PCS FLARE NUT WRENCH TOOL SET					
ntents:							
800	BALL PEEN HAMMER: 8 OZ						
104	CENTER PUNCH, SIZE: 4						
102	PIN PUNCH, SIZE: 2X30						
105	PIN PUNC	H, SIZE: 5X55					
106	PIN PUNCH, SIZE: 6X55						
100AG	HEAVY DU	TY DELUXE TYPE HACKSAW W/ 12" H.S.S. BLADE					
	6PCS-FLA	RE NUT WRENCH: 9x11,10x12,13x14,16x17, 18x19, 21x23MM					
119	MIDGET C	OMBINATION WRENCH, SIZE: 19MM					


Seventh Drawer

2612	26SV	1	26P	CS	CON	IBIN	IAT	ON	W	RE	NC	H S	5E1	Γ		
ontents:																
261	26PCS-	со	MBIN	ATIC	N WF	RENC	H: 6,	7, 8,	9, 1	10, 1	1, 1	2, 1:	3, 1	4, 15	5, 1	6,
	17 18	19	20 21	22	23.2	4 25	26 2	7 2	8 2	9 30	32	мм				


Eighth Drawer

26008SV		8PCS COMBINATION WRENCH SET			
ntents:					
	7PCS-COMBINATION WRENCH: 34, 35, 36, 38, 41, 46, 50MM				
0038A	PROFESS	SIONAL 3 FUNCTION TIRE GAUGE, L : 375MM			





C-



VORKING	T
TROLLE	

C-7DW	7-DRAWER TOOL TROLLEY W/KNOCKABLE WORKING TABLE						
ITEM NO.	W	D	н				
	26.3	18	32	Inch			
OVERALL	670	460	812	mm			
OVERALL	26	18	37.7	Inch			
(W/CASTERS)	670	460	960	mm			
5 DRAWERS	22	15	2.9	Inch			
5 DRAWERS	576	380	75	mm			
2 DRAWERS	22.8	15	6	Inch			
2 DRAWERS	576	380	154	mm			
	N.W	G.W	CUFT				
	74.5 KGS	82.5 KGS	12.32'				

JONNESWAY -----

 Top & Bottom Cover-1.2mm • Ball Bearing design for smooth sliding. • Ergonomic End of Drawer.

• Internal Locking System for extra security. • One Piece Steel of Cabinet Body. 5" X 2" Casters. 200 Lbs loading capacity for each caster.

MECHANIC TOOLS SET

Š

TOOL TROLLEY

16

ONE-DRAWER OPEN SYSTEM

ONE-DRAWER OPEN SYSTEM creates a safety operating condition to users. • Steel Thickness : Cabinet-1.0mm. Drawer & Body-1.0mm.



			and the second s
		=	
	-	_	
	_		6
9		10	0

-	C-7DW7 7-DRAWER TOOL TROLLEY W/WORKING TABLE						
No. of Contraction of	ITEM NO.	W	D	ŀ			
	0)/50411	26.3	18	3			
	OVERALL	670	460	81			
	OVERALL	26	18	37			
	(W/CASTERS)	670	460	96			
	5 DRAWERS	22.8	15	2.			
	5 DRAWERS	576	380	7			
		22.8	15	6			
	2 DRAWERS	576	380	15			
		N.W	G.W	CU			
		74.5 KGS	82.5 KGS	12.3			

ITEM NO.	W	D	н	
	26.3	18	32	Inch
OVERALL	670	460	812	mm
OVERALL V/CASTERS)	26	18	37.7	Inch
	670	460	960	mm
DRAWERS	22.8	15	2.9	Inch
DRAWERS	576	380	75	mm
DRAWERS	22.8	15	6	Inch
DRAWERS	576	380	154	mm
	N.W	G.W	CUFT	
	74.5 KGS	82.5 KGS	12.32'	

.

JONNESWAY -

BALL BEARING SLIDES



C-5DW1 5-DRAWER TOOL TROLLEY W/KNOCKABLE WORKING TABLE							
	w	D	н				
0//50.411	26.3"	18"	25.5"	Inch			
OVERALL	670	460	656	mm			
OVERALL	26.3"	18"	31.3"	Inch			
(W / CASTER	(S) 670	460	795	mm			
	22.8"	15"	2.2"	Inch			
3 DRAWER	579	380	56	mm			
	22.8	15"	4.8"	Inch			
2 DRAWER	579	380	123	mm			
	N.W.	G.W.	CUFT				
	61KGS	68KGS	10.22"				

Steel thickness : Cabinet-1.0mm drawer, 1.0mm body, 1.2mm top and bottom covers.
Ball-bearing design for smooth slicling.

Safe-designed Aluminum end to prevent scratches.

Internal locking system for extra security.
One piece steel of Cabinet Body to add more strength.

- 5" Casters 200 Lbs loading capacity
- for each caster



JONNESWAY -



BALL BEARING SLIDES



JONNESWAY.



7-DRAWER TOOL TROLLEY W/KNOCKABLE WORKING TABLE C-7DW1

	W	D	Н	
OVERALL	26.3"	18"	32"	Inch
OVERALL	670	460	813	mm
OVERALL	26.3"	18"	37"	Inch
(W / CASTERS)	670	460	943	mm
5 DRAWERS	22.8"	15"	2.2"	Inch
5 DRAWERS	579	380	56	mm
2 DRAWERS	22.8	15"	4.8"	Inch
2 DRAWERS	579	380	123	mm
	N.W.	G.W.	CUFT	
	74.5KGS	82.5KGS	12.32"	

Steel thickness : Cabinet-1.0mm drawer,1.0mm body, 1.2mm top and bottom covers.
Ball-bearing design for smooth slicling.
Safe-designed Aluminum end to prevent scratches.
Internal locking system for extra security.
One piece steel of Cabinet Body to add more strength.
5" x 2" Casters
200 Lbs loading capacity for each caster

C-7DW5 7-DRAWER TOOL TROLLEY W/WORKING TABLE

	w	D	н	
OVERALL	26.3"	18"	32"	Inch
OVERALL	670	460	813	mm
OVERALL	26.3"	18"	37"	Inch
(W / CASTERS)	670	460	943	mm
5 DRAWERS	22.8"	15"	2.2"	Inch
5 DRAWERS	579	380	56	mm
	22.8	15"	4.8"	Inch
2 DRAWERS	579	380	123	mm
	N.W.	G.W.	CUFT	
	74.5KGS	82.5KGS	12.32'	

-7DWB53 53" 7-DRAWER ROLL-WAGON • FULLY SHELF-CLOSING, BALL BEARING SLIDES • ONE DRAWER OPEN AT A TIME LOCKING SYSTEM								
				TIME LOV				
EM NO.	v	V	D			н		
	53		18		38	5/8	Inch	า
VERALL 13		58	460		9	80	mm	1
VERALL	5	3	18		45	1/2	Inch	ı
CASTERS)	13	58	460		11	50	mm	1
RAWERS	47	7/8	15		3 1	5/16	Inch	۱
RAWERS	12	15	380		1	00	mm	1
RAWERS	47	7/8	15			6	Inch	۱
RAVERS	12	15	380		1	53	mm	1
	N.	W	G.W		CL	JFT		
	140	KGS	150KG	S	30	.5'		

KNOCKABLE WORKING TABLE

136 PCS PROFESSIONAL MECHANICS TOOLS SET

8 PCS 75° OFFSET RING WRENCH SET

16 PCS COMBINATION WRENCH SET

AND HEX KEY SET

3 PCS PLIERS SET

SIZE : 6X7, 8X9, 10X11, 12X13, 14X15, 16X17, 18X19, 20X22mm

SIZE : 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 22, 24mm

8 PCS POWER HANDLE TWO WAY BALL POINT

SIZE : 2x135x75mm, 2.5x135x75mm, 3x135x75mm, 4x192x95mm,

5x192x95mm, 6x192x95mm, 8x240x110mm, 10x240x110mm

W/7-DRAWER TOOL TROLLEY

C-7DW136

W/KNOCKABLE WORKING TABLE W/TOOL HOLDER

BALL BEARING SLIDES











P0803SP	7" COMBINATION PLIER 7" HEAVY DUTY DIAGONAL CUTTING PLIER 8" LONG NOSE PLIER
S04H4125SP	25 PCS 1/2"DR. SOCKET WRENCH SET
S04H3157SP	56 PCS 1/4" & 3/8" DR.SOCKET WRENCH SET

JONNESWAY



3[™] DRAWER P2803SP D04PP08SP AG010026SP AG010002SP

P2803SP	3 PCS 10" PLIER AND ADJUSTABLE WRENCH SET
D04PP08SP	8 PCS FULL STAR SCREWDRIVER SET
AG010026SP	5 PCS HAMMER & CHISEL SET
AG010002SP	4 PCS INTERNAL & EXTERNAL PLIER SET







C-5DW108 W/TOOL HOLDER

AG010



JONNESWAY -

JONNESWAY -



1 ^{s™} DRAWE	R		
AG010026SP	P018SP	P2710SP	W45112SP

451



S04H4125SP

S04H3157SP

2[™] DRAWER

D04PP08SP

1		S 04



KNOCKABLE WORKING TABLE

W/KNOCKABLE WORKING TABLE

026SP	5 PCS HAMMER & CHISEL SET
	3 PCS PLIERS SET
8SP	8" SIDE CUTTING PLIER 8" DIAGONAL CUTTER PLIERS 8" LONG NOSE PLIER
	2PCS PLIERS SET
OSP	10" MACHINED TONGUE & GROOVE WATER PUMP PLIER 10" CURVED JAWS LOCKING PLIER WITH WIRE CUTTER
12SP	12PCS 72 TEETH RATCHETING COMBINATION WRENCH
1238	SIZE : 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22mm



Tray : EVA Form

TOOL TROLLEY & MECHANIC TOOLS SET

 Easy to organize for more efficient management Provide complete protection for tools





D737134SV		34PCS SCREWDRIVER, DOUBLE FLEX. SOCKET AND PRECISION SD SET	
CONTENTS:			
D376514LS	14PCS F	RECISION SCREWDRIVER SET : ⊕ PH#1,PH#0,	
D376514L5	PH#00, 6	→ 3.0, 2.4, 2.0, T20, T15, T10, T9, T8, T7, T6, T5	
W43A107S	7PCS DO	DUBLE FLEXIBLE SOCKET SET : 6X7,8X9,	
Wishing	10X11,12	2X13,14X15,16X17,18X19MM	
	GO-THR	OUGH SCREWDRIVER SET	
D70105S	3PCS SLOTTED:6.5X125MM,8X150MM,9.5X175MM		
	2PCS PH	HLLIPS: #2X100MM,#3X150MM	
	ANTI-S	LIP GRIP SCREWDRIVER SET	
D71PP08S	4PCS SLOTTED : 6.5X38, 4X80, 5.5X125, 6.5X150		
	4PCS F	HILLIPS : PH2X38, PH1X80, PH2X100, PH3X150	
	EVATRAY		

14PCS PLIERS SET

140MM MINIATURE BENT NEEDLE NOSE PLIERS 110MM H.D. MINIATURE END CUTTING NIPPER

115MM H.D. MINIATURE DIAGONAL PLIERS

120MM H.D. MINIATURE LINESMAN PLIERS

AG010002S 4PCS INTERNAL & EXTERNAL PLIERS SET

+ 10" CURVED JAW PLIERS

135MM H.D. MINIATURE LONG NOSE PLIERS

8" SIDE CUTTING PLIERS & 8" DIAGONAL PLIERS & 8" LONG

10" MACHINED TONGUE & GROOVE WATER PUMP PLIERS

P82714SV

NOSE PLIERS P7105S 5PCS MINIATURE PLIERS

EVA TRAY

CONTENTS:

P018S

P7101

P7102


P7103

P7104

P7105

P2710S

JONNESWAY -



H10121SV		16PCS TWO WAY HEX KEY SET AND 5PCS HAMMER CHISEL SET
CONTENTS:		
H10MB08S	8PCS TWO WAY BALL POINT HEX KEY SET, 8660 : 2X100, 2.5X100, 3X100, 4X100, 5X150, 6X150, 8X200, 10X200MM	
H10MT08S	8PCS TWO WAY STAR TAMPERPROOF KEY SET, 8660 : T10X100, T15X100, T20X100, T25X100, T27X150, T30X150, T45X200, T50X200	
AG010026S	5PCS HAMMER CHISEL SET, 1PC 300G ENGINE HAMMER 1PC HEAD DIA 35MM DEAD BLOW HAMMER, 3PCS COLD CHISEL SET	
	EVATRAY	



Tray : EVA Form
Easy to organize for more efficient management
Provide complete protection for tools



AE

JONNESWAY -



1. A 2. A 3. Al 4. Al 5. Al Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 Al
 A

JONNESWAY.

300002	SV	58PCS LUG NUT REMOVAL TOOL SET		
AN010257	2PCS	-SLIDING HAMMER LOCKING PLIERS		
AG010212	STUD	REMOVER 1/4"~3/4"		
AG010055A	7PCS	-IMPACT DRIVER SET		
AG010061	7PCS	-STUD PULLER WRENCH SET: 5, 6, 7, 8, 10, 12, 14MM		
AG010208	8PCS	-TORX PLUS EXTRATOR SET: 3, 4, 5, 6, 7, 8, 10, 12MM		
AG010213	15PCS-1/4" & 1/2"DR. LUG NUT REMOVAL SOCKET SET			
	1/4"DR. SOCKETS: 6, 8, 10, 11, 12MM			
	1/2"DR. SOCKETS: 13, 14, 15, 17, 19, 21, 24, 27MM			
	STRAIGHT RODS: Ø6XØ8X(L)74MM, Ø7XØ12X(L)80MM			
AG010214	4 4PCS-1/2"DR. LUG NUT TWISTED REMOVAL SOCKET SET			
	1/2"DR. SOCKETS: 17,19,21MMX(L)145MM			
	STRAIGHT RODS: Ø12X(L)155MM			
AG010215	5PCS-REVERSE ACTION WHEELS STUD THREAD RESTORE			
	SET: M12X1.25, M12X1.5, M14X1.5, O-RINGX2PCS			
AG010216	9PCS	-AXLE SPINDLE RETHREADING SET, SIZE: M24X2.0,		
	M24X1.5, M22X1.5, M22X1.0, M20X1.5, M20X1.25, 3/4"-20, 13/16"-20			

AI100006SV 30PCS ENGINE SERVICE TOOL SET

AI050049	CHAIN WRENCH (L: 30~160MM)
AI050008-10	10" ADJUSTABLE OIL FILTER WRENCH 50~85MM
AI050002	OIL FILTER WRENCH 3-LEG, 2-WAY, 65~120MM(2-1/2"~4")
AI050043S	3PCS STAINLESS STEEL SCRAPER KNIFE SET
AI050043	OIL FILTER MASTER PLIERS 53~118MM (2-1/8"~4-5/8")
AI050191	MAGNETIC OIL DRAIN PLIERS
AG010034	MAGNETIC PICK-UP TOOL, L:580MM
AI030022	4PCS MINI HOOK & PICK SET
A1030002A	15PCS DRAIN KEY & T-BAR SET
P6008	8" SLIP JOINT PLIERS
D70S9175	GO-THRU IMPACT SCREWDRIVER: SL9.5X175



MECHANIC TOOLS SET





W23108SP 8 PCS 75° OFFSET RING WRENCH SET

CONTENTS:

W03112SP

CONTENTS:

W03

N45112SF

W45308SP

CONTENTS:

CONTENTS: W45

W23 6x7,8x9, 10x11, 12x13, 14x15, 16x17, 18x19, 20x22MM

10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22MM

8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19MM

WRENCH SET

WRENCH SET

W45 8, 10, 11, 12, 13, 14, 17, 19MM

W47108SP 8PCS BOX WRENCH SET

12PCS NON-SLIP CLOSE END AND FAST OPERATING WRENCH SET

12PCS 72 TEETH RATCHETING COMBINATION

8PCS 72 TEETH RATCHETING COMBINATION

JONNESWAY

TOOL TROLLEY & MECHANIC TOOLS SET



JONNESWAY



JONNESWAY



JONNESWAY



JONNESWAY



JONNESWAY -----



CONTENTS:								
W471	6x7, 8x	9, 10x11	, 12x13,	14x15,	16x18,	17x19,	21X22MM	1

W47708SP 8PCS BOX WRENCH SET

CONTENTS: W477 6x7, 8x9, 10x11, 12x13, 14x15, 16x18, 17x19, 21X22MM

S04H4317SP 17PCS 1/2"DR. SOCKET SET

CONTENTS:

S04H4	13PCS-1/2" DR. 6PT FLANK SOCKETS : 8, 10, 12, 13, 14, 17, 19, 21, 22, 23, 24, 26, 32MM
S15H472 1PC-UNIVERSAL JOINT	
S17M4	2PCS-MAGNETIC SPARK PLUG SOCKETS : 16, 21MM
R2904	1PC-1/2" DR. QUICK RELEASE RATCHET HANDLE-36 TEETH





CONTENT S04H2 S04HD2 R3702 S24H2 S46H2









JONNESWAY -

JONNESWAY -----

JONNESWAY -



CONTENT 9PCS-55MM 9PCS-100M

JONNESWAY -



CONTENTS: 9PCS-55MM 9PCS-100M




JONNESWAY.

S04H2125SP		SP	24PCS 1/4"DR. SOCKET SET	
CONTENTS:				
	S04H2	11PC	S - 1/4" DR. SOCKETS: 4,5,5.5,6,7,8,9,10,11,12,13MM	
	S04HD2	9PCS	- 1/4" DR. DEEP SOCKETS: 5,6,7,8,9,10,11,12,13MM	
R3702 1PC - 1/4" DR. RATCHET HANDLE - 48TEETH S24H2 2PCS - 1/4" DR. EXTENSION BARS: 2" & 6"		1/4" DR. RATCHET HANDLE - 48TEETH		
		- 1/4" DR. EXTENSION BARS: 2" & 6"		
	S46H2	346H2 1PC - SPINNER HANDLE		

05SP	5PCS MECHANIC TOOLS SET
NTS:	
1300	1PC-1/2" DR. SLIDING T-BAR, L : 300MM
H4	2PCS-1/2" DR. EXTENSION BAR, L : 125, 250MM
020	1PC-FEELER GAUGES 20 BLADES
08	1PC-8" SLIP JOINT PLIERS

27SP	27PCS 1/2"DR. & 3/8"DR. BIT SOCKET SET
NTS:	
H4	11PCS - 1/2"DR_HEX BIT SOCKET

H4	11PCS - 1/2"DR. HEX BIT SOCKET
H4	10PCS - 1/2"DR. SPLINE BIT SOCKET
H3	6PCS - 3/8"DR. HEX BIT SOCKET



э		

10.	
1ML	T20, T25, T27, T30, T40, T45, T50, T55, T60
MML	T20, T25, T27, T30, T40, T45, T50, T55, T60

S09H4118SP 18PCS 1/2"DR. HEX BIT SOCKET SET

1ML	H5, H6, H7, H8, H10, H12, H14, H17, H19MM
MML	H5, H6, H7, H8, H10, H12, H14, H17, H19MM

MODEL : A



S29H4140SP 40PCS 3/8" & 1/2" DR. POWER BIT SET

_CONTENTS:
14PCS - 10MM HEX BITS: 30MML: 4, 5, 6, 7, 8, 10, 12 75MML: 4, 5, 6, 7, 8, 10, 12
14pcs - 10MM STAR BIT: 30MML: T20, T25, T30, T40, T45, T50, T55 75MML: T20, T25, T30, T40, T45, T50, T55
10pcs - 10MM SPLINE BITS: 30MML: M5, M6, M8, M10, M12 75MML: M5, M6, M8, M10, M12
2pcs - BIT HOLDERS: 3/8" Dr. X 10 MM, 1/2" Dr. X 10MM

JONNESWAY -

MECHANIC TOOLS SET

TOOL TROLLEY &



JONNESWAY ----



W43A 6x7, 8x9, 10x11, 12x13, 14x15, 16x17, 18x19MM

7PCS DOUBLE FLEXIBLE SOCKET WRENCH SET

S03A401SP 7PCS 1/2" DR. IMPACT SOCKET ACCESSORY SET

W43A107SP

CONTENTS:

CONTENTS.	
S03A3A4	1PC - ADAPTOR 3/8"F X 1/2"M
S03A4A	2PCS - ADAPTOR 1/2"F X 3/8"M, 1/2"F X 3/4"M
S03A4U4	1PC - 1/2" DR. UNIVERSAL JOINT
S03A4E	3PCS - 1/2" DR. EXTENSION BAR, LENGTH: 3", 5", 10"

JONNESWAY -



602444006D	22PCS 1/2" DR. 6PT FLANK IMPACT SOCKET SET(MM)
503A41225P	SET(MM)

CONTENTS:

CONTENTS.		
0000.44	11PCS - 1/2" DR. 6PT FLANK IMPACT SOCKETS: 10, 11, 12, 13, 14,	
S03A41	16, 17, 19, 21, 22, 24 MM	
00000044	11PCS - 1/2" DR. 6PT FLANK DEEP IMPACT SOCKETS: 10, 11, 12,	
S03AD41	13, 14, 16, 17, 19, 21, 22, 24 MM	

JONNESWAY -



S03A4222	2SP 22PCS 1/2" DR. 6PT FLANK IMPACT SOCKET SET(SAE)
CONTENTS:	
0000440	11PCS - 1/2" DR. 6PT FLANK IMPACT SOCKETS: 3/8", 7/16", 1/2",
S03A42	9/16", 5/8", 11/16", 3/4", 13/16", 7/8", 15/16", 1"
0004.540	11PCS - 1/2" DR. 6PT FLANK DEEP IMPACT SOCKETS: 3/8", 7/16",
S03AD42	1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8", 15/16", 1"





JONNESWAY



CONTENTS: P018 P038 P068 H01SM

JONNESWAY





JONNESWAY -



JONNESWAY -



JONNESWAY -



CONTENTS: AG010 AG010 AG010 AG010



24



CONTENTS: P2710

JONNESWAY.

P0803SP 3 PCS PLIERS SET

CONTENTS:		
	P087	7" COMBINATION PLIERS
	P097	7" HEAVY DUTY DIAGONAL CUTTING PLIERS
	P118	8" LONG NOSE PLIERS

P018SP1 PLIERS & HEX KEY SET

18	1PC-8" SIDE CUTTING PLIERS	
38	1PC-8" DIAGONAL CUTTER PLIERS	
68	1PC-8" LONG NOSE PLIERS	
1109S	1SET-HEX KEY	

018SP	PROFESSIONAL PLIERS SET
NTENTS:	
P018	1PC-8" SIDE CUTTING PLIERS
P038	1PC-8" DIAGONAL CUTTER PLIERS
P068	1PC-8" LONG NOSE PLIERS

P2803SP 3PCS PLIERS AND ADJUSTABLE WRENCH SET

CONTENTS:	
W27AS10	1PC-10" ADJUSTABLE WRENCH
P2810	1PC-10" BOX JOINT PLIERS
P32M10A	1PC-10" CURVED JAW LOCKING PLIERS

P2710SP PLIERS SET

1PC-10" MACHINED TONGUE & GROOVE WATER PUMP PLIERS P32M10A 1PC-10" CURVED JAWS LOCKING PLIERS WITH WIRE CUTTER

AG010002SP 4PCS INTERNAL & EXTERNAL PLIERS SET

0002 1PC-7"(175MM) STRAIGHT NOSE, INTERNAL PLIERS 0005 1PC-7"(175MM) BENT NOSE, INTERNAL PLIERS 0008 1PC-7"(175MM) STRAIGHT NOSE, EXTERNAL PLIERS 0011 1PC-7"(175MM) BENT NOSE EXTERNAL PLIERS	NIO.	
0008 1PC-7"(175MM) STRAIGHT NOSE, EXTERNAL PLIERS	0002	1PC-7"(175MM) STRAIGHT NOSE, INTERNAL PLIERS
	0005	1PC-7"(175MM) BENT NOSE, INTERNAL PLIERS
0011 1PC-7"(175MM) BENT NOSE EXTERNAL PLIERS	8000	1PC-7"(175MM) STRAIGHT NOSE, EXTERNAL PLIERS
	0011	1PC-7"(175MM) BENT NOSE EXTERNAL PLIERS

MODEL : A



JONNESWAY -



010026SP	5PCS HAMMER & CHISEL SET

M08503SP 3PCS HAMMER & WOOD CHISEL SET

1PC-HEAD DIA 45MM DEAD BLOW HAMMER

1PC-1" WOOD CHISEL W/ACCETATE HANDLE

1PC-160Z BALL PEEN HAMMER W/FIBERGLASS HANDLE

CONTENTS

CONTENTS:

M04016

M11045

M65225

CONTENTS.		
M09300	1PC-300G ENGING HAMMER	
M11035	1PC-HEAD DIA 35MM DEAD BLOW HAMMER	
M61	3PCS COLD CHISEL SET	

JONNESWAY -



M09513SP 13PCS HAMMER & PUNCH-CHISEL SET

CONTENTS

CONTENTS:		
	M07016	1PC - 16 0Z SOFT FACE HAMMER
	M09500	1PC - 500G DIN ENGINEER HAMMER
	M63M106S	6PCS-PIN PUNCH SET (MIRROR POLISH)
	M64M105S	5PCS-PUNCH & CHISEL SET (MIRROR POLISH)

JONNESWAY -



D71PP08SP **8PCS ANTI-SLIP SCREWDRIVERS SET**

CONTENTS:

4PCS - SLOTTED SCREWDRIVERS: 6.5X38, 4X80, 5.5X125, 6.5X150 D71S D71P 4PCS - PHILLIPS SCREWDRIVERS: #2X38, #1X80, #2X100, #3X150

JONNESWAY -



D04PP08SP **8PCS FULL STAR SCREWDRIVER SET**

CONTENTS:

4PCS-SLOTTED SCREWDRIVERS : 6.5x38, 4x80, 5.5x125, 6.5x150 D04S D04P 4PCS-PHILLIPS SCREWDRVIERS : #2x38, #1x80, #2x100, #3x150

JONNESWAY -




D70105SP 5PCS GO-THROUGH IMPACT SCREWDRIVER SET

CONTENTS

CONTENTO.	
D70S	3PCS - SLOTTED SCREWDRIVERS:6.5X125, 8X150, 9.5X175
D70P	2PCS - PHILLIPS SCREWDRIVERS: #2X100, #3X150
























JONNESWAY -







JONNESWAY.

AB10	001SP v	VINDSHIELD REPAIR KIT
CONTEN	NTS:	
Seq.	ITEM NO.	DESCRIPTION
1.	AB010029	WINDSHIELD REMOVAL KIT
2.	AB010017	QUICK RELEASE W/O CUT OUT TOOL

AG010150SP	SNAP RING PLIER SET

CONTENTS:			
ITEM NO.	A (LENGTH)	B (ANGLE)	C (TIP SIZE)
AG010150H	9"	0 °	.090" (2.3 MM)
AG010150G	8-1/2"	70°	.090" (2.3 MM)
AG010150F	8"	0 °	.070" (1.8 MM)
AG010150E	7-1/2"	70°	.070" (1.8 MM)
AG010150D	6"	0 °	.047" (1.2 MM)
AG010150C	5-1/2"	70°	.047" (1.2 MM)
AG010150B	6"	0 °	.038" (1.0 MM)
AG010150A	5-1/2"	70°	.038" (1.0 MM)
HOOK TOOL	5"	0 °	
PICK TOOL	5"	70°	

• For Internal or External Snap Rings Thumbscrew Permits Quick Conversion







AG10001SP 40PCS TAP & DIE SET(MM)

34PCS- TAP AND DIE

3X0.6, M4X0.7, M4X0.75, M5X0.8, M5X0.9, M6X0.75	
7X0.75, M7X1.0, M8X1.0, M8X1.25	
M10X1.5, M12X1.5, M12X1.75, 1/8NPT27	
WRENCH M4-M12	
TYPE TAP WRENCH	
STOCK 25MM	
O CENTER PUNCH	
EW PITCH GAUGE	
SH	







4" 2 Jaw CR-V Gear Puller

4" 3 Jaw CR-V Gear Puller

Seal Puller

AI10002SP BELT DRIVER PULLEY PULLER SET

CONTENTS:

AE310030

AE310035-1

AN010038

JONNESWAY -





AI10003SP ENGINE SERVICE KIT

CONTENTS:	
AI050004T	9PCS - OIL FILTER CAP WRENCH
Al030002A	15PCS - DRAIN KEY & T-BAR SET
AI050049	30-160 MM OIL FILTER CHAIN WRENCH

		DESC
SMM	BMW, FORD	
🔿 эмм	GENERAL MOTOR	
🔘 10ММ	FORD	
○ 12MM	FIAT LANCIA, PEUGEOT	
🔷 14MM	MERCEDES, LANCIA BMW, AUSTIN, AUDI, VW	
🔷 17MM	GENERAL MOTOR	
3/8"	BMW, RENAULT, TOYOTA	
10MM	CITROEN, PEUGEOT, RENAULT, TALBOT, VOLVO	
8MM	FORD	
11MM	NISSAN, SUBARU	
13MM	HONDA, NAZDA, RENAULT, SAAB, VOLVO	
3/8"	GENERAL MOTOR	
7MM		


CRIPTION		
	△ 10MM	RENAULT
	T-BAR TO DRIVE	
	30-16MM OIL FIL	TER CHAIN WRENCH
	3/8" OIL FILTER	CAP WRENCH
	93MM-15	GM, NISSAN, VOLVO, MAZDA, AUDI, V W, ETC
	76MM-14	V W, PORSCHE, MERCEDES, BM W, TOYOTA
	75.6MM-14	MAZDA, GENERAL MOTOR
	38MM	ETC DIESEL ENGINE
	36MM	BENZ, V W, BM W/M52, M60, M73
	32MM	GM, SAAB, SATUM
	30MM	GENERAL MOTOR
	27MM	MERCEDES
	24MM	BM W/5 & 7 SERIES











Vah

JONNESWAY -

AI100

• MADE FROM HARDENED , STAINLESS STEEL. • SHORT/LONG-HANDLE ALUMINUM/STAINLESS STEEL. MTC 306 - QUICK ADJUST DIVDERS. SIZE : 6" • EASY ADJUST. • POLISH FINISH. • METERIAL : CARBON STEEL. MTC 155 - UTILITY TECHNICAL PENCIL. SIZE : 2.0MM • TECHNICAL PENCIL WITH TUNGSTEN LEAD.

V1310SP

V13-SMART VISE CRIMER SERIES. LENGTH : 9~3/4"(247MM) • HRC 48 ° ~ 52 ° MIDDLE CARBON STEEL BODY WITH COMFORTABLE TPR HANDLE THAT LESS TIRED FOR LONG TIME CRIMPIING. V1310A-SMART VISE CRIMER- A TYPE. • SUITABLE FOR INSULATED TERMINALS / COLOR NESTS. • 22-10 AWG (0.5MM~6MM). V1310B-SMART VISE CRIMER- B TYPE. • SUITABLE FOR NON-INSULATED OPEN BARREL CONNECTORS , COMMERCIAL TYPE. • 22-10 AWG (0.5MM~6MM). V1310E-SMART VISE CRIMER- E TYPE. • SUITABLE FOR NON-INSULATED TERMINALS . • 22-8 AWG (0.5MM~10MM). V1401-PROFESSIONAL CRIMPING TOOL & WIRE STRIPPER. 1PC - #2.5 HEX KEY WRENCH. 2PC - REPLACEABLE SCREWS. 60PCS - TERMINALS KIT. AR030044 - CORDLESS CIRCUIT TESTER. • DETECTS FROM 3 TO 28 VOLTS . • SAFE WITH ECMS , SENSORS , TEANSDUCERS , AIRBAGS, ETC. • NO GROUND WIRE OR CLIP REQUIRED. • REPLACEABLE LONG-LIFE AIKALINE BATTERIES INCLUDED. AG010031A - 2 IN1 TELESOPIC MIRROR WITH MAGNETIC END.








JONNESVIAY.

AI10001SP	VALVE TIMING INSTALLER/REMOVER TOOL KIT
	 Ideal For The Replacement Of Valve Stem Seals Without Removing The Cylinder Head.
CONTENTS:	·

ITEM NO.	DESCRIPTION
AN010064	OVERHEAD VALVE SPRING COMPRESSOR
AI020056	VALVE STEM SEAL PLIERS
AI020099	HAND MOLDING VALVE SPRING COMPRESSOR
AI020100	VALVE HOLDER
AI010012A	VALVE COLLETS REPLACER
	(Seq.4)



MTC101SP 7PC. PRECISION MEASURING TOOL KIT

MTC 150 - LARGE RANGE ELECTRONIC CALIPER. SIZE : 6" DIMENSION : 150X0.01MM • EASY TO READ DIGITAL LARGE LCD DISPLAY WITH INCH / METRIC CONVERSION.

MTC 153 - PRECISION ALUMNUM SQUARE. SIZE : 300MMM DIMENSION : 300X4X1.0

• SURFACE TREATMENT : POLISHED FINISH. • TEST STANDARD : 90° ± 0.2°

MTC 156 - STAINLESS STEEL RULER. SIZE : 12" / 30CM DIMENSION : 334X23.7X1.0 • SURFACE TREATMENT : POLISHED FINISH.

• PROCESS OF SCALE : ACID- ETCHED.


MTM 1025 - MICROMTERS. SIZE : 0-25MM

• SATIN CHEOME FINISH THIMBLE AND HANDLE WITH EASY READING.

MTM 1050 - MICROMTERS, SIZE : 25-50MM

• SATIN CHEOME FINISH THIMNLE AND HANDLE WITH EASY READING.

70PC. CRIMPER AND STRIPPER ASSORTED TERMINALS TOOL KIT





04H4125SF	25PCS 1/2"DR.	6PT FLANK	SOCKET SET
-----------	---------------	-----------	------------

CONTENTS

UNTEINTS:	
S04H4	18PCS-1/2" DR. SOCKETS : 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 27, 30, 32MM
S17H4	2PCS-SPARK PLUG SOCKETS : 16 & 21MM
S24H4	2PCS EXTENSION BARS : 5" & 10"
S23H4125	1PC-SLIDING T BAR
S15H472	1PC-UNIVERSAL JOINT
R3704	1PC-12" DR. 48 TEETH QUICK RELEASE RATCHET HANDLE

JONNESWAY -



MODEL : B

CONTEN M6310 M6410 W27AS

M6451

JONNESWAY -



H10MB CONTENT H10MB0

JONNESWAY -----



H10MT

CONTENT H10MT

JONNESWAY -----





W2611







CONTENTS:	
S04H2	12PCS-1/4"DR.SOCKET:4,4.5,5,5.5,6,7,8,9,10,11,12,13,MM
S04HD2	4PCS-1/4"DR.DEEP SOCKET:8,10,12,13,MM
S04H3	8PCS-3/8"DR.SOCKET:14,15,17,18,19,20,22,24,MM
S04HD3	3PCS-3/8"DR.DEEP SOCKET:14,15,17,MM
R3702	1PC-1/4"DR.48TEETH QUICK RELEASE RATCHET HANDLE
R3703	1PC-3/8"DR.48TEETH QUICK RELEASE RATCHET HANDLE
S24H2	2PCS-EXTENSION BAR:1/4"DR.X 50MM,150MM
S24H3	2PCS-EXTENSION BAR: 3/8"DR.75MM,250MM
S16H302	1PC-ADAPTER FOR EXTENSION BAR 3/8"(F)X1/4"(M)
S16H304	1PC-ADAPTER FOR EXTENSION BAR 3/8"(F)X1/2"(M)
S17H3	2PCS-3/8"DR.SPARK PLUG SOCKET:16MM,21MM
S15H2	1PC-1/4"DR.UNIVEER JOINT
S15H3	1PC-3/8"DR.UNIVEER JOINT
S26H2	1PC-1/4"DR.SPINNER HANDLE
16PCS: 1/4"DR.BIT	SOCKET L:32MM
S10H2	3PCS-SLOTTED BIT SOCKET:4,5.5,7,MM
S09H2	4PCS-HEX BIT SOCKET :3,4,5,6,MM
S07H2	6PCS-STAR BIT SOCKET :T10,T15,T20,T25,T27,T30,
S11H2	3PCS-PHILLIPS BIT SOCKET:PH1,PH2,PH3,

S04H3157SP 57PCS 1/4" & 3/8" DR. 6PT FLANK SOCKET SET

JONNESWAY -----



S04H3536SP	36PCS 3/8" DR. SOCKET & COMBINATION WRENCH SET		
CONTENTS:			
S04H3	17PCS-3/8" DR. 6PT FLANK SOCKETS : 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22MM		
W261	11PCS-COMBINATION WRENCH : 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17MM		
R3403	1PC-72 TEETH RATCHET HANDLE		
S24H3	3PCS-EXTENSION 3", 6", 9"		
S17H3	2PCS-SPARK PLUG SOCKET, 16, 21MM		
S15H356	1PC-UNIVERSAL JOINT		
S16H403	1PC-ADAPTOR FOR EXTENSION, 1/2"(F)X3/8"(M)		

JONNESWAY -----



CONTENTS:	
S05H42	9PCS-1/2" DR. 12PT SOCKETS (CR-V) : 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8", 15/16"
S05H41	9PCS-1/2" DR. 12PT SOCKETS (CR-V) : 11, 12, 13, 14, 15, 17, 18, 19, 20MM
S05HD42	9PCS-1/2" DR. 6PT DEEP SOCKETS (CR-V) : 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8", 15/16"
S05HD41	9PCS-1/2" DR. 6PT DEEP SOCKETS (CR-V) : 11, 12, 13, 14, 15, 17, 18, 19, 20MM
R2804Q	1PC-1/2" DR. 10" QUICK RELEASE RATCHET HANDLE - 48 TEETH
S24HC4125	1PC-1/2" DR. 5" EXTENSION BAR (CR-V)

S05H4238SP 38PCS 1/2"DR. SOCKET SET

M645115SP	15PCS HACKSAW, CHISEL, PUNCH & ADJUSTABLE WRENCH SET
ONTENTS:	
M63106S	6PCS-PIN PUNCH SET, BLACK FINISH : 2x8x115MM, 3x8x125MM, 4x9.5x150MM, 5x9.5x165MM, 6x12.7x180MM, 8x12.7x180MM
M64105S	5PCS-CHISEL PUNCH SET/BLACK FINISH : TAPER PUNCH : 6x9.5x120MM, CENTER PUNCH : 2x9.5x120MM CAPE CHISEL : 5x9.5x130MM, COLD CHISEL : 12x9.5x130MM, PIN PUNCH: 4x9.5x150MM
W27AS10	1PC-10" ADJUSTABLE WRENCH W/SAE & MM SCALE
MHS100AG	3PCS-HACKSAW SET : 1PC HEAVY DUTY DELUXE TYPE HACKSAW & 2PCS-SPARE SAW BLADE

808SP	8PCS TWO WAY BALL POINT & HEX KEY SET
NTS:	
308S	8PCS-2x100, 2.5x100, 3x100, 4x100, 5x150, 6x150, 8x200, 10x200mm

ro8sp	8PCS TWO WAY STAR & TAMPERPROOF KEY SET, SNCM+V, MAT FINISHED
rs:	

T10X100, T15X100, T20X100, T25X100, T27X150, T30X150, T45X200, T50X200

16SP	16PCS COMBINATION WRENCH SET
ITS:	
61	16PCS-COMBINATION WRENCH : 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 22, 24MM



1			
w	D	н	
26"	12"	15"	Inch
660	305	380	mm
6.7"	10.5"	1.6"	Inch
172	270	41	mm
22.5	10.5"	1.6"	Inch
572	270	41	mm
22.5	10.5"	2.5"	Inch
572	270	65	mm
N.W.	G.W.	CUFT	
23kgs	26.9kgs	3.97'	
	26" 660 6.7" 172 22.5 572 22.5 572 22.5 572 N.W.	26" 12" 660 305 6.7" 10.5" 172 270 22.5 10.5" 572 270 22.5 10.5" 572 270 22.5 10.5" 572 270 22.5 10.5" 572 270 N.W. G.W.	26" 12" 15" 660 305 380 6.7" 10.5" 1.6" 172 270 41 22.5 10.5" 1.6" 572 270 41 22.5 10.5" 2.5" 572 270 65 N.W. G.W. CUFT

Steel thickness : Top chest : 1.0mm drawer, 1.0mm body, 1.0mm drop-front.
100% open ball bearing slide on small and full-width drawer.
Easy move ball bearing drawer slides on all drawers for professional use.
Drawer dentent (stopper) to prevent unintentional opening of drawer for replacement.

JONNESWAY -

JONNESWAY -



	w	D	н	
OVERALL	26"	18"	19"	Inch
OVERALL	660	455	484	mm
5 DRAWERS	22.8"	15"	1.83"	Inch
5 DRAWERS	579	380	46.6	mm
1 DRAWER	22.8	15"	2.2"	Inch
IDRAWER	579	380	56	mm
	N.W.	G.W.	CUFT	
	46.5kgs	52.5kgs	8.5'	



JONNESWAY ----

JONNESWAY



C 2011002	66PCS TOOL CHEST SET		
C-3DH203	• SIZE : 470mm x 220mm 350mm		
CONTENTS:			
W27AS10	1PC-10" ADJUSTABLE WRENCH		
M07016	1PC-16 OZ SOFT FACE HAMMER		
M09300	1PC-300g ENGINEER HAMMER		
P2710	1PC-10" MACHINED TONGUE & GROOVE WATER PUMP PLIER		
P106	1PC-6" DIAGONAL CUTTER PLIER		
P116	1PC-6" LONG NOSE PLIER		
P087	1PC-7" SIDE CUTTING PLIER		
H01M109S	9PCS-HEX KEY SET (1.5, 2, 2.5, 3, 4, 5, 6, 8, 10)		
S04H41	18PCS-1/2" DR. SOCKET (10~32mm)		
W25	8PCS-OPEN END WRENCH (6~22mm)		
W23	8PCS-75° OFFSET WRENCH (6~22mm)		
M64105S	5PCS-CHISEL - PUNCH SET		
D70	6PCS - THRU SCREWDRIVER SET		
C-3DH2	1PC-PORTABLE TOOL		
R3704	1PC-1/2" DR. QUICK RELEASE 48 TEETH RATCHET HANDLE W/ANTI SLIP GIRIP		
S15H472	1PC-1/2" DR. UNIVERSAL JOINT		
S24H4	2PCS-EXTENSION BAR 5", 10"		

C-3DH262

S04H4120ST D70SP06ST



C-T5 WORKBENCH WITH 3 DRAWER CHEST (BALL BEARING SLIDE)				
	w	D	н	
0//50411	59"	27.5"	59"	Inch
OVERALL	1500	700	1500	mm
3 DRAWERS	26"	12"	9.8"	Inch
3 DRAWERS	660	305	250	mm
	N.W.	G.W.	CUFT	
	71kgs	74.5kgs	7.74'	



32

JONNESWAY.



TETORON TOOL BAG

SIZE - 620X250X310MM

6
2

3-SECTIONS PORTABLE TOOL CHEST

• SIZE : 470mm x 220mm 350mm

62PCS TOOL CHEST SET CHEST SIZE: 470 X 220 X 350MM

- CONTENTS: 18PCS 1/2" DR. SOCKET (S04H4): 10 - 32MM 18PCS COMBINATION WRENCH (W26): 6 - 22, 24MM 9PCS EXTRA LONG ARM HEX KEY (H03SM109S) SIZE:1.5, 2, 2.5, 3, 4, 5, 6, 8, 10MM 6PCS GO-THRO SCREWDRIVER (D70) : PH#1X75, PH#2X100, PH#3X150, 5.5X100, 6.5X150, 8.0X175 1PC 7" COMBINATION PLIERS (P087) 1PC 6" DIAGONAL CUTTER PLIER (P106) 1PC 6" LONG NOSE PLIERS(P116) 1PC 1/2" DR. ANTI-SLIP RATCHET HANDLE (R2904) 2PCS 1/2" DR. EXTENSION BAR: 125, 250MM (S24H4) 1PC 1/2" DR. SLIDING T-BAR 300MM (S23H41300) 1PC 1/2" DR. FLEXIBLE HANDLE 450MM (S22H41450) 1PC 1/2" DR. UNIVERSAL JOINT (S15H472) 1PC 1/2" DR. WOBBLE EXTENSION BAR (S21H4150)
- 1PC 1/2" DR. SPARK PLUG 21MM (S17H4121)
- 1PC 3-SECTIONS PORTABLE TOOL CHEST (C-3DH2)



C-A3

Designed for

C-A3B

Designed for

HANDLE

HANDLE

C-5DW1, C-5DW2, C-7DW1, C-7DW2, C-6DW1, C-6DW2, C-4DW1, C-4DW2

C-5DW1, C-5DW2, C-7DW1, C-7DW2, C-6DW1, C-6DW2, C-4DW1, C-4DW2

JONNESWAY



JONNESWAY



C-A456	WORKING TABLE SET
CONTENTS:	
C-A4	PLASTIC HANDLE
C-A5	WORKING TABLE
C-A6	PLASTIC HOLDER

JONNESWAY



C-A8	4" ALL STEEL SWIVEL-BASE VISE			
C-A11	6" ALL STEEL SWIVEL-BASE VISE			
C-A13	10" ALL STEEL SWIVEL-BASE VISE			
Only 3" & 4" for C A9 working bench				

JONNESWAY



C-DB H	DOKS FOR:C-T5
C-DBU7	2" SINGLE HOOK
C-DBU3	4" SINGLE HOOK



°C

JONNESWAY.

TORQUE WRENCH SERIES

JONNESWAY

• Professional Quality meets ANSI/DIN Standards Special Oil-Resistance Handle • Accuracy to ±3% of Set Load • Regular and Window Scale to Meet All Demands Also Available in Digital Torque Wrench



Operation Manual

RATCHET HANDLE

TORQUE WRENCH &

1. Switch the safety lock in the bottom of the handle to the left to unlock. 2. Once the safety lock is unlocked, turn the torque adjustment ring Attention: Failing to unlock the safety lock before adjusting the torque setting will seriously damage the lock function.



until the display window shows the desired torque setting. Then turn the safety lock to the right to lock the setting.




Attention: When turning the torque adjustment ring , DO NOT exceed the maximum torque, or the inner mechanism will be seriously damaged

Application: For industrial market, such as automobile

assembly line, production line, etc.

3.Zero the torque wrench after operation. Attention: When zeroing the torque wrench, DO NOT exceed the "Stop" sign shown in the display window





_	
• S	

- Accuracy: ±3%
- · Torque setting is displayed in numbers, easy to identify the torque settings
- With soft handle to increase work comfort

T21 MICROMETER TORQUE WRENCH (RIGHT HAND) SQUARE DRIVER WEIGHT PACKING RANGE ITEM NO. PCS/CTN (ka)

T21025N	1/4"	5-25N.m.	343	0.8	6
T21026N	3/8"	5-25N.m.	343	1	6
ITEM NO.	SQUARE DRIVER	RANGE	L (mm)	WEIGHT (kg)	PACKING PCS/CTN
T21020F	1/4"	4-20Ft-Lbs	343	1	6
T21035F	3/8"	7-35Ft-Lbs	420	1	6
T21076F	1/2"	15-75Ft-Lbs	420	1.2	6
T21250F	1/2"	50-250Ft-Lbs	640	1.8	4


T27 ADJUSTABLE TORQUE WRENCH Accuracy: ±4%

. Unlock: Push the handle back to unlock. (Smart design: users do not have to hold still the handle to keep it unlocked)





· Setting: Users set torque as the drawing below (EX : 66N.m)





ADJUSTABLE TORQUE WRENCH (RIGHT HAND) **T27**

ITEM NO.	SQUARE DRIVE	RANGE	L (mm)	WEIGHT (kg)	PACKING PCS/CTN	ITEM	NO.	SQUARE DRIVE	RANGE	L (mm)	WEIGHT (kg)	PACKING PCS/CTN
T27010N	1/4"	2~10 NM	371	0.6	25	T271	00F	3/8"	15~100 FT-LB	464	1.1	12
T27030N	1/4"	4.5~30 NM	371	0.6	25	T271	50F	1/2"	20~150 FT-LB	531	1.4	12
T27031N	3/8"	4.5~30 NM	371	0.6	25	T272	50F	1/2"	30~250 FT-LB	585	1.5	12
T27100N	3/8"	20~100 NM	464	1.1	12	T276	00F	3/4"	100~600 FT-LB	1090	4.9	2
T27200N	1/2"	40~200 NM	531	1.4	12	T277	50F	3/4"	150~750 FT-LB	1090	4.9	2
T27340N	1/2"	60~340 NM	585	1.5	12	T277	51F	1"	150~750 FT-LB	1090	4.9	2
T27500N	3/4"	100~500 NM	847	3.9	4							
T27800N	3/4"	150~800 NM	1090	4.9	2							
T271000N	3/4"	200~1000 NM	1090	4.9	2							
T271001N	1"	200~1000 NM	1090	4.9	2							



. Lock: After setting the desired torque, push the handle forward to lock.



· Handle position: Make sure to keep hands on the centered handle.



· Operate: Make sure to use the torque wrench with a stable force and stop the operation when hearing the sound "click". It

JONNESWAY ----



Г09	TORQUE MULTIPLIER

ITEM NO.	NPUT DR.	OUTPUT DR.	GEAR	WIDTH	HEIGHT	MAX. OUTPUT
	(FEMALE)	(MALE)	RATIO	(MM)	(MM)	TORQUE (N-M)
T094602	1/2" DR.	3/4" DR.	1: 9	82	98	1500

 Accuracy: ± 10% • Warning: Do not use with impact wrench.





ITE R66

ié di pereağ î.

T09 TORQUE MULTIPLIER SET							
ITEM NO.	TORQUE RATIO	MAX. INPUT TORQUE	MAX. OUTPUT TORQUE	STRAIGHT REACTION BAR	90 REAC BASE)° TION BAR	BREAK-AWAY SAFETY ADAPTER
T09682500	1 : 3.3	3/4"Dr.× 758N-m (560Ft-lb)	1"Dr.× 2500N-m (1850Ft-lb)	1PC	1PC	1PC	2PCS
Accura	acv: ±	10%					

• Warning: Do not use with impact wrench.







JONNESWAY -

JONNESWAY

JONNESWAY -






JONNESWAY -









T30200NS 11PCS INTERCHANGEABLE TORQUE WRENCH SET (14X18)						
ITEM NO.	CONNECT HEAD SIZE	O	TORQUE RANGE	Ŷ	WEIGHT (G)	
T30200NS	14x18	1/2"	40~200NM	13, 14 15, 17 19, 22 24, 27 30MM	3847	

38

JONNESWAY.

R66	
1.00	

RATCHET HANDLE - 60 TEETH

• High quality material • Ergonomic grip Anti Slip handle
 Rotating Function Pushable head

• The anti slip ratchet handle is specially designed with rotating function. Users can remove or install nuts and bolts by rotating without operation back and forth in confined spaces. The rotating function could be adjusted freely by pushing or pulling the head back for forward and reverse direction. The R66 series is ideal for limited area usage.

ITEM	SIZE	GEAR TEETH	L (mm)	WIDTH	HEIGHT	WEIGHT
R6602	1/4"	60	180	27	23	181
R6603	3/8"	60	240	36	29	384
R6604	1/2"	60	290	42	37	645

RD0503

3/8" DR. SWIVEL PALM RATCHET

RD0502

1/4" DR. SWIVEL PALM RATCHET

RD05H2

1/4" DR. SWIVEL PALM RATCHET (BIT HOLDER)

RD05H22S 22PCS GO-THRU SWIVEL PALM RATCH								
Contents:								
1PC-GO-THRU SWIVEL PLAM RATCHET W/ 1/4"DR. SWIVEL ADAPTER								
11PCS-GO-THRU SOCKETS (MM/SAE): 4.5mm(3/16"), 5mm(13/64"), 5.5mm(7/32"),								
6mm(1/4"), 7mm	(9/32"), 8mm(5/16"), 9mm(11/32"), 10mm(3/8"), 11mm(7/16"),							
12mm(15/32"), 13mm(1/2")								
1PC-BIT HOLDER								
1PC-2" EXTENSION BA	R							

8PCS-BITS (T10, T15, T20, T25, PH1, PH2, PH3, SLOTTED 6.5mm)





0

R3	6	• DRIVE	E-CHRON R-CHROM POLISHEI	E MOLYB	DENUM S	-	SE				
	PACKING										
ITEM NO.	DRIVE	WIDTH (mm)	HEIGHT (mm)	L (mm)	WEIGHT (g)	TORQUE (NM)	INNER PC/BOX	OUTER PC/CTN			
R3602	1/4"	22	22	128	100	68	10	60			
R3603	3/8"	30	29	198	280	245	10	40			
R3604	1/2"	42	38	250	620	647	5	30			

LEVER TYPE RATCHET HANDLE-48 TEETH

JONNESWAY

		ANTI-SLIP GRIP RATCHET HANDLE-48 TEETH									
R3	37	HANDLE-CHROME VANADIUM STEEL DRIVER-CHROME MOLYBDENUM STEEL SATIN FINISHED QUICK RELEASE									
		WIDTH	HEIGHT		WEICHT	TORQUE	PAC	KING			
ITEM NO.	DRIVE	(mm)	(mm)	(mm)	(g)	(NM)	INNER PC/BOX	OUTER PC/CTN			
R3702	1/4"	23	22	135	115	68	10	60			
R3703	3/8"	30	29	198	280	245	5	40			
R3704	1/2"	42	38	253	620	647	5	30			

LEVER TYPE STUBBY RATCHET HANDLE-48 TEETH

80

180

420

(g) TORQUE INNER OUTER PC/BOX PC/CTN

10

10

5

60

40

30

68

245

647

HANDLE-CHROME VANADIUM STEEL
 DRIVER-CHROME MOLYBDENUM STEEL
 FULLY POLISHED
 QUICK RELEASE

L

(mm)

90

115

150

WIDTH HEIGHT (mm) (mm)

22

29

38

22

30

42

1/4"

3/8"

1/2"





JONNESWAY



Link Link WIDTH HEIGHT WEIGHT PACKING TEM NO. SIZE L (mm) WIDTH HEIGHT WEIGHT INNER PC/BOX OUTER PC/BOX OUTER PC/BOX R2902 1/4"Dr. 146 26 22 120 25 100 R2903 3/8"Dr. 185 32 30 265 12 48 R2904 1/2"Dr. 278 40 38 570 6 24			A	NTI-SLI	P GRIP	RATCH	ET HANI	DLE-36 1	ГЕЕТН
TEM NO. SIZE L (mm) WIDTH HEIGHT WEIGHT INNER PC/BOX OUTER PC/CTN R2902 1/4"Dr. 146 26 22 120 25 100 R2903 3/8"Dr. 185 32 30 265 12 48	DRIVER-CHROME MOLYBDENUM STEEL								
TEM NO. SIZE L (mm) WIDTH HEIGHT WEIGHT INNER PC/BOX OUTER PC/CTN R2902 1/4"Dr. 146 26 22 120 25 100 R2903 3/8"Dr. 185 32 30 265 12 48	PACKING								
R2903 3/8"Dr. 185 32 30 265 12 48	TEM NO.	EM NO. SIZE		L (mm)	WIDTH	HEIGHT	WEIGHT	INNER	OUTER
	R2902	1/4"Dr.		146	26	22	120	25	100
R2904 1/2"Dr. 278 40 38 570 6 24	R2903	3/8"Dr.		185	32	30	265	12	48
	R2904	1/2"Dr.		278	40	38	570	6	24

JONNESWAY



_		STUBBY FLEXIBLE RATCHET HANDLE WITH ANTI-SLIP GRIP-36 TEETH							
R42 • HANDLE-CHROME VANADIUM STEEL • DRIVER-CHROME MOLYBDENUM STEEL • CHROME PLATED • QUICK RELEASE									
					HEIGHT	WEIGHT (g)	PACKING		
TEM NO.	SIZE		(mm) WIDTH				INNER PC/BOX	OUTER PC/CTN	
R4202	1/4" DR.		125	27	25	140	25	100	
R4203	3/8" DR.		156	32	33	306	12	48	
R4204	1/2" DI	٦.	191	42	42	540	6	24	





JONNESWAY



JONNESWAY





JONNESWAY.

		Η	EAVY DU	ITY QUIC	K RELE	ASE RATC	HET HANDLE	-24 TEETH	
)(6	•		CHROME	MOLYB	IUM(SAE61 DENUM STE • QUIC			
				-		WEIGUT	PACI	KING	
).	DRIVE		D1 (mm)	l (mm)	L (mm)	WEIGHT (KGS)	INNER PC/BOX	OUTER PC/CTN	
	1/4"		28	11.2	141	0.16	10	100	
	3/8"		36	15	195	0.35	10	50	

		A	NTI SLI	P GRIP	RATCHE	ET HAND	DLE-72 1	FEETH
R48 • HANDLE-CHROME VANADIUM STEEL • DRIVER-CHROME MOLYBDENUM STEEL • SATIN FINISHED • QUICK RELEASE								
							PACI	KING
ITEM NO.	ITEM NO. SIZE		(mm)	WIDTH	HEIGHT	WEIGHT	INNER PC/BOX	OUTER PC/CTN
R4802	1/4"Dr.		146	26	22	120	25	100
R4803	3/8"Dr.		185	32	30	265	12	48
D 4004	4 (0)		070	40	00	570	0	0.1

40

38 570 6

24

		F	LEXIBL	E RATC	HET HA	NDLE-72	2 TEETH	I		
R49	9	HANDLE-CHROME VANADIUM STEEL DRIVER-CHROME MOLYBDENUM STEEL FULLY POLISHED QUICK RELEASE								
								WEIGUT	PAC	KING
ITEM NO.	SIZE		L (mm)	WIDTH	HEIGHT	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN		
R4902	1/4" DR.		141	27	25	167	25	100		
R4903	3/8" DR.		288	32	33	480	6	36		
R4904	1/2" DR		310	42	42	798	6	24		

	RATCHET EXTENDABLE HANDLE - 72TEETH						
1	HANDLE- CHROME VANADIUM STEEL DRIVER-CHROME MOLYBDENUM STEEL CHROME PLATED						
TEM NO		DRIVER	LENGTH (mm)				

300~440

1/2"DR.

	3/4" DR. REVERSIBLE RATCHET HANDLE								
2	• D	ANDLE-CHROME VAN RIVER-CHROME MOL HROME PLATED							
EM NO.		SIZE	L (mm)	WEIGHT (kg)					
1206		3/4" Dr.	500	1.8					




- Professional Quality: ANSI / DIN Standards
- Super Torque: 1.3 times as ANSI & 1.5 times as DIN
- Metric Size & SAE Size
- Full Ranges including Jumbo Type
- Mirror Polished & Matt Finished
- Flank Points to Protect Nuts
- 5 Degree Each Catch for 72 Teeth Ratcheting Combination Wrench











PRODUCTS' FUNCTIONS AND SPECIAL FEATURES:

- 1.72 Teeth ratcheting gear creates high torque and 5 degrees each catch for operation in tight space. 2.Chrome-Vanadium steel and special heat treatment
- provide thin walls with special strength. 3.Mirror Polished.
- 4.Meeting ANSI Standard.

JONNESWAY







W4

TEM NO W45108 W45109

W45110 W45111 W45112 W45113 W45114 W45115

W45116 W45117

W45118

W45119 W45121

W45122

W45123

W45124

JONNESWAY



JONNESWAY	R
-----------	---

	72 TEETH RATCHETING COMBINATION WRENCH									
• CH	ROME VA	NADIUM	• MIRRO	DR POLIS	HED					
•	B	6	D	F		PAC	KING			
(mm)	(mm)	(mm)	(mm)	(mm)	(g)	INNER PC/BOX	OUTER PC/CTN			
135.4	17.1	4.9	6.9	16.55	38	12	120			
159.5	20.7	5.8	7.5	20.2	60	12	120			
159.5	20.7	5.8	7.5	20.2	60	12	120			
165.9	22.6	6.0	8.3	22.4	68	12	120			
168.6	23.8	6.2	8.3	24.9	84	12	120			
178.5	24.9	6.5	8.5	26.4	94	12	120			
190.5	27.0	7.0	8.6	28.24	104	12	120			
199.4	28.1	7.2	9.6	31.0	130	12	120			
206.4	29.9	7.8	9.6	33.27	148	12	120			
225.4	31.9	8.2	19.8	35.53	192	12	72			
236.4	33.4	8.6	10.6	36.4	192	12	72			
247.4	34.4	8.8	10.6	38.4	240	12	72			
281	42.6	9.5	13.0	45.7	390	6	48			
281	42.6	9.5	13.0	45.7	390	6	48			
311	46.5	10.0	13.5	51.7	520	6	48			
311	46.5	10.0	13.5	51.7	520	6	36			
	A (mm) 135.4 159.5 165.9 168.6 178.5 190.5 199.4 206.4 225.4 236.4 247.4 281 281 281 311	A (mm) B (mm) 135.4 17.1 159.5 20.7 159.5 20.7 159.5 20.7 165.9 22.6 168.6 23.8 178.5 24.9 190.5 27.0 199.4 28.1 206.4 29.9 225.4 31.9 236.4 34.4 247.4 34.4 281 42.6 281 42.6 311 46.5	A (mm) B (mm) C (mm) 135.4 17.1 4.9 159.5 20.7 5.8 159.5 20.7 5.8 159.5 20.7 5.8 165.9 22.6 6.0 168.6 23.8 6.2 178.5 24.9 6.5 190.4 28.1 7.2 206.4 29.9 7.8 225.4 31.9 8.2 236.4 33.4 8.6 247.4 34.4 8.8 281 42.6 9.5 311 46.5 10.0	A (mm) B (mm) C (mm) D (mm) 135.4 17.1 4.9 6.9 159.5 20.7 5.8 7.5 159.5 20.7 5.8 7.5 159.5 20.7 5.8 7.5 165.9 22.6 6.0 8.3 168.6 23.8 6.2 8.3 178.5 24.9 6.5 8.5 190.5 27.0 7.0 8.6 206.4 29.9 7.8 9.6 205.4 31.9 8.2 19.8 236.4 33.4 8.6 10.6 247.4 34.4 8.8 10.6 241 42.6 9.5 13.0 281 42.6 9.5 13.0	A (mm) B (mm) C (mm) D (mm) E (mm) 135.4 17.1 4.9 6.9 16.55 159.5 20.7 5.8 7.5 20.2 159.5 20.7 5.8 7.5 20.2 159.5 20.7 5.8 7.5 20.2 165.9 22.6 6.0 8.3 22.4 168.6 23.8 6.2 8.3 24.9 178.5 24.9 6.5 8.5 26.4 190.5 27.00 7.00 8.6 28.24 190.5 27.00 7.00 8.6 28.24 190.4 28.1 7.2 9.6 33.27 225.4 31.9 8.2 19.8 35.53 236.4 33.4 8.6 10.6 36.4 247.4 34.4 8.8 10.6 38.4 281 42.6 9.5 13.0 45.7 281 42.6 9.5 13.0	(mm) (mm) <th< td=""><td>A (mm) B (mm) C (mm) D (mm) E (mm) WEIGHT (g) PACL INNER PC/BOX 135.4 17.1 4.9 6.9 16.55 3.8 12 135.4 17.1 4.9 6.9 16.55 3.8 12 159.5 20.7 5.8 7.5 20.2 60 12 159.5 20.7 5.8 7.5 20.2 60 12 165.9 22.6 6.0 8.3 22.4 68 12 168.6 23.8 6.2 8.3 24.9 84 12 178.5 24.9 6.5 8.5 26.4 94 12 190.5 27.0 7.0 8.6 28.4 104 12 190.5 27.0 7.0 8.6 33.0 130 12 206.4 29.9 7.8 9.6 33.27 148 12 215.4 31.9 8.2 19.8 35.53 192 1</td></th<>	A (mm) B (mm) C (mm) D (mm) E (mm) WEIGHT (g) PACL INNER PC/BOX 135.4 17.1 4.9 6.9 16.55 3.8 12 135.4 17.1 4.9 6.9 16.55 3.8 12 159.5 20.7 5.8 7.5 20.2 60 12 159.5 20.7 5.8 7.5 20.2 60 12 165.9 22.6 6.0 8.3 22.4 68 12 168.6 23.8 6.2 8.3 24.9 84 12 178.5 24.9 6.5 8.5 26.4 94 12 190.5 27.0 7.0 8.6 28.4 104 12 190.5 27.0 7.0 8.6 33.0 130 12 206.4 29.9 7.8 9.6 33.27 148 12 215.4 31.9 8.2 19.8 35.53 192 1			



7PCS 72 TEETH RATCHETING COMBINATION WRENCH SET(MM)

Contents : 10, 12, 13, 14, 15, 17, 19MM Packing : PLASTIC HOLDER 20SETS/CTN/26KGS/28KGS/2.2'

08S	8PCS 72 TEETH RATCHETING COMBINATION WRENCH SET(SAE)
	Contents : 5/16", 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4" Packing : PLASTIC HOLDER 10SETS/CTN/19.2KGS/20.5KGS/1.2'

JONNESWAY.



JONNESWAY -

WRENCH SERIES

44



13PCS - 72 TEETH RATCHETING COMBINATION WRENCH : 8, 10, 12, 13, 14, 17, 19, 21, 22, 24, 27 30, 32MM 1 PC BIT ADAPTER : 1/4"

WRENCH SET

4PCS - ADAPTER : 3/4", 1/2", 3/8", 1/4" DR.

72 TEETH RATCHETING COMBINATION

8 PCS 72 TEETH RATCHETING COMBINATION W45508S WRENCH SET

CONTENTS:

W45117S

CONTENTS:

- 4 PCS-RATCHETING COMBINATION WRENCH :10,13,17,19 MM
- 3 PCS-SOCKET ADAPTOR WITH QUICK RELEASE :1/4",3/8",1/2"DR.
- 1/4"DR. SOCKET ADAPTOR FOR 10MM RATCHETING WRENCH
- 3/8"DR. SOCKET ADAPTOR FOR 13MM RATCHETING WRENCH
- 1/2"DR. SOCKET ADAPTOR FOR 19MM RATCHETING WRENCH
- 1PC- BIT HOLDER FOR 10MM RATCHETING WRENCH

Packing:BLOW CASE


JONNESWAY -



	10PCS 72 TEETH RATCHETING COMBINATION WRENCH SET
15110S	Contents : 6PCS-RATCHETING WRENCH:8, 10, 12, 13, 17, 19MM 3PCS-SOCKET ADAPTOR WITH QUICK RELEASE:1/4", 3/8", 1/2" DR
	1PC-BIT HOLDER Packing : BLOW CASE

JONNESWAY -





W51 (STUBBY TYPE)									
ITEM NO.	SIZE (metric)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	WEIGHT (g)		
W51108	8	93.0	17.4	4.9	7.4	16.53	30		
W51109	9	95.4	20.9	5.8	7.4	20.19	40		
W51110	10	95.4	20.9	5.8	7.4	20.19	40		
W51111	11	105.0	23.4	6.2	8.7	25.1	60		
W51112	12	105.0	23.4	6.2	8.7	25.1	60		
W51113	13	106.4	24.9	6.4	8.7	26.64	65		
W51114	14	115.0	27.4	7.0	8.7	28.3	85		
W51115	15	112.0	30.4	7.8	10.3	33.3	110		
W51116	16	122.0	30.4	7.8	10.3	33.3	110		
W51117	17	125.4	31.9	8.2	10.3	35.5	130		
W51118	18	138.0	33.9	9.2	10.3	39.6	160		
W51119	19	138.0	33.9	9.2	10.3	39.6	165		

72 TEETH RATCHETING COMBINATION WRENCH

- 72 Teeth ratcheting system provides high torque and 5 degrees of

operation in tight areas

· Chrome Vanadium steel and special heat treatments provide thin walls for strength


Mirror Polished

Meeting ANSI Standard





JONNESWAY



operation in tight areas

strength

JONNESWAY.

W	66	
	00	

FLEXIBLE 72 TEETH RATCHETING COMBINATION WRENCH

ITEM NO.	SIZE (metric)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)
W66108	8	137	17.4	4.9	7.4	16.95
W66109	9	159	20.9	5.8	7.4	20.8
W66110	10	159	20.9	5.8	7.4	20.8
W66111	11	175	23.4	6.2	8.7	25.1
W66112	12	175	23.4	6.2	8.7	25.1
W66113	13	186	24.9	6.4	8.7	27.15
W66114	14	194	27.4	7.0	8.7	29.3
W66115	15	216	30.4	7.4	10.3	33.0
W66117	17	232	31 9	8 2	10 3	35 2
W66119	19	250	33.9	9.2	10.3	39.4

· Packing : w/plastic hanger

7 PCS FLEXIBLE 72 TEETH RATCHETING **COMBINATION WRENCH SET (MM)**

Contents : 8, 10, 11, 13, 14, 17, 19MM Packing : PLASTIC DEMO BOX 20SETS/CTN/26KGS/28KGS/2.2'



7 PCS FLEXIBLE 72 TEETH RATCHETING COMBINATION WRENCH SET (SAE)

Contents : 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4" Packing : PLASTIC DEMO BOX 20SETS/CTN/26KGS/28KGS/2.2'

W68	8	72 TE	ETH R	ATCH	IETIN	g BO)	(END	WREN	існ
ITEM NO.	SIZE (MM)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	H (mm)
W680809	8 X 9	φ17.4	7.4	8.6	3.4	10.3	7.4	φ20.9	130.4
W680810	8 X 10	φ17.4	7.4	8.6	3.4	10.3	7.4	φ20.9	130.4
W681011	10 X 11	¢20.9	7.4	10.3	3.6	11.3	8.7	φ22.9	144.4
W681213	12 X 13	φ23.4	8.7	11.5	4	12.3	8.7	φ24.9	166.0
W681415	14 X 15	φ27.4	8.7	13.5	4.5	15.0	10.3	φ 30.4	181.4
W681618	16 X 18	φ30.4	10.3	15.0	5	16.8	10.3	φ33.9	205.9
W681719	17 X 19	¢31.9	10.3	15.5	5.2	17.0	10.3	φ34.4	224.4

· 72 Teeth ratcheting system provides high torque and 5 degrees of

· Chrome Vanadium steel and special heat treatments provides thin walls for

Meeting ANSI standard

JONNESWAY.

JONNESWAY -

WRENCH SERIES



4PCS 72 TEETH RATCHETING STAR WRENCH SET W67104S SIZE : E6 X E8, E10 X E12, E14 X E18, E20 X E24

75° OFFSET RING WRENCH(MM)

7.4

7.4

8.1

8.1

8.1

8.8

9.5

10.1

10.1

10.9

10.9

10.9

11.2

6.3

7.0

7.0

7.7

7.7

8.4

8.4

8.4

9.1

9.8

10.4

10.4

11.4

11.4

11.4

11.6

12.4 13.4 329

168

183

183

198

198

217

217

217

239

260

292

292

318

318

318

327

D L WEIGHT INNER OUTER (mm) (mm) (g) PC/BOX PC/CTN

43

62

62

88

88

131

131

131

152

189

240

240

330

330

330

362

436

600

12

12

12

12

12

12

12

12

12

12

12

9

9

9

9

9

9

9

240

180

180

180

180

120

120

120

120

48

48

48

48

48

48

48


48


24



JONNESWAY -

JONNESWAY -





16.6 x 18.0

16.6 x 18.0

19.5 x 20.9

19.5 x 20.9

19.5 x 20.9

W233032 30 x 32 45.5 x 48.5 14.4 15.2 362

14 x 15 22.4 x 23.7

16 x 17 25.3 x 26.7

17 x 19 28.2 x 29.7

18 x 19 28.2 x 29.7

19 x 21 31.1 x 34.0

19 x 22 31.1 x 34.0

10 x 11

10 x 12

11 x 13

12 x 13

W232022 20 x 22 31.1 x 34.0

W232123 21 x 23 32.6 x 35.5

W232427 24 x 27 36.9 x 41.0

W23

W231011

W231012

W231113

W231213

W231415

W231617

W231719

W231819


W231921

W231922

W231214 12 x 14

· An-	
, 💭 🗕	





OFFSET 12-POINT WRENCH

· Offset and thin-wall rings provide better entry to recessed fasteners.

• 30° increments

46

JONNESWAY -



	8PCS 75° OFFSET RING WRENCH SET(MM)
N23108S	Contents : 6x7, 8x9, 10x11, 12x13, 14x15, 16x17, 18x19, 20x22MM Packing : POUCH + COLOR BOX

12SETS/CTN/18KGS/20KGS/1.2'



JONNESWAY.


	6PCS 45°OFFSET RING WRENCH SET(SAE)
206S	Contents : 1/4"x5/16", 3/8"x7/16", 1/2"x9/16", 5/8"x11/16", 3/4"x7/8", 15/16"x1" Packing : POUCH + COLOR BOX
	12SETS/CTN/17KGS/18KGS/1.2'

FLARE NUT WRENCH(MM)										
W24 • CHROME VANADIUM • HEAT TREAT • CHROME PLATED • DIN 3118 STANDARD						ATED				
PACKING										
	SIZE	BxB1	с	DxD1	L	WEIGHT				
ITEM NO.	(mm)	(mm)	(mm)	(mm)	(mm)	(g)	INNER PC/BOX	OUTER PC/CTN		
W240809	8 x 9	18.0 x 20.0	7.0 x 8.5	6.0 x 7.0	145	50.0	12	360		
W240810	8 x 10	18.0 x 20.0	7.0 x 8.5	6.0 x 7.0	145	50.0	12	360		
W241011	10 x 11	20.0 x 22.0	8.5 x 9.0	7.0 x8.5	152	65.0	12	240		
W241012	10 x 12	2 20.0 x 22.0	8.5 x 9.0	7.0 x9.0	152	65.0	12	240		
W241213	12 x 1	3 22.0 x 26.0	9.0 x 10.5	8.5 x10.0	165	110.0	12	240		
W241214	12 x 1	4 24.0 x 28.0	9.5 x 11.0	9.0 x 11.0	178	150.0	12	180		
W241314	13 x 1	4 24.0 x 28.0	9.5 x11.0	9.0 x 11.0	178	150.0	12	180		
W241417	14 x 1	7 28.0 x 30.0	11.0 x 12.0	11.0 x 14.0	196	135.0	12	120		
W241617	16 x 1	7 28.0 x 30.0	11.0 x 12.0	11.0 x 14.0	196	135.0	12	120		
W241719	17 x 1	9 30.0 x 32.0	12.0 x 14.0	14.0 x 15.0	210	180.0	12	96		
W241922	19 x 2	2 32.0 x 38.0	14.0 x 16.0	15.0 x 17.0	233	260.0	6	60		
W242123	21 x 2	3 38.0 x 42.0	16.0 x 17.0	17.0 x 18.0	252	290.0	6	48		
W242224	22 x 2	4 38.0 x 42.0	16.0 x 17.0	17.0 x 18.0	252	290.0	6	48		
W242427	24 x 2	7 42.0 x 46.0	17.0 x 18.0	18.0 x 20.0	265	350.0	6	48		
W243032	30 x 3	2 50.0 x 52.0	21.0 x 23.0	22.0 x 24.0	285	480.0	3	24		
W243236	32 x 3	6 52.0 x 60.0	23.0 x 25.0	24.0 x 25.0	315	780.0	3	24		
W243641	36 x 4	1 60.0 x 67.0	25.0 x 27.0	25.0 x 32.0	350	1200.0	3	24		

• 8~14mm : 6pt, 15~41mm :12pt

6PCS FLARE NUT WRENCH SET(MM)

Contents : 8x9, 10x11, 10x12, 13x14, 16x17, 17x19MM Packing : POUCH + COLOR BOX 12SETS/CTN/7.5KGS/11.5KGS/1.2'



W25 · CHROME VANADIUM · HEAT TREATED · CHROME PLATED · DIN 3110 STANDARD							
ITEM NO.	SIZE (mm)	BxB1 (mm)	C (mm)	L (mm)	WEIGTH (g)	INNER PC/BOX	OUTER PC/CTN
W250607	6 x 7	15.5 x 18.0	3.7	123	17.0	12	360
W250809	8 x 9	20.4 x 22.7	4.0	140	31.0	12	360
W250810	8 x 10	20.4 x 22.7	4.0	140	31.0	12	360
W251011	10 x 11	24.9 x 27.1	5.0	156	43.0	12	240
W251012	10 x 12	24.9 x 27.1	5.0	156	43.0	12	240
W251113	11 x 13	29.2 x 31.2	5.5	172	60.0	12	240
W251213	12 x 13	29.2 x 31.2	5.5	172	60.0	12	240
W251214	12 x 14	31.3 x 33.3	5.5	180	75.0	12	180
W251415	14 x 15	33.3 x 35.3	5.9	190	81.0	12	180
W251417	14 x 17	33.3 x 38.9	6.1	195	95.0	12	180
W251617	16 x 17	37.1 x 38.9	6.3	204	109.0	12	120
W251819	18 x 19	40.9 x 42.8	6.7	221	155.0	12	120
W251922	19 x 22	44.8 x 48.8	7.1	237	220.0	12	96
W252022	20 x 22	44.8 x 48.8	9.1	237	220.0	12	96
W252123	21 x 23	46.8 x 50.8	7.7	247	230	12	48
W252224	22 x 24	46.8 x 50.8	7.7	247	230	6	48
W252427	24 x 27	52.8 x 59.1	8.1	263	275	6	48
W253032	30 x 32	65.4 x 69.8	9.0	298	440	6	36

OPEN END WRENCH(MM)

JONNESWAY -



8PCS OPEN END WRENCH SET(MM)

N25108S Contents : 6x7, 8x9, 10x11, 12x13, 14x15, 16x17, 18x19, 20x22MM PACKING : POUCH + COLOR BOX 12SETS/CTN/12KGS/16KGS/0.95'

JONNESWAY -



W29		STAR WRENCH									
		CHROME VANADIUM MAT FINISHED									
					PAC	KING					
ITEM NO.	TEM NO. 5		L (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN					
W290608	E6 x E8		112	14	12	360					
W290711	E7 x E11		125	30	12	360					
W291012	E10 x E12		140	30	12	360					
W291418	E14 x E18		180	70	12	240					
W291622	E16 x E22		200	124	12	120					
W292024	E20) x E24	224	144	12	96					

W71130 W71132

JONNESWAY.

W74	1

ITEM NO.


W71106 W71107 W71108 W71109 W71110 W71111 45° COMBINATION WRENCH (12PT)


CHROME VANADIUM
 MAT FINISHED

	IZE nm)	L (mm)	B (mm)	C (mm)	D (mm)	F (mm)	H (mm)	T (mm)
6	1/4	90	13.4	95	4.0	4.2	7.0	2.4
7	-	95	14.9	107	4.0	4.6	7.5	2.8
8	5/16	105	17.5	125	4.6	5.2	8.3	3.0
9	-	115	20.6	135	5.0	5.8	9.5	3.0
10	3/8	125	21.5	147	5.2	6.42	10.5	3.2
11	7/16	140	23.2	166	5.5	7	11.5	3.4
12	-	155	25.5	18	5.7	7.6	12.5	3.6
13	1/2	165	28.2	192	6.0	8	13.5	3.8
14	-	180	29.1	202	6.2	8.3	14.0	4.0
15	9/16	190	33.4	214	6.4	9.4	15.0	4.2
16	-	205	34.6	235	6.7	9.7	15.3	4.5
17	11/16	215	37.8	25	7.2	10.5	17.0	4.8
18	-	230	37.1	257	7.3	11	17.5	5.0
19	3/4	240	40.2	277	8.0	12	18.0	6.0
20	-	255	42.5	285	8.3	13	18.8	6.2
21	13/16	265	45	32	8.5	13.4	21.5	6.4
22	-	280	47.4	33	8.7	13.8	20.5	6.6
23	-	290	49	35	9.0	14.2	22.5	7.0
24	-	305	51	36	9.7	14.6	22.6	7.4
25	(26)	330	56.6	38	10.0	16.2	24.8	7.8
27	-	345	58.5	40	10.4	17.5	25.2	8.2
28	-	365	60	42	10.8	18	25.2	8.5
30	(29)	380	63.8	44	11.0	19.2	26.0	8.7
32	-	405	68	365	11.6	20.5	27.5	8.7

WRENCH SERIES








COMBINATION WRENCH


- Slim ends for better entry
- 30° increments
- Side or top approach to objects

W20		CHROME F	ME VANADIUM • HEAT TREATED ME PLATED 113 STANDARD				
						PAC	KING
ITEM NO.	SIZE (mm)	BxB1 (mm)	CxC1 (mm)	L (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
W26106	6	15.5 x 10.1	4.2 x 4.7	105	15.0	12	360
W26107	7	17.0 x 11.5	4.4 x 5.0	115	18.8	12	360
W26108	8	19.2 x 12.8	4.6 x 5.5	125	23.5	12	360
W26109	9	21.2 x 14.2	4.8 x 5.9	135	32.1	12	360
W26110	10	23.2 x 15.6	5.0 x 6.5	145	40.0	12	360
W26111	11	25.3 x 16.9	5.4 x 6.9	155	50.0	12	240
W26112	12	27.2 x 18.3	5.5 x 7.3	165	61.0	12	240
W26113	13	29.4 x 19.7	5.9 x 7.8	175	74.0	12	240
W26114	14	31.5 x 21.2	6.2 x 8.3	185	83.0	12	180
W26115	15	33.2 x 22.5	6.4 x 8.6	195	100.0	12	180
W26116	16	34.7 x 24.0	6.7 x 8.9	205	111.0	12	120
W26117	17	36.5 x 25.3	6.9 x 9.3	215	125.6	12	120
W26118	18	38.7 x 26.8	7.2 x 9.9	225	146.0	12	120
W26119	19	40.7 x 28.1	7.4 x 10.5	235	156.0	12	96
W26120	20	43.1 x 29.7	7.7 x 10.9	245	186.0	12	96
W26121	21	44.8 x 31.3	8.0 x 11.3	255	207.0	12	96
W26122	22	46.9 x 32.6	8.2 x 11.5	265	226.0	12	72
W26123	23	48.3 x 34.2	8.4 x 11.8	275	261.0	6	48
W26124	24	50.4 x 35.5	8.7 x 12.1	285	276.0	6	48
W26125	25	52.0 x 36.9	8.9 x 12.5	295	319.0	6	48
W26126	26	53.6 x 38.2	9.2 x 12.8	305	357.0	6	48
W26127	27	55.7 x 39.6	9.4 x 13.1	315	365.0	6	48
W26128	28	57.6 x 40.9	9.7 x 13.3	325	402.0	6	48
W26129	29	59.7 x 42.3	9.9 x 13.5	335	442.0	6	36
W26130	30	61.8 x 43.7	10.1 x 13.7	345	502.0	6	36
W26132	32	65.8 x 46.4	10.4 x 14.3	365	572.0	6	24
W26133	33	69.2 x 48.4	10.7 x 15.0	380	645.8	6	12
W26134	34	69.2 x 48.4	10.7 x 15.0	380	649.0	6	12
W26135	35	74.0 x 53.0	13.5 x 19.4	410	800.0	6	12
W26136	36	74.0 x 53.0	13.5 x 19.4	410	812.0	6	12
W26138	38	77.0 x 56.0	15.0 x 20.4	430	989.0	6	12
W26141	41	84.0 x 61.0	16.0 x 21.6	460	1,160.0	3	6
W26143	43	84.0 x 61.0	16.0 x 21.6	460	1,211.0	3	6
W26145	45	92.0 x 66.0	17.0 x 23.0	500	1,629.0	3	6
W26146	46	92.0 x 66.0	17.0 x 23.0	500	1,800.0	3	6
W26148	48	102.0 x 73.0	18.0 x 24.6	540	2,100.0	3	6
W26150	50	102.0 x 73.0	18.0 x 24.6	540	2,204.0	3	6
W26155	55	118.0 x 86.0	21.5 x 28.0	560	2,800.0	3	6
W26160	60	126.0 x 94.0	23.5 x 30.0	600	3,927.0	2	4
W26165	65	148.0 x 108.0	25.0 x 32.0	680	5,800.0	2	4
W26105 W26170	70	148.0 x 108.0	25.0 x 32.0	680	5.850.0	2	4

COMBINATION WRENCH(MM)









J	0		N	E	儿		Y	ß
---	---	--	---	---	---	--	---	---

COMBINATION WRENCH- LONG PATTERN TYPE
CUNDINATION WRENCH-LUNG PATTERN TTPE

W	264	

ANSI/ASME B107.6 STANDARD CHROME VANADIUM HEAT TREATED TRIPLE CHROME PLATED

ITEM NO.	SIZE (mm)	ITEM NO.	SIZE (inch)	BxB1 (mm)	CxC1 (mm)	L (mm)	WEIGHT (g)	PAC INNER PC/BOX	KING OUTER PC/CTN
W26406PR	6	W26406	1/4"	15.3 x 10.6	4.3 x 5.8	129	21.6	12	360
W26407PR	7	-	-	16.3 x11.8	4.6 x 6.0	135	24.4	12	360
W26408PR	8	W26408	5/16"	18.5 x 13.0	4.7 x 6.6	142	30.2	12	360
W26409PR	9	-	-	19.2 x 13.8	4.7 x 6.6	155	39.0	12	240
W26410PR	10	W26410	3/8"	20.8 x 15.4	5.1 x 7.4	161	55.0	12	240
W26411PR	11	W26411	7/16"	23.2 x 17.2	5.9 x 7.8	168	61.5	12	240
W26412PR	12	-	-	24.0 x 17.8	5.9 x 8.2	174	77.6	12	240
W26413PR	13	W26413	1/2"	26.5 x 19.2	6.3 x 8.6	180	83.7	12	180
W26414PR	14	W26414	9/16"	26.8 x 10.0	6.3 x 8.6	193	107.3	12	180
W26415PR	15	-	-	30.8 x 22.5	7.1 x 9.0	200	122.1	12	120
W26416PR	16	W26416	5/8"	32.7 x23.0	7.9 x 9.2	207	134.4	12	120
W26417PR	17	W26417	11/16"	34.4 x24.4	7.9 x 10.4	227	171.5	12	120
W26418PR	18	-	-	37.5 x26.4	8.7 x 11.1	239	207.0	12	96
W26419PR	19	W26419	3/4"	39.1 x 27.7	9.3 x 11.5	250	279.0	12	96
W26420PR	20	-	-	40.7 x28.8	9.5 x 11.9	259	284.0	12	96
W26421PR	21	W26421	13/16"	43.5 x 30.8	9.8 x 12.7	271	336.0	12	48
W26422PR	22	W26422	7/8"	45.8 x 32.7	10.2 x 13.5	295	369.0	12	48
W26423PR	23	-	-	49.5 x 34.6	10.5 x 14.2	317	372.0	6	48
W26424PR	24	W26424	15/16"	49.5 x 34.6	10.5 x 14.2	317	407.8	6	48
W26425PR	25	W26425	1"	51.5 x 36.6	11.4 x 14.9	339	495.3	6	48
W26426PR	26	-	-	51.5 x 36.6	11.4 x 14.9	339	563.0	6	36
W26427PR	27	W26427	1-1/16"	55.3 x 38.6	12.1 x 15.7	362	600.0	6	36
W26428PR	28	-	-	58.5 x42.4	12.8 x 16.5	394	710.0	6	24
W26429PR	29	-	-	58.5 x42.4	12.8 x 16.5	394	790.0	6	24
W26430PR	30		1-1/8"	58.5 x 42.4	12.8 x 16.5	394	818.0	6	24
W2045011	-	W26431	1-3/16"	68.5 x 42.4	12.8 x 16.5	394	969.0	6	24
W26432PR	32	W26431	1-1/4"	65.0 x 45.6	13.4 x 18.0	429	997.0	6	24
W20452FK	52	W26432	1-5/16"	71.0 x 49.5	15.5 x 19.0	471	1,130.0	6	24
W26434PR	34	W26434	1-3/8"	71.0 x 49.5	15.5 x 19.0	471	1,150.0	6	24
1120404111		W26435	1-7/16"	76.0 x 55.0	16.5 x 19.0	510	1,230.0	3	12
W26436PR	36	W26436	1-1/2"	76.0 x 55.0	16.5 x 19.0	510	1,270.0	3	12
W2043011	-	W26430	1-5/8"	83.0 x 66.0	17.4 x 19.0	550	1,670.0	3	12
W26438PR	- 38	W26437	1-11/16"	83.0 x 66.0	17.4 x 19.0	550	1,670.0	3	12
W26441PR	41	VV20438		83.0 x 66.0	17.4 x 19.0	550	1,670.0	3	12
1120441111	41		1-3/4"	86.0 x 61.0	19.0 x 20.5	613	2.200.0	3	6
-	-	W26443	1-13/16"	86.0 x 61.0	19.0 x 20.5	613	2,200.0	3	6
W26446PR	46	W26446	1-7/8"	96.0 x 73.0	19.0 x 24.0	651	2,618.0	3	6
1120110111	-	W26448	1-15/16"	96.0 x 73.0	19.0 x 24.0	651	2,816.0	3	6
W26450PR	50	W26450	2"	96.0 x 73.0	19.0 x 24.0	651	3.000.0	3	6
	50	W26452	2-1/16"	113.0 x 82.0	23.4 x 31.0	724	4,580.0	2	4
-		W26452	2-1/16	113.0 x 82.0	23.4 x 31.0	724	4,580.0	2	4
W26455PR	55	W26455	2-3/16"	113.0 x 82.0	23.4 x 31.0	724	4,580.0	2	4
1120-100FR	- 55	W26455 W26457	2-3/16	113.0 x 82.0	23.4 x 31.0	724	4,580.0	2	4
-	-	W26457	2-1/4	119.0 x 93.5	119.0 x 93.5	743	5,600.0	2	4
	- 60	W26460	2-3/18	119.0 x 93.5	119.0 x 93.5	743	5,600.0	2	4
-		W26462	2-3/8	119.0 x 93.5	119.0 x 93.5	743	5,600.0	2	4
-	-	W26462	2-1/2"	119.0 x 93.5	119.0 x 93.5	743	5,600.0	2	4
	65	vv20403	2-112	119.0 x 93.5	119.0 x 93.5	743	5,600.0	2	4
-	-	- W26466	2-9/16"	134.0 x 102.0	134.0 x 102.0	743	7,300.0	-	4
	-	W26466	2-9/16	134.0 x 102.0	134.0 x 102.0	756	7,300.0		3
-	-	W26467	2-5/8	134.0 x 102.0	134.0 x 102.0	756	7,300.0		3
W/2647000	- 70	W26468	2-11/16			756	,		3
W26470PR	10	vv∠o470	2-3/4"	134.0 x 102.0	134.0 x 102.0	100	7,300.0		3



JONNESWAY.

WRENCH SERIES



A JONNESWAY

ATATA A

JONNESWAY




	12PCS COMBINATION WRENCH SET(MM)
W26112S	Contents : 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 19, 22MM Packing : POUCH + COLOR BOX 12SETS/CTN/13.5KGS/17.5KGS/1.2'
	14PCS COMBINATION WRENCH SET(MM)
W26114S	Contents : 10, 11, 12, 13, 14, 16, 17, 19, 21, 22, 24, 27, 30, 32MM Packing : POUCH + COLOR BOX 6SETS/CTN/17KGS/19.5KGS/1'
W26116S	16PCS COMBINATION WRENCH SET(MM)
	Contents : 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 22, 24MM Packing : METAL CASE + COLOR BOX 6SETS/CTN/9.5KGS/20KGS/1.13'
	26PCS COMBINATION WRENCH SET(MM)
W26126S	Contents : 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 32MM

12SETS/CTN/11KGS/14.5KGS/1.2'

8PCS COMBINATION WRENCH SET-LONG

Packing : POUCH



ITEM N W6108 W61101 W61101 W61121 W61131 W61141 W61161 W6117 W61222

JONNESWAY -



W61

	CONTEN
	W61
	PACKI
1	

JONNESWAY	
JOININLOWAI	



-	W264108PRS	PATTERN TYPE(MM)		
44	W204100FK3	Contents : 10, 11, 12, 13, 14, 15, 17, 19MM Packing : PLASTIC HOLDER 12SETS/CTN/11KGS/14.5KGS/1.2'		
		11PCS COMBINATION WRENCH SET(MM)		
	W26411PRS	Contents : 7, 8, 9, 10, 11, 12, 13, 14, 15, 17, 19MM Packing : POUCH + COLOR BOX 12SETS/CTN/12KGS/16.5KGS/0.9'		
0.0				
6	W26411SA	11PCS COMBINATION WRENCH SET-LONG PATTERN TYPE(SAE)		
	W204113A	Contents : 3/8". 7/16', 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8", 15/16", 1" Packing : POUCH + COLOR BOX 8SETS/CTN/20KGS/21KGS/1.1'		
50				
Lan St.		14PCS COMBINATION WRENCH SET(SAE)		
No. o	W26414S	Contents : 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8", 15/16", 1", 1-1/16", 1-1/8", 1-1/4" Packing : POUCH + COLOR BOX 4SETS/CTN/24KGS/24.5KGS/0.9'		

JONNESWAY -

JONNESWAY



3 3 3 8 5 5 5 6 6


Torque As 1.2 Times As ANSI Standard

Chrome Vanadium Steel

Mirror Polished

Short Shank For Operating Easily In Combined Space
 15° Offset Ring End Of Design For Easy Operation

W53		MIDGET COMBINATION WRENCH						
ITEM NO.	SIZE (inch)	L (mm)	B (mm)	D (mm)	S1 (mm)	S2 (mm)	WEIGHT (g)	
W53216	5/8"	121	35.0	23.8	6.6	10.1	84.5	
W53217	11/16"	127	37.5	25.0	6.8	10.8	107.1	
W53219	3/4"	137	41.3	28.0	7.8	11.9	142.5	



52

J	0	N	N	E	37	<u>//</u>	/	®
---	---	---	---	---	----	-----------	---	---

		E	EXTRA-I	LONG D	OUBLE	RING E	ND WR	ENCH	
61		CHROME-MOLYBDFNUM MIRROR FINI SHED							
10.	sizi	E	L (mm)	C (mm)	B (mm)	C1 (mm)	B1 (mm)	T (mm)	WT (mm)
310	8X1	0	235	15.1	12.6	8.5	7.5	4.4	78
011	10X1	11	395	19.1	16.2	9.1	8.4	4.6	124
)12	10X1	12	395	19.1	16.2	9.1	8.4	4.6	124
214	12X1	14	330	26.5	22.2	14.5	12.8	5.8	200
315	13X1	15	370	26.5	22.2	14.6	12.9	5.8	308
117	14X1	17	370	26.5	22.	14.6	12.9	5.8	308
618	16X1	18	405	29.3	26.2	16.0	15	7.8	432
719	17X1	19	405	29.3	26.6	16.0	15	7.8	432
224	22X2	24	435	35.0	33.0	18.6	17.3	9.2	573

10	6S	6PCS EXTRA-LONG DOUBLE RING WRENCH SET
NTS:		
	10X	(11, 12X14, 13X15, 16X18, 17X19, 22X24MM
NG	PO	UCH

		D	OUBLE	EENDE	D RIN	G WRE	NCH (STAR	FER)
65		•(CHROME	VANADIL	JM •	MAT FINI	SHED		
10.	SIZI	E	L (mm)	C (mm)	B (mm)	C1 (mm)	B1 (mm)	T (mm)	WT (mm)
810	8X1	0	137	15.6	14.3	6.5	6.2	4.0	45
01 1	10X	(11	141	15.6	18.2	6.6	6.5	4.2	56
012	10X1	12	141	15.6	18.2	6.6	6.5	4.2	56
113	11X1	13	166	18.2	21.0	8.2	8.0	4.9	93
315	13X1	15	190	22.0	25.0	9.2	8.2	5.3	134
417	14X1	17	190	22.0	25.0	9.2	8.2	5.3	134
618	16X1	18	220	25.5	28.0	9.6	8.8	5.6	190
922	19X2	22	256	28.6	32.5	11.1	10.1	6.6	240

-5-	2

	DOU	DOUBLE FLEXIBLE SOCKET WRENCH						
W43		CR-V MAT FINISHED						
	SIZE		WEIGHT	PAC	KING			
ITEM NO.	(mm)	(mm)	(g)	INNER PC/BOX	OUTER PC/CTN			
W43A0607	6 x 7	180	72	12	240			
W43A0809	8 x 9	180	78	12	240			
W43A1011	10 x 11	202	115	12	192			
W43A1012	10 x 12	202	125	12	192			
W43A1213	12 x 13	222	155	12	96			
W43A1214	12 x 14	223	170	12	96			
W43A1415	14 x 15	245	245	12	96			
W43A1417	14 x 17	245	245	12	96			
W43A1617	16 x 17	260	330	12	48			
W43A1719	17 x 19	260	330	12	48			
W43A1819	18 x 19	280	414	12	48			
W43A2022	20 x 22	305	595	12	24			



ITEM NC W27AR8 W27AR1

Auto-release **ON** : Opearting Instruction






N1311066	OPCS DOUBLE FLEXIBLE SOCKET WRENCH SET OR-V • MAT FINISHED
N43A106S	Contents : 8X9, 10X11, 12X13, 14X15, 16X17, 18X19 Packing : BLOWING CASE + COLOR BOX 6SETS/CTN/9KGS/10KGS/1.08'




	FLEX	FLEXIBLE SOCKET WRENCH							
W43E	- 01(-	CR-V MAT FINISHED							
	0.75		WEIGHT	PAC	KING				
ITEM NO.	SIZE (mm)	L (mm)	(g)	INNER PC/BOX	OUTER PC/CTN				
W43B108	8	170	65	12	240				
W43B109	9	170	65	12	240				
W43B110	10	180	76	12	200				
W43B111	11	190	105	12	150				
W43B112	12	195	114	12	150				
W43B113	13	218	140	12	150				
W43B114	14	230	186	12	100				
W43B115	15	230	195	12	100				
W43B116	16	235	234	12	72				
W43B117	17	235	234	12	72				
W43B118	18	255	307	12	72				
W43B119	19	255	307	12	72				





W27

JONNESWAY -





W27AT4

ITEM NO.

W27AT6 W27AT8 W27AT10 W27AT12

W27AT15



JONNESWAY.

AUTO-RELEASE ADJUSTABLE WRENCH W27AR

С	SIZE	MAX.JAW OPENING NOT LESS THAN (MM)
3	8"(200)	26.9
10	10"(250)	34



'AS		ADJU	ISTA	BLE AN	GLE V	VRENCH	I						
AJ		MAT FINISHED • DIN 3117 ANSI/ASME B107.8M											
SIZE	N	MAX. JAW	USING	RANGE FOR	OVERALL	LOAD BENDING	WEIGHT	PAC	KING				
INCH OPENI		ENING NOT S THAN(mm)	Metric	SAE	LENGTH (mm)	TEST MIN. (cm-kgf)	(g)	INNER PC/BOX	OUTER PC/CTN				
4" (100)		13	M1-M8	W1/8-W1/4	105 - 110	714	50-57	6	120				
6" (150)		20	M1-M12	W1/8-W7/16	155 - 162	1674	120-127	6	120				
3" (200)		24	M1-M16	W1/8-W1/2	203 -211	3061	240-254	6	60				
0" (250)		29	M1-M18	W1/8-W5/8	250 - 260	5204	410-425	6	36				
2" (300)		34	M1-M22	W1/8-W3/4	300 -310	8776	630-690	6	24				
5" (380)		43	M1-M27	W1/8-W1	375 -390	17347	1180-1240	4	16				
8" (450)		53	M1-M33	W1/8-W1-1/4	450 -470	23469	1900-1960	6	12				

W27AT

TIGER'S PAW ADJUSTABLE WRENCH


	0175	STANDARD	MAX. JAW	MEIOUT	PACKING		
	SIZE (inch/mm)	JAW OPENING WIDTH (mm)	OPENING NOT LESS THAN (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN	
	4" (100)	13	17.0	0.06	6	120	
	6" (150)	19	23.9	0.122	6	120	
	8" (200)	24	28.6	0.242	6	60	
)	10" (250)	29	32.8	0.397	6	48	
2	12" (300)	34	38.1	0.609	6	24	
5	15" (375)	43	51.0	1.14	1	16	

Ensuring security in use.
Meeting DIN/ANSI Standard.
Button at the end of the handle increases the strength over 200 kgf, which is triver at the original design. Ergonomic handle design allows proper usage and durability of the tod.
Wider jaw opening 18%-25%
Less weight with increased torsional rigidity.
Anti-slip opening end

56

W2848R







• Self adjusting wrench head automatically adjusts to different pipe sizes up to 1-1/2" diameter. • Ergonomic design allows one-handed fitting, adjusting, torquing and removal.

• Spring loaded jaw enables fast ratchet action.

• The patented 3-point jaw design provides an extra-strong grip for increased torque.

Conveninet thumb tnigger provides easy, quick release.

Material : DUCTILE IRON

DUCTILE IRON

ITEM NO.	Overall Length (mm)	Capacity (mm)	Max Open Width (mm)
W28HD08	(200) 8"	(10.16 - 21.8) 0.4" - 0.86"	(21.8) 0.86"
W28HD10	(250) 10"	(12.7 - 30) 0.5" - 1.15"	(30) 1.15"
W28HD12	(300) 12"	(15.87 - 35.3) 0.625" - 1.39"	(35.3) 1.39"
W28HD14	(350) 14"	(17.78 - 50.8) 0.7" - 2"	(50.8) 2"

JONNESWAY -

EASY OPERATION



 Push the Tumb Trigger Downwards to Open the Jaw



• Patented 3 Points Jaw Design Provides an Extra-Strong Grip for Increase Torque





ITEM NO. W28A14 W28A18 W28A24 W28A36 W28A48



• 3 Points Jaw Design Fit Around Pipe & Release the Thumb Trigger to Operate




• To Release the Pipe, Push the Thumb Trigger Downward

JONNESWAY.

28		DROP FORGED PIPE WRENCH									
		• BODY : CAST IRON • JAW : CHROME MOLYBDENUM									
inch		SIZE	JAW CAPACITY (PIPE SIZE I.D.)		WEIGHT	PACKING					
		mm	inch	mm	mm (kg)		OUTER PC/CTN				
	8"	200	1"	25.4	0.36	6	36				
	10"	250	1-1/2"	38.1	0.65	6	36				
	12"	300	2"	50.8	0.95	6	24				
	14"	350	2"	50.8	1.25	6	12				
	18"	450	2-1/2"	63.5	2	6	12				
	24"	600	3"	76.2	3.7	2	6				
	36"	900	5"	127	7	1	2				
	48"	1200	6"	152.4	14	1	1				

		ALUMINUM ALLOY PIPE WRENCH									
Ì	8A	• BODY : ALUMINUM ALLOY • JAW : CHROME MOLYBDENUM DROP FORGED									
SIZE		SIZE	JAW CAPACITY (PIPE SIZE I.D.)		WEIGHT	PACKING					
	inch	mm	inch	mm	(kg)	INNER PC/BOX	OUTER PC/CTN				
	14"	350	2"	50.8	0.95	6	24				
	18"	450	2-1/2"	63.5	1.55	2	12				
	24"	600	3"	76.2	2.45	2	8				
	36"	900	5"	127	4.75	1	4				
	48"	1200	6"	152.4	9	1	2				

Aluminum alloy body
CR-MO drop forged Jaw
Pipe size on hook jaw for quick adjustment to proper width.
Hardened forged steel jaw provides maximum strength at stress point.
Replaceable heel jaw supported by high strength shoulder.
Deep milled teeth hardened to stay sharp.
Balanced for proper weight distribution.
Heavy duty spring maintains preset jaw adjustment, aids in positive pipe engagement.
Large knurl and power threads provide fast jaw adjustment.



W72	CHROME-MOLYBDENUM MAT FINISHED MANGANESE PHOSHATING						
ITEM NO.	SIZE	L (mm)	C (mm)	C1 (mm)	T (mm)	WT (mm	
W72122	22	163	42.0	15.5	8.0	242	
W72123	23	163	42.0	15.5	8.0	242	
W72124	24	163	42.0	15.5	8.0	242	
W72125	25	163	42.0	15.5	8.0	242	
W72126	26	180	46.0	16.5	10.0	340	
W72127	27	180	46.0	16.5	10.0	340	
W72128	28	180	46.0	16.5	10.0	340	
W72129	29	190	52.0	17.5	10.0	416	
W72130	30	190	52.0	17.5	10.0	416	
W72132	32	190	52.0	17.5	10.0	416	
W72133	33	190	52.0	17.5	10.0	416	
W72134	34	205	58.0	18.5	11.0	518	
W72135	35	205	58.0	18.5	11.0	518	
W72136	36	205	58.0	18.5	11.0	518	
W72138	38	205	58.0	18.5	11.0	518	
W72140	40	230	66.0	20.5	12.0	735	
W72141	41	230	66.0	20.5	12.0	735	
W72142	42	230	66.0	20.5	12.0	735	
W72143	43	230	66.074.0	20.5	12.0	930	
W72144	44	240	74.0	22.5	14.0	930	
W72145	45	240	74.0	22.5	14.0	930	
W72146	46	240	74.0	22.5	14.0	930	
W72147	47	240	74.0	22.5	14.0	116	
W72148	48	255	80.0	24.5	16.0	116	
W72150	50	255	80.0	24.5	16.0	116	
W72152	52	255	80.0	24.5	16.0	136	
W72155	55	270	86.0	25.5	17.0	165	
W72160	60	280	96.0	26.5	18.0	165	
W72165	65	280	96.0	26.5	18.0	165	
W72170	70	335	108.0	32.0	23.0	353	
W72175	75	335	108.0	32.0	23.0	353	
W72180	80	365	121.0	36.0	23.0	520	
W72185	85	365	121.0	36.0	23.0	520	
W72190	90	400	141.0	40.0	24.0	750	
W72195	95	400	141.0	40.0	24.0	750	
W721100	100	435	164.0	37.0	28.0	1020	
W721105	105	435	164.0	37.0	28.0	1020	

SLUGGING WRENCH



New Patent in Worldwide !!

SUPER TECH SERIES

- The revolutionary "SUPER TECH" ONE DRIVE FIT ALL" solution for all fastening needs.
- The SUPER TECH system fits Metric 6pt. Metric 12pt, SAE 6pt, SAE 12PT, E-TORX, Spline, Square & 50% rounded off nuts bolts.
- The nuts'/ bolts' point of contact are evenly distributed onto larger surface areas during application, thus distributing pressure instead connecting to several sharp point, so as the nuts / bolts will not be damaged easily.
- Manufactured from high quality materials including improved Chrome Vanadium Steel (Cr-V4), Molybdenum and Tungsten which extends the life ability 10 times the DIN standard.
- Torque exceeds double the normal DIN standard.
- The SUPER TECH system can be applied to a wide variety of markets-Automotive, Industrial. Retail & Hardware.



FIXING CONVERSION TABLES								
SIZE	METRIC	SAE	STAR	SIZE	METRIC	SAE	STAR	
3.2	3.2	1/8"	E4	16	16	5/8"	E20	
4	4	5/32"	E5	17	17	21/32"		
4.5	4.5			18	18	11/16"	E22	
5	5	3/16"	E6	19	19	3/4"	E24	
5.5	5.5	7/32"	E7	20	20	25/32"		
6	6		E8	21	21	13/16"	E26	
1/4"		1/4"	E8	22	22	7/8"	E28	
7	7	9/32"		23	23	29/32"	E28	
8	8	5/16"	E10	24	24	15/16"	E30	
9	9	11/32"	E11	25	25	31/32"	E32	
10	10	3/8"	E12	26	26	1"	E32	
11	11	7/16"	E14	27	27	1-1/16"	E34	
12	12	15/32"		28	28	1-3/32"	E36	
13	13	1/2"	E16	29	29	1-1/8"	E36	
14	14	9/16"	E18	30	30	1-3/16"	E38	
15	15	19/32"		32	32	1-1/4"	E40	











SUPER TECH COMBINATION WRENCH (CR-V)

New Patent in Worldwide !!

SUPER TECH SERIES





	OPEN END	R	NG END SIZ	E	L	WEIGHT
ITEM NO.	SIZE	METRIC	SAE	STAR	(mm)	WEIGHT (9) 21 23 26 29 39 52 64 68 87 102 114 135 154 178 192 216 237 282 309 314 344
W84106	6	6	-	E8	105	21
W84107	7	7	9/32"	-	115	23
W84108	8	8	5/16"	E10	125	26
W84109	9	9	11/32"	E11	135	29
W84110	10	10	3/8"	E12	145	39
W84111	11	11	7/16"	E14	155	52
W84112	12	12	15/32"	-	165	64
W84113	13	13	1/2"	E16	175	68
W84114	14	14	9/16"	E18	185	87
W84115	15	15	19/32"	-	195	102
W84116	16	16	5/8"	E20	205	114
W84117	17	17	21/32"	-	215	135
W84118	18	18	11/16"	E22	225	154
W84119	19	19	3/4"	E24	235	178
W84120	20	20	25/32"	-	245	192
W84121	21	21	13/16"	E26	255	216
W84122	22	22	7/8"	E28	265	237
W84123	23	23	29/32"	E28	275	282
W84124	24	24	15/16"	E30	285	309
W84125	25	25	31/32"	E32	295	314
W84126	26	26	1"	E32	305	344
W84127	27	27	1-1/16"	E34	315	369
W84128	28	28	1-3/32"	E36	325	412
W84129	29	29	1-1/8"	E36	335	441
W84130	30	30	1-3/16"	E38	345	493
W84132	32	32	1-1/4"	E40	365	464

Material: CR-V
 SATIN Finish

JONNESWAY -




W84108S 8PCS SUPER TECH COMBINATION WRENCH SET

CONTENTS:

W84

• 8PCS - SUPER TECH COMBINATION WRENCH : 8, 10, 11, 12, 13, 14, 17, 19mm • FINISH : SATIN FINISH

New Patent in Worldwide !!





• FINISH : SATIN FINISH STRAIGHT





JONNESWAY.

12PCS SUPER TECH 72 TEETH REVERSIBLE RATCHETING COMBINATION WRENCH SET

• 12PCS - SUPER TECH 72 TEETH RATCHETING COMBINATION WRENCH : 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19mm • FINISH : SATIN FINISH

`		21					
	METRIC	SAE	STAR	SIZE	METRIC	SAE	STAR
	8	5/16"	E10	14	14	9/16"	E18
	9	11/32"	E11	15	15	19/32"	-
	10	3/8"	E12	16	16	5/8"	E20
	11	7/16"	E14	17	17	21/32"	-
	12	15/32"	-	18	18	11/16"	E22
	13	1/2"	E16	19	19	3/4"	E24

New Patent in Worldwide !!

Fit in 7 different nuts.



		SIZE		5440		
ITEM NO.	METRIC	SAE	STAR	D(MM)	L(MM)	W.(G)
S68H2103	3.2	1/8"	E4	13	25	12
S68H2104	4	5/32"	E5	13	25	12
S68H21045	4.5	-	-	13	25	12
S68H2105	5	3/16"	E6	13	25	12
S68H21055	5.5	7/32"	E7	13	25	13
S68H2106	6	-	E8	13	25	13
S68H21065	-	1/4"	E8	13	25	13
S68H2107	7	9/32"	-	13	25	13
S68H2108	8	5/16"	E10	13	25	13
S68H2109	9	11/32"	E11	14	25	17
S68H2110	10	3/8"	E12	15	25	19
S68H2111	11	7/16"	E14	17	25	21
S68H2112	12	15/32"	-	18	25	24
S68H2113	13	1/2"	E16	19	25	28
S68H2114	14	9/16"	E18	21	25	25

1/4" SUPER TECH SOCKET

- The revolutionary SUPER TECH is the ONE DRIVE FIT ALL solution for all fastening needs.
- The SUPER TECH system fits Metric 6pt., Metric 12pt., SAE 6pt., SAE 12pt., E-Trox, Spline, Square & 50% Rounded off nuts & bolts.
- The nuts' / bolts' point of contact are evenly distributed onto larger surface; areas during application, thus distributing pressure instead of connectin to several sharp point so the nuts / bolts will not be damaged easily.
- Manufactured from high quality materials including improved Chrome Vanadium Steel(Cr-V4), Molybdenum and Tusgsten which extends the life ability 10 times the DIN standand.
- Torque exceeds double the normal DIN standard.
- The SUPER TECH system can be applied to a wide variety of markets - Automotive, Industrial, Retail & Hardware.
- Patent worldwide:
- Taiwan, U.S.A. Germany, European Union, Japan, India, China,

S68H3 3/8" SUPER TECH SOCKET

9.5 MM (3/8")

S68H2

		SIZE				
ITEM NO.	METRIC	SAE	STAR	D(MM)	L(MM)	W.(G)
S68H3106	6	-	E8	18	28	23
S68H31065	-	1/4"	E8	18	28	23
S68H3107	7	9/32"	-	18	28	23
S68H3108	8	5/16"	E10	18	28	23
S68H3109	9	11/32"	E11	18	28	24
S68H3110	10	3/8"	E12	18	28	24
S68H3111	11	7/16"	E14	18	28	27
S68H3112	12	15/32"	-	18	28	28
S68H3113	13	1/2"	E16	19	28	29
S68H3114	14	9/16"	E18	21	28 28	29
S68H3115	15	19/32"	-	22		34
S68H3116	16	5/8"	E20	23	28	38
S68H3117	17	21/32"	-	25	30	50
S68H3118	18	11/16"	E22	26	30	54
S68H3119	19	3/4"	E24	27	30	61
S68H3120	20	25/32"	-	28	30	59
S68H3121	21	13/16"	E26	29	30	64
S68H3122	22	7/8"	E28	31	32	79
S68H3123	23	29/32"	E28	32	32	87
S68H3124	24	15/16"	E30	33	32	89

New Patent in Worldwide !!

Fit in 7 different nuts.



ITEM N S68H4 S68H4 S68H41 S68H41 S68H41 S68H4 S68H4 S68H4 S68H41 S68H41 S68H41 S68H41 S68H412 S68H41 S68H41 S68H41 S68H41

• The revolutionary SUPER TECH is the ONE DRIVE FIT ALL solution for all fastening needs.

- The SUPER TECH system fits Metric 6pt., Metric 12pt., SAE 6pt., SAE 12pt., E-Trox, Spline, Square & 50% Rounded off nuts & bolts.
- The nuts' / bolts' point of contact are evenly distributed onto larger surface; areas during application, thus distributing pressure instead of connectin to several sharp point so the nuts / bolts will not be damaged easily.
- Manufactured from high quality materials including improved Chrome Vanadium Steel(Cr-V4), Molybdenum and Tusgsten which extends the life ability 10 times the DIN standand.
- Torque exceeds double the normal DIN standard.
- The SUPER TECH system can be applied to a wide variety of markets - Automotive, Industrial, Retail & Hardware.
- Patent worldwide:
- Taiwan, U.S.A. Germany, European Union, Japan, India, China,

62

JONNESWAY.

S68H41 1/2" SUPER TECH SOCKET

12.7 MM (1/2")

		SIZE		5445		
ITEM NO.	METRIC	SAE	STAR	D(MM)	L(MM)	W.(G)
S68H4108	8	5/16"	E10	23	38	48
S68H4109	9	11/32"	E11	23	38	51
S68H4110	10	3/8"	E12	23	38	53
S68H4111	11	7/16"	E14	23	38	54
S68H4112	12	15/32"	-	23	38	55
S68H4113	13	1/2"	E16	23	38	56
S68H4114	14	9/16"	E18	23	38	59
S68H4115	15	19/32"	-	23	38	63
S68H4116	16	5/8"	E20	24	38	70
S68H4117	17	21/32"	-	25	38	74
S68H4118	18	11/16"	E22	26	38	75
S68H4119	19	3/4"	E24	27	38	70
S68H4120	20	25/32"	-	29	40	86
S68H4121	21	13/16"	E26	30	40	95
S68H4122	22	7/8"	E28	31	40	96
S68H4123	23	29/32"	E28	32	40	107
S68H4124	24	15/16"	E30	33.5	42	122
S68H4125	25	31/32"	E32	33.5	42	135
S68H4126	26	1"	E32	36	42	152
S68H4127	27	1-1/16"	E34	38	44	173
S68H4128	28	1-3/32"	E36	39	44	151
S68H4129	29	1-1/8"	E36	40	44	186
S68H4130	30	1-3/16"	E38	41	45	193
S68H4132	32	1-1/4"	E40	44	45	225

New Patent in Worldwide !! **SUPER TECH SERIES**



S68H4127S 27PCS 1/2"DR. SUPER TECH SOCKET SET

CONTENTS:

- 1PC 1/2"DR. SLIDING T-BAR
- 1PC 1/2"DR. UNIVERSAL JOINT
- 2PCS 1/2"DR. EXTENSION BAR : 125, 250mm
- 2PCS 1/2"DR. SPARK PLUG SOCKET : 16, 21mm
- 1PC 1/2"DR. RATCHET HANDLE 36 TEETH: R2904
- 20PCS 1/2"DR. SUPER TECH SOCKET : 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 27, 30, 32mm

SIZE	METRIC	SAE	STAR	SIZE	METRIC	SAE	STAR
8	8	5/16"	E10	18	18	11/16"	E22
9	9	11/32"	E11	19	19	3/4"	E24
10	10	3/8"	E12	20	20	25/32"	-
11	11	7/16"	E14	21	21	13/16"	E26
12	12	15/32"	-	22	22	7/8"	E28
13	13	1/2"	E16	23	23	29/32"	E28
14	14	9/16"	E18	24	24	15/16"	E30
15	15	19/32"	-	27	27	1-1/16"	E34
16	16	5/8"	E20	30	30	1-3/16"	E38
17	17	21/32"	-	32	32	1-1/4"	E40

JONNESWAY

SUPER TECH SERIES



68H5234111S 111PCS 1/4",3/8"&1/2"DR. SUPER TECH SOCKET SET

CONTENTS:

- 1PC 1/4"DR. RATCHET HANDLE 48 TEETH : R3702
- 1PC 1/4"DR. UNIVERSAL JOINT 1PC 1/4"DR. SPINNER HANDLE
- 2PCS 1/4"DR. EXTENSION BAR : 50, 150mm
- 13PCS 1/4"DR. SUPER TECH SOCKET : 3.2, 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13mm
- 21PCS 1/4"DR. SOCKET BITS : 1, 2, 3 1, 2, 3 4, 5.5, 7 3, 4, 5, 6, 7, 8
- T10, T15, T20, T25, T30, T40
- 1PC 3/8"DR. UNIVERSAL JOINT
 1PC 3/8"DR. RATCHET HANDLE 48 TEETH : R3703
- 2PCS 3/8"DR. EXTENSION BAR : 75, 150mm
- 2PCS 3/8"DR. SPARK PLUG SOCKET : 14, 18mm 11PCS 3/8"DR. SUPER TECH SOCKET : 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19mm
- 1PC 1/2"DR. UNIVERSAL JOINT
- 1PC 1/2"DR. RATCHET HANDLE 48 TEETH : R3704 2PCS 1/2"DR. EXTENSION BAR : 125, 250mm
- 2PCS 1/2"DR. SPARK PLUG SOCKET : 16, 21mm
- 14PCS 1/2"DR. SUPER TECH SOCKET: 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 27, 30, 32mm
 12PCS SUPER TECH COMBINATION WRENCH: 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19mm
- 3PCS T-M HEAD : 3/8"(F) X 1/4"(M) & 3/8"(F) X 1/2"(M) & 1/2"(F) X 3/8"(M)
- 2PCS COUPLER : 3/8"DR. * 5/16" HEX & 1/2"DR. * 5/16" HEX
- 15PCS 5/16" BITS : 🗘 3, 4 🚍 8, 10, 12 🔿 8, 10, 12, 14 🛟 3, 4 🛟 T40, T45, T50, T55
- 3PCS HEX KEY WRENCH : 1.5, 2.0, 2.5,mm


• FINISH : SATIN FINISH

SIZE	METRIC	SAE	STAR	SIZE	METRIC	SAE	STAR
3.2	3.2	1/8"	E4	15	15	19/32"	-
4	4	5/32"	E5	16	16	5/8"	E20
4.5	4.5	-	-	17	17	21/32"	-
5	5	3/16"	E6	18	18	11/16"	E22
5.5	5.5	7/32"	E7	19	19	3/4"	E24
6	6	-	E8	20	20	25/32"	-
7	7	9/32"	-	21	21	13/16"	E26
8	8	5/16"	E10	22	22	7/8"	E28
9	9	11/32"	E11	23	23	29/32"	E28
10	10	3/8"	E12	24	24	15/16"	E30
11	11	7/16"	E14	25	25	31/32"	E32
12	12	15/32"	-	27	27	1-1/16"	E34
13	13	1/2"	E16	30	30	1-3/16"	E38
14	14	9/16"	E18	32	32	1-1/4"	E40



- Professional Quality: ANSI / DIN Standards
- Super Torque: 1.5 times over DIN & 1.3 times over ANSI Standards
- Manual Sockets & Impact Sockets
- Regular Sockets & Deep Sockets
- Metric Size & SAE Size
- Flank Point with Maxi-Drive: to Protect Nuts and Create Higher Torque

64




MESHIN












1		1/4	4" DR.	6PT F	LANK	SOCI	KETS		
	S04H2	Ŭ	HROME EMI MAT			EL			
1								DAO	
	ITEM NO.	S (mm)	D2 (mm)	D1 (mm)	T (mm)	L (mm)	WEIGHT (g)	PACI INNER PC/BOX	OU PC/
	S04H2104	4	6.8	11.8	7	25	9.5	60	1080
	S04H21045	4.5	7.3	11.8	9	25	9.9	60	1080
	S04H2105	5	8.0	11.8	9	25	9.9	60	1080
	S04H21055	5.5	8.6	11.8	9	25	10.1	60	1080
	S04H2106	6	9.2	11.8	9	25	10.4	60	1080
	S04H2107	7	10.5	11.8	9	25	11.2	60	1080
	S04H2108	8	11.7	11.4	9	25	10.2	60	1080
	S04H2109	9	12.7	11.6	9	25	11.7	60	1080
	S04H2110	10	13.7	12.8	9	25	13.1	60	1080
	S04H2111	11	15.7	14.4	9	25	18	60	1080
	S04H2112	12	16.6	13.7	9	25	22.4	60	720
	S04H2113	13	17.6	13.9	9	25	23.5	60	720

The Hardness & The Torque Conform To International Standard





JONNESWAY -

S04HD2 · CHROME VANADIUM STEEL • SEMI MAT FINISHED									
	ITEM NO.	S (mm)	D2 (mm)	D1 (mm)	T (mm)	L (mm)	WEIGHT (g)	PACI INNER PC/BOX	KING OUTER PC/CTN

1/4" DR. 6PT FLANK DEEP SOCKETS

							1 0/00/	10/0111
S04HD2104	4	8.0	12.0	20	50	20	30	540
S04HD21045	4.5	8.0	12.0	20	50	20	30	540
S04HD2105	5	8.0	12.0	20	50	20	30	540
S04HD21055	5.5	8.6	12.0	20	50	20	30	540
S04HD2106	6	9.2	12.0	20	50	20	30	540
S04HD2107	7	10.5	12.0	20	50	22	30	540
S04HD2108	8	12.0	11.5	20	50	22	30	540
S04HD2109	9	13.1	12.4	20	50	28	30	540
S04HD2110	10	14.4	13.3	20	50	34	30	540
S04HD2111	11	15.9	14.8	20	50	56	30	540
S04HD2112	12	17.0	15.8	20	50	60	30	360
S04HD2113	13	17.8	16.8	20	50	66	30	360

Professional Quality

Professional Quality

• DIN 3124


 The Hardness & The Torque Conform To International Standard • DIN 3124



S04HD3

ITEM N S04HD31 S04HD31 S04HD31 S04HD31 S04HD31







JONNESWAY.

S04H3

3/8" DR. 6PT FLANK SOCKETS

CHROME VANADIUM STEEL
 SEMI MAT FINISHED

	S	52	D1	т	I	WEIGUT	PAC	KING
ITEM NO.	(mm)	D2 (mm)	(mm)	ו (mm)	L (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
S04H3106	6	9.6	16.8	6	28	24	40	360
S04H3107	7	10.7	16.8	6	28	24	40	360
S04H3108	8	12.0	16.8	8	28	24	40	360
S04H3109	9	13.3	16.8	8	28	24	40	360
S04H3110	10	14.4	16.8	8	28	24	40	360
S04H3111	11	15.8	16.8	8	28	24	40	360
S04H3112	12	16.8	16.0	9	28	24	40	360
S04H3113	13	19.0	18.0	9	28	24	40	360
S04H3114	14	19.7	18.8	10	28	30	40	360
S04H3115	15	20.8	19.8	10	28	40	40	360
S04H3116	16	22.0	20.8	10	28	40	40	360
S04H3117	17	23.8	22.0	10	28	56	40	360
S04H3118	18	25.7	24.1	12	28	58	40	160
S04H3119	19	25.7	24.1	12	28	60	40	160
S04H3120	20	27.6	25.0	12	32	70	40	160
S04H3121	21	27.6	25.0	14	32	76	40	160
S04H3122	22	29.6	27.8	14	32	76	40	160
S04H3124	24	31.0	29.8	16	32	112	40	160

Professional Quality

 The Hardness & The Torque Conform To International Standard Inch Size Available

• DIN 3124

3/8" DR. 6PT FLANK DEEP SOCKETS


 CHROME VANADIUM STEEL SEMI MAT FINISHED

	S	52	D4	т	I	WEIGUT	PAC	KING
10.	(mm)	D2 (mm)	D1 (mm)	ו (mm)	L (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
106	6	9.8	16.8	7	63	43	20	180
107	7	10.8	16.8	7	63	45	20	180
108	8	12.0	16.8	8	63	50	20	180
109	9	13.3	16.8	9	63	60	20	180
110	10	14.4	17.0	9	63	60	20	180
111	11	15.8	17.0	10	63	60	20	180
112	12	17.7	17.0	12	63	66	20	180
113	13	19.0	18.0	12	63	76	20	180
114	14	19.7	18.8	15	63	80	20	180
115	15	20.8	19.8	15	63	90	20	180
116	16	22.0	20.8	15	63	92	20	180
117	17	23.8	22.8	15	63	110	20	180
118	18	26.0	23.8	18	63	125	20	80
119	19	26.0	23.8	18	63	130	20	80
120	20	27.8	24.8	18	63	140	20	80
121	21	28.0	25.8	18	63	150	20	80
122	22	30.0	27.8	21	63	168	20	80
124	24	32.0	28.0	21	63	193	20	80

Professional Quality
 International Standard For The Hardness And Torque

SOCKETS SERIES






 Professional Quality International Standard For Hardness And Torque DIN 3124

S04H4	Ŭ		VANADI FINISHE		EL			
							PAC	KING
ITEM NO.	S (mm)	D2 (mm)	D1 (mm)	T (mm)	L (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
S04H4108	8	13.8	21.8	8	38	50	20	300
S04H4109	9	14.3	21.8	8	38	50	20	300
S04H4110	10	15.4	21.8	9	38	50	20	300
S04H4111	11	16.7	21.8	9	38	50	20	300
S04H4112	12	18.0	21.8	9	38	53	20	300
S04H4113	13	19.0	21.8	10	38	55	20	300
S04H4114	14	20.3	22.0	12	38	55	20	300
S04H4115	15	21.3	22.0	12	38	55	20	300
S04H4116	16	23.3	22.0	12	38	60	20	300
S04H4117	17	23.8	23.0	12	38	67	20	160
S04H4118	18	24.8	23.5	12	38	71	20	160
S04H4119	19	27.0	24.0	12	38	84	20	160
S04H4120	20	28.0	24.0	12	38	87	20	160
S04H4121	21	29.0	24.0	12	38	90	20	160
S04H4122	22	30.0	28.0	14	38	98	20	160
S04H4123	23	30.7	28.0	14	38	115	20	120
S04H4124	24	31.8	28.0	16	38	125	20	120
S04H4125	25	33.8	28.0	16	38	150	20	120
S04H4126	26	34.0	30.0	16	42	155	20	120
S04H4127	27	35.7	28.0	18	42	165	20	120
S04H4128	28	38.0	30.0	20	42	165	20	80
S04H4129	29	38.0	32.0	20	42	170	20	80
S04H4130	30	39.8	34.0	20	42	200	20	80
S04H4132	32	42.0	36.0	22	42	240	20	80
S04H4134	34	45	40	24	48	280	6	54
S04H4136	36	48	42	24	48	333	5	45


1/2" DR. 6PT FLANK SOCKETS





 Professional Quality International Standard For Hardness And Torque • DIN 3124





- Professional Quality
- · International Standard For Hardness And Torque • DIN 3124

							PAC	KING
ITEM NO.	S (mm)	D2 (mm)	D1 (mm)	T (mm)	L (mm)	(g)	INNER PC/BOX	OUTER PC/CTN
S04HD4108	8	12.7	21.8	9	76	114	10	150
S04HD4109	9	14.3	21.8	9	76	114	10	150
S04HD4110	10	15.4	21.8	10	76	114	10	150
S04HD4111	11	16.7	21.8	12	76	114	10	150
S04HD4112	12	18.0	21.8	13	76	114	10	150
S04HD4113	13	19.0	21.8	14	76	118	10	150
S04HD4114	14	20.3	22.0	15	76	130	10	150
S04HD4115	15	21.3	22.0	16	76	136	10	150
S04HD4116	16	23.0	22.0	17	76	138	10	150
S04HD4117	17	23.8	23.0	18	76	144	10	80
S04HD4118	18	24.8	23.0	19	76	150	10	80
S04HD4119	19	25.8	24.0	20	76	178	10	80
S04HD4120	20	28.0	24.0	21	76	180	10	80
S04HD4121	21	29.0	24.0	23	76	190	10	80
S04HD4122	22	30.0	26.0	27	76	240	10	80
S04HD4123	23	31.8	28.0	27	76	248	10	60
S04HD4124	24	31.8	28.0	27	76	250	10	60
S04HD4125	25	33.8	28.0	27	76	265	10	60
S04HD4126	26	33.8	28.0	27	76	282	10	60
S04HD4127	27	35.7	28.0	28	76	320	10	60
S04HD4128	28	38.0	30.0	28	76	300	10	40
S04HD4130	30	39 8	34 0	34	76	324	10	40

1/2" DR. 6PT FLANK DEEP SOCKETS


 CHROME VANADIUM STEEL SEMI MAT FINISHED



JONNESWAY ----

<u>/</u>]





- Professional Quality International Standard For Hardness And Torque
 DIN 3124



S04HD4

1/2" DR. 12PT SOCKETS(MM)

S04H49

CHROME VANADIUM STEEL
 SEMI MAT FINISHED

		DO	D1	-	1	WEIGUT	PAC	KING
ITEM NO.	S (mm)	D2 (mm)	(mm)	T (mm)	L (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
S04H4908	8	13.8	21.8	8	38	50	20	300
S04H4909	9	14.3	21.8	8	38	50	20	300
S04H4910	10	15.4	21.8	9	38	50	20	300
S04H4911	11	16.7	21.8	9	38	50	20	300
S04H4912	12	18.0	21.8	9	38	53	20	300
S04H4913	13	19.0	21.8	10	38	55	20	300
S04H4914	14	20.3	22.0	12	38	55	20	300
S04H4915	15	21.3	22.0	12	38	55	20	300
S04H4916	16	23.3	22.0	12	38	60	20	300
S04H4917	17	23.8	23.0	12	38	67	20	160
S04H4918	18	24.8	23.5	12	38	71	20	160
S04H4919	19	27.0	24.0	12	38	84	20	160
S04H4920	20	28.0	24.0	12	38	87	20	160
S04H4921	21	29.0	24.0	12	38	90	20	160
S04H4922	22	30.0	28.0	14	38	98	20	160
S04H4923	23	30.7	28.0	14	38	115	20	120
S04H4924	24	31.8	28.0	16	38	125	20	120
S04H4925	25	33.8	28.0	16	38	150	20	120
S04H4926	26	34.0	30.0	16	42	155	20	120
S04H4927	27	35.7	28.0	18	42	165	20	120
S04H4928	28	38.0	30.0	20	42	165	20	80
S04H4929	29	38.0	32.0	20	42	170	20	80
S04H4930	30	39.8	34.0	20	42	200	20	80
S04H4932	32	42.0	38.0	22	42	240	20	80


SOCKETS SERIES

	1/2	1/2" DR. 12PT FLANK DEEP SOCKETS								
S04HD4		ROME VA MI MAT FI		STEEL						
		D2	D1		WEIGHT	PAC	<ing< th=""></ing<>			
ITEM NO.	(mm)	D2 (mm)	D1 (mm)	L (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN			

TIEM NO.	(mm)	(mm)	(mm)	(mm)	(g)	INNER PC/BOX	OUTER PC/CTN
S04HD4710	10	15	21.8	76	114	10	150
S04HD4711	11	16.3	21.8	76	114	10	150
S04HD4712	12	17.6	21.8	76	114	10	150
S04HD4713	13	18.8	21.8	76	118	10	150
S04HD4714	14	20.4	21.8	76	130	10	150
S04HD4715	15	22	21	76	136	10	150
S04HD4716	16	22	21	76	138	10	150
S04HD4717	17	24	22	76	144	10	80
S04HD4718	18	26	23	76	150	10	80
S04HD4719	19	26	23	76	178	10	80
S04HD4720	20	28	24	76	180	10	80
S04HD4721	21	28	24	76	190	10	80
S04HD4722	22	30	26	76	240	10	80
S04HD4723	23	32	28	76	248	10	80
S04HD4724	24	32	28	76	250	10	60

SOCKETS SERIES





S04H6	• SE	HROME VA EMI MAT FI N 3124		TEEL			
						PAC	KING
ITEM NO.	S (mm)	L (mm)	D1 (mm)	D2 (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
S04H6119	19	49.5	30	36	220	25	100
S04H6121	21	49.5	32	36	220	25	100
S04H6122	22	49.5	33	36	220	25	100
S04H6123	23	49.5	34	36	220	25	100
S04H6124	24	49.5	35	36	220	25	100
S04H6125	25	50	36	36	220	25	100
S04H6126	26	50	37	36	220	25	100
S04H6127	27	52	38	36	220	25	100
S04H6128	28	52	39	36	220	25	100
S04H6129	29	53	40	38	237	25	100
S04H6130	30	54	42	38	262	25	75
S04H6132	32	56	44	38	281	25	75
S04H6133	33	56	46	38	312	25	75
S04H6134	34	58	46	38	312	25	50
S04H6135	35	58	48	42	358	25	50
S04H6136	36	58	50	42	400	25	50
S04H6138	38	60	52	45	450	25	50
S04H6141	41	64	56	45	537	10	30
S04H6146	46	68	62	48	650	10	30
S04H6150	50	72	68	48	783	10	30

3/4" DR. 6PT FLANK SOCKETS



ITEM NO S06H204 S06H205 S06H206 S06H207 S06H208

S06




ITEM NO S06H308 S06H310 S06H311 S06H312 S06H314 S06H316

S06

JONNESWAY -





504H64	• SEMI MAT	• CHROME VANADIUM STEEL • SEMI MAT FINISHED • ANSI / ASME B107.1								
ITEM NO.	S (size)	L (mm)	D1 (mm)	D2 (mm)	WEIGHT (g)					
S04H6419	3/4"	49.5	30	36	220					
S04H6421	13/16"	49.5	32	36	220					
S04H6422	7/8"	49.5	33	36	220					
S04H6424	15/16"	49.5	35	36	220					
S04H6426	1"	50	37	36	220					
S04H6427	1-1/16"	52	38	36	220					
S04H6429	1-1/8"	53	40	38	237					
S04H6430	1-3/16"	54	42	38	262					
S04H6432	1-1/4"	56	44	38	281					
S04H6433	1-5/16"	56	46	38	312					
S04H6435	1-3/8"	58	48	42	358					
S04H6436	1-7/16"	58	50	42	400					
S04H6438	1-1/2"	60	52	45	450					
S04H6441	1-5/8"	64	56	45	537					
S04H6444	1-3/4"	64	56	45	537					
S04H6446	1-13/16"	68	62	48	650					
S04H6447	1-7/8"	68	62	48	650					
S04H6450	2"	72	68	48	783					
S04H6456	2-1/4"	76	75	48	1000					

3/4" DR. 12PT FLANK SOCKETS

 Professional Quality · International Standard For Hardness And Torque

JONNESWAY

5

JONNESWAY



 Professional Quality International Standard For Hardness And Torque • DIN 3120



 \bigwedge

70



JONNESWAY.

			1/4" C)R. S1	TAR S	OCKE	TS			
• CHROME VANADIUM STEEL • SEMI MAT FINISHED • DIN 3120										
	A (size)		S D1 (mm) (mm	D1	D2	L1	L2	WEIGHT	PACĶING	
Э.				(mm)	(mm)	(mm)	(mm)	(g)	INNER PC/BOX	OUTER PC/CTN
4	E4		6.350	12	6.2	25	11	10	50	1000
5	E5		6.350	12	7.2	25	11	10	50	1000
6	E6		6.350	12	8.2	25	11	11	50	1000
7	E7		6.350	12	9.0	25	11	11	50	1000
8	E8		6.350	12	10.3	25	11	12	50	1000

H3 •CHROME VANADIUM STEEL •SEMI MAT FINISHED •DIN 3120									
				-	-				
			D 4	50	14		WEIGUT	PAC	KING
	A (size)	S (mm)	D1 (mm)	D2 (mm)	L1 (mm)	L2 (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
3	E8	9.525	17	11.2	28	12	24	40	800

3/8" DR. STAR SOCKETS

3001300	EO	9.525	17	11.2	20	12	24	40	800
S06H310	E10	9.525	17	13.2	28	12	25	40	800
S06H311	E11	9.525	17	13.8	28	12	25	40	800
S06H312	E12	9.525	17	14.8	28	12	26	40	800
S06H314	E14	9.525	18	16.8	28	12	33	40	800
S06H316	E16	9.525	20	18.8	28	12	43	40	480
S06H318	E18	9.525	22	20.8	28	12	53	20	300
S06H320	E20	9.525	24	22.8	28	12	61	20	300

S06H	4	• CHROME VANADIUM STEEL • SEMI MAT FINISHED • DIN 3120								
ITEM NO.	A (size)	S (mm)	D1 (mm)	D2 (mm)	L1 (mm)	L2 (mm)	WEIGHT (g)	PAC INNER PC/BOX	KING OUTER PC/CTN	
S06H410	E10	12.700	22	13.2	38	17	50	20	300	
S06H411	E11	12.700	22	13.9	38	17	50	20	300	
S06H412	E12	12.700	22	15.0	38	17	53	20	300	
S06H414	E14	12.700	22	16.7	38	17	53	20	300	
S06H416	E16	12.700	22	18.8	38	17	55	20	300	
S06H418	E18	12.700	22	20.8	38	17	80	20	160	
S06H420	E20	12.700	22	23.0	38	17	90	20	160	
S06H422	E22	12.700	22	25.0	38	17	93	20	160	
S06H424	E24	12.700	22	27.0	38	17	111	20	160	

1/2" DR. STAR SOCKETS


SOCKETS SERIES

JONNESWAY

I,A,

JONNESWAY


	-	




	1/4" DR. 6PT DEEP SOCKETS (MAXI-DRIVE)
S05HD2	CHROME VANADIUM STEEL
	POLISH-FINISHED
	ANSI/ASME B107.1

	•	DI	D 2		WEIGHT	PAC	KING
ITEM NO.	A (size)	D1 (mm)	D2 (mm)	(mm)	(g)	INNER PC/BOX	OUTER PC/CTN
S05HD2105	5	12.0	8.0	50	18	30	540
S05HD2106	6	12.0	9.2	50	18	30	540
S05HD2107	7	12.0	10.5	50	20	30	540
S05HD2108	8	12.0	12.0	50	20	30	540
S05HD2109	9	13.1	13.1	50	20	30	540
S05HD2110	10	14.4	14.4	50	20	30	540
S05HD2111	11	15.9	15.9	50	25	30	540
S05HD2112	12	17.0	17.0	50	35	30	360
S05HD2113	13	17.8	17.8	50	50	30	360







ITEM NO.

S07H206


S07H2

S07H3

		L3	в		D	d	L1	L2	WEIGHT	PAC	KING
ITEM NO.	A (size)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(g)	INNER	
	· ,	. ,	· ,	· ,	· ,	. ,	• •	. ,		PC/BOX	PC/CTN
S07H310	T10	30	6.30	48	18	13.8	16.5	26	36	30	240
S07H315	T15	30	6.30	48	18	13.8	16.5	26	36	30	240
S07H320	T20	30	6.30	48	18	13.8	16.5	26	36	30	240
S07H325	T25	30	6.30	48	18	13.8	16.5	26	36	30	240
S07H327	T27	30	6.30	48	18	13.8	16.5	26	36	30	240
S07H330	T30	30	6.30	48	18	13.8	16.5	26	36	30	240
S07H340	T40	30	6.30	48	18	13.8	16.5	26	38	30	240
S07H345	T45	30	7.88	48	18	15.8	16.5	26	42	30	240
S07H350	T50	30	7.88	48	18	15.8	16.5	26	46	30	240
S07H355	T55	30	10.00	48	18	16.1	16.5	26	52	30	240
S07H360	T60	30	10.00	48	18	16.1	16.5	26	56	30	240


S07H315	
S07H320	ſ
S07H325	
S07H327	
S07H330	
S07H340	
S07H345	
S07H350	
S07H355	


S07H



mai		
WHE		

9.525






	3/8" [)R. 12PT	SOCKE	TS (MA)	(I-DRIVE)				
S05H3	• POLIS	CHROME VANADIUM STEEL POLISH - FINISHED ANSI/ASME B107.1								
		PACKING								
ITEM NO.	A (size)	D1 (mm)	D2 (mm)	L (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN			
S05H3808	8	16.8	12.0	28	20	40	360			
S05H3809	9	16.8	13.3	28	20	40	360			
S05H3810	10	17.0	14.4	28	20	40	360			
S05H3811	11	17.7	15.8	28	25	40	360			
S05H3812	12	17.7	17.7	28	25	40	360			
S05H3813	13	19.0	19.0	28	35	40	360			
S05H3814	14	19.7	19.7	28	30	40	360			
S05H3815	15	20.8	20.8	28	40	40	360			
S05H3816	16	22.0	22.0	28	40	40	360			
S05H3817	17	23.8	23.8	30	50	40	360			
S05H3819	19	26.0	26.0	30	70	40	160			

JONNESWAY -

JONNESWAY





	1/2" [DR. 12PT	SOCKE	TS (MA)	(i-drive	i)			
S05H4	• POLIS	• CHROME VANADIUM STEEL • POLISH - FINISHED • ANSI/ASME 107.1							
						PAC	KING		
ITEM NO.	A (size)	D1 (mm)	D2 (mm)	L (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN		
S05H4810	10	21.8	15.4	38	60	20	300		
S05H4812	12	21.8	18.0	38	60	20	300		
005114040	40	01.0	40.0			00	000		

	(size)	(mm)	(mm)	(mm)	(g)	PC/BOX	PC/CTN
S05H4810	10	21.8	15.4	38	60	20	300
S05H4812	12	21.8	18.0	38	60	20	300
S05H4813	13	21.8	19.0	38	60	20	300
S05H4814	14	22.0	20.3	38	60	20	300
S05H4815	15	22.0	22.0	38	60	20	300
S05H4817	17	23.7	23.8	38	70	20	300
S05H4819	19	25.8	25.8	38	80	20	160
S05H4821	21	27.8	27.8	38	90	20	160



1/4" DR. STAR BIT SOCKETS

• CHROME VANADIUM STEEL
 • SEMI MAT FINISHED
 • DIN 3120

A L3 B L D d L1 L2 WEIGHT INNER IUTER (size) (mm)		1.0			_	-1	14	1.0	WEIGUT	PAC	KING
To Lo Gr Tr Tr <thtr< th=""> Tr Tr Tr<!--</td--><td></td><td></td><td>-</td><td>(mm)</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></thtr<>			-	(mm)							
TB 25 6.3 37 12 10.8 13 19 14 40 240 T9 25 6.3 37 12 10.8 13 19 14 40 240 T9 25 6.3 37 12 10.8 13 19 14 40 240 T10 25 6.3 37 12 10.8 13 19 14 40 240 T10 25 6.3 37 12 10.8 13 19 14 40 240 T15 25 6.3 37 12 10.8 13 19 14 40 240 T20 25 6.3 37 12 10.8 13 19 14 40 240 T25 25 6.3 37 12 10.8 13 19 14 40 240 T27 25 6.3 37	T6	25	6.3	37	12	10.8	13	19	14	40	240
T9 25 6.3 37 12 10.8 13 19 14 40 240 T10 25 6.3 37 12 10.8 13 19 14 40 240 T10 25 6.3 37 12 10.8 13 19 14 40 240 T15 25 6.3 37 12 10.8 13 19 14 40 240 T20 25 6.3 37 12 10.8 13 19 14 40 240 T20 25 6.3 37 12 10.8 13 19 14 40 240 T25 25 6.3 37 12 10.8 13 19 14 40 240 T27 25 6.3 37 12 10.8 13 19 14 40 240 T30 25 6.3 37	T7	25	6.3	37	12	10.8	13	19	14	40	240
Tio 25 6.3 37 12 10.8 13 19 14 40 240 T15 25 6.3 37 12 10.8 13 19 14 40 240 T15 25 6.3 37 12 10.8 13 19 14 40 240 T20 25 6.3 37 12 10.8 13 19 14 40 240 T20 25 6.3 37 12 10.8 13 19 14 40 240 T25 25 6.3 37 12 10.8 13 19 14 40 240 T27 25 6.3 37 12 10.8 13 19 14 40 240 T30 25 6.3 37 12 10.8 13 19 14 40 240	Т8	25	6.3	37	12	10.8	13	19	14	40	240
T15 25 6.3 37 12 10.8 13 19 14 40 240 T20 25 6.3 37 12 10.8 13 19 14 40 240 T20 25 6.3 37 12 10.8 13 19 14 40 240 T25 25 6.3 37 12 10.8 13 19 14 40 240 T27 25 6.3 37 12 10.8 13 19 14 40 240 T27 25 6.3 37 12 10.8 13 19 14 40 240 T30 25 6.3 37 12 10.8 13 19 14 40 240	Т9	25	6.3	37	12	10.8	13	19	14	40	240
T20 25 6.3 37 12 10.8 13 19 14 40 240 T25 25 6.3 37 12 10.8 13 19 14 40 240 T25 25 6.3 37 12 10.8 13 19 14 40 240 T27 25 6.3 37 12 10.8 13 19 14 40 240 T30 25 6.3 37 12 10.8 13 19 14 40 240	T10	25	6.3	37	12	10.8	13	19	14	40	240
T25 25 6.3 37 12 10.8 13 19 14 40 240 T27 25 6.3 37 12 10.8 13 19 14 40 240 T30 25 6.3 37 12 10.8 13 19 14 40 240	T15	25	6.3	37	12	10.8	13	19	14	40	240
T27 25 6.3 37 12 10.8 13 19 14 40 240 T30 25 6.3 37 12 10.8 13 19 14 40 240	T20	25	6.3	37	12	10.8	13	19	14	40	240
T30 25 6.3 37 12 10.8 13 19 14 40 240	T25	25	6.3	37	12	10.8	13	19	14	40	240
	T27	25	6.3	37	12	10.8	13	19	14	40	240
T40 25 6.3 37 12 10.8 13 19 16 40 240	T30	25	6.3	37	12	10.8	13	19	14	40	240
	T40	25	6.3	37	12	10.8	13	19	16	40	240

	3/8'	' DR.	STAI	R BIT	SOC	KET	5	
	• SEN		VANAD FINISH	IUM ST ED	EEL			
Ą	L3	в	L	D	d	L1	L2	ľ

	1/2" DR. STAR BIT SOCKETS
4	CHROME VANADIUM STEEL SEMI MAT FINISHED DIN 3120

А	L3	в		D	d	11	12	WEIGHT	PACI	KING
A (size)	(mm)	в (mm)	(mm)	(mm)	a (mm)	(mm)	L2 (mm)	(g)	INNER PC/BOX	OUTER PC/CTN
T20	30	7.88	55	22	15	20	38	70	20	200
T25	30	7.88	55	22	15	20	38	70	20	200
T27	30	7.88	55	22	15	20	38	70	20	200
Т30	30	7.88	55	22	15	20	38	70	20	200
T40	30	7.88	55	22	15	20	38	72	20	200
T45	30	7.88	55	22	15	20	38	72	20	200
T50	30	7.88	55	22	15	20	38	76	20	200
T55	30	10	55	22	17	20	38	84	20	200
T60	30	12	55	24	22	20	38	114	20	200
T70	30	14	55	24	22	20	38	116	20	200
T20	75	7.88	100	24	15	20	38	88	20	200
T25	75	7.88	100	24	15	20	38	90	20	200
T27	75	7.88	100	24	15	20	38	90	20	200
Т30	75	7.88	100	24	15	20	38	90	20	200
T40	75	7.88	100	24	15	20	38	92	20	200
T45	75	7.88	100	24	15	20	38	92	20	200
T50	75	7.88	100	24	15	20	38	92	20	200
T55	75	10	100	24	17	20	38	112	20	200
T60	75	14	100	24	22	20	38	172	20	200
T70	75	14	100	24	22	20	38	178	20	200


HEX BIT SOCKET

74




		1/4'	1/4" DR. STAR BIT SOCKETS(TAMPERPROOF)												
S08F	12	• SEM	CHROME VANADIUM STEEL SEMI MAT FINISHED DIN 3120												
ITEM NO.	A (size)	L3 (mm)	B (mm)	L (mm)	D (mm)	d (mm)	L1 (mm)	L2 (mm)	WEIGHT (g)	PACI INNER PC/BOX					
S08H206	T6	25	6.3	37	12	10.8	13	19	14	40	240				
S08H207	T7	25	6.3	37	12	10.8	13	19	14	40	240				
S08H208	T8	25	6.3	37	12	10.8	13	19	14	40	240				
S08H209	Т9	25	6.3	37	12	10.8	13	19	14	40	240				
S08H210	T10	25	6.3	37	12	10.8	13	19	14	40	240				
S08H215	T15	25	6.3	37	12	10.8	13	19	14	40	240				
S08H220	T20	25	6.3	37	12	10.8	13	19	14	40	240				
S08H225	T25	25	6.3	37	12	10.8	13	19	14	40	240				
S08H227	T27	25	6.3	37	12	10.8	13	19	14	40	240				
S08H230	T30	25	6.3	37	12	10.8	13	19	14	40	240				
S08H240	T40	25	6.3	37	12	10.8	13	19	14	40	240				

JONNESWAY -



S08H3 ·CHROME VANADIUM STEEL •SEMI MAT FINISHED •DIN 3120												
SEMI MAT FINISHED												
A L3 B L D d L1 L2 WEIGHT PACKING												
ITEM NO. A L3 B L D d L1 L2 WEIGHI (mm) (mm) (mm) (mm) (mm) (mm) (mm) (mm)	OUTER PC/CTN											
S08H310 T10 30 6.30 48 18 13.8 15.5 26.5 36 30	240											
S08H315 T15 30 6.30 48 18 13.8 15.5 26.5 36 30	240											
S08H320 T20 30 6.30 48 18 13.8 15.5 26.5 36 30	240											
S08H325 T25 30 6.30 48 18 13.8 15.5 26.5 36 30	240											
S08H327 T27 30 6.30 48 18 13.8 15.5 26.5 36 30	240											
S08H330 T30 30 6.30 48 18 13.8 15.5 26.5 36 30	240											
S08H340 T40 30 6.30 48 18 13.8 15.5 26.5 38 30	240											






			• SEMI MAT FINISHED • DIN 3120										
ITEMNO	A	L3	В	L	D	d	L1	L2	WEIGHT	PACKING			
ITEM NO.	(size)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(g)	PC/BOX			
S08H420	T20	30	7.88	55	24	15	20	38	70	20	200		
S08H425	T25	30	7.88	55	24	15	20	38	70	20	200		
S08H427	T27	30	7.88	55	24	15	20	38	70	20	200		
S08H430	T30	30	7.88	55	24	15	20	38	70	20	200		
S08H440	T40	30	7.88	55	24	15	20	38	72	20	200		
S08H445	T45	30	7.88	55	24	15	20	38	72	20	200		
S08H450	T50	30	7.88	55	24	15	20	38	74	20	200		
S08H455	T55	30	10	55	24	17	20	38	82	20	200		
S08H460	T60	30	12	55	24	22	20	38	112	20	200		
S08H470	T70	30	14	55	24	22	20	38	114	20	200		


CHROME VANADIUM STEEL

1/2" DR. STAR BIT SOCKETS(TAMPERPROOF)

S08H4







S09



JONNESWAY.

S09F	12	• SEM	ROME V MI MAT 7422			EEL					
ITEM NO.	A (size)	L3 (mm)	B (mm)	L (mm)	D (mm)	d (mm)	L1 (mm)	L2 (mm)	WE I GHT (g)	PACI INNER PC/BOX	≺ING OUTER PC/CTN
S09H203	H3	25	6.3	37	12	10.8	13	19	14	40	240
S09H204	H4	25	6.3	37	12	10.8	13	19	14	40	240
S09H205	H5	25	6.3	37	12	10.8	13	19	14	40	240
S09H206	H6	25	6.3	37	12	10.8	13	19	16	40	240
S09H207	H7	25	6.3	37	12	10.8	13	19	16	40	240

1/4" DR. HEX BIT SOCKETS

		3/8'	' DR.	HEX	BIT S	SOCK	ETS							
S09H	3	CHROME VANADIUM STEEL SEMI MAT FINISHED DIN 7422												
ITEM NO.	A (size)	L3 (mm)	B (mm)	L (mm)	D (mm)	d (mm)	L1 (mm)	L2 (mm)	WEIGHT (g)	PACI INNER PC/BOX	OUTER			
S09H303	H3	30	6.30	48	18	13.8	16.5	26	36	30	240			
S09H304	H4	30	6.30	48	18	13.8	16.5	26	36	30	240			
S09H305	H5	30	6.30	48	18	13.8	16.5	26	38	30	240			
S09H3055	H5.5	30	6.30	48	18	13.8	16.5	26	38	30	240			
S09H306	H6	30	6.30	48	18	13.8	16.5	26	38	30	240			
S09H307	H7	30	7.88	48	18	15.8	16.5	26	44	30	240			
S09H308	H8	30	7.88	48	18	15.8	16.5	26	44	30	240			
S09H310	H10	30	10.0	48	18	16.1	16.5	26	52	30	240			
S09H312	H12	30	10.0	48	18	16.1	16.5	26	62	30	240			
S09H314	H14	30	10.0	48	18	16.1	16.5	26	78	30	240			

	1/2" DR. HEX BIT SOCKETS
H4	• CHROME VANADIUM STEEL • SEMI MAT FINISHED • DIN 7422

	A	A	L3		в		D	d	L1	L2	WEIGHT	PACI	KING
ITEM NO.	(size)	(mm)	(g)		OUTER PC/CTN								
S09H404	H4	30	7.88	55	24	15	20	38	72	20	200		
S09H405	H5	30	7.88	55	24	15	20	38	72	20	200		
S09H406	H6	30	7.88	55	24	15	20	38	74	20	200		
S09H407	H7	30	7.88	55	24	15	20	38	74	20	200		
S09H408	H8	30	7.88	55	24	15	20	38	76	20	200		
S09H410	H10	30	10	55	24	17.8	20	38	86	20	200		
S09H412	H12	30	12	55	24	22	20	38	118	20	200		
S09H414	H14	30	14	55	24	22	20	38	122	20	200		
S09H416	H16	30	14	55	24	22	20	38	132	20	200		
S09H4304	H4	75	7.88	100	24	15	20	38	92	20	200		
S09H4305	H5	75	7.88	100	24	15	20	38	92	20	200		
S09H4306	H6	75	7.88	100	24	15	20	38	92	20	200		
S09H4307	H7	75	7.88	100	24	15	20	38	92	20	200		
S09H4308	H8	75	7.88	100	24	15	20	38	96	20	200		
S09H4310	H10	75	10	100	24	20.8	20	38	116	20	200		
S09H4312	H12	75	14	100	24	22	20	38	176	20	200		
S09H4314	H14	75	14	100	24	22	20	38	180	20	200		
S09H4316	H16	75	14	100	24	22	20	38	222	20	200		

75






		1/4	'DR.	SLO	ITED	BIT	SOCI	(ETS					
\$10H	12	CHROME VANADIUM STEEL SEMI MAT FINISHED DIN 5264 / 3120											
ITEM NO.	A (size)	L3 (mm)	B (mm)	L (mm)	D (mm)	d (mm)	L1 (mm)	L2 (mm)	WEIGHT (g)	PACI INNER PC/BOX			
S10H240	4mm	25	6.3	37	12	10.8	13	21	14	40	240		
S10H255	5.5mm	25	6.3	37	12	10.8	13	21	14	40	240		
S10H270	7mm	25	6.3	37	12	10.8	13	21	16	40	240		



JONNESWAY -





JONNESWAY -

Û

(]]





		3/8'	3/8" DR. SLOTTED BIT SOCKETS												
S10F	13	CHROME VANADIUM STEEL SEMI MAT FINISHED DIN 5264 / 3120													
ITEM NO.	A (size)	L3 (mm)	B (mm)	L (mm)	D (mm)	d (mm)	L1 (mm)	L2 (mm)	WEIGHT (g)	PACKING					
S10H340	4mm	30	6.30	48	18	13.8	15.5	26.5	36	30	240				
S10H350	5mm	30	6.30	48	18	13.8	15.5	26.5	36	30	240				
S10H355	5.5mm	30	6.30	48	18	13.8	15.5	26.5	36	30	240				
S10H360	6mm	30	6.30	48	18	13.8	15.5	26.5	36	30	240				
S10H370	7mm	30	6.30	48	18	13.8	15.5	26.5	38	30	240				
S10H380	8mm	30	7.88	48	18	15.8	15.5	26.5	40	30	240				
S10H3100	10mm	30	10.00	48	20	17.8	15.5	26.5	42	30	240				
S10H3120	12mm	30	10.00	48	20	17.8	15.5	26.5	42	30	240				


JONNESWAY

JONNESWAY -



		1/4'	' DR.	PHIL	LIPS	BIT	SOCK	ETS						
S11H2		• SEM	CHROME VANADIUM STEEL SEMI MAT FINISHED DIN 5260 / 3120											
	A	L3	в		р	d	1.1	12	WEIGHT	PAC	KING			
ITEM NO.	(size)	(mm)	(mm)	(mm)	(mm)		(mm)	(mm)	(a)	INNER PC/BOX	OUTER PC/CTN			

S11H200 PH0 25 6.30 37 12 10.8 13 19 14 40 240 S11H201 PH1 25 6.30 37 12 10.8 13 19 14 40 240 S11H201 PH1 25 6.30 37 12 10.8 13 19 14 40 240 S11H202 PH2 25 6.30 37 12 10.8 13 19 14 40 240 S11H202 PH2 25 6.30 37 12 10.8 13 19 14 40 240 S11H203 PH3 25 6.30 37 12 10.8 13 19 16 40 240	TIEM NO.	(size)	(mm)	(g)	INNER PC/BOX							
S11H202 PH2 25 6.30 37 12 10.8 13 19 14 40 240	S11H200	PH0	25	6.30	37	12	10.8	13	19	14	40	240
	S11H201	PH1	25	6.30	37	12	10.8	13	19	14	40	240
S11H203 PH3 25 6.30 37 12 10.8 13 19 16 40 240	S11H202	PH2	25	6.30	37	12	10.8	13	19	14	40	240
	S11H203	PH3	25	6.30	37	12	10.8	13	19	16	40	240





THESE SOCKETS SHOULD NEVER BE USED ON POWER DRIVE OR IMPACT WRENCHES!

JONNESWAY.

3/8" DR. PHILLIPS BIT SOCKETS

S1	1	E	3

CHROME VANADIUM STEEL
 SEMI MAT FINISHED
 DIN 5260 / 3120

		1.0					14	1.0		PAC	KING
ITEM NO.	A (size)	L3 (mm)	B (mm)	L (mm)	D (mm)	d (mm)	L1 (mm)	L2 (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
S11H300	PH0	30	6.30	48	18	13.8	16.5	26	36	30	240
S11H301	PH1	30	6.30	48	18	13.8	16.5	26	36	30	240
S11H302	PH2	30	6.30	48	18	13.8	16.5	26	36	30	240
S11H303	PH3	30	6.30	48	18	15.8	16.5	26	38	30	240
S11H304	PH4	30	7.88	48	18	15.8	16.5	26	42	30	240

	1/4" DR. POZI BIT SOCKETS										
S12H2 • CHROME VANADIUM STEEL • SEMI MAT FINISHED											
ITEM NO.	A (size)	L3 (mm)									OUTER
S12H200	PZ0	25	6.30	37	12	10.8	13	19	14	40	240
S12H201	PZ 1	25	6.30	37	12	10.8	13	19	14	40	240
S12H202	PZ2	25	6.30	37	12	10.8	13	19	14	40	240
S12H203	PZ3	25	6.30	37	12	10.8	13	19	16	40	240

		3/8" DR. POZI BIT SOCKETS									
S12H3 • CHROME VANADIUM STEEL • SEMI MAT FINISHED											
										KING	
ITEM NO.	A (size)	L3 (mm)	B (mm)	L (mm)	D (mm)	d (mm)	L1 (mm)	L2 (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
S12H300	PZ0	30	6.30	48	18	13.8	16.5	26	36	30	240
S12H301	PZ 1	30	6.30	48	18	13.8	16.5	26	36	30	240
S12H302	PZ2	30	6.30	48	18	13.8	16.5	26	36	30	240
S12H303	PZ3	30	6.30	48	18	13.8	16.5	26	38	30	240
S12H304	PZ4	30	7.88	48	18	15.8	16.5	26	42	30	240

JONNESWAY.



S15U43S	3PCS POWERI	UL UNIVERS	AL JOINT SE	т
SIZE	D1	D2	L1	L2
1/4"F×1/4"M	18	16	39	43
3/8"F×3/8"M	24	22	51	58
1/2"F×1/2"M	30	28	65	72

UNIVERSAL JOINTS

• DIN 3123

D1 (mm)

25

14

18

D1 (mm)

S (size)

1/2"

1/4"

3/8"

S (size)

· CHROME VANADIUM STEEL

D2 (mm)

25

18

D2 (mm)

3/4" 39.7 39.5 106.2 535

14

PACKING

INNER OUTER PC/BOX PC/CTN

60 540

PACKING

INNER OUTER PC/BOX PC/CTN

15

80

216

30

10

24

WEIGHT (g)

150

70

WEIGHT

(g)

35 30

L (mm)

69

49

L (mm)

S15H

Mat Finished

ITEM NO.


S15H472

S15H356


S15H240 Polish Finished

ITEM NO.

S15H6109









S17M

S 27	1

	CHROME PLATED							
		6		WEIGHT	PACI	KING		
ITEN	/I NO.	S (size)	(mm)	(g) WEIGHT INNER PC/BOX		OUTER PC/CTN		
S2	7H2	1/4"	145	57	50	300		
S2	7H3	3/8"	193	280	50	100		
S2	7H4	1/2"	205	285	25	50		

	ITEM
	S27
	S27
	S27

JONNESWAY -

S27H2

JONNESWAY -



JONNESWAY -



 Material: CR-V olished Finish


 	• Po
	• S6

JONNESWAY -

SOCKETS SERIES



JONNESWAY -



ITEM NO. S (size) A (mm) D1 (mm) D2 (mm) L (mm) WEIGHT (mm) PACKIN INNER (p) S16H1438 1/4" (F) x 3/8" (M) 9.52 6.35 14 25 16 60 7 S16H3812 3/8" (F) x 1/2" (M) 12.7 9.52 17 35 44 40 40 S16H1238 1/2" (F) x 3/8" (M) 9.52 12.7 22 34 52 30 30 Polish Finished PACKIN	C4CU	ADAPTE	RS							
ITEM NO. S (size) A (mm) D1 (mm) D2 (mm) L (mm) WEIGHT (mm) PACKIN INNER (p) S16H1438 1/4" (F) x 3/8" (M) 9.52 6.35 14 25 16 60 7 S16H3812 3/8" (F) x 1/2" (M) 12.7 9.52 17 35 44 40 40 S16H1238 1/2" (F) x 3/8" (M) 9.52 12.7 22 34 52 30 30 Polish Finished PACKIN	910 H	of in conne	VANAD	IUM ST	EEL					
ITEM NO. S (size) A (mm) D1 (mm) D2 (mm) L (mm) WEGHT (mm) INNER (g) D PC/BOX D PC/BOX <thd>PC/BOX <thd>PC/BOX <thd< td=""><td colspan="9">Mat Finished</td></thd<></thd></thd>	Mat Finished									
ITEM NO. (size) (mm) (mm) (mm) (mm) (mm) (g) INNER O PC/BOX PC O PC/BOX PC \$16H1438 1/4" (F) x 3/8" (M) 9.52 6.35 14 25 16 60 - \$16H3812 3/8" (F) x 1/2" (M) 12.7 9.52 17 35 44 40 - \$16H1238 1/2" (F) x 3/8" (M) 9.52 12.7 22 34 52 30 - Polish Finished PACKIN				D 4	50		WEIGUT	PAC	, KING	
S16H3812 3/8" (F) x 1/2" (M) 12.7 9.52 17 35 44 40 S16H1238 1/2" (F) x 3/8" (M) 9.52 12.7 22 34 52 30 Polish Finished PACKIN	ITEM NO.								OUTER PC/CTN	
S16H1238 1/2" (F) x 3/8" (M) 9.52 12.7 22 34 52 30 Polish Finished PACKIN	S16H1438	1/4" (F) x 3/8" (M)	9.52	6.35	14	25	16	60	1080	
Polish Finished	S16H3812	3/8" (F) x 1/2" (M)	12.7	9.52	17	35	44	40	360	
PACKIN	S16H1238	1/2" (F) x 3/8" (M)	9.52	12.7	22	34	52	30	270	
Polish Finished PACK		., .,								
PACKIN	Polish Finished									
ITEM NO S A D1 D2 L WEIGHT		e	_	D1	D2		WEIGHT	PACI	KING	


		•		D2		WEIGUT	FAU	ING
ITEM NO.	S (size)	A (mm)	D1 (mm)	(mm)	L (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
S16H1234	1/2" (F) x 3/4" (M)	19.05	12.7	27	45	134	50	100
S16H1034	1" (F) x 3/4" (M)	19.05	26.0	50	60	362	25	50
S16H3412	3/4" (F) x 1/2" (M)	12.7	19.05	35	51	186	25	50
S16H3410	3/4" (F) x 1" (M)	25.3	19.05	39.7	59.6	360	25	50

S16		ADAPTERS								
			• CHROME VANADIUM STEEL MAT FINISHED • DIN 3123							
			A		D 0		WEIGUT	PACKING		
ITEM NO.		S (size) (I	A D1 (mm) (mm)	D2 (mm)	(mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN		
S16H302	1/4"	(M) x 3/8" (F)	6.35	9.75	18.6	28	28.6	60	720	
S16H304	1/2"	(M) x 3/8" (F)	12.7	9.75	23.5	43.7	67.8	25	225	
S16H403	3/8"	(M) x 1/2" (F)	9.5	12.9	23.5	40	64.6	20	300	

78







	SPARK	SPARK PLUG SOCKETS								
S17H	• GHINOWE	• INSIDE SLEEVE - RUBBER • CHROME VANADIUM STEEL • MAT FINISHAD • DIN 3120								
	s	A	D1	D2		WEIGHT	PACI	KING		
ITEM NO.	(size)	(mm)	(mm)	(mm)	(mm)	(g)	INNER PC/BOX	OUTER PC/CTN		
S17H4116	1/2"DR.*16mm	12.700	21.8	21.8	65	92	40	160		
S17H4121	1/2"DR.*21mm	12.700	27.6	23.6	65	146	20	80		

SPARK PLUG SOCKETS W/MAGNETIC

INSIDE SLEEVE - MAGNETIC
 CHROME VANADIUM STEEL
 MAT FINISHED
 DIN 3120

			54	D2			PACKING		
Э.	s (size)	A (mm)	D1 mm)	(mm)	L (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN	
16	3/8"DR.*16mm	9.525	21.7	18.8	65	110	100	200	
21	3/8"DR.*21mm	9.525	27.6	21.5	65	160	50	100	
16	1/2"DR.*16mm	12.700	21.8	21.8	65	110	100	200	
21	1/2"DR.*21mm	12.700	27.6	23.6	65	166	50	100	

Г		Π	
	_		

FLEXIBLE EXTENSION BARS

CHROME VANADIUM STEEL

	EXTE	EXTENSION BARS										
H		CHROME VANADIUM STEEL DIN 3123										
shed												
				PACKING								
Э.	S (size)	(mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN							
)	1/4"	50	22	30	540							
5	1/4"	75	34	40	600							
00	1/4"	100	44	40	480							
50	1/4"	150	63	25	200							
-												

	1/4	50	22	30	540
	1/4"	75	34	40	600
0	1/4"	100	44	40	480
0	1/4"	150	63	25	200
	3/8"	75	78	20	160
0	3/8"	150	150	20	80
5	3/8"	225	225	10	100
0	3/8"	300	305	10	40
	1/2"	50	110	12	216
	1/2"	75	112	10	150
5	1/2"	125	198	10	90
0	1/2"	250	394	5	45

Polish Finished

				PACKING		
ITEM NO.	S (size)	L (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN	
S24H6100	3/4"	100	426	30	60	
S24H6150	3/4"	150	558	10	30	
S24H6200	3/4"	200	734	10	30	
S24H6400	3/4"	400	1386	10	20	
S24H8200	1"	200	1300	10	20	
S24H8400	1"	400	2420	5	10	


S60H4304S

4PCS 1/2" DR. LOCK EXTENSION BAR SET

60H4304S: 3", 5", 10", 15"

PACKING





	FLEX	BLE HAND	ILES		
\$22H	• CHROME VANADIUM STEEL • DIN 3122				
Mat Finished					
	S		WEIGHT	PACI	KING
ITEM NO.	(size)	(mm)	(g)	INNER PC/BOX	OUTER PC/CTN
S22H41375	1/2"	375	696	15	30
S22H41450	1/2"	450	790	10	20
S22H31200	3/8"	200	294	30	60
S22H21150	1/4"	150	120	30	100
Polish Finishe	ed				
	s		WEIGHT	PACI	KING
ITEM NO.	size)	(mm)	(g)	INNER PC/BOX	OUTER PC/CTN
S22H6500	3/4"	500	1880	7/8	15
S22H41600	1/2"	600	1332	5	20





CONTENTS:

JOINTEINIO.	
S04H41	18PCS-1/2" DR. SOCKET 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 24, 27, 30, 34MM
S15H472	1PC-UNIVERSAL JOINT
S24H4	2PCS-EXTENSION BAR 5" & 10"
S23H4125	1PC-SLIDING T BAR
S17H4116	1PC-16MM SPARK PLUG SOCKET
R3704	1PC-48 TEETH QUICK RELEASE RATCHET HANDLE
PACKING	METAL CASE + COLOR BOX 5SETS/CTN/24.5KGS/25KGS/0.98'

- DIN Standard

S04H41


CONTEN S04H

JONNESWAY










		SL	IDING	T-HA	NDLE	SOCK	ETS
	S40H	-	HROME AT FINIS		JM STEE	EL	
T	ITEM NO.	S (size)	D (mm)	D1 (mm)	L (mm)	L1 (mm)	WEIGH
	S40H108	8	12.5	10	300	200	300
	C40U400	0	14	10	200	200	210

							PAC	KING
ITEM NO.	EM NO. S D D1 L L1 WEIG (size) (mm) (mm) (mm) (mm) (g)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN				
S40H108	8	12.5	10	300	200	300	25	50
S40H109	9	14	10	300	200	310	25	50
S40H110	10	14.8	10	300	200	320	25	50
S40H111	11	15.5	10	300	200	330	25	50
S40H112	12	16.8	10	300	200	340	25	50
S40H113	13	18.0	10	300	200	350	25	50
S40H114	14	19.0	10	300	200	350	25	50





80

 Mat Finished

S23H

		S			I AOI	
1	ITEM NO.	(size)	(mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
S	23H21130	1/4"	130	48	250	500
S	623H31200	3/8"	200	157	50	100
S	623H41250	1/2"	250	440	25	50
S	23H41300	1/2"	300	465	25	50
• F	Polish Finishe	ed				
		0		WEIGUT	PAC	KING
		5	L	WEIGHT		

SLIDING BARS

• DIN 3122

CHROME VANADIUM STEEL

ITEM NO.	S (size)	L (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
S23H6450	3/4"	450	1213	10	20
S23H6500	3/4"	500	1322	10	20
S23H8660	1"	660	3760	3	6

JONNESWAY -

JONNESWAY -

JONNESWAY.

1215	21PCS 3/4" DR. 6PT FLANK SOCKET SET(MM)
06	1PC-3/4" DR. 500MM (20") REVERSIBLE RATCHET HANDLE
475	1PC-3/4" DR. FLEXIBLE HANDLE (475MM)
100	1PC-3/4" DR. 100MM (4") EXTENSION BAR
200	1PC-3/4" DR. 200MM (8") EXTENSION BAR
400	1PC-3/4" DR. 400MM (16") EXTENSION BAR
412	1PC-3/4"FX1/2"M ADAPTER
410	1PC-3/4"FX1"M ADAPTER
61	12PCS-6PT SOCKETS : 19, 21, 22, 24, 27, 30, 32, 36, 38, 41, 46, 50MM
109	1PC-UNIVERSAL JOINT
	1PC-BLOW CASE (530X340X85MM)
NG	BLOW CASE 1SET/CTN/15KGS/15.5KGS/0.71'

S04H4724S 24PCS 1/2" DR. SOCKET SET

Chrome Vanadium Steel, Professional Quality

Quick Release Ratchet Handle With Reversible Function

 Smooth Precise Ratchet Operation Rounded-Off Nut/Bolt Can Be Loosened

Increasing Torsion More Than 10%

04H4125S	25PCS 1/2" DR. SOCKET SET
ONTENTS:	
S04H4	18PCS-1/2" DR. SOCKETS : 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 27, 30, 32MM
S17H4	2PCS-SPARK PLUG SOCKET 16 & 21MM
S24H4	2PCS-EXTENSION BAR 5" & 10"
S23H4125	1PC-SLIDING T BAR
S15H472	1PC-UNIVERSAL JOINT
R3704	1PC-1/2" DR. RATCHET HANDLE-48 TEETH
PACKING	METAL CASE + COLOR BOX 5SET/CTN/25.2KGS/25.7KGS/0.97'

58S	58PCS 1/2" DR. 6PT FLANK SOCKET & BIT SET
TS:	
72	17PCS-1/2" DR. 6PT SOCKETS : 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 24, 27, 30, 32MM
04	8PCS-1/2" DR. DEEP SOCKETS : 10, 11, 12, 13, 14, 15, 17, 19MM
ł	2PCS-1/2" DR. 5" & 10" EXTENSION BAR
72	1PC-1/2" DR. UNIVERSAL JOINT
04	1PC-3/8"(F) X 1/2"(M) T-BAR ADAPTER
4	1PC-1/2" DR. 10" QUICK RELEASE RACHET HANDLE-72 TEETH
4	2PCS-1/2" DR. 16MM & 21MM SPARK PLUG SOCKET
	1PC-1/2" DR. BIT ADAPTOR
	25PCS-BIT X 30L (
١G	BLOW CASE + COLOR BOX 3SET/CTN/16KGS/16.6KGS/1.34'

SOCKETS SERIES



04H52460S	60PCS 1/2" & 1/4" DR. TOOL KIT
ONTENTS:	
S04H41	9PCS-1/2" DR. SOCKETS : 12, 13, 14, 15, 17, 18, 19, 22, 24,MM
R2904	1PC-1/2" DR. 36TEETH QUICK RELEASE RATCHET HANDLE
S24H	2PCS-1/2" DR. EXTENSION 125MM (5") & 250MM (10")
S16H304	1PC-3/8" (F) X 1/2" (M) ADAPTER FOR EXTENSION
S15H472	1PC-1/2" DR. UNIVERSAL JOINT
S17H	2PCS-1/2" DR. SPARK PLUG SOCKET 16 & 21MM
S04H21	7PCS-1/4" DR. SOCKETS : 6, 8, 9, 10, 11, 12, 13MM
S24H275	1PC-1/4" DR. EXTENSION BAR 75MM (3")
	1PC-1/4" DR. FLEXIBLE EXTENSION
S23H21130	1PC-1/4" DR. SLIDING T HANDLE
S26H2150	1PC-1/4" DR. SPINNER HANDLE
	1PC-1/4" DR. COUPLER
	18PCS 1/4" DR. BITS : SLOTTED : 3, 4, 5, 6MM TORX : T10, T15, T20, T25, T27, T30, T40 PHILLIPS : #1, #2, #3 HEX : 3, 4, 5, 6MM
W261	6PCS-COMBINATION WRENCH : 8, 10, 12, 13, 14, 17MM
P2810	1PC-BOX JOINT PLIERS
P087	1PC-CUTTING PLIER
M09500	1PC 500G ENGINER'S HAMMER WITH HICKORY HANDLE (GS)
D04	4PCS-FULL STAR SCREWDRIVERS : PH1X80MM(+), PH2X100MM(+) 0.8X4X80MM(-), 1.2X6.5X100MM(-)
PACKING	BLOW CASE + COLOR BOX 4SET/CTN/23KGS/23.5KGS/1.47'

Professional Quality
 36 Teeth Ratchet Handle Quick Release With Reversible Function
 Increasing Torsion More Than 10%
 Chrome Vanadium Steel

SOCKET SET

82PCS 1/4" & 1/2" DR. COMBINATION

DIN Standard

S04H52482S

JONNESWAY



1/4" DR. PART	
S04H21	13PCS-6PT FLANK SOCKETS : 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13 14MM
	17PCS-SOCKET BIT (L : 37MM) HEX : 3, 4, 5, 6MM STAR : T8, T10, T15, T20, T25, T30 SLOTTED : 4, 5.5, 7MM PHILLIPS : PH1, PH2, POZI : PZ1, PZ2
R3702	1PC-48 TEETH RATCHET HANDLE
S23H21130	1PC-SLIDING T HANDLE
S24H	2PCS-EXTENSION 2", 4"
S15H240	1PC-UNIVERSAL JOINT
S27H2	1PC-FLEXIBLE EXTENSION
S26H2150	1PC-SPINNER HANDLE
	1PC-BIT ADAPTER (25MML)
1/2" DR. PART	
S04H41	12PCS-6PT FLANK SOCKETS : 14, 15, 16, 17, 18, 19, 20, 22, 24, 27, 30, 32MM
	15PCS-5/16" BIT (L : 30MM) HEX : 8, 10, 12, 14MM STAR : T40, T45, T50, T55 SLOTTED : 8, 10, 12MM PHILLIPS : PH3, PH4, POZI : PZ3, PZ4
S24H	2PCS-EXTENSION : 5", 10"
S17H	2PCS-SPARK PLUG SOCKETS : 16, 21MM
S44H208	1PC-BIT HOLDER 1/2" DR. X 5/16"
R3704	1PC-48 TEETH RATCHET HANDLE
S15H472	1PC-UNIVERSAL JOINT
S16H304	1PC-ADAPTER FOR EXTENSION 3/8" (F) X 1/2" (M)
W261	9PCS-COMBINATION WRENCH : 8, 10, 11, 12, 13, 14, 17, 19, 22MM
PACKING	BLOW CASE + COLOR BOX 3SET/CTN/17.3KGS/17.8KGS/1.15'

Professional Quality

DIN Standard
Chrome Vanadium Steel

- Increasing Torsion More Than 10%
 Quick Release Ratchet Handle with Anti-slip Grip









CONTEN 1/4" DR. S04H

PACKI Profession DIN Standard
 Chrome Vanadium Steel



82

JONNESWAY.

S04H52494S	94PCS 1/4" & 1/2" DR. COMBINATION SOCKET SET
CONTENTS:	
1/4" DR. PART	
S04H21	13PCS-6PT FLANK SOCKETS : 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13, 14MM
S04HD21	8PCS-6PT DEEP FLANK SOCKETS : 6, 7, 8, 9, 10, 11, 12, 13MM
	18PCS-SOCKET BIT (L :37MM) HEX : 3, 4, 5, 6MM STAR : T8, T10, T15, T20, T25, T27, T30 SLOTTED : 4, 5.5, 6.5MM PHILLIPS : PH1, PH2, POZI : PZ1, PZ2
R3702	1PC-48 TEETH RATCHET HANDLE
S23H21130	1PC-SLIDING T BAR
S15H240	1PC-UNIVERSAL JOINT
S24H	2PCS-EXTENSION BARS : 2", 4"
S26H2150	1PC-SPINNER HANDLE
	3PCS-HEX KEY : 1.5, 2, 2.5MM
1/2" DR. PART	
S04H41	17PCS-6PT FLANK SOCKETS : 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 24, 27, 30, 32MM
S04HD41	5PCS-6PT FLANK DEEP SOCKETS : 14, 15, 17, 19, 22MM
	16-5/16" BIT (L : 30MM) HEX : 7, 8, 10, 12, 14MM STAR : T40, T45, T50, T55 SLOTTED : 8, 10, 12MM PHILLIPS : PH3, PH4, POZI : PZ3, PZ4
R3704	1PC-48 TEETH RATCHET HANDLE
S17H	2PCS-SPARK PLUG SOCKETS : 16, 21MM
S24H	2PCS-EXTENSION BAR : 5", 10"
S15H472	1PC-UNIVERSAL JOINT
S44H4208	1PC-BIT HOLDER 5/16"
S16H304	1PC-ADAPTER FOR EXTENSION 3/8" DR. X 1/2" (M)
PACKING	BLOW CASE + COLOR BOX 3SET/CTN/18.2KGS/18.7KGS/1.15'
Professional C	Juality

Increasing Torsion More Than 10%
 Quick Release Ratchet Handle with Anti - Slip Grip

S04H524127S 127CS 1/2" DR. & 1/4"DR. TOOL KIT

NTS:	
12	12PCS -1/4"DR. SOCKETS: 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13MM
D2	5PCS -1/4"DR. DEEP SOCKETS: 7, 8, 10, 12, 13MM
12	5PCS- 1/4"DR. STAR SOCKETS: E4, E5, E6, E7, E8
-14	18PCS -1/2"DR. SOCKETS: 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 24,
	27, 30, 32MM
D4	7PCS -1/2"DR. DEEP SOCKETS: 10, 12, 13, 14, 15, 17, 19MM
-14	8PCS -1/2"DR. STAR SOCKETS: E10, E12, E14, E16, E18, E20, E22, E24
н	2PCS -1/2"DR. SPARK PLUG SOCKETS: 16, 21MM
н	3PCS -WOBBLE EXTENSION BARS: 1/4"DR.X50, 1/4"DR.X150, 1/2"DR.X50MM
н	2PCS -SLIDING T- BARS: 1/4"DR.X130, 1/2"DR.X250MM
н	2PCS -UNIVERSAL JOINT: 1/4"&1/2"DR.
н	3PCS - EXTENSION BARS: 1/2"DR.X125, 1/2"DR.X250, 1/4"DR.X75MM
12	1PC -FLEXIBLE EXTENSION BARS: 1/4"DR.X145MM
1375	1PC -FLEXIBLE HANDLE: 1/2"DR.X375MM
Э	2PCS -36 TEETH RATCHET HANDLE: 1/4"&1/2"DR.
6	19PCS -COMBINATION WRENCH: 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 19,
	21, 22, 24, 27, 30, 32MM
4	5PCS -FLARE NUT WRENCH: 8X10, 9X11, 12X13, 14X17, 17X19MM
109S	9PCS -SHORT ARM HEX KEY SET: 1.5, 2, 2.5, 3, 4, 5, 6, 8, 10MM
07S	7PCS -STAR KEY SET: T10, T15, T20, T25, T27, T30, T40
05S	5PCS -CHISEL-PUNCH SET: 4X9.5X150, 5X9.5X130, 12X9.5X130, 3X9.5X120,
	NO.2X9.5X120MM
10	1PC -10" BOX JOINT PLIERS
06	1PC -6" DIAGONAL CUTTING PLIERS
)7	1PC -7" COMBINATION PLIERS
034	1PC -MAGNETIC PICK-UP TOOL
00	1PC -500G HAMMER
1	6PCS -ANTI-SLIP GRIP SCREWDRIVER: PH2X38, PH2X100, PH1X75MM,
	SL6.5X38, SL6X100, SL5X75MM

SOCKETS SERIES



JONNESWAY -

SOCKETS SERIES



JONNESWAY



JONNESWAY -



S04H3125S	25PCS 3/8" DR. SOCKET SET
CONTENTS:	
S04H3	17PCS-3/8" DR. SOCKETS : 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22MM
R3703	1PC-1-3/8" DR. RATCHE HANDLE-48 TEETH
S24H3	2PCS-EXTENSION BARS 3" & 6"
S23H31200	1PC -SLIDING T BAR
S15H356	1PC-UNIVERSAL JOINT
S17H3	2PCS-SPARK PLUG 16 & 21MM
PACKING	METAL CASE + COLOR BOX 10SET/CTN/26KGS/27.1KGS/1.17'

S04H3120S	20PCS 3/8" DR. SOCKET SET
CONTENTS:	
S04H3	13PCS-3/8" DR. SOCKETS : 6, 7, 8, 9, 10, 11, 12, 13, 14, 17, 19, 21, 23MM
S17H3121	1PC-SPARK PLUG 21MM
R2903	1PC-3/8" DR. RATCHET HANDLE-36 TEETH
S24H3	2PCS-EXTENSION BARS 3" & 6"
S22H31200	1PC-FLEXIBLE HANDLE 8"
S23H31200	1PC-SLIDING T-HANDLE 8"
S15H356	1PC-UNIVERSAL JOINT
PACKING	METAL CASE + COLOR BOX 5SET/CTN/21KGS/21.5KGS/0.97'


S04H353	6S 36PCS 3/8" DR. COMBINATION TOOL SET
CONTENTS	t
S04H3	17PCS-3/8" DR.6PT FLANK SOCKETS: 6,7,8,9,10,11,12,13,14,
	15,16,17,18,19,20,21,22MM
W26	11PCS-COMBINATION WRENCH: 7,8,9,10,11,12,13,14,15,16,17MM
R3503	1PC-72 TEETH RATCHET HANDLE
S24H	3PCS-EXTENSION:3",6",9"
S17H	2PCS-SPARK PLUG SOCKETS:16,21MM
S15H356	1PC-UNIVERSAL JOINT
S16H403	1PC-ADAPTER FOR EXTENSION, 1/2"(F)X3/8"(M)
PACKING	METAL CASE+ COLOR BOX 5SETS/CTN/21KGS/21.5KGS/0.97'

S04H3157S 57PCS 1/4" & 3/8" DR. COMBINATION SOCKET SET

CONTENTS:

1/4" DR. PARTS	
S04H2	12PCS-SOCKETS : 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13MM
S04HD2	4PCS-DEEP SOCKETS : 8, 10, 12, 13MM
S09H2 S11H2 S10H2	16PCS-SOCKET BIT HEX 3, 4, 5, 6MM STAR : T10, T15, T20, T25, T27, T30 SLOTTED 4, 5.5, 7MM PHILLIPS PH1, PH2, PH3
R3702	1PC-RATCHET HANDLE-48 TEETH
S24H2	2PCS-EXTENSION BARS 2" & 6"
S16H302	1PC-ADAPTER FOR EXTENSION 1/4" (M) X 3/8" (F)
S15H240	1PC-UNIVERSAL JOINT
S26H2150	1PC-SPINNER HANDLE
3/8" DR. PARTS	
S04H3	8PCS-SOCKETS : 14, 15, 17, 18, 19, 20, 22, 24MM
S04HD3	3PCS-DEEP SOCKETS : 14, 15, 17MM
R3703	1PC-RATCHET HANDLE-48 TEETH
S17H3	2PCS-SPARK PLUG SOCKETS : 16.21MM
S15H356	1PC-UNIVERSAL JOINT
S16H403	1PC-ADAPTER FOR EXTENSION 3/8" (M) X 1/2" (F)
S24H3	2PCS-EXTENSION BARS 3" & 10"
PACKING	METAL CASE + COLOR BOX 5SETS/CTN/21.5KGS/22KGS/0.98'





JONNESWAY -





JONNESWAY -

S04H2141S	41PCS 1/4" DR. SOCKET SET
CONTENTS:	
S04H2	10PCS-1/4" DR. SOCKETS: 4, 5, 5.5, 6, 7, 8, 10, 11, 12, 13MM
S04HD2	3PCS-1/4" DR. DEEP SOCKETS : 7, 8, 10MM
S09H2	4PCS-HEX SOCKET BIT : 3, 4, 5, 6MM
S07H2	6PCS-STAR SOCKET BIT : T10, T20, T25, T27, T30, T40
S10H2	3PCS-SLOTTED SOCKET BIT : 0.8X4, 10X5.5, 1.2X7
S11H2	3PCS-PHILLIPS SOCKET BIT : H1, PH2, HP3
R3702	1PC-1/4"DR RATCHET HANDLE-48 TEETH
S24H	2PCS-EXTENSION BARS 2" & 6"
S27H2150	1PC-FLEXIBLE EXTENSION 6"
S15H240	1PC-UNIVERSAL JOINT
S26H2150	1PC-SPINNER HANDLE
S16H3814	1PC-ADAPTER FOR EXTENSION : 3/8" DR. (F) X 1/4" DR. (M)
	4PCS-HEX KEY WRENCH : 1.5, 2, 2.5, 3MM
PACKING	METAL CASE + COLOR BOX 5SETS/CTN/9KGS/10KGS/0.7'

JONNESWAY

ARA AAAA AAA AAAAAAAAA

0000



PACK



THESE SOCKETS SHOULD NEVER BE USED ON POWER DRIVE OR IMPACT WRENCHES!

84

JONNESWAY.

604H2118S	18PCS 1/4" DR. SOCKET SET
ONTENTS:	
S04H2	12PCS-1/4" DR. 6POINT SOCKETS : 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13MM
R2902	1PC-1/4" DR. RATCHET HANDLE-36 TEETH
S24H2	2PCS-EXTENSION BARS 2" & 4"
S22H2150	1PC-FLEXIBLE HANDLE 6"
S23H2	1PC-SLIDING T-HANDLE 4-1/2"
S15H240	1PC-UNIVERSAL JOINT
PACKING	METAL CASE + COLOR BOX 5SETS/CTN/9KGS/10KGS/0.7'

SOCKETS SERIES

1258	25PCS	1/4"	DR.	SOCKET	SET
------	-------	------	-----	--------	-----

H2	11PCS-1/4" DR. SOCKETS : 4, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13MM
HD2	9PCS-1/4" DR. DEEP SOCKETS : 5, 6, 7, 8, 9, 10, 11, 12, 13MM
702	1PC-1/4" DR. RATCHET HANDLE-48 TEETH
H2	2PCS-1/4" DR. EXTENSION BARS 2" & 6"
2150	1PC-SPINNER HANDLE
KING	METAL CASE + COLOR BOX 12SETS/CTN/9KGS/10KGS/0.72'

S06H425S	25PCS 1/4" & 1/2" DR. STAR SOCKET SET
CONTENTS:	
S07H2	7PCS -1/4* DR. STAR BIT SOCKET (L : 32MM) T8, T10, T15, T20, T25, T27, T30
S07H3	5PCS -1/2" DR. STAR BIT SOCKET (L : 55MM) T40, T45, T50, T55, T60
S06H2	5PCS-1/4" DR. STAR SOCKE E4, E5, E6, E7, E8
S06H4	5PCS-1/2" DR. STAR SOCKE E10, E11, E12, E14, E18
H08	3PCS-STAR KEY T6, T8, T10
PACKING	METAL CASE + COLOR BOX 16SETS/CTN/16KGS/17KGS/0.7'

JONNESWAY -



05H4916S	16PCS 1/2" DR. SOCKET SET (SAE)
----------	---------------------------------

CONTENTS:

S05H49	13PCS-1/2" DR. 12PT SOCKETS : 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8", 15/16", 1", 1-1/16", 1-1/8", 1-1/4"
S22HC4380	1PC-1/2" DR. 15" FLEX HANDLE
S24HC4125	1PC-1/2" DR. 5" EXTENSION BAR
R2804Q	1PC-1/2" DR. QUICK RELEASE RATCHET HANDLE
PACKING	METAL CASE + COLOR BOX 5SETS/CTN/21.2KGS/22.2KGS/0.82'





JONNESWAY -



CONTENTS: S14H3 10PCS-10, 11, 12, 13, 14, 15, 16, 17, 18, 19mm PACKING METAL CLIP RAIL + SLIDE CARD 5SETS/CTN/9KGS/10KGS/0.7'



S05H2223S	23PCS 1/4" DR. SOCKET SET (SAE)
CONTENTS:	
S05H2	10PCS-1/4" DR. 6PT SOCKETS (CR-V) : 5/32", 3/16", 7/32", 1/4", 9/32", 5/16", 11/32", 3/8" 7/16", 1/2"
S05HD2	8PCS-1/4" DR. 6PT DEEP SOCKETS (CR-V) : 3/16", 7/32", 1/4", 9/32", 5/16", 11/32", 3/8", 7/16"
S24HC2	2PCS-1/4" DR. 3" & 6" EXTENSION BARS (CR-V)
	1PC-1/4" DR. UNIVERSAL JOINT (CR-V)
S34HC2165	1PC-1/4" DR. 6-1/2" SPINNER HANDLE
R2802Q	1PC-1/4" DR. 5-1/2" QUICK RELEASE RATCHET HANDLE (48 TEETH) (GEAR TO GEAR) (CR-V)
PACKING	METAL CASE + COLOR BOX 10SETS/CTN/12KGS/14KGS/0.46'
















JONNESWAY -----

JONNESWAY



Ο

CONTENTS:







JONNESWAY -









SOCKETS SERIES




JONNESVIAY.

S06H310S 10PCS 1/4" & 3/8" DR. STAR SOCKET SET


-	
С	
. ר	
	•

10.	
2	4PCS-1/4" DR. : E4, E6, E7, E8
3	6PCS-3/8" DR. : E10, E11, E12, E14, E16, E18
١G	METAL CLIP RAIL + SLIDE CARD 5SETS/CTN/9KGS/10KGS/0.7'


10PCS 3/8" DR. FLEX UNIVERSAL SOCKET SET



• 8 PCS 55MM(L): M5, M6, M8, M9, M10, M12, M14, M16 • 7 PCS 100MM(L) : M5, M6, M8, M9, M10, M12, M14 • 7 PCS 140MM(L) : M5, M6, M8, M9, M10, M12, M14 • 4 PCS 200MM(L) : M8, M10, M12, M14



• MATERIAL : BIT S2 SOCKET : CR/V • 9 PCS 55MM(L) : 5, 6, 7, 8, 10, 12, 14, 17, 19MM • 8 PCS 100MM(L) : 5, 6, 7, 8, 10, 11, 12, 13MM • 7 PCS 140MM(L) : 5, 6, 7, 8, 10, 12, 14MM • 6 PCS 200MM(L) : 5, 6, 7, 8, 10, 12MM



• MATERIAL : BIT S2 SOCKET : CR/V • 10 PCS 55MM(L) : T20, T25, T27, T30, T40, T45, T50, T55, T60, T70 • 10 PCS 100MM(L) : T20, T25, T27, T30, T40, T45, T50, T55, T60, T70 • 6 PCS 140MM(L) : T40, T45, T50, T55, T60, T70 • 6 PCS 200MM(L) : T40, T45, T50, T55, T60, T70


DIN 3129 QUALITY STANDARDS



	S03A4	• DIN 31: • PHOSE	29 PHATE CO	ATING	CHROME MOLYBDENUM			
		SIZE	D1	D2		WEIGHT	PACI	
	ITEM NO.	(mm)	(mm)	(mm)	(mm)	(g)	INNER PC/BOX	OUTER PC/CTN
	S03A4108	8	14.6	24	38	56	12	180
	S03A4109	9	15.0	24	38	59	12	180
	S03A4110	10	17.0	24	38	59	12	180
	S03A4111	11	19.0	24	38	63	12	180
	S03A4112	12	20.0	24	38	65	12	180
	S03A4113	13	20.8	24	38	67	12	180
	S03A4114	14	22.0	24	38	71	12	180
	S03A4115	15	24.0	24	38	78	12	180
	S03A4116	16	24.0	24	38	74	12	180
	S03A4117	17	26.0	26	38	87	12	180
	S03A4118	18	28.0	27	38	108	12	180
	S03A4119	19	28.0	28	38	104	12	180
	S03A4120	20	30.0	30	38	139	12	144
	S03A4121	21	30.0	30	38	146	12	144
	S03A4122	22	32.0	30	38	130	12	144
r -	S03A4123	23	34.0	30	38	119	12	144
	S03A4124	24	34.0	30	43	129	12	144
	S03A4125	25	35.8	30	43	168	12	144
	S03A4126	26	37.0	30	43	160	12	144
37	S03A4127	27	38.0	30	43	171	12	144
	S03A4128	28	39.0	30	48	188	6	72
	S03A4129	29	40.0	30	48	214	6	72
	S03A4130	30	42.0	30	48	210	6	72
	S03A4131	31	44.0	30	48	222	6	72
	S03A4132	32	44.6	30	48	224	6	72

1/2" DR. 6PT FLANK IMPACT SOCKETS (MM)

DIN 3129 QUALITY STANDARDS





DIN 3121 QUALITY STANDARDS



|--|

	1/2" DR. 6PT FLANK IMPACT SOCKETS (SAE)								
S03A4	ANSI / ASME B107.2 PHOSPHATE COATING CHROME MOLYBDENUM								
						PAC	KING		
ITEM NO.	SIZE (SAE)	D1 (mm)	D2 (mm)	(mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN		
S03A4208	5/16"	14.0	24	38	59	12	180		
S03A4210	3/8"	16.0	24	38	60	12	180		
S03A4211	7/16"	18.4	24	38	62	12	180		
S03A4213	1/2"	20.5	24	38	66	12	180		
S03A4214	9/16"	22.0	24	38	69	12	180		
S03A4216	5/8"	24.0	24	38	74	12	180		
S03A4217	11/16"	26.0	26	38	88	12	180		
S03A4219	3/4"	28.0	28	38	90	12	180		
S03A4221	13/16"	30.0	30	38	123	12	144		
S03A4222	7/8"	32.0	30	38	133	12	144		
S03A4224	15/16"	34.6	30	38	137	12	144		
S03A4226	1"	36.4	30	38	136	12	144		
S03A4227	1-1/16"	38.0	30	48	215	12	144		
S03A4229	1-1/8"	40.0	30	48	207	6	72		
S03A4230	1-3/16"	42.0	30	48	203	6	72		
S03A4232	1-1/4"	44.6	30	48	237	6	72		

JONNESWAY -



S03A4111S 11PCS 1/2" DR. 6PT FLANK IMPACT SOCKET SET (MM)

CONTENTS:

S03A4	11PCS-1/2" DR. 6PT FLANK IMPACT SOCKETS : 10, 11, 12, 13, 14, 16, 17, 19, 21, 22, 24MM
PACKING	BLOW CASE + COLOR BOX 10SETS/CTN/12KGS/13KGS/0.56'

88

JONNESWAY.

1/2" DR. 6PT FLANK DEEP IMPACT SOCKETS (MM)	

• DIN 3129
PHOSPHATE COATING

	0175				WEIGUT	PACKING		
NO.	O. SIZE D1 D2 (mm) (mm) (mm)		(mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN		
4110	10	17.0	24	78	140	12	180	
4111	11	19.0	24	78	156	12	180	
4112	12	19.6	24	78	162	12	180	
4113	13	20.8	24	78	166	12	180	
4114	14	22.0	24	78	157	12	180	
4116	16	24.0	24	78	159	12	72	
4117	17	26.0	26	78	185	12	72	
4119	19	28.0	28	78	228	12	72	
4121	21	30.0	30	78	243	12	72	
4124	24	34.6	30	78	303	12	72	

41115	11PCS 1/2" DR. 6PT FLANK DEEP IMPACT SOCKET SET (MM)
NTS:	
AD4	11PCS-1/2" DR. 6PT FLANK DEEP IMPACT SOCKETS : 10, 11, 12, 13, 14, 16, 17, 19, 21, 22, 24MM
(ING	BLOW CASE + COLOR BOX 10SETS/CTN/12KGS/13KGS/0.53

	1/2" DR.	ADAPTE	RS	
\4A	• DIN 3121 • CHROME	MOLYBDE	NUM	
				PACKING

				WEIGUT	PACKING		
NO.	SIZE	D (mm)	L (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN	
4A3	3/8"	25	38	70	15	120	
44A6	3/4"	30	48	140	12	144	

	1/2" DR.	UNIVER	SAL JOIN	т	
\4U	• DIN 3121 • CHROME	MOLYBDE	NUM		
		-			PACKING

		_		WEIGUT	PACKING		
1 NO.	SIZE	(mm)	L (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN	
\4U4	1/2"	25	75	150	12	60	

	1/2" DR.	EXTENS	ION BARS	;						
\4E	• DIN 3121 • CHROME MOLYBDENUM									
PACKING										
		D	1	WEIGHT	PACI	KING				
NO.	SIZE	(mm)	(mm)	(g)	INNER PC/BOX	OUTER PC/CTN				
4E3	3"	25	75	170	15	180				
4E4	4"	25	100	200	10	120				
4E5	5"	25	125	230	5	50				
4E6	6"	25	150	260	12	120				
4E8	8"	25	200	340	6	72				
4E10	10"	25	250	420	5	60				

DIN 3129 QUALITY STANDARDS



277	

		ME MOLYE PHATE CO					
ITEM NO.	SIZE (mm)	D1 (mm)	D2 (mm)	L (mm)	WEIGHT (g)	PAC INNER PC/BOX	KING OUTEF PC/CTN
S03A6117	17	29.5	38	51	375	6	72
S03A6118	18	31.4	38	51	319	6	72
S03A6119	10	33.0	38	51	320	6	72
S03A6120	20	34.0	38	51	327	6	72
S03A6121	20	35.0	38	51	333	6	72
S03A6122	22	37.0	38	51	340	6	72
S03A6123	23	38.0	38	51	338	6	72
S03A6124	24	39.0	38	51	371	6	72
S03A6125	25	40.0	38	51	352	6	72
S03A6126	26	41.0	38	51	346	6	72
S03A6127	27	43.0	40	53	374	6	72
S03A6128	28	44.0	40	53	398	6	72
S03A6129	29	45.0	42	53	407	6	72
S03A6130	30	46.0	44	53	407	6	72
S03A6131	31	47.6	44	53	417	6	72
S03A6132	32	49.0	44	57	468	6	36
S03A6133	33	51.0	44	57	488	6	36
S03A6134	34	51.0	44	57	400	6	36
S03A6135	35	53.0	44	57	475	6	36
S03A6136	36	54.0	44	57	506	6	36
S03A6137	37	55.0	44	57	532	6	36
S03A6138	38	56.0	44	57	547	6	36
S03A6139	39	57.7	44	57	565	6	36
S03A6140	40	59.0	44	57	611	6	36
S03A6141	40	60.0	44	57	578	6	36
S03A6142	41	61.4	44	57	584	6	36
S03A6143	43	62.7	44	62	666	6	36
S03A6144	44	64.0	44	62	667	6	36
S03A6145	44	65.0	44	62	727	6	36
S03A6146	46	66.4	44	62	712	6	36
S03A6147	40	67.6	44	67	768	6	36
S03A6148	48	68.8	44	67	822	3	18
S03A6149	49	70.0	44	72	848	3	18
S03A6150	50	71.4	54	72	1058	3	18
S03A6151	51	72.8	54	72	1110	3	18
S03A6152	52	74.0	54	72	1190	3	18
S03A6153	53	75.0	54	72	1214	3	18
S03A6154	54	76.4	54	72	1214	3	18
S03A6155	55	77.7	54	74	1310	3	18
S03A6156	56	79.0	54	74	1279	3	18
S03A6157	57	80.0	54	74	1333	3	18
S03A6158	58	81.5	54	75	1435	3	18
S03A6159	59	82.7	54	75	1437	3	18
S03A6160	60	84.0	54	75	1437	3	18
S03A6163	63	87.6	54	75	1435	3	12
S03A6165	65	90.0	54	78	1655	3	12
S03A6167	67	92.7	54	80	1715	3	12
S03A6170	70	96.4	54	83	2094	3	12


3/4" DR. 6PT FLANK IMPACT SOCKETS (MM)

S03A6 • DIN 3129

ANSI / ASME B107.2 QUALITY STANDARDS







JONNESWAY.

	0/4 0		EANN		OUCKEI		
S03A6	•CHRON	ASME B10 ME MOLYE PHATE CO	BDENUM				
	SIZE	D1	D2	L	WEIGHT	PAC	
ITEM NO.	(inch)	(mm)	(mm)	(mm)	(g)	INNER PC/BOX	OUTER PC/CTN
S03A6217	11/16"	30.6	44	51	318	6	72
S03A6219	3/4"	32.6	44	51	320	6	72
S03A6221	13/16"	34.7	44	51	275	6	72
S03A6222	7/8"	36.6	44	51	339	6	72
S03A6224	15/16"	38.9	44	51	347	6	72
S03A6226	1"	40.7	44	51	368	6	72
S03A6227	1-1/16"	42.6	44	53	374	6	72
S03A6229	1-1/8"	44.5	44	53	402	6	72
S03A6230	1-3/16"	46.4	44	53	403	6	72
S03A6232	1-1/4"	48.9	44	53	443	6	36
S03A6233	1-5/16"	50.6	44	56	420	6	36
S03A6235	1-3/8"	52.7	44	56	432	6	36
S03A6236	1-7/16"	54.6	44	57	500	6	36
S03A6238	1-1/2"	56.4	44	57	547	6	36
S03A6240	1-9/16"	58.9	44	57	596	6	36
S03A6241	1-5/8"	60.1	44	57	571	6	36
S03A6243	1-11/16"	62.7	44	62	666	6	36
S03A6244	1-3/4"	64.5	44	62	687	6	36
S03A6246	1-13/16"	66.4	44	62	712	6	36
S03A6248	1-7/8"	68.8	44	62	822	3	18
S03A6249	1-15/16"	70.2	44	62	848	3	18
S03A6251	2"	72.8	54	72	1110	3	18
S03A6253	2-1/16"	74.4	54	72	1168	3	18
S03A6254	2-1/8"	76.4	54	72	1244	3	18
S03A6256	2-3/16"	80.0	54	72	1279	3	18
S03A6257	2-1/4"	80.2	54	75	1333	3	18
S03A6259	2-5/16"	82.0	54	75	1455	3	18
S03A6260	2 - 3/8"	84.1	54	75	1435	3	18
S03A6263	2-1/2"	88.2	54	80	1545	3	12
S03A6265	2-9/16"	90.2	54	80	1655	3	12
S03A6267	2-5/8"	92.3	54	80	1715	3	12
S03A6270	2-3/4"	96.4	54	80	2094	3	12

3/4" DR. 6PT FLANK IMPACT SOCKETS (SAE)

SOCKETS SERIES

3/4" DR. 6PT FLANK DEEP IMPACT SOCKETS (MM)

32

18

PACKING

INNER OUTER PC/BOX PC/CTN

24

6

WEIGHT (g)

750

DIN 3129 QUALITY STANDARDS



	0175	D1	50		WEIGUT	PACI	KING
ITEM NO.	SIZE (mm)	(mm)	D2 (mm)	(mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
S03AD6117	17	30.1	44	90	574	1	32
S03AD6118	18	31.4	44	90	588	1	32
S03AD6119	19	32.6	44	90	599	1	32
S03AD6120	20	33.8	44	90	611	1	32
S03AD6121	21	35.1	44	90	633	1	32
S03AD6122	22	36.6	44	90	642	1	32
S03AD6123	23	37.6	44	90	655	1	32
S03AD6124	24	38.9	44	90	637	1	32
S03AD6125	25	40.1	44	90	641	1	32
S03AD6126	26	41.3	44	90	645	1	32
S03AD6127	27	42.6	44	90	632	1	32
S03AD6128	28	44.0	44	90	639	1	32
S03AD6129	29	45.1	44	90	656	1	32
S03AD6130	30	46.4	44	90	679	1	32
S03AD6131	31	47.6	44	90	729	1	32
S03AD6132	32	48.9	44	90	736	1	32
S03AD6133	33	50.6	44	90	771	1	32
S03AD6134	34	51.4	44	90	788	1	32
S03AD6135	35	52.7	44	90	815	1	32
S03AD6136	36	53.9	44	90	840	1	32
S03AD6137	37	55.2	44	90	862	1	32
S03AD6138	38	56.4	44	90	882	1	32

58.9 60.1

66.4

42 61.4 43 62.7

49 70.2

44 44

44

44

54

44 90

44 90

910 970

1006 1037

1256 1425

1647

90

90

90

• DIN 3129
 • CHROME MOLYBDENUM

PHOSPHATE COATING

S03AD6

S03AD6140 S03AD6141

S03AD6142

S03AD6143

S03AD6146 S03AD6149

S03AD6150

40 41

46

50


JONNESWAY

SOCKETS SERIES

DIN 3121 QUALITY STANDARDS



	3/4" DR. ADAPTERS									
S03A6A	• DIN 3121 • CHROME	MOLYBDE	NUM							
		-			PAC	KING				
ITEM NO.	SIZE	D (mm)	(mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN				
S03A6A4	1/2"	44	58	330	12	72				
S03A6A8	1"	44	63	410	6	48				



JONNESWAY -



	3/4" DR.	EXTENS	ION BARS	3			
S03A6E • DIN 3121 • CHROME MOLYBDENUM							
					PAC	KING	
ITEM NO.	SIZE	D (mm)	L (mm)	(g)	INNER OUTER PC/BOX PC/CTM		
S03A6E35	3-1/2"	44	89	560	12	48	
S03A6E04	4"	44	100	600	12	24	
S03A6E06	6"	44	150	680	12	24	
S03A6E07	7"	44	175	770	12	24	
S03A6E08	8"	44	200	880	12	24	
S03A6E10	10"	44	250	1030	12	20	


JI / AJIVI	E B107.2	S03A8	1" DR. 6PT FLANK IMPACT SOCKETS (SA				(SAE)		
ALITY S'	TANDARDS	JUJAO	• ANSI / A	SME B107.2	2 •CHRO	ME MOLYB	DENUM •	PHOSPHAT	E COAT I N
		ITEM NO.	SIZE (SAE)	D1 (mm)	D2 (mm)	L (mm)	WEIGHT	INNER	KING OUTER
		S03A8226	(GAL) 1"	43.7	54	58	553	PC/BOX	PC/CTN 36
		S03A8229	1-1/8"	47.0	54	60	612	1	36
		S03A8235	1-3/8"	55.0	54	62	692	1	36
		S03A8238	1-1/2"	59.4	54	65	784	1	27
	L	S03A8241	1-5/8"	63.1	54	65	846	1	27

DIN 3121 QUALITY STANDARDS





JONNESWAY -





8 A	1" DR. A	DAPTERS	6						
• DIN 3121 • CHROME MOLYBDENUM									
		5		WEIGUT	PAC				
NO.	SIZE	D (mm)	L (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN			
8A6	3/4"	54	75	660	1	10			
A12	1-1/2"	54	90	960	1	10			

\8U	1" DR. U	NIVERSA	L JOINT						
100	• DIN 3121 • CHROME MOLYBDENUM								
		5	WEIGUT	PAC	KING				
NO.	SIZE	D (mm)	L (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN			
8U8	1"	54	130	1380	1	10			

\8E	1" DR. EXTENSION BARS							
40E	• DIN 3121 • CHROME MOLYBDENUM							
		D		WEIGHT	PACI	KING		
NO.	SIZE	(mm)	(mm)	(g)	INNER PC/BOX	OUTER PC/CTN		
3E04	1"	54	100(4")	1000	2	20		
3E06	1"	54	150(6")	1200	2	20		
3E07	1"	54	175(7")	1350	2	20		
3E08	1"	54	200(8")	1580	1	18		
3E10	1"	54	250(10")	1960	1	10		
3E12	1"	54	300(12")	2150	1	10		
3E13	1"	54	330(13")	2240	1	10		

JONNESWAY -

JONNESWAY -


DIN 3121 QUALITY STANDARDS



S05A408S	8PCS 1/2" DR. HEX BIT IMPACT SOCKET SET
CONTENTS:	
	8PCS-1/2" DR. HEX BIT IMPACT SOCKETS : H5, H6, H8, H10, H12, H14, H17, H19
PACKING	BLOW CASE + COLOR BOX 20SETS/CTN/24KGS/25KGS/1.5

DIN 3121 QUALITY STANDARDS





JONNESWAY -

S03AD4 S03AD4



CONTEN S03AD PACK

S03AD4

JONNESWAY -

JONNESWAY -



ITEM N S18A4 S18A4 S18A4121

S1





/2′

 \mathbf{O}

S06A408S

CONTENTS:

S06A4

PACKING

S16A45	1/2"DR. SPLINE BIT IMPACT SOCKET
--------	----------------------------------

8PCS 1/2" DR. STAR BIT IMPACT SOCKET SET

BLOW CASE + COLOR BOX 20SETS/CTN/21KGS/22KGS/1.5

8PCS-1/2" DR. STAR BIT IMPACT SOCKETS : T30, T40, T45, T50, T55, T60, T70, T80 (L:78MM)

CONTENTS: T30, T40, T45, T50, T55, T60, T70, T80

ITEM NO.	SIZE	D (mm)	l (mm)	L (mm)
S16A4506	M6	25	6.0	100
S16A4508	M8	25	8.0	100
S16A4510	M10	25	8.5	100
S16A4512	M12	25	9.0	100
S16A4514	M14	25	9.5	100
S16A4516	M16	25	10.0	100
S16A4518	M18	25	11.0	100



SOCKETS SERIES

JONNESWAY.

S034

ITEM

1/2" DR. 6PT FLANK THIN WALL DEEP IMPACT SOCKET						
0175	D		WEIGUT	PACI	KING	
(mm)	(mm)	(mm)	(g)	INNER PC/BOX	OUTER PC/CTN	
	SOCKET	SOCKET	SOCKET	SIZE D L WEIGHT	SIZE D L WEIGHT INNER	

TEWINO.	(mm)	(mm)	(mm)	(g)	PC/BOX	PC/CTN
S03AD4317	17	24	85	200	8	48
S03AD4319	19	26	85	210	8	48
S03AD4321	21	28	85	220	8	48

4303S	3PCS 1/2" DR. 6PT FLANK THIN WALL DEEP IMPACT Socket set
NTS:	
D43	3PCS-1/2" DR. 6PT FLANK THIN WALL DEEP IMPACT SOCKETS : 17, 19, 21MM
KING	BLOW CASE + COLOR SLEEVE 24SETS/CTN/20.4KGS/21.4KGS/1.1'

8A	1/2"DR.	1/2"DR. WHEEL NUT IMPACT DEEP SOCKET						
NO.	SIZE	D (mm)	L (mm)	WEIGHT (g)	COLOR			
117	17	27	85	219	BLUE			
119	19	28.5	85	248	GREEN			
121	21	31	85	272	RED			

S18A4121M

AFTER LOOSENING, THE SCREW WILL STICK ON THE INSIDE OF MAGNETIC, WITHOUT FALLING OFF.

28.5

31

19

21

A4M	1/2"DR (MAGN		UT IMPACT	DEEP SOCK	ΈT
		-			
NO.	SIZE	D (mm)	L (mm)	WEIGHT (g)	COLOR
117M	17	27	85	220	BLUE

85

85

233

252

GREEN

RED



JONNESWAY PROFESSIONAL PLIERS



JONNESWAY



P098

JONNESWAY



ITEM P106 P107

JONNESWAY



ITEM P116 P118

PLIERS series

• Chrome Vanadium Steel CR-MO Handles for Locking Pliers Precision Forged

• Ergonomic Grip Designs

JONNESWAY.

COMBINATION PLIERS

		MERCHIT	PACI	KING
L (inch)	L (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
6"	160	250	12	72
7"	180	310	12	60
8"	200	410	12	60

P08

ITEM

P086 P087 P088

HEAVY DUTY DIAGONAL CUTTING PLIERS

	WEIGUT	PACKING		
L (inch)	(mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
7"	180	280	12	72
8"	200	300	12	60

DIAGONAL CUTTING PLIERS

	WEIGHT	PACĶING		
L (inch)	(mm)	(g)	INNER PC/BOX	OUTER PC/CTN
6"	160	240	12	60
7"	180	270	12	72

P11

LONG NOSE PLIERS

	PAC		KING	
L (inch)	(mm)	(g) 180	INNER PC/BOX	OUTER PC/CTN
6"	160	180	12	72
8"	200	260	12	60

JONNESWAY PROFESSIONAL PLIERS

- 1. Hardness 60 64 degrees on cutting edge because of special "high frequency" heat treatment. Cutting edges remain very sharp after multiple operation on hard materials.
- 2. Precision compact junction on cutting edge.
- 3. Patented design of off-center for saving manual power.



	P01 SIDE CUTTING PLIERS						
1				MAX CAPACITY DIA.	WEIGHT	PAC	KING
	ITEM	L (inch)	(mm)	(mm) (a) INNER (OUTER PC/CTN
	P017	7"	190	ø3.2	248	6	60
	P018	8"	212	ø3.5	342	6	60

JONNESWAY



P08A LINESMEN'S PLIERS						
			WEIGHT	PACKING		
ITEM	(inch) (mm)	(mm)	(g)	INNER PC/BOX	OUTER PC/CTN	
P086A	6"	163	200	12	72	
P087A	7"	194	310	12	60	
P088A	8"	224	410	12	60	

JONNESWAY -



P028 8" PATENTED WIRE CUTTERS GERMAN NO. M94028540				MAN PAT	ENT	
ITEM	L (inch)	L (mm)	MAX CAPACITY DIA. (mm)	WEIGHT (g)	PACI INNER PC/BOX	KING OUTER PC/CTN
P028	8"	202	ø4.0	275	6	60

JONNESWAY PROFESSIONAL PLIERS

- 1. Hardness 47 59 degrees on cutting edge because of special "high frequency heat treatment. Cutting edges remain very sharp after multiple operation on hard materials.
- 2. Precision compact junction on cutting edge.
- 3. Patented design of off-center for saving manual power.





JONNESWAY



JONNESWAY



JONNESWAY



JONNESWAY



ITEM P6006 P6008



JONNESWAY.

8" DIAGONAL CUTTING PLIERS

			WEIGUT	PAC	KING
L (inch)	L (mm)		WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
8"	197	2.0~3.0	270	6	60

9A	A HEAVY DUTY DIAGONAL CUTTING PLIERS					
			MERCHA	PACKING		
	L (inch)	L (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN	
٩	7"	190	240	12	72	

46	46 6" DIAGONAL CUTTING PLIER			PLIERS		
				WEIGHT	PACI	KING
	L (inch)	(mm)	MAX CAPACITY DIA. WEIGHT (mm) (g)		INNER PC/BOX	OUTER PC/CTN
	6"	160	1.8~2.0	155	6	60

68	3	8" LONG NOSE PLIERS					
	(in	L ich)	L (mm)	MAX CAPACITY DIA. (mm)	WEIGHT (g)	PACI INNER	OUTER
	8	B"	200	2.5	180	PC/BOX 6	PC/CTN 60

			MEIOUT	PACI	KING
	L (inch)	L WEIGHT (mm) (g)		INNER PC/BOX	OUTER PC/CTN
、 、	6"	167	130	12	96
\	8"	200	180	12	60

LONG NOSE W/SIDE CUTTER PLIERS

SLIP JOINT PLIERS

			WEIGUT	PACKING		
	L (inch)	L (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN	
6	6"	160	180	12	96	
3	8"	200	290	12	72	

JONNESWAY PROFESSIONAL PLIERS

1.CR-V Steel 2.Precision Forged 3.Polish Finished



P6210 9-3/4" CRIMPING TOOL					
ITEM	L (inch)	L (mm)	WEIGHT (g)	PACH INNER PC/BOX	KING OUTER PC/CTN
P6210	9-3/4"	240	340	6	60



PLIERS



P 27	MACHIN	IED TONGUE	& GROOVE	WATER PUN	NP PLIERS
			WEIGHT	PAC	KING
ITEM	(inch)	(mm) (g)	INNER PC/BOX	OUTER PC/CTN	
P2708	8"	200	340	12	72
P2710	10"	250	400	12	60

JONNESWAY -



PZ6 BOX JOINT PLIERS							
ITEM	L (inch)	L (mm)	WEIGHT (g)	PACE INNER PC/BOX	KING OUTER PC/CTN		
P2810	10"	250	430	12	60		

*BLACK FINISHED

* CR-V STEEL, DROP FORGED HEAT TREATMENT

P7719 9" WIRE TWISTING PLIERS

JONNESWAY -



					-	
	SIZE		WEIGHT	PACKING		
ITEM NO.	(inch)		CAPACITY (mm)	(g)	INNER PC/BOX	OUTER PC/CTN
P7719	9"	270	Ø0.55 stainless	360	1	50





JONNESWAY











100

ITEM P5605



01	11" L0	11" LONG PLIERS								
	ANGLE	INCH	METRIC (mm)	WEIGHT (g)	INNER PC / BOX	OUTER PC / CTN				
	0 DEGREE	11"	275	330	12	60				

* A combination of the 80mm extended shanks and the 90 degrees angled gripping jaws provides easy access to low-lying work areas, minimizing the risk of accidental burns on the hand while working on a hot engine block.

11" LONG PLIERS

	ANGLE	INCH	METRIC (mm)	WEIGHT (g)	INNER PC / BOX	OUTER PC / CTN
2	45 DEGREE	11"	275	330	12	60

* A combination of the 80mm extended shanks and the 90 degrees angled gripping jaws provides easy access to low-lying work areas, minimizing the risk of accidental burns on the hand while working on a hot engine block.

03	11" EI	11" END CUTTING PLIERS							
	ANGLE	INCH	METRIC (mm)	WEIGHT (g)	INNER PC / BOX	OUTER PC / CTN			
3	90 DEGREE	11"	275	330	12	60			

* A combination of the 80mm extended shanks and the 90 degrees angled gripping jaws provides easy access to low-lying work areas, minimizing the risk of accidental burns on the hand while working on a hot engine block.

509		11" EXTRA LONG ROUND JAWS PLIERS DIA 19MM (3/4")								
10.	DIA.	LENGTH INCH	WEIGHT (g)	INNER PC / BOX	OUTER PC / CTN					
)	19mm (3/4")	11"	330	12	60					

Made from CR-MO material.
Suitable for using on hoses, spark plug wires, etc....

	4" SIDE CUTTER PLIERS								
602		•FOR WIRES BELOW 1.0MM. •THIN CUTTING JAWS. •ABLE TO STRIP WIRE.							
1		L L WEIGHT (inch) (mm) (g)		PACKING INNER OUTE PC/BOX PC/C					
2		4"	100	8	6	PC/CTN 120			

		5" SIDE CUTTER PLIERS									
603	• SUITABLE FOR SOFT WIRE BELOW DIA. 1.6MM • DO NOT USE TO CUT STEEL WIRE.										
				WEICHT	PACKING						
I		(inch)	L WEIGHT (mm) (g)		INNER PC/BOX	OUTER PC/CTN					
3		5"	125	13	6	120					

	5" SNI	5" SNIP NOSE PLIERS									
605	• WITH CUTTER. • SERRATED FOR EASY TAKING UP.										
1	L (inch)	L (mm)	WEIGHT (g)	INNER	KING OUTER						
5	5"	125	10	PC/BOX 6	PC/CTN 120						





JONNESWAY



P7	104	м	MINIATURE LINEMAN'S PLIERS							
ITEM NO.	L	L3	W3	W4	T1	WEIGHT	CUTTING	Tensile Strength	PACK	

ITEM NO.	L	L3	W3	W4	T1	(g)	WIRE	Strength	INNER PC/BOX	
P7104	120	15.8	13.6	4	8.2	90	1.25	1241	6	72

Ergonomic design for comfortable grip.
Spring loaded.
Lay-on joint.
Meeting standard cutting & loading test.
Chrome nickel steel drop forged for hardened cutting edges.
Serrated jaws.

	CURVED JA	CURVED JAW LOCKING PLIERS WITH WIRE CUTTERS						
P32M	CHROME MO	CHROME MOLYBDENUM JAW CHROME MOLYBDENUM HANDLE NICKLE PLATED						
	017E	WEICHT	PACKING					

	0175	WEIGUT	170	
ITEM NO.	SIZE (inch)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
P32M10A	10"	560	6	36
P32M07A	7"	330	6	72
P32M05A	5"	175	6	72

	STRAIGHT J	AW LOCKING	PLIERS	
P30M	CHROME MO	CHROME MOLYBDENUM JAW CHROME MOLYBDENUM HANDLE NICKLE PLATED		
	SIZE	WEIGHT	PACI	KING
ITEM NO.	(inch)	(g)	INNER PC/BOX	OUTER PC/CTN
P30M10A	10"	540	6	36
P30M07A	7"	360	6	72

JONNESWAY



JONNESWAY -



JONNESWAY

102



ITEM NO. SIZE (inch) WEIGHT (g) PACKING P36M09A 9" 360 6 36	P36M	CHROME MO	LYBDENUM JAW	ERS WITH WIRE	CUTTERS
PC/BOX PC/CTN	ITEM NO.			INNER	OUTER
	P36M09A	()		PC/BOX 6	

	LOCKING PL	.IERS			
P52M	CHROME VAI	PROFESSIONAL QUALITY CHROME VANADIUM JAW CHROME MOLYBDENUM HANDLE			
	0175		PAC	KING	
ITEM NO.	SIZE (inch)	(g)	INNER PC/BOX	OUTER PC/CTN	
P52M10	10"	520	6	36	

P32M03S **3PCS LOCKING PLIERS SET** CHROME MOLYBDENUM JAW NICKEL PLATED

ITEM NO.	DESCRIPTION
P36M06A	6" LONG NOSE LOCKING PLIERS WITH WIRE CUTTER
P32M07A	7" CURVED JAW LOCKING PLIERS WITH WIRE CUTTER
P32M10A	10" CURVED JAW LOCKING PLIERS WITH WIRE CUTTER

2 COLOR SANTOPRENE HANDLES







JONNESWAY -









P36

ITEM N

P38

ITEM NO. P53M11

JONNESWAY -



JONNESWAY.

	CURVED JA	W LOCKING PL	IERS WITH WI	KE CUTTER		
MC	CHROME MO	CHROME VANADIUM JAW CHROME MOLYBDENUM HANDLE NICKLE PLATED				
	OIZE	WEIGUT	PACł	KING		
NO.	SIZE (inch)	WEIGHT (g)				

NO.	(inch)	(g)	INNER PC/BOX	OUTER PC/CTN
10C	10"	560	6	36
07C	7"	330	6	72
05C	5"	175	6	72

STRAIGHT JAW LOCKING PLIERS
CHROME VANADIUM JAW CHROME MOLYBDENUM HANDLE NICKLE PLATED

	0175	WEIGUT	PACKING	
NO.	SIZE (inch)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
10C	10"	540	6	36
07C	7"	360	6	72

	LONG NOSE	LOCKING PLI	ERS WITH WIRE	E CUTTER		
MC	CHROME VANADIUM JAW CHROME MOLYBDENUM HANDLE NICKLE PLATED					
	SIZE	WEIGUT	PACł	KING		
NO.	(inch)	WEIGHT (a)	INNER	OUTER		

ITEM NO.	SIZE (inch)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
P36M09C	9"	360	6	36
P36M06C	6"	180	6	72

• CHROME VANADIUM JAWS • CHROME MOLYBDENUM HANDLES • DEEP U-SHAPED JAWS PROVIDE EXCELLENT VIEW & AMPLE WORKING SPACE • NICKLE PLATED		WELDING CLAMPS
	BM	CHROME MOLYBDENUM HANDLES DEEP U-SHAPED JAWS PROVIDE EXCELLENT VIEW & AMPLE WORKING SPACE

	SIZE	WEIGHT (g)	PACĶING			
NO.	(inch)		INNER PC/BOX	OUTER PC/CTN		
11A	11"	650	1	40		

	LONG LOCKING C-CLAMP WITH PAD
M	NICKEL PLATED FINISHED LOCKS & UNLOCKS QUICKLY SMOOTH PRESSURE ADJUSTMENT FLEXIBLE PADS
	DACKING

SIZE	JAW OPENING	WEIGUT						
(inch)	WIDTH (mm)	I I I I I I I I I I I I I I I I I I I		OUTER PC/CTN	A (mm)	ы (mm)	(mm)	
11"	0~90 mm	730	10	30	85	70	95	

	SHEET METAL LOCKING PLIERS						
P54M	CR-MO JAW NICKEL PLATED FINISHED						
	0175	WEIGUT	PACKING				
ITEM NO.	SIZE (inch)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN			
P54M10A 10" 6		650	1	48			

JONNESWAY.

		AG010001	5"(1) PLIE		RAIGHT NO	SE, INTEI	RNAL
100	Capacity 6-15, 12-65, 32-80mm.	AG010002	7"(1 PLIE		RAIGHT NO	SE, INTEI	RNAL
	For hole. Chrome Vanadium.	AG010003	9"(23 PLIE		RAIGHT NO	SE, INTEI	RNAL
JONNESWAY							
		AG010005	5 7"(1) PLIE		NT NOSE, I	NTERNAL	
X	Capacity 6-15, 12-65, 32-80mm. For hole.	AG010006	9"(23 PLIE	30MM) BE RS	NT NOSE, I	NTERNAL	
JONNESWAY	Chrome Vanadium.						
		AG010008	7"(1	75MM) S1	RAIGHT NO	SE, EXTE	RNAL
	Capacity 3-15, 10-40, 32-80mm. For shaft.		PLIE	RS	RAIGHT NO		
	Chrome Vanadium.	AG010009				0L, LATE	
JONNESWAY							
		AG010011	7"(17) PLIER	5MM) BEN RS	NT NOSE, EX	TERNAL	
	Capacity 3-15, 10-40, 32-80mm. For shaft.	AG010012	9"(23 PLIER		NT NOSE, EX	TERNAL	
	Chrome Vanadium.						
JONNESWAY							
235		P9920A	20" (50	DOMM) ST NAL PLIE	RAIGHT NO RS	SE,	
		P9920AS	20" (50 INTER	DOMM) ST Nal Plie	RAIGHT NO RS W/BENT	SE, TIPS	
			L	L	WEIGHT		KING
<u>Mø3.5</u> P9920/	AS	ITEM NO. P9920A	(inch) 20"	(mm) 508	(g) 1652	INNER PC/BOX	OUTER PC/CTN 12
Internal JONNESWAY	2	 Using For Large Capacity : 165~ For Hole : 4.5 ~ 	Vehicle B 300mm				
10		P9920C		DOMM) ST	RAIGHT NO	SE,	
200		P9920CS			RAIGHT NO		
				L	1		KING
<u> </u>		ITEM NO.	L (inch)	(mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
	-	P9920C	20"	508	. 1669	1	12
External		 Using For Large Capacity : 165 - For Hole : 4.5 -5 	300mm	uilding / rep	bair		



JONNESWAY -

PACKI

JONNESWAY





JONNESWAY



JONNESWAY -

V10 FEATUF EQUIPF PACKII



PLIERS

JONNESVIAY.

401	PROFESSIONAL CRIMPING TOOL & WIRE STRIPPER				
	-MULTI-PURPOSE. QUICK & EASY WORK •10~22 AWG				

402	PROFESSIONAL CRIMPING TOOL & WIRE STRIPPER
URES	MULTI-PURPOSE (8 IN 1) QUICK & EASY WORK PAT
KING	SLIDE CARD 50SETS/CTN/13KGS/14KGS/1.2'

501	HEAVY DUTY EASY STRIPPER
URES	• CRIMPED TYPE OF TERMINAL • INSULATED TERMINALS • NON-INSULATED TERMINAL • AUTO IGNITION TERMINAL • LENGTH : 205MM • WEIGHT : 305G
KING	SLIDE CARD 60SETS/CTN/20KGS/21KGS/1.8'

V1503	HEAVY DUTY EASY STRIPPER
	LENGTH : 172MM WEIGHT : 245G
PACKING	SLIDE CARD 60SETS/CTN/17KGS/18KGS/1.4'

HEAVY DUTY HAND RIVETER
DROP FORGE HANDLE, ALUMINUM BODY TUV + GS APPROVAL JAWS MADE OF SCM 4
4 NOSE PIECES : 2.4MM (3/32"), 3.2MM (1/8"), 4.0MM (5/32"), 4.8MM (3/16")
SLIDE CARD 24SETS/CTN/14KGS/15KGS/1'

SCISSOR ACTION INDUSTRIAL RIVETER
MADE OF DURABLE HIGH CARBON STEEL
4 NOSE PIECES : 2.4MM (3/32"), 3.2MM (1/8"), 4.0MM (5/32"), 4.8MM (3/16")
COLOR BOX 10SETS/CTN/20KGS/21KGS/1.4'

004	FREE SUCTION HAND RIVETER
URES	• HEAD ROTATES 360° FOR ANY ANGLE RIVETING
IPPED	4 NOSE PIECES : 2.4MM (3/32"), 3.2MM (1/8"), 4.0MM (5/32"), 4.8MM (3/16")
KING	SLIDE CARD 24SETS/CTN/14KGS/15KGS/1.5'

JONNESWAY.

PACKING

INNER

PC/BOX

6

6

OUTER PC/CTN

48

48



JONNESWAY



20A	AVIATION TIN SNIPS	CR-MO
-----	--------------------	-------

Drop forged CR-MO steel blades

P19A

ITEM

P199LA

P199RA

Hardened serrated edges of HRC55-60

Hardened cutting edges of HRC60-62

Drop forged CR-MO steel blades
 Hardened serrated edges of HRC55-60

Hardened cutting edges of HRC60-62

L (inch)

9-3/4"

9-3/4"

• Cutting capacity up to 1.2mm cold rolled steel or 0.7mm stainless steel

OFFSET TIN SNIPS (L/R) CR-MO

• Cutting capacity up to 1.2mm cold rolled steel or 0.7mm stainless steel

WEIGHT

(g)

395

395

L (mm)

240

240

			MEIOUT	PACI	KING
ITEM	L (inch)	L (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
P2010SA	10"	250	395	6	48


JONNESWAY -



P2207A 7" Cuts up to 0.56mm cold rolled steel of 0.38mm stainless steel P2208A 8" Cuts up to 0.61mm cold rolled steel of 0.41mm stainless steel P2210A 10" Cuts up to 0.78mm cold rolled steel of 0.45mm stainless steel P2212A 12" Cuts up to 0.91mm cold rolled steel of 0.71mm stainless steel

JONNESWA	Y





P22A	DROP FORGED HIGH CARBON STEEL					
Designed for all straight cutting including inside and outside corners Drop forged						

STRAIGHT PATTERN SNIPS

Induction hardened HRC 55-60

				WEIGUT	PAC	KING
ITEM		L (inch)	(mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
P2207	4	7"	180	266	10	60
P2208	۹ (8"	205	316	6	36
P2210	A	10"	254	472	6	36
P2212	A	12"	305	645	6	24

COMBINATION INTERNAL - EXTERNAL SNAP RING PLIERS P266

			WEIGUT	PACI	KING
ITEM	L (inch)	(mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
P266	6"	150	200	12	72


Internal limits 3/8" (12mm) - 2" (50mm) External limits 1/4" (6mm) - 2" (50mm)

Use with either internal or external retaining rings With 4 pieces convertible tips.

1 piece 90° angle tip

 1 piece 45° angle tip • 2 pieces straight tip (1.50 & 1.20)

*Each displayed with double tray on card *Each in plastic case then on sliding card *Each in plastic case with hanging hole & shrink



- \bigstar Serrated cutting edges are heat-treated which can easily and firmly grip bolt and cost-saving on labor.
- * Three cutting functions in one which including bolt, wire and cable.
- * Thick & ergonomic TPR handle grip.



JONNESWAY -

* Drop-forged blades with chrome molybdenum steel

*Micro finished blades

* Thick & ergonomic TPR handle grip



JONNESWAY -

* Drop-forged blades with chrome vanadium steel

★ High tensile

* Thick & ergonomic TPR handle grip



PLIERS

JONNESVIAY.

3	BOLT & WIRE & CABLE 3 IN 1 CUTTERS									
3	•SERRA	•SERRATED BLADE								
	CUT	TING CAP	ACITY ¢ ı		PAC	KING				
L (inch) BOLT		DLT	WIRE	CABLE	WEIGHT (kg)	INNER PC/BOX	OUTER PC/CTN			
	Soft Metals	Medium Metals			(rg)	FC/BOX	FC/CTN			
9"	3(1/8")	3(1/8")	2(3/32")	5(3/16")	0.4	6	60			
14"	7(1/4")	5(3/16")	3.2(1/8")	8(5/16")	1.015	1	20			
18"	8(5/16")	6(1/4")	5(3/16")	10(3/8")	1.57	1	12			
24"	10(3/8")	8(5/16")	7(9/32")	12(15/32")	2.68	1	10			
30"	13(1/2")	8(5/16")	9(3/8")	14(9/16")	4.2	1	6			
36"	16(5/8")	10(3/8")	12.7(1/2")	17(11/18")	6.34	1	5			

-			

BOLT CUTTERS

		0.1777.0.0		PAC	KING
0	SIZE	CUTTING CAPACITY ¢m/m	WEIGHT (kg)	INNER PC/BOX	OUTER PC/CTN
ŀ	14"(350mm)	7	1.03	1	20
3	18"(450mm)	8	1.58	1	20
6	36"(900mm)	15	6.15	1	5

ANGLE BOLT CUTTERS

				PAC	KING
10	SIZE	CUTTING CAPACITY ¢m/m	WEIGHT (kg)	INNER PC/BOX	OUTER PC/CTN
4	24"(600mm)	10	2.7	1	10
6	36"(900mm)	15	6.5	1	5



INSULATED PLIERS

- ANTI ELECTRO-SHOCK
- HANDLE INSULATION MEETS ALL REQUIRMENTS OF THE VDE STANDARD RELEVANT INTERNATIONAL STANDARDS(IEC 60900).





PV01	B INSULAT	ED HI-LEVERA	GE COMBINATI	ON PLIERS
ITEM NO.	L (INCH)	L (MM)	WEIGHT (G)	INNER (PC/BOX)
PV018	8-1/2"	215	460	6

JONNESWAY -

PLIERS



PV08 INSULA		ED COMBINATION PLIERS			
ITEM NO.	L (INCH)	L (MM)	WEIGHT (G)	INNER (PC/BOX)	
PV086	6"	160	250	6	
PV087	7"	180	300	6	
PV088	8"	200	375	6	

JONNESWAY -



PV06	INSULAT	ED BENT NOSE	PLIERS	
ITEM NO.	L (INCH)	L (MM)	WEIGHT (G)	INNER (PC/BOX)
PV066	6"	160	185	6
PV068	8"	200	290	6

JONNESWAY -



PV11	INSULAT	ED LONG NOSE	E PLIERS	
ITEM NO.	L (INCH)	L (MM)	WEIGHT (G)	INNER (PC/BOX)
PV1106	6"	160	185	6

JONNESWAY -



PV111		INSU	ILATED L	ONG NOS	E PLIER	5	
	ITEM NO.	L (mm)	Omm) mm) mm	mm	WEIGHT (g)
L	PV1118	200	4.0	3.0	2.0	1.6	250



ANTI ELECTRO-SHOCK
 HANDLE INSULATION MEETS ALL REQUIRMENTS OF THE VDE STANDARD RELEVANT INTERNATIONAL STANDARDS(IEC 60900).





ITEM NC PV106

PV1



JONNESWAY

JONNESWAY -

JONNESWAY -





ITEM NC PV156

PV1



JONNESWAY _



PV

JONNESWAY.

06	INSULATED DIAGONAL CUTTING PLIERS			
о.	L (INCH)	L (MM)	WEIGHT (G)	INNER (PC/BOX)
5	6"	160	240	6

810 INSULATED WATER PUMP PLIERS				
0.	L (INCH)	L (MM)	WEIGHT (G)	INNER (PC/BOX)
0	10"	250	280	6

56 INSULATED WIRE STRIPPING PLIERS				5		
Э.	(IN	L CH)	L (MM)	WEIGHT (G)	INNER (PC/BOX)	MAX CAPACITY
i		6"	160	190	6	4.5mm ²

51	0	INSU	LATED HE	AVY DUTY	CABLE CU	TTER
Э.	(IN	L ICH)	L (MM)	WEIGHT (G)	INNER (PC/BOX)	CAPACITY
0		10"	250	530	6	∮ 13mm/60mm ²

05 INSULATED CABLE CUTTER					
Э.	L (INCH)	L (MM)	WEIGHT (G)	INNER (PC/BOX)	CAPACITY
6	6"	160	180	6	∮ 9mm/60mm ²
В	8"	200	300	6	∮ 11mm/38mm ²

ANTI ELECTRO-SHOCK
HANDLE INSULATION MEETS ALL REQUIRMENTS OF THE VDE STANDARD RELEVANT INTERNATIONAL STANDARDS(IEC 60900).





OV13	1000V INSULATED SCREWDRIVERS GS & VDE APPROVED

ITEM NO.	SIZE	BLADE (mm)	GRIP (mm)	L (mm)
DV13S275	2.5	75	98	173
DV13S3100	3.0	100	98	198
DV13S4100	4.0	100	98	198
DV13S5125	5.5	125	104	229
DV13S6150	6.5	150	110	260
DV13S8175	8.0	175	120	295
DV13P060	PH0	60	98	158
DV13P180	PH1	80	104	184
DV13P2100	PH2	100	110	210
DV13P3150	PH3	150	120	270

JONNESWAY



OV13PP07S 7PCS 1000V INSULATED SCREWDR	VER SE
--	--------

CONTENTS:	
D)///00	3PCS-SLOTTED INSULATED SCREWDRIVERS : 4.0X100, 5.5X125,
DV13S	6.5X150 (mm)
DV13P	3PCS-PHILLIPS INSULATED SCREWDRIVERS : PH0X60, PH1X80,
	PH2X100 (mm)
DV13PP-TP	1PC-"GS" TESTER PEN 220-250V

JONNESWAY



DV41M06S	6PCS 1000V INSULATED NUT DRIVERS SET
CONTENTS:	

6PCS-M5, M6, M7, M8, M10. M13

DV41

JONNESWAY



	8PCS 1000V INSULATED SCREWDRIVER SET (GS & VDE APPROVED)
D02AP08S	ACETATE PLASTICS HANDLE CHROME VANADIUM STEEL
ONTENTS:	

D02S	4PCS-SLOTTED SCREWDRIVERS : 0.4x 2.5x 85, 0.8x 4.0x100, 1.0x5.5x125, 1.2x6.5x150MM
D02P	3PCS-PHILLIPS SCREWDRIVERS : PH0x75, PH1x100, PH2x100
	1PC-ELECTRIC TESTER : 220V-250V
PACKING	BLOW CASE + COLOR BOX 12SETSCTN/15KGS/16KGS/1.9'






SCREWDRIVER series

- Chrome Vanadium Steel
- Professional Quality: ANSI / DIN Standards
- CR-MO Blades
- Comfort-Design Grips

Santoprene Comfort Grip With Pressure, Oil and Acid Resistance



D71P	D71P ANTI - SLIP GRIP SCREWDRIVER - PHILLIPS -BLADES HARDENED SATIN FINISHED WITH MAGNETIC BLACK TIP -DIN 5262 -STRONG MAGNETIC								
ITEM NO.	siz	ZE	SHANK DIA. (mm)	L1 (mm)	L2 (mm)	L (mm)	PACH INNER PC/BOX	OUTER PC/CTN	
D71P060	PF	10	3	60	90	150	12	144	
D71P138	PH	11	5	38	56	93	12	144	
D71P175	PF	11	5	75	110	185	12	144	
D71P180	PH	41	5	80	110	190	12	144	
D71P1100	PH	11	5	100	110	210	12	144	
D71P1150	PF	+1	5	150	110	250	12	144	
D71P238	PH	12	6	38	56	94	12	144	
D71P2100	PF	12	6	100	119	219	12	144	
D71P2200	PH	12	6	200	119	269	12	144	
D71P2150	PF	12	6	150	119	369	12	72	
D71P2250	PH	12	6	250	119	419	12	72	
D71P2300	PH	12	6	300	120	320	12	72	
D71P3125	PF	13	8	125	129	254	12	72	
D71P3150	PH	13	8	150	129	279	12	72	
D71P4200	Ph	14	10	200	129	329	12	72	

ANTI - SLIP GRIP SCREWDRIVER - SLOTTED

50 72

250 110

38 56

100 119

175 129

SHANK DIA. L1 L2 (mm) (mm) (mm)

STRONG MAGNETIC

2.4

4

5

5

5

6

7

BLADES HARDENED SATIN FINISHED WITH MAGNETIC BLACK TIP
 DIN 5262

80 90 170

200 90 290

200 110 310

300 110 410

150 119 269

150 129 279

175 129 304
 200
 129
 329

 250
 129
 379

38 56 94

L (mm)

122

60 72 132 12 144

75 110 185 12 144

 125
 110
 235
 12
 144

 150
 110
 260
 12
 144

360

94

219

304

PACKING INNER OUTER PC/BOX PC/CTN 12 144

12 144

12 144

12 144

12 144 12 144

12

12


 12
 144

 12
 144

144

144

12



D71T D71T D71T D71T D71T9 D71T D71T1 D71T2 D71T2 D71T D71T3 D71T D71T4 D71T5

D71

ITEM

JONNESWAY -

JONNESWAY -

JONNESWAY -



L1 — L2 —

L1 ____ L2 ___

L

1



PACK

	ANTI-SLIP	GRIP BALL	POINT SC	REWDRIVE	RS
D71HB	• STRONG M	IAGNETIC TIP			
	CHROME S	SILICIUM VANA	DIUM STEEL		
ITEM NO.	SIZE	SHANK DIA. (mm)	L1 (mm)	L2 (mm)	L (mm)
D71HB2	2	2	75	72	147
D71HB25	2.5	2.5	100	72	172
D71HB3	3	3	100	72	172
D71HB4	4	4	100	90	190
D71HB5	5	5	100	110	210
D71HB6	6	6	125	119	244
D71HB8	8	8	150	129	279



D71N	ANTI-SLI	P GRIP NUT	DRIVERS		
	• CHROME	CHROME VANADIUM STEEL			
ITEM NO.	SIZE	SHANK DIA. (mm)	L1 (mm)	L2 (mm)	L (mm)
D715N05	5	1/4"	125	119	244
D715N06	6	1/4"	125	119	244
D715N07	7	1/4"	125	119	244
D715N08	8	1/4"	125	119	244
D715N09	9	1/4"	125	119	244
D715N10	10	1/4"	125	119	244
D715N11	11	1/4"	125	119	244
D715N12	12	1/4"	125	119	244
D715N13	13	1/4"	125	119	244
D715N14	14	1/4"	125	119	244

	ITEM NO.	SIZE
	D71S250	2.4
	D71S360	3
	D71S480	4
	D71S4200	4
	D71S538	5.5
L1 — L2 —	D71S575	5.5
	D71S5125	5.5
	D71S5150	5.5
	D71S5200	5.5
P will announcer @	D71S5250	5.5
	D71S5300	5.5
	D71S638	6.5
L	D71S6100	6.5
	D71S6150	6.5
	D71S8150	8
	D71S8175	8
	DT (00000	

D71S

D71S8200

D71S8250

D71S9175

8

8

JONNESWAY	
JOININLOWAI	

•

JONNESWAY -



D71PP)8S	8PCS ANTI-SLIP GRIP SCREWDRIVER SET
CONTENT	S:	
D71S		4PCS-SLOTTED SCREWDRIVERS : 6.5x38, 4x80, 5.5x125, 6.5x150MM
D71P		4PCS-PHILLIPS SCREWDRIVERS : PH2x38, PH1x80, PH2x100, PH3x150
PACKIN	G	BLOWING CASE + COLOR BOX 12SETS/CTN/10KGS/11KGS/1.9'

112

SCREWDRIVER SERIES

JONNESWAY .

IT		IAGNETIC TIP SILICIUM VANA	DIUM STEEL						
	-								
NO.	SIZE	SHANK DIA. (mm)	L1 (mm)	L2 (mm)	L (mm)				
Т5	T5	3	60	72	132				
Т6	Т6	3	60	72	132				
Т7	T7	3	60	72	132				
Т8	Т8	3	60	72	132				
Т9	Т9	3	60	72	132				
F10	T10	4	80	90	170				
F15	T15	4	80	90	170				
F20	T20	5	100	110	210				
[25	T25	5	100	110	210				
[27	T27	6	100	119	219				
F30	T30	7	125	119	244				
F40	T40	8	150	129	279				
F45	T45	8	200	129	329				
50	T50	10	200	129	329				


ANTI-SLIP GRIP STAR SCREWDRIVERS

S
ũ
œ
ш
S
Ш
>
2
2
-
9
2
Ш
2
ō
S


D71T107S	7PCS ANTI-SLIP GRIP STAR SCREWDRIVER SET
CONTENTS:	
D71T	7PCS-STAR SCREWDRIVERS : T10, T15, T20, T25, T27, T30, T40
PACKING	COLOR BOX
D71T109S	9PCS ANTI-SLIP GRIP STAR SCREWDRIVER SET
CONTENTS:	

<u>110.</u>	
1T	9PCS-STAR SCREWDRIVERS : T8, T9, T10, T15, T20, T25, T27, T30, T40
KING	COLOR BOX





D70	GO - TH	RU IMP	ACT SCF	REWDRI	VER		
			10			PAC	KING
ITEM NO.	SIZE	L1 (mm)	L2 (mm)	CUFT	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
D70P175	PH1X75	75	182	0.8'	95	12	144
D70P2100	PH2X100	100	227	1.0'	152	12	144
D70P238	PH2X38	38	57	0.7'	40	12	144
D70P3125	PH3X125	125	265	0.8'	268	12	72
D70S475	SL4X75	75	182	0.75'	80	12	144
D70S5100	SL5.5X100	100	207	0.85'	99	12	144
D70S6125	SL6.5X125	125	252	1.1'	159	12	144
D70S6150	SL6.5X150	150	277	1.15'	165	12	144
D70S638	SL6.5X38	38	57	0.7'	40	12	144
D70S8150	SL8X150	150	294	0.8'	250	12	72
D70S8200	SL8X200	200	344	0.9'	269	12	72
D70S9175	SL9.5X175	175	319	0.85'	293	12	72
D70S9200	SL9.5X200	200	344	0.9'	301	12	72
D70S9250	SL9.5X250	250	394	1_0'	317	12	72



• ISO 9001 AND DIN 5262 OR 5265

JONNESWAY -

- BLADES WITH HEAT TREATMENT, SATIN FINISHED, AND MAGNETIC TIPS
- ABS COMFORT GRIP, WITH PRESSURE, OIL AND ACID RESISTANCE


 Mechanic Go Thru Screwdriver Has Been Ergonomically Designed. The Handle has Been Created Using Impact - Resistant And Cold-Resistant Steel Made From CrMoVa, Precision And Rid Of Hydrogen Process.

- The Appliance For Any Metal Or Non-metal Operation System, Such As : Steel, Wood, Porcelain, Mineral.....ETC.
 Can be used as Punch, Chisel, Screwdriver, and Pry Bar.

10PCS GO THRU IMPACT SCREWDRIVER SET

- Can be used with Wrench to Increase the Torque.
- It can take 3000G Impact Of Hammer.

D70 Mechanic Go Thru Screwdrivers Suitable For Automotive Tool, Machinery Tool, Wall Construction, And Household Use.



D70PP10S **10PCS GO-THRU IMPACT SCREWDRIVER SET**

CONTENTS

CONTENTS:	
	1-450 mm Pick Up
D70P	1.0x75, 2.0x100, 3.0x125, 2.0x38
D70S	5.5x100, 6.5x125, 8.0x150, 9.5x175, 6.5x38
	6SET/CTN/14KGS/15KGS/CUFT:1.5'

D70PP07S 7PCS GO-THRU IMPACT SCREWDRIVER SET

CONTENTS:

O OITTENTO.	
	1-450 mm Pick Up
D70P	O 1.0x75, 2.0x100, 3.0x125
D70S	€ 5.5x100, 6.5x125, 8.0x150
	12SET/CTN/19.5KGS/20.5KGS/1.85'





l	1	ì	
		1	
		1	

DO



		FULL STAR SCREV	VDRIVI	ER			
)	4	BLADES HARDENED SATIN FINISHED WITH MAGNETIC BLACK TIP DIN 5262 OR DIN5265 STRONG MAGNETIC					
	PACKING						
•	BLADE THICKNESS x WIDTH x LENGTH		L1 (mm)	L2 (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
		PH1 x 80 (3-1/8")	80	174	55	12	144
		PH2 x 38 (1-1/2")	38	89	45	12	144
)	PH2 x 100 (4")		100	212	95	12	144
5	5 PH3 x 125 (5")		125	254	170	12	72
)		PH3 x 150 (6")	150	273	195	12	72
	4	x80 (5/32" x 3-1/8")	80	170	45	12	144
	6.	5 x 38 (1/4" x 1-1/2")	38	109	50	12	144
)	6	6.5 x 100 (1/4" x 4")	100	212	95	12	144
)	6	6.5 x 150 (1/4" x 6")	150	260	105	12	144
)	8	3 x 150 (5/16" x 6")	150	280	160	12	72
5	5	.5 x 125 (7/32"x 5")	125	220	60	12	144

D04PP08S	8PCS FULL STAR SCREWDRIVER SET
CONTENTS:	
D04S	4PCS-SLOTTED SCREWDRIVERS : 6.5x38, 4x80, 5.5x125, 6.5x150MM
D04P	4PCS-PHILLIPS SCREWDRIVERS : PH2x38, PH1x80, PH2x100, PH3x150
PACKING	BLOWING CASE + COLOR BOX 12SETS/CTN/10KGS/11KGS/1.9'
B0455400	
D04PP16S	16PCS FULL STAR SCREWDRIVER SET
CONTENTS:	16PCS FULL STAR SCREWDRIVER SET
	16PCS FULL STAR SCREWDRIVER SET 8PCS-SLOTTED SCREWDRIVERS : 3x50(1/8"x2"), 5.5x75(7/32"x3"), 3x150(1/8"x6"), 6.5x38(1/4"x1-1/2"), 5.5x200(7/32"x8"), 8x150(5/16"x6"), 5.5x125(7/32"x5"), 6.5x100(1/4"x4")
CONTENTS:	8PCS-SLOTTED SCREWDRIVERS : 3x50(1/8"x2"), 5.5x75(7/32"x3"), 3x150(1/8"x6"), 6.5x38(1/4"x1-1/2"), 5.5x200(7/32"x8"), 8x150(5/16"x6"),

PACKING

PACKING

OUTER PC/CTN

72

72

72

72

72

72

INNER PC/BOX

12

12

12

12

12

12

INNER PC/BOX

OUTER PC/CTN





	50 Length
	D3750T20 🗰 T20 X 50
1000	-

D3750T20 🗰 T20 X 50	12	72
D3750T15 🗰 T15 X 50	12	72
D3750T10 🗰 T10 X 50	12	72
D3750T9 🗰 T9 X 50	12	72
D3750T8 🗰 T8 X 50	12	72
D3750T7 🗰 T7 X 50	12	72
D3750T6 🗰 T6 X 50	12	72
D3750T5 🗰 T5 X 50	12	72
computer & Tooling Repair		

6PCS PRECISION SCREWDRIVER SET(L:50MM)

D3750T08S 8PCS PRECISION SCREWDRIVER SET(L:50MM)

Co ng Rep

'50P06S

D3



Computer, Electric Device & Glasses Repair

50 Length

D3750P1 **()** N0.1 X 50 D3750P0 **()** N0.0 X 50

D3750P00 🛟 N0.00 X 50

D3750S30 3.0 X 50 D3750S24 2.4 X 50 D3750S20 2.0 X 50

D3765T06S 6PCS PRECISION SCREWDRIVER SET(L:65MM)				
PACKING				
65 Length	INNER PC/BOX	OUTER PC/CTN		
D3765T10 🗰 T10 X 65	12	72		
D3765T9 🗯 T9 🗙 65	12	72		
D3765T8 🗰 T8 🗙 65	12	72		
D3765T7 🗰 T7 🛛 X 65	12	72		
D3765T6 🗰 T6 🗙 65	12	72		
D3765T5 🌲 T5 X 65	12	72		

JONNESWAY -



D3765P08S 8PCS PRECISION SCREWDRIVER SET(L:65MM)

	PAC	KING
75 Length	INNER PC/BOX	OUTER PC/CTN
D3765P1 🛟 N0.1 X 65	12	72
D3765P0 🗘 N0.0 X 65	12	72
D3765P00 🛟 N0.00 X 65	12	72
D3765S30 🚍 3.0 X 65	12	72
D3765S24 🛖 2.4 🛛 X 65	12	72
D3765S20 🗬 2.0 X 65	12	72
D3765S35 🛖 3.5 🛛 X 65	12	72
D3765S40 🚍 4.0 X 65	12	72

Computer, Electric Device & Glasses Repair





JONNESWAY -



resistance and durability

(1) Meets DIN standard.



JONNESWAY -







19PCS RATCHET DRIVER BIT SET

• 1PC-RATCHET DRIVER • 2PCS-PHILLIPS:#1, #2(25MML) • 2PCS-SLOTTED:4.5, 7MM(25MML) • 2PCS-POZI:#1, #2(25MML) • 6PCS-STAR:T10, T15, T20, T25, T30, T40(25MML) • 6PCS-HEX:2MM, 2.5MM, 3MM, 4MM, 5MM, 6MM(25MML)

DR0253S **53PCS FLEXIBLE RATCHET DRIVER BIT SET**

CONTENTS:

• 1PC-FLEXIBLE RATCHET DRIVER • 3PSC-PHILLIPS: #1, #2, #3(25MML) • 4PCS-SLOTTED: 3, 4, 5.5, 7MM(25MML) • 4PCS-POZI: #0, #1, #2, #3(25MML) • 6PCS-HEX: 2MM, 2.5MM, 3MM, 4MM, 5MM, 6MM(25MML) • 10PCS-STAR: T6, T8, T9, T10, T15, T20, T25, T27, T30, T40(25MML) • 8PCS-STAR W/TAMPERPROOF: T8, T10, T15, T20, T25, T27, T30, T40(25MML) • 1PC 1/4" HEX DRIVE SHANNKS ADAPTER • 15PCS-1/4"DR.6PT SOCKET: 4MM, 5MM, 6MM, 7MM, 8MM, 9MM, 10MM, 11MM, 12MM, 13MM, 3/16", 1/4", 5/16", 3/8", 1/2" • 1PC-MAGNETIC HOLDER

(2) Integrative shaping by CNC machine improves precision.

(3) Streamline shaping prevents stress concentration, greatly increases product endurance. (4) Precision tailoring provides precise cut to fit different drive codes of each screw and provides extra protection for the screw.

(5) Special heat treatment increases the strength and tenacity, thus increases the abrasion

(6) Special surface treatment to prevent precision variation caused from thickness change from plating, and greatly solve the surface rusting problem. (7) Special double groove tailoring provides better anti-slip grip.

RD01032S 32PCS 1/4" HEX MINI RATCHET BIT SET

1pc-Mini disc ratchet handle(1/4" bit holder)-60 teeth 1pc-Magnetic bit holder-60mm 30pcs 1/4" Hex shank insert bits 4pcs-Phillips: #1×1pc,#2×2pcs, #3×1pc 4pcs-Hex: 3, 4, 5, 6mm 4063-F162, 3, 4, 5, 61/01 2pcs-Square: SQ1,SQ2 3pcs-Pozi: P21,P22,P23 7pcs-Star: T10,T15,T20,T25,T27,T30,T40 3pcs-Slotted: 4, 5.5, 6, 5mm

7pcs-Star tamperproof: T10,T15,T20,T25,T27,T30,T40

RD02040S 40PCS 1/4"DR MINI RATCHET BIT SET

CONTENTS:
1pc-Mini flexible ratchet handle-60 teeth
7pcs-1/4" Dr sockets:6,7,8,10,11,12,13mm
1pc-1/4" Hex bit holder
1pc-1/4"Dr extension bars
30pcs 1/4" Hex shank insert bits :
4pcs-Phillips:#1×1pc,#2×2pc, #3×1pc
4pcs-Hex: 3, 4, 5, 6mm
2pcs-Square:SQ1,SQ2
3pcs-POZI:PZ1,PZ2,PZ3
7pcs-Star:T10,T15,T20,T25,T27,T30,T40
3pcs-Slotted:4, 5.5, 6.5mm
7pcs-Star tamperproof:T10,T15,T20,T25,T27,T30,T40







JONNESWAY -

JONNESWAY -



CONTENTS:	
	7PCS-HEX BITS : 2, 3, 4, 5, 6, 7, 8MM (30MML)
	1PC-OFFSET BIT HOLDER WRENCH
PACKING	BLISTER CARD 100SET/CTN/12.3KGS/13.5KGS/1.1'

S08H2H8S 8PCS 1/4" DR. HEX BIT SET

8PCS 1/4" DR. BIT SET

7PCS-1/4" BIT (30MML) : PHILLIPS BITS : PH1, PH2, PH3 SLOTTED BITS : 4, 7MM POZI BITS : PZ1, PZ2

1PC-OFFSET BIT HOLDER WRENCH

PACKING BLISTER CARD 100SET/CTN/12.3KGS/13.5KGS/CUFT : 1.1'

S29H2133S	33PCS 1/4" DR. SECURITY BIT SET
-----------	---------------------------------

CONTENTS

S08H208S

CONTENTS:

CONTENTS.	
	1PC-MAGNETIC BIT HOLDER (60MML)
	32PCS-1/4" SECURITY BIT (25MML)
	STAR SET 6, 8, 10 TRI-WING 1, 2, 3, 4
	SPANNER 4, 6, 8, 10 HEX SECURITY 5/32", 9/64", 1/8", 7/64", 3/32", 5/64", 2, 2.5, 3, 4, 5, 6MM
	9PCS-STAR TAMPERPROOF T-8H, T-10H, T-15H, T-20H, T-25H, T-27H, T-30H, T-35H, T-40H
PACKING	PLASTIC CASE + SLIDE CARD 48SETSCTN/12KGS/13KGS/0.78'

JONNESWAY -



S29H4140S	40PCS 3/8" & 1/2" DR. POWER BIT SET
CONTENTS:	
	14-10MM HEX BITS : 30MML : 4, 5, 6, 7, 8, 10, 12 75MML : 4, 5, 6, 7, 8, 10, 12
	14-10MM STAR BITS : 30MML : T20, T25, T30, T40, T45, T50, T55 75MML : T20, T25, T30, T40, T45, T50, T55
	10-10MM SPLINE BITS : 30MML : M5, M6, M8, M10, M12 75MML : M5, M6, M8, M10, M12
	2PCS-BIT HOLDERS : 3/8" DR. x 10MM, 1/2" DR. x 10MM
PACKING	10SET/CTN/21KGS/23KGS/0.75'







	H03SA1
	H03SA2
:	Anti - S More T

1035

035

JONNESWAY ----

JONNESWAY -



JONNESWAY -



H16⁻

JONNESWAY.

9PCS ANTI-SLIP LONG ARM HEX KEY SET (MM) H02SA109 CHROME PLATED •S2

CONTENTS
CONTLINIO.

H02SA109S 9PCS: 1.5, 2, 2.5, 3, 4, 5, 6, 8, 10MM

Anti - Slippery Grooves
More Torque Increased

A109S	9PCS ANTI-SLIP EXTRA LONG ARM HEX KEY SET (MM)
A209S	9PCS ANTI-SLIP EXTRA LONG ARM HEX KEY SET (SAE)
NTS:	
A109S	9PCS - 1.5, 2, 2.5, 3, 4, 5, 6, 8, 10 MM
A209S	9PCS - 1/16", 5/64", 3/32", 1/8",5/32", 3/16", 1/4", 5/16", 3/8"

Slippery Grooves Torque Increased

A109S	9PCS ANTI-SLIP EXTRA LONG ARM BALL POINT HEX KEY SET (MM)
A209S	9PCS ANTI-SLIP EXTRA LONG ARM BALL POINT HEX KEY SET (SAE)
NTS:	

A109S	9PCS - 1.5, 2, 2.5, 3, 4, 5, 6, 8, 10 MM
A209S	9PCS - 1/16", 5/64, 3/32, 1/8",5/32", 3/16, 1/4", 5/16", 3/8"
Clippon	Croover

9PC EXTRA LONG ARM STAR HEX KEY SET
9PCS - TS10, TS15, TS20, TS25, TS27, TS30, TS40, TS45, TS50



H01M07SF	7PCS FOLDABLE HEX KEY SET(MM)	
	•CR-V •CHROME PLATED	
H01M08SF	8PCS FOLDABLE HEX KEY SET(SAE)	
nutwicosr	CR-V CHROME PLATED	
CONTENTS:		
H01M07SF	7PCS : 2.5, 3, 4, 5, 6, 8, 10MM	
H01M08SF	8PCS : 5/64", 3/32", 1/8", 5/32", 3/16", 1/4", 5/16", 3/8"	



\frown	Н015М1095	9PCS SHORT ARM HEX KEY SET(MM)
\bigcirc		•S2 •CHROME PLATED
	11040110000	9PCS SHORT ARM HEX KEY SET(SAE)
	H01SM209S	•S2 •CHROME PLATED
	CONTENTS:	
	H01SM109S	9PCS : 1.5, 2, 2.5, 3, 4, 5, 6, 8, 10MM
	H01SM209S	9PCS : 1/16", 5/64", 3/32", 1/8', 5/32", 3/16', 1/4", 5/16', 3/8"

JONNESWAY -

JONNESWAY -



H02SM109S	9PCS LONG ARM HEX KEY SET(MM)	
	•S2 •CHROME PLATED	
H02SM209S	9PCS LONG ARM HEX KEY SET(SAE)	
	•S2 •CHROME PLATED	
CONTENTS:		
H02SM109S	9PCS : 1.5, 2, 2.5, 3, 4, 5, 6, 8, 10MM	
H02SM209S	9PCS : 1/16", 5/64", 3/32", 1/8", 5/32", 3/16", 1/4", 5/16", 3/8"	

JONNESWAY -



1105014000	9PCS LONG ARM BALL POINT HEX KEY SET(MM)	
H05SM109S	•S2 •CHROME PLATED	
LINEGMONOG	9PCS LONG ARM BALL POINT HEX KEY SET(SAE)	
H05SM209S	•S2 •CHROME PLATED	
CONTENTS:		
H05SM109S	9PCS : 1.5, 2, 2.5, 3, 4, 5, 6, 8, 10MM	
H05SM209S	9PCS : 1/16", 5/64", 3/32", 1/8", 5/32", 3/16", 1/4", 5/16", 3/8"	

JONNESWAY -




H06S109S	9PCS EXTRA LONG ARM BALL POINT HEX KEY SET(MM)
HUDDIUDD	•S2 •SATIN FINISHED
H06S209S	9PCS EXTRA LONG ARM BALL POINT HEX KEY SET(SAE)
HU032093	•S2 •SATIN FINISHED
CONTENTS:	
H06S109S	9PCS : 1.5, 2, 2.5, 3, 4, 5, 6, 8, 10MM

H06S109S	9PCS : 1.5, 2, 2.5, 3, 4, 5, 6, 8, 10MM
H06S209S	9PCS : 1/16", 5/64", 3/32", 1/8", 5/32", 3/16", 1/4", 5/16", 3/8"
PACKING	HOLDER + SLIDE CARD 36SETS/CTN/17.5KGS/18.5KGS/1.6'








JONNESWAY -





®

S2 CHROME PLATED
SIZE (MM)
1.5
2.0
3.0
3.0
4.0
5.0
6.0
8.0
10.0

SM2	LONG ARM BALL POINT HEX KEY (SAE)
SIVIZ	S2 CHROME PLATED
).	SIZE (INCH)
15	1116"
20	5/64"
25	3/32"
30	1/8"
40	5/32"
50	3/16"
60	1/4"
80	5/16"
100	3/8"

5S1	EXTRA LONG ARM BALL POINT HEX KEY (MM)		
	S2 • SATIN FINISHED		
).	SIZE (MM)		
5	1.5		
)	2		
5	3.		
)	3		
)	4		
)	5		
)	6		
)	8		
00	10		

H06S2	EXTRA LONG ARM BALL POINT HEX KEY (SAE)	
HU052	S2 • SATIN FINISHED	
ITEM NO.	SIZE (INCH)	
H06S215	1/16"	
H06S220	5/64"	
H06S225	3/32"	
H06S230	1/8"	
H06S240	5/32"	
H06S250	3/16"	
H06S260	1/4"	
H06S280	5/16"	
H06S2100	3/8"	

JONNESWAY




H03MT109S	9 IN 1 9PCS EXTRA LONG ARM HEX KEY SET W/HANDLE	
	SNCM+V #8660 MAT FINISHED	
CONTENTS:		
H03MT109S	9PCS : 1.5, 2, 2.5, 3, 4, 5, 6, 8, 10MM	


НЕХ КЕҮ



	H06MT109S	9 IN 1 9PCS EXTRA LONG ARM BALL POINT HEX KEY SET W/HANDLE
2 ¹⁰ Al	11001111000	SNCM+V #8660 MAT FINISHED
.143	CONTENTS:	
	H06MT109S	9PCS - 1.5,2,2.5,3,4,5,6,8,10 MM









	9PCS STAR KEY SET			
H07M09S	•S2 •CHROME PLATED			
	9PCS STAR KEY W/TAMPERPROOF SET			
H08MTP09S	•S2 •CHROME PLATED			
CONTENTS:				
	9PCS-T10, T15, T20, T25, T27, T30, T40, T50			
PACKING	PLASTIC CASE 72SETS/21KGS/22KGS/0.9'			

JONNESWAY -

JONNESWAY -



	10PCS EXTRA LONG ARM STAR TAMPERPROOF KEY SET		
H08S110S	•S2 •SATIN FINISHED		
CONTENTS:			
H08S	10PCS : T9, T10, T15, T20, T25, T27, T30, T40, T45, T50		










JONNESWAY -

JONNESWAY -



JONNESWAY.

	8PCS TWO WAY BALL POINT & HEX KEY SET			
B08S	•8660 •MAT FINISHED			
NTS:				
MB	8PCS : 2X100, 2.5X100, 3X100, 4X100, 5X150, 6X150, 8X200, 10X200MM			

9PCS TWO WAY STAR & TAMPERPROOF KEY SET				
•8660 •MAT FINISHED				
9PCS : T10X100, T15X100, T20X100, T25X100, T27X150, T30X150, T40X150, T45X200, T50X200M				

MT	TWO WAY STAR & TAMPERPROOF KEY					
ITEM NO.		SIZE	L1 (mm)			
H10MT10	100	T10	100			
H10MT15	100	T15	100			
H10MT20	100	T20	100			
H10MT25	100	T25	100			
H10MT27	150	T27	150			
H10MT30150		T30	150			
H10MT40150		T40	150			
H10MT45200		T45	200			
H10MT50200		T50	200			

MB	TWO WAY BALL POINT & HEX KEY					
ITEM NO.		SIZE	L1 (mm)			
H10MB2100		2	100			
H10MB25	100	2.5	100			
H10MB31	00 3		100			
H10MB41	34100 4		100			
H10MB5150		5	150			
H10MB6150		6	150			
H10MB8200		8	200			
H10MB10200		10	200			



HEX KEY

HAMMER

JONNESWAY -

— L1 — L2

H20MB	TWO WAY BALL POINT HEX KEY (SAE)				
ΠΖΟΙΝΙΒ	S2				
ITEM NO.	SIZE	L1 (mm)	L2 (mm)		
H20MB2020	H5/64	100	12		
H20MB2025	H3/32	110	12		
H20MB2030	H1/8	120	12		
H20MB2040	H5/32	125	14		
H20MB2050	H3/16	155	15		
H20MB2060	H1/4	165	15		
H20MB2080	H5/16	185	16		
H20MB20100	H3/8	210	20		

MO ITEM NO. M04008

M04012 M04016 M04024 M04032

НЕХ КЕҮ



H02MH		LONG ARM HEX KEY SET			
	Material : Chrome Vanadium steel, Chrome Plated.				
ITEM NO. PCS		SIZE			
H02MH118S 18 1.		1.5, 2, 2.5, 3, 3.5, 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 12, 14, 17, 19MM			



JONNESWAY -



MK2040 QUICK CHANGE BLADE RETRACTABLE UTILITY W/2PCS BLADE			
Special Feature	s :		
	Oil Resistance Rubber Paint for Non-Slip function Cold Resistance to -20* Ouick Change Blade Function.		
PACKING	BLISTER CARD 72SETS/CTN/19.5KGS/20.5KGS/2.3'		



JONNESWAY -

JONNESWAY -

ITEM NO. M07016



A		BALL	PEEN HAM	MER				
4		• 60% F I	BERGLASS HAND	LE W/PP JACKET	TED & OVERMOU	LDED TPR GRIP		
		D WGT	LENGTH	WEIGHT	PACI			
).		(OZ)	(mm)	(g)	INNER PC/BOX	OUTER PC/CTN		
3		8	278±6	395	12	48		
2		12	283±6	527	6	36		
6		16	327 <u>±</u> 6	780	6	36		
1		24	383±6	1063	6	24		
2		32	385±6	1208	4	24		

		BALL	PEEN HAM	MER		
8	• WIT		HICKORY H	ANDLE		
					PACI	KING
).	HEAD WGT (OZ)		LENGTH (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
2	12		325±6	444	6	36
6	16		350±6	584	6	36
4		24	396±6	1042	6	24
2		32	400±6	1208	4	24

)E		CLAW HAMMER								
15	• 60% FIBERGLASS HANDLE W/PP JACKETED & OVERMOULDED TF									
			. ENOTI	WEIGUT	PACI	KING				
о.		D WGT (OZ)	LENGTH (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN				
6	16		330 <u>±</u> 6	750	6	36				
0		20	330 <u>±</u> 6	830	6	24				

)7		SOFT FACE HAMMER								
		TPR MATERIAL (BLACK) TRANSPARENT ACETATE MATERIAL								
					PACI	KING				
Э.	HEAD WGT (OZ)		LENGTH (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN				
6		16	314	840	6	24				

JONNESWAY -----

JONNESWAY -----

JONNESWAY -



M03	SOL	SOLID STEEL ONE PIECE CLUB HAMMER					
INIUS	۰w	WITH SHOCKWAVE TPR GRIP					
			-				
				PACI	KING		
ITEM NO.	HEAD WG (lb)	LENGTH (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN		
M03040	4	276±6	2167	4	12		

JONNESWAY -


HAMMER







M













_		I
		(

H	an la canada	1000)

MOG	CLUB HAMMER
WUO	• 60% FIBERGLASS HANDLE W/PP JACKETED & OVERMOULDED TPR GRIP

				PACKING		
ITEM NO.	HEAD WGT (lb)	LENGTH (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN	
M06030	3	263 <u>±</u> 6	1550	4	12	
M06040	4	276±6	2250	4	12	

JONNESWAY -



M09		ENGINEER'S HAMMER						
		• WITH HIC	KORY HANDLE					
				PACKING				
ITEM NO.	HEA	(g)	LENGTH (mm)	INNER PC/BOX	OUTER PC/CTN			
M09300		300	300 <u>±</u> 6	6	48			
M09500		500	320±6	6	36			

JONNESWAY -



DEAD	DEAD BLOW HAMMER							
• STEE	• STEEL HAMMER GRIP COVERED WITH SYNTHETIC RUBBER							
	OVERALI		PAC	KING				
HEAD DIA (mm)	LENGTH (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN				
35	260	400	6	48				
45	286	520	6	36				
55	350	1050	4	24				
65	370	1500	4	16				
	• STEE HEAD DIA (mm) 35 45 55			• STEEL HAMMER GRIP COVERED WITH SYNTHE HEAD DIA (mm) OVERALL LENGTH (mm) WEIGHT (g) PACI INNER PC/BOX 35 260 400 6 45 286 520 6 55 350 1050 4				



		CENTER PUNCH							
M60	J		CHROME VANADIUM PHOSPHATE SUNK FINISHED						
						PAC	KING		
ITEM NO.	SIZ	Ξ	L (mm)	HEX SHANK (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN		
M60102	2		120	9.5	33	200	400		
M60103	3		100	8	33	200	400		
M60104 4			120	9.5	57	200	400		
M60105 5			150	12.7	114	90	180		

		COLD CHISEL										
61			CHROME VANADIUM PHOSPHATE SUNK FINISHED									
						PACI	KING					
).	SIZE		L (mm)	HEX SHANK (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN					
)	10		150	9.5	80	120	240					
:	12		130	9.5	80	120	240					
;	13		150	9.5	82	120	240					
;	16		180	12.7	171	60	120					
)	19		180	15.8	260	40	80					
2	22		200	15.8	307	30	60					
;	25		200	19.0	449	25	50					

		TAPER PUNCH								
62	2	-	CHROME VANADIUM PHOSPHATE SUNK FINISHED							
						PAC	KING			
0.	SIZE		L HEX SHANK (mm) (mm)		WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN			
12	2		120	9.5	53	200	400			
13	3		120	9.5	55	200	400			
4	4		120	9.5	57	200	400			
15	5		120	9.5	59	200	400			
6	6		120	9.5	60	200	400			

63 PIN PUNCH • CHROME VANADIUM • PHOSPHATE SUNK FIN		PIN PUNCH					
			SHED				
						PACKING	
).	SIZE	Ξ	L (mm)	HEX SHANK (mm)	WEIGHT (g)	INNER PC/BOX	OUTER PC/CTN
2	2X30		115	8	33	250	500
3	3X40		125	8	34	250	500
ŧ	4X50		150	9.5	63	150	300
5	5X5	0	165	9.5	71	150	300
6	6X5	3	180	12.7	132	80	160
3	8X5	3	180	12.7	144	70	140

105S	5PCS CHISEL PUNCH SET		
1035	PHOSPHATE SUNK FINISHED		
NTS:			
104	1PC-PIN PUNCH : 4 x 9.5 x 150MM		
105	1PC-CAPE CHISEL : 5 x 9.5 x 130MM		
112	1PC-COLD CHISEL : 12 x 9.5 x 130MM		
103	1PC-TAPER PUNCH : 3 x 9.5 x 120MM		
102	1PC-CENTER PUNCH : NO.2 x 9.5 x 120MM		
KING	PLASTIC HOLDER + SLIDER CARD 40SETS/CTN/15KGS/16KGS/0.5'		

106S	6PCS PIN PUNCH SET		
1000	PHOSPHATE SUNK FINISHED		
NTS:			
63	6PCS-PIN PUNCH : 2x8.0x115MM, 3x8.0x125MM, 4x9.5x150MM, 5x9.5x165MM, 6x12.7x180MM, 8x12.7x180MM		
KING	PLASTIC HOLDER + SLIDER CARD 30SETS/CTN/16KGS/17KGS/0.6'		



· Made of hardened, stainless steel.

CALIPER

N.W/G.W/CUF

16.0/18.0/1.6

18.0/20.0/2.3

10.4/15.0/1.65


N.W/G.W/CUF'T


Polish finish.

JONNESWAY -

Material : carbon steel.







JONNESWAY -

MTC1150 6"/ 15 CM 150X0.02MM 50/CTN 16.0/17.0/1.53 MTC1200 8"/ 20 CM 200X0.02MM 20.4/22.0/2.24 50/CTN MTC1300 12"/30 CM 300X0.02MM 14.6/16.3/1.60 20/CTN

LARGE RANGE ELECTRONIC CALIPER

PACKING

50/CTN

50/CTN

20/CTN

PACKING

DIMENSION

(mm)

150X0.01MM

200X0.01MM

300X0.01MM

DIMENSION

(mm)

VERNIER CALIPER

МТС

SIZE

6"

8"

12"

SIZE

ITEM NO.

MTC150

MTC200

MTC300

MTC1

ITEM NO.

JONNESWAY -

JONNESWAY -

Made of stainless steel.

- Made of stainless steel.
- Dialindicator has fine line indicting hand.
- Four measurements inside, outside, depth and step.

• Four measurements - inside, outside, depth and step.



• Easy to read digital Large LCD display with inch / metric conversion.

MTC2	DIAL VE	DIAL VERNIER CALIPER			
ITEM NO.	SIZE	DIMENSION (mm)	PACKING	N.W/G.W/CUF'T	
MTC2150	6"	150X0.02MM	50/CTN	13.0/15.0/1.0	
MTC2200	8"	200X0.02MM	50/CTN	17.0/19.0/1.4	
MTC2300	12"	300X0.02MM	25/CTN	16.0/18.0/1.4	

JONNESWAY -

· Satin chrome finished thimble and handle with easy reading scale.



МТМ	MICROMETER	MICROMETERS		
ITEM NO.	SIZE	PACKING	N.W/G.W/CUF'T	
MTM1025	0-25MM	50/CTN	15.0/16.0/0.6	
MTM1050	25-50MM	50/CTN	25.0/26.0/0.8	
MTM1075	50-75MM	30/CTN	24.0/25.0/1.2	
MTM1100	75-100MM	25/CTN	20.0/21.0/1.0	

JONNESWAY -

MTC 155 Technical pencil with tungsten lead.

MTC155		5 UNILITY TEC	HNICAL PENCIL	
	ITEM NO.	SIZE	PACKING	N.W/G.W/CUF'T
ſ	MTC155	2.0MM	300/CTN	6.0/7.0/0.6

1	2	0
н	Ζ	0



'C3	QUICK ADJ	QUICK ADJUST DIVIDERS			
0. SIZE		PACKING	N.W/G.W/CUF'T		
6	6"	10/box, 100/CTN	12.0/13.5/2.5		
8	8"	10/box, 100/CTN	16.0/17.0/2.5		

'C4	QUICK ADJU	IST OUTSIDE CALIPE	RS
O. SIZE		PACKING	N.W/G.W/CUF'T
6	6"	10/box, 100/CTN	12.0/13.5/2.5
8 8"		10/box, 100/CTN	16.0/17.0/2.5

C5	QUICK ADJU	QUICK ADJUST INSIDE CALIPERS		
0.	SIZE	PACKING	N.W/G.W/CUF'T	
6	6"	10/box, 100/CTN	12.0/13.5/2.5	
8	8"	10/box, 100/CTN	16.0/17.0/2.5	

MEASURING TAPE & HACKSAW



	MEASUKING TAPES SM X 19MM
MT07	• HIGH IMPACT ABS CASE W/ RUBBER PROTECTED • RUBBER COVERED CASE, COMFORTABLE

		PAC	KING
ITEM NO.	SIZE	INNER PC/BOX	OUTER PC/CTN
MT0701	3Mx19MM	12	120

JONNESWAY



	MEASURING TAPES 7.5M / 25FT			
MT03	HIGH IMPACT ABS CASE W/ RUBBER PROTECTED RUBBER COVERED CASE , COMFORTABLE			
		PAC	KING	
ITEM NO.	SIZE	INNER PC/BOX	OUTER PC/CTN	
MT0303	7.5M / 25FT x 1" (25mm)	6	48	

JONNESWAY -



MHS100AG	HEAVY DUTY DELUXE TYPE HACKSAW W/12" H.S.S. BLADE	
Special Features	5:	
	Blade being positioned for 45° or 90° normal cutting Adjustable handle to increase tension up to 34000 PSI Torgue	

Extra blades tp be stored in top bar COLOR SLEEVE 36SETS/CTN/23KGS/24KGS/2.2' PACKING

JONNESWAY

in unan di

- Industrial Safety

AIR TOOLS SERIES

DAILY J

• Excellent Performance • Powerful & Low Noise Compact & Light Weight


AIR IMPACT WRENCH SERIES



The NEW upgraded ULTRA-LIGHT IMPACT WRENCH with compact mechanism which highly reduce the tool's weight and volume more than 30%. With SIX unique functions, it is not only increase the operation efficiency but also enhance operating comfortable and convenience for the end users.

Market Sales Application:

The design for repair of heavy truck tire and large engineering construction, like railway and bridge building.....etc.



Motor unit has high precision components which highly increase output efficiency.

weight and volume.

JAI-

TECHNI Square Dr Std Bolt Si Free Spee Working T MAX. Torq Overall Le Air Inlet Siz Air Hose (Avg. Air Co Net Weigh Clutch Me Vibration (Noise Leve



CE

Special design of easy adjusting trigger has two directions for different operating option.

Soft material of housing cover protects the tool from external bumping.

Compact components and special design reduce the Special handle design combines with soft material highly increases operating comfortable for long time usage.

1" SQ.DR.Super Duty Air Impact Wrench W/6" Extended Anvil		
JAI-1138L		
1'	и	
1-27/64"	M36	
5,0	000	
1,800 (ft-lb)	2,430 (Nm)	
2,000 (ft-lb)	2,712 (Nm)	
19.2"	487 (mm)	
1/2"		
3/4"		
9 (cfm)	255 (l/min)	
18.3 (lbs)	8.3 (kgs)	
Twin Hammer		
18		
98		
	Wrench W/6" Exter JAI 1-27/64" (1-27/64") (1-27/64" (1-27/64" (1-27/64") (1-27/64" (1-27/64") (1-27/6	


CE

AIR IMPACT WRENCH SERIES

The new advance ULTRA-LIGHT IMPACT WRENCH with compact mechanism which highly reduce the tool's weight and volume more than 30%. With several special functions, they increase operating comfort and efficiency. Also they improve convenience for longtime usage.

Market Sales Application:

The friendly design for repair of heavy truck tire and large engineering construction, such as railway, bridge building and steel construction building.....etc.



with spring component increases

Additional handle design improves operating convenience.

		-	1	h
	키	E		j

JAI-1408L W/8" Extended Anviltwin Hammer			
	NICAL DATA	JAI-1	
Square D	rive	1	
Std. Bolt	Size	1-3/4"	45mm
Free Spe	ed (rpm)	4,8	00
Working 7	Torque	2,400(Ft-lb)	3,270(N.M.)
Max Torq	ue	2,600(Ft-lb)	3,520(N.M.)
Overall Le	ength	22.5"	570 (mm)
Air Inlet S	ize	1/2"	
Air Hose	(I.D.)	1/2"	
Air Press	ure	90 PSI	
Avg. Air C	onsumption	16 (cfm) 450 (l/min)	
Net Weight		26.2 (lbs)	11.9 (kgs)
Clutch Me	echanism	Twin Hammer	
Exhaust [Direction	Side E	xhaust
Vibration	M/S ²	12.32	
vibration	K (M/S ²)	1.72	
	Pressure A (dB)	94.5	
Sound	Power A (dB)	105.5	
Sound	Pressure C (dB)	93.9	
	K (dB)	(dB) 3	

1" SQ, DR, Super Duty Air Impact Wrench

The NEW upgraded HEAVY-DUTY COMPOSITE IMPACT WRENCH with special patent design twin hammer mechanism offer you seven unique functions for easy operation which 20% light weight compare with Alumium-Alloy Tools and 10% higher torgue reached compare tools with same standard.


1. The anvil is made by high quality material with special heat treatment to improve its lifetime.



1.5m


2.Strong housing can handle 1.5m drop floor test and also pass the test of vehicle grinding.

JAI-0936



JONNESVIAY.

CE



4. Patent design mechanism improves its lifetime.

3. Motor unit with high precision increases output efficiency.

> 5. Forward/reverse switch and special air inlet adjustment for easy operation

6. Special channel with patent design improves motor efficiency

7. The valve system has special design to increase its lifetime.

3/4" SQ. DR. Heavy-Duty Composite **Impact Wrench**

JAI-0936			
3/4	4"		
1"	M25		
6,5	00		
1,200 (Ft-lb)	1,620 (N.M.)		
1,500 (Ft-lb)	2,025 (N.M.)		
8-55/64"	225 (mm)		
3/8	3/8"		
1/2	2"		
6.7 (cfm)	190 (l/min)		
8.58 (lbs)	3.89 (kgs)		
90.5			
4			
Twin Hammer			
Rear E	Rear Exhaust		
	3/ 1" 6,5 1,200 (Ft-lb) 1,500 (Ft-lb) 8-55/64" 3/ 1/ 6.7 (cfm) 8.58 (lbs) 90 4 Twin Hi		

CE

AIR IMPACT WRENCH SERIES



JAI-0924	1/2" DR. Composite Impact Wrench
UAI-VUZET	In Division Division and Divisi

TECHNICAL DATA		JAI-0924	
Square Drive		1/2"	
Max Torque	550 Ft-lb 746 N.M.		746 N.M.
Norking Torque		510 Ft-lb	681 N.M.
Free Speed	rpm	8,500	
	in	5/8	
Std Bolt Size	mm	16	
Lanath	in	7.52	
Length	mm	191	
	lbs	4.27	
Weight	kgs	1.94	
Min Hose	in	3/8	
Size	mm	10	
Ave.air Con-	cfm	4.7	
Sumption	l/mm	133	
Air Inlet Size		1/4"	
Noise Level (dBA)		98.5	
Vibration (M/S ²)		4.31	
Clutch Mechanism		Twin Ham	mer

The "Stubby" Impact Wrench, includes special design of "Jumbo Hammer Mechanism" and short length idea that reduce the tool's length and weight. Its tightness design can go through narrow area and high torque output function increases its excellent performance. Also the tool has light weight and short length much less 20% than traditional product.

Market Sales Application:

Ideal for tire change, mold and machine equipment assembly, and agriculture machinery.





JAI-0923	3/8" DR. Composite Impact Wrench

TECHNICAL DATA		JAI-0923	
Square Drive		3/8"	
Max Torque		280 Ft-Ib	380 N.M.
Norking Torque	•	250 Ft- I b	335 N.M.
ree Speed	rpm	11,0	00
	in	1/2	2
Std Bolt Size	mm	13	}
	in	6.5	6
Length	mm	166.5	
	lbs	2.6	
Weight	kgs	1.2	
Vin Hose	in	3/8	
Size	mm	10	
Ave.air Con-	cfm	2.5	5
Sumption	l/mm	7'	1
Air Inlet Size		1/4	1"
Noise Level (dBA)		92	.5
Vibration (M/S ²)		4.3	
Clutch Mechanism		Twin Ha	ammer



JAI-1

TE

Square Driv Std. Bolt Siz Free Speed Working Tor Max Torque Overall Ler Air Inlet Size Air Hose (I. Air Pressur Avg. Air Cor Net Weight Clutch Med Exhaust Di

Sound

Vibration



CE

Short length design can be worked for narrow area. Light weight design reduces operator burden. Soft material grip improves operating comfort to avoid long time usage tiredness.

014 1/2" St	ubby Impact Wre	ench	
CHNICAL DATA	JAI-1	1014	
ive	1/2	2"	
ize	5/8"	M16	
d (rpm)	10,0	000	
orque	420(Ft-lb)	560(N.M.)	
e	450(Ft-lb)	600(N.M.)	
ngth	4.27"	108.5 (mm)	
ze	1/4	4"	
.D.)	3/8"		
re	90 PSI		
nsumption	4.5 (cfm)	127 (l/min)	
t	2.87 (lbs)	1.3 (kgs)	
chanism	Jumbo H	lammer	
irection	Rear E	xhaust	
M/S ²	9.57		
K (M/S²)	1.44		
Pressure A (dB)	97.1		
Power A (dB)	108.1		
Pressure C (dB)	103		
K (dB)	3		

JONNESVIAY.

AIR IMPACT WRENCH

CE

AIR IMPACT WRENCH SERIES



1

JAI-6211 JAI-6211L	W/2" An	vil per Duty A	Air Impact Air Impact	
TECHNICAL DATA	JAI-	6211	JAI-6	211L
Square Drive	3/	/4"	3	/4"
Std Bolt Capacity	1"	M25	1"	M25
Free Speed (RPM)	65	00	6500	
Max. Torque	750 Ft-Lbs	1016 N.M.	750 Ft-Lbs	1016 N.M.
Overall Length	9-19/64"	236 MM	15-19/64"	388 MM
Air Inlet	1/4"		1/4"	
Air Hose (I.D.)	3/8"	9.5 MM	3/8"	9.5 MM
Air Pressure	90 PSI	6.3kg/cm ²	90 PSI	6.2 BAR
Air Consumption	7 CFM	198 L/MIN	7 CFM	198 L/MIN
Anvil Length	2	2" 6")"
Clutch Mechanism	Twin Hammer		Twin Hammer	
Weight	10.0 LBS	4.55 KGS	10.15 LBS	4.66 KGS
Exhaust	SIDE EXHAUST		SIDE EXHAUST	
Sound dBA	87		89	
Vibration	0.7 1.0			.0

JAI-1054

TECHNICAL DATA

Square Drive

Std Bolt Size

Free Speed (rpm)

Max. Torque (Ft-lb)

Overall Length

Air Hose (I.D)

Air Inlet Size (PT)

Net Weight (kgs)

Noise Level (dB)

Clutch Mechanism

Exhaust Direction

Vib. (M/S²)

Avg. Air Consumption (cfm)

Working Torque (Ft-lb)

1/2" SQ. DR. Heavy-Duty Impact Wrench

JAI-1054

1/2"

5/8" (M16)

7,000

580 (780 N.M.)

680 (920 N.M.)

8-1/16" (205 mm)

1/4"

3/8"

2.97 (6.6 lbs)

90

4.3

Twin Hammer

Rear Exhaust

4.2 (119 l/min)









CE

CE



		2" SQ. DR. Heavy-Duty Impact rench
TECHNICAL DATA		JAI-1044
Square Drive		1/2"
Std Bolt Size		5/8" (M16)
Free Speed (rpm)		8,000
Working Torque (Ft-lb)		480 (650 N.M.)
Max. Torque (Ft-lb)		580 (780 N.M.)
Overall Length		7-15/16" (202 mm)
Air Inlet Size (PT)		1/4"
Air Hose (I.D)		3/8"
Avg. Air Consumption (cfm)		4.2 (119 l/min)
Net Weight (kgs)		2.79 (6.1 lbs)
Noise Level (dB)		90
Vib. (M/S ²)		3.6
Clutch Mechanism		Twin Hammer
Exhaust Direction		Rear Exhaust





AI-1044K	1/2" SQ. DR. Heavy-Duty Impact Wrench Kit
CONTENTS	1 PC JAI-1044 1/2" DR. Impact Wrench
	10 PCS CR-MO Socket Set 9,10, 11, 13, 14, 17, 19, 22, 24, 27mm
	1 PC CR-MO 125mm Extension Bar
	1 PC 1/4" Mini Oiler
	1 PC T27 STAR HEX. KEY WRENCH
	1 PC 1/4" Air Nipple
	1 PC Oil Pot
	1 PC Blow Case

JAI-6202	1/2" Professional	Air Impact Wrench	
CHNICAL DATA	JAI- 6202		
uare Drive	1/	2"	
Bolt Capacity	5/8"	M16	
e Speed (RPM)	70	00	
x. Torque	380 Ft/Lbs	516 N.M.	
erall Length	7-1/2"	190 MM	
Inlet	1/4"		
Hose (I.D.)	3/8"	9.5 MM	
Pressure	90 PSI	6.2 BAR	
Consumption	4.2 CFM	119.9 L/MIN	
/il Length	STANDARD		
tch Mechanism	PIN CLUTCH		
ight	5.9 LBS	2.7 KGS	
naust	SIDE EXHAUST		

JAI-6202K	17Pcs 1/2" Air Impact Wrench Kit
ONTENTS	1 PC JAI-6202 1/2" Impact Wrench (Pin Clutch)
	10 PCS CR-MO Socket Set 9, 10, 11, 13, 14, 17, 19, 22, 24, 27 mm
	1 PC CR-MO 125 mm Extension Bar
	1 PC 1/4" Mini Oiler
	1 PC 4 mm Hex Key Wrench
	1 PC 1/4" Air Nipple
	1 PC Oil Pot
	1 PC Blow Case

JONNESWAY.

AIR IMPACT WRENCH

AIR IMPACT WRENCH SERIES



JAI-0501	1/2" Heavy Duty Air Impact Wrench
TECHNICAL DATA	JAI-0501
Square Drive	1/2" (12.7 mm)
Std Bolt Capacity	3/4" (18 mm)
Net Weight	5.8 lbs (2.66 kgs)
Length	7-1/4" (183 mm)
Avg. Air Cons.	4.6CFM (130 L/MIN)
Air Inlet	1/4"
Hose Size	3/8" (9.5 mm)
Air Pressure	90 PSI (6.3 kg/cm ²)
Max. Torque	450 Ft-Lbs (610N.M.)
Free Speed	7,000 r.p.m.
Exhaust	HANDLE EXHAUST
Clutch Mechanism	Twin Hammer

17Pcs 1/2" Air Impact Wrench Kit

1 PC JAI-0501 1/2" Impact Wrench Twin Hamer

1 PC CR-MO 125mm Extension Bar

1 PC 4mm Hex Key Wrench

1 PC 1/4" Mini Oiler

1 PC 1/4" Air Nipple

1 PC Oil Pot

1 PC Blow Case

10 PCS CR-MO Socket Set 9,10, 11, 13, 14, 17, 19, 22, 24, 27mm

JAI-0501K

CONTENTS

- Twin Hammer Mechanism provides more power and smooth impact blows.
- Steel hammer case provides maximum protection.
- Two-Piece construction for easy service and trouble-free operation.





JAI-0405	1/2" Heavy Duty Impact Wrench
TECHNICAL DATA	JAI-0405
Square Drive	1/2" (12.7 mm)
Std Bolt Capacity	3/4" (19 mm)
Net Weight	5.9 lbs (2.66 kgs)
Max. Torque	500 Ft-Lbs (680N.M.)
Avg. Air Cons.	4.5 CFM (127.4 L/min)
Air Inlet	1/4"
Hose Size	3/8" (10 mm)
Air Pressure	90 psi (6.2 kg/cm ²)
Free Speed	7,000 r.p.m.
Exhaust	FRONT EXHAUST
Clutch Mechanism	Twin Hammer

JAI-0405K	17Pcs 1/2" Heavy Duty Impact Wrench Kit			
CONTENTS	1 PC JAI-0405 1/2" Heavy Duty Impact Wrench			
	10 PCS CR-MO Socket Set 9,10, 11, 13, 14, 17, 19, 22, 24, 27mm			
	1 PC CR-MO 125mm Extension Bar			
	1 PC 1/4" Mini Oiler			
	1 PC 5mm Hex Key Wrench			
	1 PC 1/4" Air Nipple			
	1 PC Oil Pot			
	1 PC Blow Case			



AIR RATCHET, DRILL & SCREWDRIVER SERIES

CE

"SUPER DUTY AIR RATCHET WRENCH" the patent design of close type ratchet housing prolongs its endurance. The tool also has several useful functions including durable planetary gear unit, powerful motor unit, ergonomic trigger and housing design, 360° adjustable air inlet, comfortable soft material grip... etc.

Market Sales Application:

Ideal for industrial production line and maintenance market, such as machine equipment & vehicle... etc.





AIR RATCHET, DRILL & SCREWDRIVER SERIES

JONNESWAY	®
-----------	---

VAIL-0303A	1/2 neavy buty An Natchet Wrench					
JAR-6310A	3/8" Heavy	/ Duty Aiı	Ratchet	Wrench		
TECHNICAL DATA	JAR - 6	5309A	JAR - 6	6310A		
Square Drive	1.	/2"	3,	3/8"		
Std Bolt Capacity	3/8"	M10	3/8"	M10		
Free Speed (RPM)	1	70	1	70		
Max Torque	75 Ft/Lbs	75 Ft/Lbs 100 N.M.		100 N.M.		
Overall Length	10 - 3/4" 275 MM 10 -		10 -3/4"	275 MM		
Air Inlet	1.	/4"	1/4"			
Air Hose (I.D.)	3/8"	9.5 MM	3/8"	9.5 MM		
Air Pressure	90 PSI	6.2 BAR	90 PSI	6.2 BAR		
Air Consumption	4 CFM	113 L/MIN	4 CFM	113 L/MIN		
Weight	3.1 LBS	1.4 KGS	2.9 LBS	1.3 KGS		
Exhaust	REAR REAR					
Noise Level (dBA)		87				
Vibration (M/S ²)		5.58				

AR-6309A 1/2" Heavy Duty Air Ratchet Wrench

JAR-6309AK 1/2" Heavy Duty Air Ratchet Wrench Kit

CONTENTS

1 PC JAR-6309A Heavy Duty Air Ratchet Wrench	
7 PCS Socket Set 1/2" DR. 9, 10, 11, 13, 14, 17, 19 M	1M
1 PC 75MM Extension Bar	
1 PC 1/2" or 3/8"Square Universal Joint	
1 PC 1/2" or 3/8" Square Bits Holder	
3 PCS Screwdriver Bits	
1 PC Blow Case	

AR-6311-1	1/2" Heavy Duty Air Ratchet Wrench					
AR-6311	3/8" Heavy Duty Air Ratchet Wrench					
CHNICAL DATA		JAR	8-6311-1	JAR-6311		
uare Drive		1/2"		3/8"		
Bolt Capacity		7/16"	7/16" M11		M11	
e Speed (RPM)		650		6	50	
x Torque		76 Ft/Lbs 102 N.M.		76 Ft/Lbs	102 N.M.	
e ne II la nanthe		11.0"	200 1414	11 0"	200 1414	

ax Torque	76 Ft/Lbs	102 N.M.	76 Ft/Lbs	102 N.M.	
rerall Length	11.8"	300 MM	11.8"	300 MM	
Inlet	1/	/4"	1/4"		
Hose (I.D.)	3/8"	9.5 MM	3/8"	9.5 MM	
Pressure	90 PSI	6.2 BAR	90 PSI	8.2 BAR	
Consumption	3.2 CFM	90 L/MIN	3.2 CFM	90 L/MIN	
eight	3.52LBS	1.6 KGS	3.52LBS	1.6 KGS	
haust	RE	AR	RE	AR	

*** PIN CLUTCH-REACTIONLESS**

SCREWDRIVER SERIES

¢

AIR RATCHET, DR

CE		
	-	



JAR-6313 JAR-6312	3/8" Stubby Air Ratchet Wrench 1/4" Stubby Air Ratchet Wrench				
TECHNICAL DATA		JA R	- 6313	JA R-	6312
Square Drive		3/	/8"	1/	/4"
Std Bolt Capacity		3/8"	M10	3/8"	M10
Free Speed (RPM)		230 230		30	
Max Torque		25 Ft/Lbs 34 N.M. 25 Ft/Lbs 34 N		34 N.M.	
Overal Length		6-1/2"	6-1/2" 165 MM 6-1/2" 165 MM		165 MM
Air Inlet		1/4" 1/4"		/4"	
Air Hose (I.D.)		3/8"	9.5 MM	3/8"	9.5 MM
Air Pressure		90 PSI	6.2 BAR	90 PSI	6.2 BAR
Air Consumption		3 CFM	85 L/MIN	3 CFM	85 L/MIN
Weight		1.1 LBS	0.5 KGS	1.1 LBS	0.5 KGS
Exhaust		REAR REAR			
Noise Level (dBA)		90.6			
Vibration (M/S ²)		5.9			

CE

CE







JAD-1021	3/8" Air Angle Drill
TECHNICAL DATA	JAD-1021
Free Speed (RPM)	1900
Chuck Capacity (MM)	10 mm (3/8")
Air Inlet	1/4"
Air Pressure Bar	90 PSI
Air Consumption (CFM)	280 L/MIN
Net Weight	0.96 kg
Length x Height	190 x 110 mm
Exhaust System	REAR

JAD-6252A	3/8" Air Straight I	Drill
TECHNICAL DATA	JAD	-6252A
Free Speed (RPM)	25	500
Capacity of Chuck	3/8"	9.5 MM
Air Inlet	1/4"	
Hose Size (I.D.)	3/8"	9.5MM
Air Pressure	90 PSI	6.2 BAR
Air Consumption	4 CFM	113 L/MIN
Spindle Thread	3/8"- 24UNF	
Length	9"	228 MM
Weight	2 LBS	0.9 KGS

JAD-6233	3/8" A	ir Drill		
JAD-6234	3/8" Air Revers		ible Drill	
TECHNICAL DATA	JAD-	6233	JAD	6234
Free Speed (RPM)	2500		18	300
Capacity of Chuck	3/8"		3	/8"
Air Inlet	1/4"		1	/4"
Hose Size (I.D.)	3/8"		3	/8"
Air Pressure	90 PSI	6.2 BAR	90 PSI	6.2 BAR
Air Consumption	4 CFM	113 L/MIN	4 CFM	113 L/MIN
Spindle Thread	3/8"- 24UNF		3/8"-	24UNF
Length	6-1/2"	165 MM	6-1/2"	165 MM
Weight	2.5 LBS	1.1 KGS	2.5 LBS	1.1 KGS

CE





CE







JAD-1015 Air Spot Weld Drill W/Hook

TECHNICAL DATA	JAD-1015	
Free Speed (RPM)	18	800
Air Pressure	90 PSI	6.2 BAR
Air Consumption	10 CFM	283 L/MIN
Air Inlet	1/4"	
Drill Capacity (Dia.)	5/16"	8 MM
Hose Size (I.D.)	3/8"	9.5 MM
Length	10"	254 MM
Weight	4.6 LBS	2.1 KGS

JAD-1015K	9Pcs Air Spot Weld Drill W/Hook Kit
CONTENTS	1 PC JAD - 1015 Spot Weld Drill
	1 PC Mini Oiler
	1 PC Swivel Connector (1/4" x 1/4")
	4 PCS Extra 8MM & 6.5MM Drill Bit
	1 PC 2.5MM "L" Type Hex Key Wrench
	1 PC Blow Case

Air Spot Weld Dr	111
JAD	- 6246
1	800
90 PSI	6.2 BAR
10 CFM	283 L/MIN
	1/4"
5/16"	8 MM
3/8"	9.5 MM
10"	254 MM
3.74 LBS	1.7 KGS
	JAD 1 90 PSI 10 CFM 5/16" 3/8" 10"

JAD-6246K 10Pcs Air Spot Weld Drill Kit

ONTENTS	1 PC JAD-6246 Air Spot Weld Drill
	1 PC Mini Oiler
	1 PC Swivel Connector (1/4"X1/4")
	4 PCS Extra 8MM & 6.5MM Drill Bit
	1 PC Air Nipple
	1 PC 2.5MM "L" Type Hex Key Wrench
	1 PC Blow Case

AIR DIE GRINDER SERIES

CE

Tool-free adjustable torque control Ergonomic design handle Two step trigger control 360° adjustable air inlet Rear exhaust design Hanging ring design (Hanger design)



	Shut-Off Torque Control Screwdrivrer
JAB-2052	Shut-Off Torque Control Screwdrivrer

TECHNICAL DATA	JAB-2051	JAB-2052
Capacity (mm)	4	3.5
Free Speed (RPM)	1400	1400
Torque Range (N.m.)	1.4~2.6	0.9~1.6
Overall Length (mm)	195	195
Weight (kgs)	0.95	0.95
Air Inlet Size	1/4"	1/4"
Air Pressure (psi)	90	90
Noise Level (dB)	80	80
Air Consumption (CFM)	7	7

CE



JAB-7023 Pistol Reversible Adjustable Air Screwdriver		
TECHNICAL DATA JAB - 7023		7023
Hex Size of Bit	1/4"	6.35 MM
Capacity of Screw	N	15
Free Speed (RPM)	800	
Max Torque IN-LBS	45-145	
Overall Length	8-1/2" 216 MM	
Air Inlet	1/4"	
Air Hose (I.D.)	3/8"	
Air Pressure	90 PSI	6.2 BAR
Air Consumption	4 CFM	113 L/MIN
Clutch Mechanism	Internal Adjustable Clutch	
Weight	2.67 LBS 1.21 KGS	



AIR DIE GRINDER

JAG-0903RM

0.3 HP

6 MM

152 MM

6.2 BAR

113 L/MIN

0.35 KGS

25000

1/4"

3/8"

REAR

ſF







- •Lightweight, compact size is easy to handle.
- •Safety lever throttle.

AIR DIE GRINDER SERIES

- •Composite sleeve for comfortable TPR handle.
- •Rear Exhaust keeps air away from you and your working area.
- •Built-in the silencer and regulator.



- •Lightweight, compact size is easy to handle.
- •Safety lever throttle.
- •Composite sleeve for comfortable TPR handle.
- •Rear Exhaust keeps air away from you and your working area.
- •Built-in the silencer and regulator.

CONTENTS	1 PC JAG-0903 Mini Die Grinder
	5 PCS 1/4" (6mm) Shank Mounted Stone

JAG-0903R 1/4" Heavy Duty Mini Air Die Grinder

JAG-0903RM 6mm Heavy Duty Mini Air Die Grinder

JAG-0903R

0.21 KW

1/4"

6"

90 PSI

4 CFM

0.77 LBS

JAG-0903RK 1/4" Mini Air Die Grinder Kit

TECHNICAL DATA

Free Speed (RPM)

Overall Length Air Inlet

Air Hose (I.D.)

Air Consumption

Exhaust System

Air Pressure

Weight

Motor Collet Size

5 PCS 1/8" (3mm) Shank Mounted Stone
2 PCS Open Wrench
1 PC 1/8" (3mm) Reducer
1 PC Blow Case

JAG-0913F	1/4" Heavy Duty Mini	Angle Air Die Grinder
JAG-0913RM	6mm Heavy Duty Mir	ni Angle Air Die Grinder
TECHNICAL DATA	JAG-0913R	JAG-0913RM
Free Speed (RPM)	18	3000
Motor	0.21 KW	0.3 HP
Collet Size	1/4"	6 MM

Collet Size	1/4"	6 MM		
Overall Length	6.1"	155 MM		
Air Inlet	1.	/4"		
Air Hose (I.D.)	3	/8"		
Air Pressure	90 PSI	6.2 BAR		
Air Consumption	3 CFM	85 L/MIN		
Exhaust System	RE	AR		
Weight	1.08 LBS	0.49 KGS		





Heavy Duty

148

- Safety lever throttle
- Composite sleeve for comfortable TPR handle
- Keeps air away from you and your work area using a rear exhaust
- built-in the silencer and regulator

18	000	
	0.3 HP]
	6 MM]
	155 MM]
1	/4"	1 r c c
3	/8"	



- Lightweight, compact size is easy to handle
- Safety lever throttle
- Composite sleeve for comfortable TPR handle
- A built-in silencer and regulator

Exhaust System

Noise Level (dBA)

Vibration (M/S²)

Weight






JAG-0973R 7" Extension 1/4" Air Die Grinder JAG-0973RM 7" Extension 6mm Air Die Grinder

TECHNICAL DATA	JAG-0973R	JAG-0973RM
Free Speed (RPM)	20	000
Motor	0.21 KW	0.3 HP
Collet Size	1/4"	6 MM
Overall Length	11.13"	282 MM
Air Inlet	1,	/4"
Air Hose (I.D.)	3	/8"
Air Pressure	90 PSI	6.2 BAR
Air Consumption	4 CFM	113 L/MIN
Exhaust System	RE	AR
Weight	2 LBS	0.9 KGS





• Built-in the silencer and regulator. • Comfortable TPR handle.

Safety lever throttle.

JONNESWAY.

3/8"

90 PSI

4 CFM

FRONT

1.17 LBS

AG-0906R	1/4" Heavy Duty Medium Air Die Grinder			
AG-0906RM	6mm Heavy Duty Medium Air Die Grinder			
AG-0906F	1/4" Heav	vy Duty Me	dium Air Die Grinder	
CHNICAL DATA	JAG-0906R	JAG-0906RM	JAG-0906F	
e Speed (RPM)	22	000	22000	
tor	0.29 KW	0.4 HP	0.42 KW	
let Size	1/4"	6 MM	1/4"	
erall Length	6.8"	175 MM	5.7"	
Inlet	1.	/4"	1/4"	

3/8"

90 PSI 6.2 BAR

REAR

112 L/MIN

0.6 KGS

92.3

2.5

4 CFM

1.3 LBS

JAG-0906RMK 6mm Air Die Grinder Kit

ONTENTS	1 PC JAG-0906RM Medium Die Grinder
	5 PCS 1/4" (6mm) Shank Mounted Stone
	5 PCS 1/8" (3mm) Shank Mounted Stone
	2 PCS Open Wrench
	1 PC 1/8" (3mm) Reducer
	1 PC Blow Case

	AG-0976RM	7"	Extension	6mm	Air	Die	Grinder	
--	-----------	----	-----------	-----	-----	-----	---------	--

CHNICAL DATA	JAG-0976RM	
e Speed (RPM)	22000	
tor	0.6 HP	
let Size	6 MM	
erall Length	260 MM	
Inlet	1/4"	
Hose (I.D.)	3/8"	
Pressure	6.2 BAR	
Consumption	112 L/MIN	
naust System	REAR	
light	0.64 KGS	

AIR DIE GRINDER

CE

AIR DIE GRINDER SERIES



JAG-0806R	1/4" Heav	y Duty A	ir Die Gri	inder
JAG-0806RM	6mm Hea	vy Duty A	Air Die G	rinder
TECHNICAL DATA	JAG-	0806R	JAG-0	806RM
Free Speed (RPM)	40	00	40	00
Motor	0.42 KW	0.6 HP	0.42 KW	0.6 HP
Collet Size	1/	4"	6 N	MM
Overall Length	9"	220 MM	9"	220 MM
Air Inlet	1/	4"	1/4"	
Air Hose (I.D.)	3/	8"	3/	8"
Air Pressure	90 PSI	6.2 BAR	90 PSI	6.2 BAR
Air Consumption	10.6 CFM	300 l/min	10.6 CFM	300 l/min
Exhaust System	RE	AR	RE	AR
Weight	1.6 lbs	0.75 kgs	1.6 lbs	0.75 kgs

CE





JAG-6608	22000 RPM Micro Air Grinder
TECHNICAL DATA	JAG-6608
Free Speed (RPM)	22000
Capacity	30 MM PAD
Air Inlet	1/4"
Air Hose (I.D.)	5 MM
Work Air Pressure	90 PSI / 6.2 BAR
Avg. Air Consumption	0.1m³/min
Net Weight	0.203 kgs
Diamensions (MM)	16.5 x 136

TEC Ch Boru Pist Blov Ovee Air I Air I Air I Air I Vei

CE



JAG-0707	60000 RPM Micro Air Grinder
TECHNICAL DATA	JAG-0707
Free Speed (RPM)	60000
Capacity	Option: 3MM, 1/8", 3/32"
Air Inlet	1/4"
Air Hose (I.D.)	6.35 MM
Work Air Pressure	90 PSI / 6.2 BAR
Avg. Air Consumption	0.08m³/min
Net Weight	0.132 kgs
Diamensions (MM)	21 x 155



JONNESWAY

AG-6638 (" Professional Air Angle Grinder Lever Throttle)	
AG-6612	4 (l	" Professional Air Lever Throttle)	r Angle Grinder
CHNICAL DATA	۱.	JAG-6638	JAG-6612
e Speed RPM		11000	11000
posity Polt Sizo	IN	5"	4"
pacity Bolt Size	MM	125	100
oral Longth	IN	9	9
erall Length	MM	230	230
Inlet (PT)		1/4"	1/4"
Hose (ID)		3/8"	3/8"
ork Air Pressure	PSI	90	90
IK AII FIESSUIE	BAR	6.2	6.2
Air Concumption	CFM	6	6
g. Air Consumption	L/MIN	170	170
t Woight	LBS	4.0	4.0
t Weight	KGS	1.8	1.8
wer KW (HP)		0.7 (0.93)	0.7 (0.93)
indle Thread		5/8"-11UNC	3/8"-24UNC
g. Air Comp (HP)		2	2

JAH-6833H 250mm Air Hammer (Hex)

ECHNICAL DATA		JAH-6	5833H
Chisel Shank	Round	-	
	Hex	0.410"	
ore Diameter (I.D).)	3/4" 19 MM	
ston Stroke Length 3.5 " 90 MM		90 MM	
ow Per Min. (BPM)		2100	
verall Length		8.7 "	220 MM
r Inlet		1/	4"
r Hose (I.D.)	3/8"		8"
r Pressure		90 PSI	6.2 BAR
r Consumption		7.4 CFM	210 L/MIN
eight		4.4 LBS	2 KGS

AH-6833H	K 8 Pcs 250mm Air Hammer Kit (Hex)
CONTENTS	1 PC JAH- 6833H Air Hammer
	1 PC Spring retainer
	5 PCS 7" CR- MO Chisel
	JAZ - 3901(H) PanelCutter
	JAZ - 3904(H) Spot Weld Cutter
	JAZ - 3934(H) Tapered Punch
	JAZ - 3903(H) Flat Chisel
	JAZ - 3935(H) Single End Cutter
	1 PC BLOW CASE

CE



_	C	E



JAH-0288	Air Needle Scaler		
TECHNICAL DATA	JAH - 0288		
No. of Needle	12 PCS		
Blow Per Min. (BPM)	5,000	5,000	
Overall Length	11.4" 290 MM		
Air Inlet	1/4"		
Air Pressure	90 PSI		
Air Consumption	49 L/MIN		
Piston Size	18 X 14 MM		
Weight	1.3 KGS		
Needle Diameter (MM)	3 X 125		
Piston Stroke	32MM		

JAH-6836	Air Needle Scaler
TECHNICAL DATA	JAH-6836
Blow Per Min. (BPM)	4600
Needle Diameter (mm)	3 X 180
Numbers of Needles	19 pcs
Air Inlet	1/4"
Air Pressure (BAR)	6.2
Air Consumption (L/MIN)	232
Weight (kg)	2.8
Overall Length (mm)	460
Piston	25.4 x 43.5
Sound Pressure Level	92.26 dBA
Sound Power Level	104.3 dBA
Vibration Level	10.2 M/Sec ²
Piston Stroke	38MM (1.5")

CE



TECHNICAL DATA	JAH-7105
Weight	2.7 kg
Length	10"
Air Consumption	3 CFM
Air Pressure	90 PSI
Air Inlet	1/4"
Blow Per Minute	3700
Piston (mm)	23.5 X 20 X 73
Numbers of Needles	(Φ 2 X 29pcs), Φ 3 X 19pcs
Sound Pressure Level	97.0 dBA
Sound Power Lever	103.8 dBA
Vibration Level	8.7 M/Sec ²

JAH-7105 Needle Scaler

CE

JAH-7102C	Mini Air Chipping	Hammer (Round)	
TECHNICAL DATA	JAH-7102C		
Piston Diameter	25/32"	20 mm	
Piston Stroke	1-49/64"	45 mm	
Blow Per Min (BPM)	30	3000	
Overall Length	9-9/16"	243 mm	
Air Inlet	1/4"		
Air Hose (I.D.)	3/8"		
Air Pressure	90 PSI	6.2 BAR	
Air Consumption	6 CFM	170 L/MIN	
Sug. Air Comp (HP)	1.5	1.5 HP	
Chisel Shank	ROUNE	ROUND 14 mm	
Weight	5.7 LBS	2.6 KGS	

Standard Type of Retainer



AIR DIE GRINDER SERIES

PROFESSIONAL AIR SANDER SERIES

AIR SANDER

AIR SANDER



JAS-1207-6	HE 6" Composite Mini Random Orbital Sanders
TECHNICAL DATA	JAS-1207-6HE
Vac. system	Self-Gen Vac.
Free Speed PRM	12,000
Orbit Dia	3/16in.
Motor	0.28hp 209w
Pad Dim	6in. 152mm
Air Flow	17CFM (481L /MIN)
Product Net Wt.	1.94Lbs 0.88kg
Height	3.3in. 83mm
Length	9.1in. 232mm
Face Pad	HOOK



AIR SANDER



JAS-1208-5HE	5" Air Polishing Sander
TECHNICAL DATA	JAS-1208-5HE
Pad Dia.	5"
Air Inlet	1/4"
Air Hose(I.D.)	3/8"
Air Pressure(psi)	90
Pad Face	НООК
Free Speed (rpm)	2,400
Air Consumption. cfm(l/min)	6(170)
Weight (kg)	0.8

CE













JAS-6534-6HE	6" Self Generated Vacuum Random Orbital Air Sander
TECHNICAL DATA	JAS-6534-6HE
Pad Size	6"(150 MM)
Free Speed (RPM)	10000
Orbit Dia.	5 MM (3/16")
Air Inlet	1/4"
Air Hose (I.D.)	3/8"
Air Pressure	90 PSI / 6.2 BAR
Air Consumption	0.3 m ³ / min / 11.9 CFM
Weight	1.02 KG
Face Pad	HOOK
 Four Bearing Special Design Well Balance Anti-Dust Optional Orbital Dia : 2.5MM 	 Comfortable Grip Durable Powerful Vacuum Suction System

JONNESWA	Y ®
----------	------------

JAS-6697-5HE JAS-6697-6HE	Air Sander	6" Central-Vacuum Random Orbital		
TECHNICAL DATA	JAS- 6697- 5HE	JAS- 6697- 6HE		
Pad Size	5"	6"		
Free Speed (RPM)	9000	9000		
Orbit Dia.	5 MM	5 MM		
Air Inlet	1/4"	1/4"		
Air Hose (I.D.)	3/8"	3/8"		
Air Pressure	5 - 7 KG/CM ²	5 - 7 KG/CM ²		
Air Consumption	13.4 CFM	13.4 CFM		
Weight	2.4 LBS	2.4 LBS		
Face Pad	HOOK	НООК		

JAS-6698-5HE JAS-6698-6HE	5" Self Generated Vacuum Random Orbital Air Sander 6" Self Generated Vacuum Random Orbital Air Sander		
TECHNICAL DATA	JAS- 6698- 5HE	JAS- 6698- 6HE	
Pad Size	5"	6"	
Free Speed (RPM)	9000	9000	
Orbit Dia.	5 MM	5 MM	
Air Inlet	1/4"	1/4"	
Air Pressure	5 - 7 KG/CM ²	5 - 7 KG/CM ²	
Air Consumption	380 L/MIN	380 L/MIN	
Weight	1.04 KGS	1.05 KGS	
Face Pad	HOOK	HOOK	

AS-1033-6HE	6" Dust Free Type Orbital Air Sander
CHNICAL DATA	JAS-1033-6HE
Size	6"(150 MM)
Speed (RPM)	10000
t Dia.	7
nlet	1/4"
lose (I.D.)	3/8"
Pressure	90 PSI
Consumption	0.4 m³/min
dle Thread	5/16-24 UNF
e Pad	HOOK

JONNESWAY.

AIR SANDER

CE

The New Advance Air Belt Sanders and Cut-Off Tool have the same housing which provides unique functions to increase performance highly. . The soft material grip on the housing improves operating comfort and reduces tiredness for long time usage. Also the special design of user friendly enhance the work efficiency.

Market Sales Application:

The special design of stopper can be easily

and quickly to change the grinding belt.

The new ideal design for finishing metal surface like metal cart products, stone & wood products, plastic products, glass and earthenware...etc. And the Cut-Off tool is for cutting plate.

> The powerful motor unit has precision components increase working efficiency

> > Soft material pad improves operating comfort when the hand press on the finger plate.


Safety cover avoids operating accident and protects the bearing pollution from dust.

> The soft material grip on the housing improves operating comfort for long time usage.

Adjustable air valve controls the input of air for different application and operating selection



JAS-0452	2 AIR BELT SANDER(20X520mm) W/2 pcs Belts(#80,#100)		
TECHNICAL DATA	JAS-0452		
Free Speed	16,00	00 rpm	
Size of Belt	20 x 520 mm		
Air Consumption	4 CFM		
Horsepower	0.5 HP		
Overall Length	430 mm		
Net Weight	1.4 kg		
Air Inlet Size	1/4"		
Air Hose (I.D)	3/8"	10mm	
Air Pressure	90PSI	6.2BAR	
Vibration (M/S ²)	2.8		
Noise Level (dBA)	95		







CE





JAS-6542	Air Belt Sander (20 X 520mm)	
TECHNICAL DATA	JAS-	6542	
Cardina Danas	7/8" >	: 20"	
Sanding Paper	20 x 52	20 MM	
Free Speed (RPM)	160	000	
Overall Length	14-1/5"		
	360 MM		
Air Inlet	1/4"		
Air Hose (I.D.)	3/8"		
Air Pressure	90 PSI	6.2 BAR	
Air Consumption	9 CFM	254 L/MIN	
Weight	2.6 LBS	1.2 KGS	
Noise Level (dBA)	79.5		
Vibration (M/S ²)	4.5		

JAS-6552	7" Air Vertical Pol	isher
TECHNICAL DATA	JAS-	6552
Disc Size	7"	178 MM
Spindle Size	5/8" - 1	11UNC
Free Speed (RPM)	25	500
Overall Length	7-1/2"	190 MM
Air Inlet	1/	4"
Air Hose (I.D.)	3/	8"
Air Consumption	6 CFM	170 L/MIN
Air Pressure	90 PSI	6.2 BAR
Suggested Air Compresso	- 2	HP
Weight	6.1 LBS	2.8 KGS

AS-1009	6	" Dual Action Air	r Sander (Vinvl)
			· · · · · · · · · · · · · · · · · · ·
CHNICAL DATA		JAS-	1009
d Size		6	5"
e Speed (RPM)		10000	
Inlet		1,	/4"
Hose (I.D.)		3/8"	
Pressure		90 PSI	6.2 BAR
Consumption		5 CFM	140 L/MIN
ndle Thread		5/16" - 24 UNF	
ight		4.8 LBS	2.2 KGS
e Pad		V	inyl

JAS-6660	2	" Diamoi	nd Air Sa	nder	
AS-6660-3	3	" Diamoi	nd Air Sa	nder	
CHNICAL DATA		JAS-6660		JAS-6	660-3
d Size		2" 50 MM		3"	75 MM

d Size	2"	50 MM	3"	75 MM
e Speed (RPM)	10000		10000	
oit Dia.	3 MM		3 MM	
Inlet	1/4"		1/4"	
Hose (I.D.)	3/8"		3	/8"
Pressure	90 PSI	6.2 BAR	90 PSI	6.2 BAR
Consumption	11.6 CFM	330 L/MIN	11.6 CFM	330 L/MIN
ight	1.54 LBS	0.7 KGS	1.54 LBS	0.7 KGS

AIR SAW

CE



JAT-1010	Low Vibration Mechanism Air Saw
TECHNICAL DATA	JAT-1010
Blow Per Minute (BPM)	10,000
Stroke Length (MM)	10
Avg. Air Consumption	6 CFM
Net Weight	0.72 Kgs
Air Inlet	1/4" NPT (PT)
Air Hose Size	O.D. 3/8"
Vibration	9.0 m/s ²
Sound Pressure	85 dBA

CE

AIR SAW



JAT-1010K Low Vibration Mechanism Air Saw Kit

CONTENTS :

• 1PC-JAT-1010 LOW VIBRATION MECHANISM
AIR SAW

- 5PCS-18 TEETH SAW BLADES
- 5PCS-24 TEETH SAW BLADES
- 5PCS-32 TEETH SAW BLADES

FEATURES :

- Designed with following patents to assure Extreme Low Vibration and operator comfort
- Portable Pneumatic Tool assembled with module units
- Suspension Vibration-Reducing means for portable pneumatic tools
- Patented quick change Blade Holder makes changing saw blades / files easily
- Lock off Throttle to prevent accidental start ups
- Adjustable Guard/Guide allows operators to set depth of cut
- Rear exhaust directs air away from work-piece

CE	0 317 29% 8 FUX
	 341 209 Balling

APP B FLES

JAT-10T18	5 Pcs 18 Teeth Saw Blades
JAT-10T24	5 Pcs 24 Teeth Saw Blades
JAT-10T32	5 Pcs 32 Teeth Saw Blades







CE









AT-6946	Air Body Saw(Rear Exhaust)
---------	----------------------------

TECHNICAL DATA	JAT-6946
Blow Per Minute (BPM)	5000
Stroke Length	10 MM
Capacity Cutting Size	Steel 1.2 MM
Air Inlet	1/4"
Air Pressure	6.2 BAR
Air Consumption	230 L/MIN
Overall Length	250 MM
Weight	1.1 KGS

JAT-6676	A	ir Body Saw (Re	ar Exhaust)
TECHNICAL DATA		JAT-	6676
Blow Per Minute (BPM)		9000 -	- 10000
Air Consumption		8.2 CFM	230 L/MIN
Air Inlet		1/	4"
Air Pressure		90 PSI	6.2 BAR
Size of Belt		10 X 3	30 MM
Stroke Length		10	MM
Cutting Capacity		STEEL 1.6MM	I THICKNESS
Overall Length		235	MM
Blade Shaft		1.2 -1	.6 MM
Weight		2.2 LBS	1.0 KGS
Exhaust		RE	AR

JAT-6679	Low Speed Air Tire Buffer (Rear Exhaust)
TECHNICAL DATA	JAT-6679
Free Speed (RPM)	2500
Power	0.42 KW
Size of Q.C.	HEX 11.11 MM
Air Inlet	1/4"
Air Pressure	6.2 BAR
Air Consumption	350 L/MIN
Overall Length	228.6 MM
Exhaust System	REAR
Weight	0.91 KG

1/4" (6.4MM) Heavy Duty Air Hydraulic Riveter <u>JAT-667</u>3B

CHNICAL DATA	JAT-6673B
d Rivet Setting Capacity	3/32" TO 1/4" (2.4 TO 6.4 MM)
ction Power kg⋅F(Lb⋅F)	1700 (3740)
oke Length mm (inch)	18 (0.708")
Inlet PT (NPT)	1/4"
Hose (I.D.)	3/8"
Pressure	90 PSI (6.2 BAR)
Consumption	2.9 L / Cycle
se Piece	2.4 (3/32"), 3.2 (1/8"), 4.0 (5/32"), 4.8 (3/16"), 6.0 , 6.4 (1/4")
Ith x Height (mm)	170 X 298
ight KGS (LbS)	1.75 (3.9)

Max. Blind Rivet Seeting Capacity (Head/Mandrel) : 6.4mm (Stainless-Stainless) Only For JAT-6673B

JONNESWAY.

AIR BLOW GUN







JAT-6004K		6Pcs Air Grease Gun(400 CC)	
CONTENTS 1 G		un Body JAT - 6004	
	2. Hexagonal Spout		
		. Quick Coupler	
		ose Fitting	
5. 9		" Nylon Hose	

6. Hand Operation Gun Handle Set

JAT-460	Lever Type Hand Grease Gun
TECHNICAL DATA	JAT-460
Capacity Bulk	400 CC.
Capacity Cartridge	14 OZ
Finish	Container Tube: Chrome Plated
Size (mm x mmL)	56.4 x 350
Pressure Tested	Working Pressure: 310 Bar (4500 PSI)
Weight	1.02 Kgs

JAZ-6704	3/8" PT Air Filter, Regulator & Lubricator
TECHNICAL DATA	JAZ-6704
Port Size	3/8" PT
Applied Flure	Air of Pressure
Max. Pressure	10 kgf / cm ² (1400 kpa)
Range of Pressure	1.0 - 9.8 kgf / cm ²
Filteration	5 - 50 micron
Min. Dropped Flow	1250 L/MIN
Ambient Temperature	5°- 50°C
Discharge Method	Broken pressure auto discharge or hand discharge
Lubricating Method	Spraying from 30 L/MIN
Storage	120 C.C.
Usable Oil	VG- 32 or OM-300A
Weight	2.1 kgs






Technical Data		Flow rate L/min (ANR)	Pressure Range Kgf/cm²(Kpa)	Filter Grade
JAZ-0514	1/2"	3000	0.5-8.5 (50-850)	5µLm

F.R. Piggyback Unit

Technical Data	Port Size RC (PT)	Flow rate L/min (ANR)	Gauge Connection RC(PT)	Filter Grade
JAZ-0534	1/2"	3000	1/4"	5µLm











JAT-6905A





JAT-6905B

JAT-6905D

AIR GREASE GUN / AIR CONTROL UNIT





JONNESWAY.

4" LONG NOSE ANGLE NOZZLE AIR BLOW JAT-6959 GUN (100MM) 11" LONG NOSE ANGLE NOZZLE AIR BLOW GUN (280MM) **JAT-6959A**

 Body Material: Nylon Fiber Nozzle Material: Steel • Working Pressure: 75~120PSI / 5.0~8.0KGS Max Perssure: 160PSI Sound Pressure: 85-90dBA • Thread Type: 1/4" NPT Female 1/4" PS Female • Temperature Range: -40° TO 140° F

JAT-6905S

AIR BLOW GUN W/ 6 PCS NOZZLES

• Ergonomic handle design for comfortable operation.

• Composite material housing for light weight.

• Durable construction increases long lifetime.

• Two smart hangers provide better tool storage and more convenient to use. • 6 pcs of smart nozzle include several functions.

1PC-HOUSING

1PC-BIG AIR FLOW NOZZLE

1PC-1" NOZZLE

1PC-TRIANGLE NOZZLE

1PC-1/2" RUBBER NOZZLE

1PC-3" SAFE NOZZLE

1PC-4" NOZZLE

ITEM NO.	
JAT-6905A	AIR BLOW GUN W/ BIG AIR FLOW NOZZLE
JAT-6905B	AIR BLOW GUN W/1" NOZZLE
JAT-6905C	AIR BLOW GUN W/ TRIANGLE NOZZLE
JAT-6905D	AIR BLOW GUN W/1/2" RUBBER NOZZLE
JAT-6905E	AIR BLOW GUN W/3" SAFE NOZZLE
JAT-6905F	AIR BLOW GUN W/4" NOZZLE





JAT-6905C







JAT-6905F

PU ETHER - Hydrolysis Resistant Hose

- Excellent flexibility in cold weather softer than Ester in winter
- Resistant to attacks from moisture
- To Extend Service Life of Hose Reel 3 times longer than Ester
- Excellent weather resistance



JAZ-29510 Spring Driven Hose Reel (9.5MM X 10M)

TECHNICAL DATA	JAZ-29510
Air Hose (I.D.)	9.5 MM (3/8")
Max. Working Pressure At 23°C (75°F)	15 BAR
Bursting Pressure At 23°C (75°F)	60 BAR
Hose Length (inlet)	50 CM
Hose Length (outlet)	10 M
Hose Type	PU BRAID
Fitting Thread Size (inlet + outlet)	3/8 + 3/8
Weight (N.W.)	9.5 KGS



JAZ-0001A	Auto Air - Hose Winder 9.5 x 13.5MM x 12M (3/8" x 40Ft)
	Auto Air - Hose Winder 8 x 12MM x 15M (5/16" x 50Ft)





JAZ-0005A Auto - Winding Work Lamp 33 Ft (10M)

Material:Steel ,Chrome plated (European Type , USA Type , Japanese Type ,etc . available

ONE TOUCH QUICK COUPLER				ONE TOUCH QUICK COUPLER		
	TECHNICAL DATA	THREAD SIZE			TECHNICAL DATA	THREAD SIZE
	SM-20A	PT 1/4", MALE		FO	SF-20A	PT 1/4 _" , FEMALE
	SM-30A	PT 3/8", MALE			SF-30A	PT 3/8", FEMALE

ONE TOUCH QUICK COUPLER

	TECHNICAL DATA	THREAD SIZE	
	SH-20A	5/16", HOSE BARB	
	SH-30A	3/8", HOSE BARB	

QUICK COUPLER		QUICK COUPLER			
	TECHNICAL DATA	INSIDE DIA OF HOSE		TECHNICAL DATA	INSIDE DIA OF HOSE
	SM-20	PT 1/4", MALE		SF-20	PT 1/4", FEMALE
	SM-30	PT 3/8",MALE		SF-30	PT 3/8", FEMALE
	SM-40	PT 1/2", MALE	-	SF-40	PT 1/2", FEMALE
QUICK COUPLER					

	TECHNICAL DATA	INSIDE DIA OF HOSE
	SH-20	5/16", HOSE BARB
	SH-30	3/8", HOSE BARB
	SH-40	1/2", HOSE BARB

PLUG			PLUG		
	TECHNICAL DATA	THREAD SIZE		TECHNICAL DATA	THREAD SIZE
	PM-20	PT 1/4", MALE		PF-20	PT 1/4", FEMALE
and the second second	PM-30	PT 3/8", MALE		PF-30	PT 3/8", FEMALE
	PM-40	PT 1/2", MALE		PF-40	PT 1/2", FEMALE
PLUG					

	TECHNICAL DATA	THREAD SIZE
	PH-20	5/16", HOSE BARB
	PH-30	3/8", HOSE BARB
	PH-40	1/2", HOSE BARB



SPRAY GUN SERIES



JAZ-3811B Spring Balancer (0.6 - 1.5Kg)								
TECHNICAL DATA	Capacity (kg)	Weight (kg)		Rope Option	Rope Dia. (mm)	A (mm)	B (mm)	
JAZ-3811B	0.6-1.5	0.52	1.6	Nylon/Cable	2.5	240	44	

TECHNICAL DATA	DESCRIPTION	APPLIED TOOLS	TECHNICAL DATA	DESCRIPTION	APPLIED TOOLS
JAZ-3714	QUICK CHANGE TYPE RETAINER	JAH-6832, JAH-6832H JAH-6833, JAH-6833H	JAZ-3713	ZIP CHANGE TYPE RETAINER	JAH-6832, JAH-6832H JAH-6833, JAH-6833H







Pad For JAS-6697, JAS-6689, JAS-6698



PU Sanding Pad (Thickness : 10mm, Hook Face) JAZ-0034D 6"x6 HOLE • JAZ-0034B 5"x6 HOLE





TECHNICAL DATA	DESCRIPTION	APPLIED TOOLS	PART NO.
JAZ-3945H	5PCS LONG CHISEL (HEX) SHANK : 0.39" L : 175MM	JAH-6832H JAH-6833H	A.JAZ- 3934 TAPERED PUNCH B.JAZ- 3903 FLAT CHISEL C.JAZ- 3904 SPOT WELD CUTTER D.JAZ- 3935 SINGLE END CUTTER E.JAZ- 3901 PANEL CUTTER







SPRAY GUN SERIES



JA-HVLP-40 P	PROFESSIONAL H.V.L.P SPRAY GUN							
	PROFESSIONAL H.V.L.P SPRAY GUN (WATER BASE)							
TECHNICAL DATA JA-HVLP-40 JA-HVLP-40W								
Air Pressure Inlet	Bar	2	2					
All Flessule Illiet	Psi	29	29					
Air Cap Pressure	Psi	<10	<10					
Air Inlet		1/4"	1/4"					
Fluid Inlet		M16x1.5P	M16x1.5P					
	Cfm	10	10					
Air Consumption	L/min	283	283					
	Lbs	1.0	1.0					
Weight Gun Only	Kgs	0.46	0.48					
Capacity Of Cup Liter		0.6NC	0.6NC/WB					
Standard Fluid Tip Size	mm	1.4	1.4					
Optional Nozzle Size mm		1.0, 1.2, 1.3, 1.5, 1.7, 1.9, 2.2	1.0, 1.2, 1.3, 1.5, 1.7, 1.9, 2.2					







JA-6111		Deluxe Professional Gravity Feed Spray Gun			
SPECIFICATIO	NS:				
TECHNICAL	ATA	JA-6111			
Alla David and	BAR	3.5-5			
Air Pressure	PSI	50-70			
Air Inlet		1/4"			
Fluid Inlet		M16 X 1.5P			
Air Consumption	CFM	14			
Air Consumption	L/MIN	396			
Weight	LBS	1.54			
Weight	KGS	0.7			
Capacity of Cup		0.6L			
Type of Cup		NYLON			
Standard Fluid Tip S	Size (MM)	1.4			
Length x Height (MM	Л)	170 X 325			
Feed Type		GRAVITY			

Optional Nozzle Size : 1.0, 1.2, 1.3, 1.5, 1.7, 2.0, 2.3, 2.5, 3.0mm
 Incl : Fluid Nozzle + Needle + Air Cap

Standard Nozzle : Steel

Optional Nozzle : Stainless Steel
Optional Cup : 0.6L, 1.0L Aluminum Cup




JA-6111K	Deluxe Professional Gravity Feed Spray Gun Kit
• 1PC - JA-6111 Prof	
 1PC - 600 C. C. Nyl 1PC - 250 C. C. Nyl 2PCS - Needle 	
• 2PCS - Air Nozzle Cap	
2PCS - 1.7MM & 2.0MM Fluid Nozzle	

1PC - Adapter
3PCS - Stainless Strainer
1SET - Tune Up Kit
1SET - Spanner & Brush Kit









166

SPECIFICATIONS:

CHNICAL DATA		AS-0001D
Pressure	BAR	3
ressure	PSI	43
nlet		1/4"
d Inlet		3/8"
	CFM	13.9
Consumption	L/MIN	390
ght	LBS	2.2
	KGS	1.0
acity of Cup		1L
e of Cup		ALUMINUM
ndard Fluid Tip Size (MM)		1.7
gth x Height (MM)		175 X 295
d Type		SUCTION

JONNESWAY.

Optional Nozzle Size : 1.0, 1.4, 1.5, 2.0, 2.3mm
 Incl : Fluid Nozzle + Needle + Air Cap
 Nozzle Needle : Stainless Steel

AS-0001A H.V.L.P Spray Gun

SPECIFICATIONS:

TECHNICAL DATA		AS-0001A		
Air Pressure	BAR	3		
Air Pressure	PSI	43		
Air Inlet		1/4"		
Fluid Inlet		3/8"		
	CFM	14		
Air Consumption	L/MIN	396		
Weight	LBS	2.2		
weight	KGS	1.0		
Capacity of Cup		1L		
Type of Cup		ALUMINUM		
Standard Fluid Tip Size (MM)		1.7		
Length x Height (MM	1)	175 X 295		
Feed Type		SUCTION		

Optional Nozzle Size : 1.0, 1.2, 1.4, 2.0, 2.3, 2.5mm
 Incl : Fluid Nozzle + Needle + Air Cap
 Nozzle Needle : Stainless Steel

JA-507S

Professional Spray Gun

SPECIFICATIONS:

CHNICAL DATA		JA-507S
	BAR	3-6
Pressure	PSI	43-90
nlet		1/4"
Consumation	CFM	12-15
Consumption	L/MIN	337-421
d Inlet		3/8"
	LBS	2.3
ght	KGS	0.8
acity of Cup		1L
e of Cup		ALUMINUM
ndard Fluid Tip Size (MM)		1.6
d Type		SUCTION

• Optional Nozzle Size : 1.0, 1.5, 1.8, 2.0, 2.5mm



JA-506G Prof		ofessional Spray Gun
TECHNICAL DATA		JA-506G
	BAR	3.5-5
Air Pressure	PSI	50-70
Air Inlet		1/4"
Fluid Inlet		1/4'
1: 0 II	CFM	12-15
Air Consumption	L/MIN	337-421
Capacity of Cup		0.4L
Type of Cup		STAINLESS STEEL
Standard Fluid Tip Size		1.4MM
\A/_:	LBS	2.3
Weight	KGS	0.8
Feed Type		GRAVITY

• Optional Nozzle Sizes : 1.1, 1.8, 2.0mm

		fessional Spray Gun ction Type)		
TECHNICAL I	DATA	JA-23S		
Air December 1	BAR	3.9 - 4.9		
Air Pressure	PSI	56 - 71		
Air Inlet		1/4"		
Fluid Inlet		1/4"		
1: 0 r	CFM	14		
Air Consumption	L/MIN	396		
M/sisht	LBS	0.66		
Weight	KGS	0.3		
Capacity of Cup		0.6 L		
Standard Fluid Tip Size (MM)		1.4		

• Optional Nozzle Size : 0.8, 1.1, 1.3, 1.5, 1.8, 2.0mm





JAZ-0042



AUTOMOTIVE TOOLS


- Body and Interior Tools
- Brake Service Tools
- Engine Tools
- General Repair Tools
- Tools for Axle Repairs Silent Blocks & Bushes
- Clutch Repair Tools & Transmission Tools
- Tools for Steering System & Springs and Shock Absorbers




- 20005th

FASTEN








AE020002A AIR / HYDRAULIC PUMPS

ITEM NO.	AE020002A
RATED PRESSURE	10,000 psi
USABLE OIL CAPACITY	50 Cu. In.
OUTPUT FLOW RATE	Unload Load
(Cu. In. / Per Min.)	42.7 6.7
AIR PRESSURE RANGE	70 ~ 170 psi
AIR CONSUMPTION	9 CFM
WEIGHT	6.0 kgs

Features:

- Air-power hydraulic pumps are designed for using with single-acting cylinders and tools, like Jackram's ram series.
- Rugged construction and most components are made of Aluminum.
- Alloy are built for long service life, easy operation and portability. • Automatic overload relief valve setting at 10,000 psi protects components in
- hydraulic system and work safety regardless of air pressure. • New inlet & outlet design features low exhaust air volume, no-noise effect and can be operated in all directions.
- Oil capacity can be modified according to your specific application.











AE030002		2 ти	TWO-SPEED HAND PUMPS							
ITEM NO.	PRESSURE RATING (bar) 1st/2nd STAGE	USABLE OIL CAPACITY (c.c.)	OIL VOLUME PER STROKE(c.c.) 1st/2nd STAGE	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	OIL PORT THREAD (F)	WEIGł (kgs)
AE030002	13.8 / 700	350	13.0 / 2.8	343	310	66	146	142	3/8 NPT	5.9

- JONNESWAY heavy duty hand pumps are featured with their forged construction.
- Dropping forged base and rugged welded construction prevents collision and deformation efficiently.
- Professional choice for a wide range of industrial applications.
- Both single and two-speed models are available.
- Internal overload valve prevents pump from being used beyond its rated capacity. • Two-speed pumps provide fast pumping to meet the loading with the cylinder
- unloaded. · External adjustable relief valve with anti-losing mechanism design.
- Carrying handles for easy portability.



F080004	TELESCOPIC TRANSMISSION JACKS		
	CAPACITY : 800 kgs		

- For use with transmissions and transaxles of passenger cars and light trucks. · Foot-operated pump for maximum lift with minimum effort and fast contact
- with load.
- Fully adjustable universal saddle with adjustable corner brackets and safety chain for optimum alignment of transmission bolt patterns.
- · Safety overload system protects jack from being used beyond its rated capacity. • N.W. 68kgs G.W. 71kgs CUFT 3.4'





AUTOMOTIVE TOOLS

JONNESVIAY.

AE170006

UNIVERSAL TRANSVERSE ENGINE SUPPORTS

- Special new design for 4 fixing point to be a bridge to support the engine. • Especially using one the car that without inner fender.
- Adjustable in height and width to bridge various vehicle fender walls and securely hold engine in place.
- With rubber in the 4 fixing point to prevent slip or damage the vehicle.
- AE170006 equiped with two feet to use on the car with inner fender.
- N.W. 38 kg G.W. 40 kg CUFT. 2.5, 2 pcs / carton

80L WASTE OIL DRAINER (MANUAL AE300165 VALVE)

ITEM NO.	AE300165
DIMENSION	470 x 560 x 1140~1580 m/m
CAPACITY	80 L
WEIGHT	36 kgs
POWER	Compressed Aiv 100-120 psi
OIL DRAINING	Air Pressure

• Waste oil mobile reservoirs to be used for motor and gear oil collection. • Drainers can be set under vehicle lifts or inside lubrication pit.

• Large handle for easy maneuverability.

• Two brake wheels (ϕ 3") and two casters (ϕ 3")

• Extra large drain bowl / Adjustable collecting bowl / For the convenient and safe collection.

AE300051

PRESSURE BRAKE BLEEDER

M NO.	AE300051
ENSION	350 x 275 x 450 m/m
ACITY	5 L
GHT	9.6 kgs

Air operated pressure brake bleeder.

• Suitable for clutch bleed as well as brake bleed.

• 5 Litre capacity tank.

Complete with AE300051 master cylinder adaptor kit.

AE300064

17 PC RADIATOR PRESSURE TESTER

· Including: adaptors, hand pump, airline regulator assembly, and instruction manual

Different adaptors can be applied to most of car brands, such as AUDI, BMW, CITROEN, FIAT, FORD, VAUXHALL, OPEL, PEUGEOT, VOLVO,


and VOLKSWAGEN

• With 3 pcs of universal adaptors, which can be apply to any vehicles with the same size radiator cap

• For quick detection of radiator or hose system leakage

• Special designed storage case shows storage place for each adaptor, and provide easy accessory management





- Detecting leak of car radiator or tube system precisely, rapidly.
- Offer professional service quality, and easy operation. Conform every kind of car radiator's opening diameter & high quality of full-set
- accessories

COOLING SYSTEM & RADIATOR CAP

Applications

Truck

GM 4 cylinder (BUICK, CHEVROLET,

OLDSMOBILE, PONTIAC, CADILLAC)

MERCEDES-BENZ, FORD, CHRYSLER,

ACURA, DODGE, EAGLE, GEO, HONDA, ISUZU, LEXUS, MAZDA, MITSUBISHI, SUZUKI, TOYOT INFINITI, NISSAN, GM (NOVA, SPECTRUM, SPRINT), PEUGEOT, FORD, CHRYSLER. TOYOTA, HONDA, MITSUBISHI, SUZUKI,

LEXUS, CHRYSLER, ACURA, DODGE, GEO.

GM, JEEP, TRUCK, PEUGEOT.

Testing the pressure cap

Testing the pressure cap

with pressure Gauge

PRESSURE TESTER

• The main body is Aluminum Alloy material.

AE300161

System Testing Adapter NO.1

System Testing Adapter NO.2

System Testing Adapter NO.3

System Testing Adapter NO.4

System Testing Adapter NO.5


"2.3" Cap adapter

"4.5" Cap adapter


Cooling System pump

Contents















easier.







16L WASTE OIL STORAGE AE300103

• Capacity : 16 L / Size : 600x450x180 mm/ Weight : 1.05 kgs





- For DIY or professional use.
- · Simple and easy to operate. • Suitable for engine oil, gear oil, transmission and brake fluid water.



172

AUTOMOTIVE TOOLS



AE300178 COMBO FLUID EXTRACTOR

- Adopt durable polyethylene material.
- Uses both manual or air for operation
- Venturi system design to provide excellent performance.
- Oil depletion : manual or air.
- Dimension : 265x315x650m/m
- Capacity : 9.5 litre. · Maintenance free.
- Suction tubes included (4pcs). (1) 7 mm steel oil suction tube
- (2) 6 mm oil suction tube.
- (3) 6mm steel oil suction tube
- (4) 10 mm gear oil tube.

~		
•	\bigcirc	

VACUUM BRAKE FLUID BLEEDER

TRANSMISSION FILLING SYSTEM

AE300176-A OPTIONAL ADAPTORS

• Dimension: 260X370X59 5M/M Capacity: 7.5L

AE300176-A

• Weigh: 3.44KG

AE300176-A

• OPTIONAL ADAPTORS FOR (1) Mercedes 722.9 (2) VW/AUDI DSG (3) VW/AUDI CVT



PNEUMATIC OIL & LIQUID DISPENSER AE300187 (6000C.C)

• Provide with the safety valve helps the pre-setting pressure (43psi(3kg/cm²)) relief automatically. • Provide with pressure gauge makes read and control the air pressure in the tank



- Drain brake and power steering fluid from reservoirs.
- Works great on cars, motorcycle, truck etc...
- Use with brake bleeding

Accessory kit to bleed brakes lines.











E300200	PNEUMATIC	BRAKE	OIL	CHANGER
---------	-----------	-------	-----	---------

Features:

- Easy to operate & carry
- Automatic stop function
- Time saving
- Simple & neat
- Open & close vale to control extraction

Size	11" X 8"
Includes	Bleeding Tube Φ 5.8mm OD X 1.5m / Refill pot 1liter
Capacity	2L
Max Temperature	100°c
Working pressure	90psi
Air Inlet Size	1/4" NPT
Weight	1.8kgs



- Can have capacity 12-22kg original bucket grease or in bulk 30L grease suit for 00#-2# grease.
- Can have capacity 12-22kg original bucket grease or grease suit for 00#-2# grease.

ITEM NO.		AIR INLET PRESSURE		FLUID OUTPUT PRESS	DELIVER RATE	HOSE LENGTH
AE300072	30L	4-9 kg/cm ²	45 : 1	180-405 kg/cm ²	30c.c./sec	10 ft

AE300213 BRAKE BLEEDER

- Capacity: 1L
- Material of blow gun: P.O.M. Air consumption: 160L/MIN (5.6 CFM)
- Blow gun air inlet: 1/4"
- Santoprene hose: 1M
- Working pressure: 5~8 BAR (72~116 PSI)





AE300195 UTILITY IN & OUT FLUID SYRINGE

- Manual Operation
- · Capacity: 350ml • Size: 381 x 75 x 75mm
- · Accessory: Oil resistant tube
 - OD Ø9.8mm x L300mm OD Ø11 mm x L300mm
- Tube plug Net weight: 0.48kg
- Product Features:
- 1. It can be used for any non-corrosive lubricants
- 2. The flow rate is adjustable
- 3. Connect different tubes for different functions























6 WAYS MULTI PURPOSE HYDRAULIC AE310001 GEAR PULLER

- 1pc Hydraulic Ram (SCM415 φ 37.7MM x L160 x 16t) 1pc Combination Cross Head (Carbon Steel) 3pcs Combination Leg (SCM415 Drop Forged Hardened 42°~45°) 6pc Steel Plate 1pc Extension Rod (1" x 1-1/4" Carbon Steel)
- 1pc Extension Rod (1" x 2" Carbon Steel)
- 6pcs Screw Nut & Washer
- Packing : 5sets/CTN/24/25/1.3"

AE310004 HYDRAULIC SEPARATOR PULLER SET

1pc Hydraulic Ram (SCM415 φ 37.7mm x L160 x 16t)

- 1set bearing separator & bolts (SCM415 Drop forged hardened 42°~45°, capacity 6") (Bolt 5/8"x11ncxL216mm φ 16mm SCM415)
- 2pcs main rod (hex bar21mmxL7"x5/8"11nc carbon steel) 2pcs extension rod (hex bar 21mmxL7"x5/8" 11nc) carbon steel
- 1pc beam, carbon steel
- 1pc adaptor, carbon steel
- 1set/metal box/ctn/0.8'/24/25kg

PRESSURE SCREW SEPARATOR PULLER AE310005 SET

- 1pc beam, carbon steel 1pc central bolt φ 18.65mmxL11.5"x10t
- 1pc nut, carbon steel
- 1set bearing separator & bolts (SCM415 drop forged hardened 42°~45° capacity 75-105mm)
- 2pcs main rod (8"x1.75p carbon steel) 2pcs extension rod (8"x1.75p, carbon steel)
- Packing : 4sets/metal box/ctn/1'/30/31kg

AE310006

TWO SETS BEARING SEPARATOR ASSEMBLY

- 1set bearing separator & bolts
- 1set bearing separator & bolts
- 4pc main rod (hex bar 17mmx7/8"xL127mmx16t)
- 1pc beam, carbon steel
- 1pc center bolt (9/16"XL175X10t/inch carbon steel)
- Packing : 5 boxs/ctn/1.2'/21/22kg







AE310008	INTERNAL & EXERNAL PULLER SET						
· · · · · · · · · · · · · · · · · · ·	S45C Carbon Steel) 5/8 x 18T x L425mm						
AE310008-2 Hamme	er (S45C Carbon Steel) 53mmxL100mm 1.2kgs						
AE310008-3 Nut							
AE310008-4 Centre	Screw						
AE310008-5 Washe	r						
AE310008-6 Internal Puller Capacity : 15mm-30mm							
AE310008-7 Internal Puller Capacity : 30mm-80mm							
AE310008-8 External Puller Capacity : 15mm-80mm							
AE310008-9 Adapter 31x10							
AE310008-10 Adapter 18x6.5							
AE310008-11 Triple Head							
AE310008-12 Screw	1						
Packing : 1 Set/Blow (Case, 4sets/ctn./18/19/1.8'						

• Size : Small of internal puller 15mm~30mm Large of internal puller 30mm~80mm Exernal puller 15mm~80mm

• Locking the nut to open 3-jaws and clip the bearing. And then use the slide hammer to pull out the bearing.









SIZE:














AE310010	SLIDE HAMMER
----------	--------------

1pc T Bar (Carbon Steel)
1pc Hammer (5Lbs. Cast Iron)
1pc Axle Puller (Drop Forged Carbon Steel)
1pc Grip Wrench Adapter
1pc Nut
1pc Two Jaw Head
1pc Three Jaw Head
3pc Screw & Nut
1pc Attachment
3pc Jaw (Drop Forged Carbon Steel)
1pc Tapping Screw
1pc Hook
Packing : 1 metal box, 2 sets/ctn/14/15/1'

- Increased the coverange with the two axle pullers.
- Works together with other tools is more easy.
 Included 3-Jaw puller and many types of joints.





- One slide hammer assemble & 4 clamp.
- Attachments for 3/8" to 1/2"(10-14mm), 9/16" to 11/16" (15-19mm), 5/8" to 1" (18-25mm) & 1" to 1-1/4"(25-32mm) I.D. bearings' pulling.
- · Open clamps by turning handle clockwise to snug against the bearing for pulling out evenly without damage the parts.

176

JONNESWAY.

AE310082 BEARING HOLE PULLER KIT

• Open clamps by turning handle clockwise to snug against the bearing for pulling out evenly without damage the parts.

AE310018 WASHER SLIDE HAMMER SET

• Pull with slide hammer with washer in the body.


• Special steel for removing the ball pivots on steering arms, steering tie rocks,

AE310013 UNIVERSAL WHEEL HUB PULLER

• 90~140mm/3-1/2"~5-1/2" • 130~180mm/5-1/8"~7-1/16"

A BEFORE JSING APPEN SESASETC THREAD





178





AE310022 PITMAN ARM PULLER

Pitman Arm Puller (SCM 415) Hardened 42º 43° Centre Bolt : (S45C Carbon Steel) Hardened 42° 43° Packing : Tray/Skin Packed 5Sets/Inner 20Sets/18/19/1'

AE310023 BALL JOINT PULLER

SCM-4140 Hardened 45° Bolt : SCM-4140 Hardened 45° Centre Connector : SCM-4140 Hardened 45° Packing : Inner Box 20Sets/21/22/1'





50mm



75mm



100mm



E240440	BALL JOINT EXTRACTOR
E310110	SIZE : 23 MM
E240444	BALL JOINT EXTRACTOR
E310111	SIZE : 29 MM



- SCM415 Hardened 42[®] 45°
- Capacity : 1-1/4"-2-1/4" (30mmx50mm)
- Boltφ 9.5mmxL125mmx3/8"x24t Packing : 20set/ctn/20/21kg/0.5'



- SCM415 Hardened 42[&] 45°
- Capacity : 2-1/4"-3-1/2" (50mmx75mm)
- Boltφ 12.7mmxL135mmx1/2"x20t Packing : 12set/ctn/18/19kg/0.6'


AE310026 BEARING SEPARATOR

- SCM415 Hardened 42[®] 45°
- Capacity 3"-4-1/2" (75mmx105mm)
- Boltø 16mmxL165mmx5/8"x18t
- Packing : 10set/ctn/20/21kg/0.7'



- SCM415 Hardened 42[&] 45°
- Capacity 4"-6" (105mmx150mm)
- Boltφ 19mmxL260mmx3/4"x16t
- Packing : 6set/ctn/30/31kg/1'




















E310205	2TON GEAR PULLER
E310206	5TON GEAR PULLER
E310207	7TON GEAR PULLER

• Unique design patented for windly industrial using. · Changeable jaws for 2&3 operation. Adjustble angle fixed jaws for easily working.

1. The product made by high quality material of CR-MO, SK5 within high torque strength for professional using.

2. Adjustable angle fixed jaws have convenience working easily. 3. Quick release to save time and easy operation for effective working. 4. Easy simple action to change the jaws be inside or outside working 5. Changeable jaws for 2 or 3 jaws operation.

ITEM NO.	RANGE	WEIGHT
AE310205	2"~4"	0.42kg
AE310206	4"~7"	1.4kg
AE310207	5"~8"	2.9kg

AE310149 4 WAY BALL JOINT REMOVER TOOL

· Heat Treated drop forged steel body & bolt for long rought usage. Spread ball joints easily where space prevents use of direct action method. Total Length:165mm Opening Angle:24~45mm

Jaw Opening:20mm
Body Material:SCM440

AE310151 GEAR PULLER (THIN JAWS)

Special puller with ultra thin jaws for removal of crankshaft timing gear. Depth:100 mm Outside:40-90 mm

AE310150 PULLER FOR RIBBED DRIVE PULLEYS


Clamps onto any ribbed pulley

· Suitable for use on crankshafts, alternators, air conditioning units and water



Removal and replacement tool for wheel axle bearings.
Applicable : BENZ, BMW, TOYOTA, FORD, MITSUBISHI...etc. NW : 4.9 kgs GW : 5.1 kgs





- Features:
 Special package model includes 2/3 jaws puller and 2 jaws puller with attachment in one set.

- Ideal impact package with light PE case for carrying.
 One complete set with two kinds of puller for user's convenience always.





	CAPACITY	REA (m		SPREAD (mm) STROKE (mm) PUMP TIP (mm)		mm)		WEIGHT						
NO.	Α	В	С	D	Н	Е	F	G	Α	В	С	I	(kg)	
AE310095	4 Ton	185/250	70	75/55	255/110	60	42	22	84	11	6	22	32	4.5/8.5



(el
5
9

	AE310029-33
	ITEM NO.
	AE310029
	AE310030
	AE310031
	AE310032

ITEM NO.	SIZE	RANGE (MM)	CAPACITY (Ton)

TIEMINO.	OILL		
AE310029	3"	40-76	1.5
AE310030	4"	50-102	3.5
AE310031	6"	60-152	5
AE310032	8"	80-203	8
AE310033	12"	120-306	13

2-JAWS CR-V GEAR PULLER

AE310034-38	3-JAWS CR	3-JAWS CR-V GEAR PULLER				
ITEM NO.	SIZE	RANGE (MM)	CAPACITY (Ton)			
AE310034	3"	40-76	2			
AE310035	4"	50-102	5			
AE310036	6"	60-152	7			
AE310037	8"	80-203	12			
AE310038	12"	120-305	18			

|--|

ITEM NO.	DISASSEMBLY OUTWHEEL CAPACITY
AE310048	19-35 mm
AE310049	24-55 mm







Screw









JONNESWAY.

AE310072 DISC BRAKE PISTON SPREADER

AE310053 9 PIECES HARMONIC BALANCE PULLER

Yoke 1 Piece (Ductile)

- Bolt 1 Piece (φ 15.5mmxL140mmx11t/inch Carbon Steel) Adapter : 1Piece
- 3 Pieces 3/8" x 24 UNF x 3"
- 3 Pieces 3/8" x 16 UNC x 3"
- Packing : 1Set/Blow Case
 - 16Sets/ctn/28/29/1.5'

HEAVY DUTY COIL SPRING COMPRESSOR AE320023~24

• Drop forged by fully CR-MO and heat treated ensure obtain professional job. • The tool is designed for use in limited space under wheel arch. · Jaw design is fitting to wrap coil claws for safety.

e e 1	,
ITEM NO.	MAXIMUM JAW OPENING
AE320023	270mm
AE320024	370mm

AE320034

MACPHERSON SPRING DUMPER EXTRACTOR / INSTALLER(CHANGEABLE)

• Spring compressors are multi-application tools specifically developed for modern McPherson suspensions, using a range of 3 sets of interchangeable mono block forks.

• Application : BMW, TOYOTA, FORD. MITSUBISHI, VW, AUDI, SAAB NISSAN, HONDA, ACCORD, SUBARU, VOLVO, OPEL, PORSCHE.

182



AR020042 SMART CAR BATTERY TESTER 12V 10 - 80 AH					
TECHNICAL DATA	12Vdc Battery System				
INPUT VOLTAGE SYSTEM	9- 16 Vdc				
POWER DISSIPATION	50 - 150 mA				
OUTPUT INTERFACE (OPTION)	Photo Couple Output				
OUTPUT DISPLAY MODEL	LCD Display				
AUDIO ALARM	2Khz Buzzer				
DIMENSION, (L*W*H)	87*38*22.4 mm				
OPERATION ENVIRONMENT	-20 °C ~ 70 ° C < 80%RH				
WEIGHT	200 gm				















- 8A safety gear inside. • The automatic power failure will start when voltage is over the limit.
- This tool also can test positive and negative voltage.
- Tests continuity in switches, relays, diodes & fuses, and wiring harnesses.
- Polarity test cables and sockets. · Find short circuits and bad earths fast



AR020060 2000A DCA/ACA CLAMP METER + DMM 2+1 TRUE RMS

Features:

- 2 in 1, 2000 A clamp meter +Digital multimeter.
- Meet IEC 1010 CATIII 1000V safety requirement.
- True rms reading for ACV & ACA measurement.
- 4000 counts, Auto range , multi-functions for ACA , DCA , ACV, DCV , Ohms , Capacitance , Frequency (Hz), Diode , Duty cycle and continuity check.
- LSI circuit provides high reliability and durability.
- Wide ranges (2000A , 400 A) clamp on current measurement both for ACA & DCA.
- 4 ranges (400 uA , 4000 uA , 40mA , 400 mA) direct current input
- measurement both for ACA & DCA.
- Zero adjustment : DCA : Push bottom adjustment . Other ranges : Automatic adjustment.
- Overload protection circuit is provided for all ranges.
- 240uA-240mA small direct current input.
- 65mm measuring conductor size with unique two way open clamp.
- Data hold, Relative key, Back light.
- Compact & heavy duty ABS, panel water resistance and fireproof plastic case.



AR020061 TRUE RMS MULTIMETER

- Heavy duty CAT III-1000V category, meet IEC 1010 CAT III 1000 V safety requirement.
- 4000 counts, Auto range with manual range selection.
- Large LCD(65 mm x 48 mm)display with measurement unit with bar graph indicator, digit height 23 mm.
- True RMS ACV:400.0 mV /4 V/40 V/400 V/1000 V;continuity buzzer;ACA&DCA
- (10 A/400 mA/40 mA/4000 uA/400 uA);diode;DCV(400.0 mV /4 V/40 V/400 V/ 1000 V);Duty cycle; Capacitance(40 nF/400 nF/4 uF/40 uF/100 Uf);ohms (400/4 K/40 K/400 K/4 M/40 M ohm); Hz(4 Hz/40 Hz/400 Hz/4 KHz/40 KHz/ 400 KHz/4 MHz).
- Data hold, Relative, range hold.
- High input impedance for mV range.
- 10 Amp. current with fuse protection.

JONNESVIAY.

DIGITAL AUTOMOTIVE ANALYZER & AR020016 MULTI METER

• Function :

- RPM, Dwell, Volts DC, Volts AC, Amps DC,
- Resistance, Duty Cycle, Temperature, Pulse Width, Frequency, Diode test,
- Audible Continuity, Battery Test

AR020017

UNIQUE COMPRESSION TESTER KIT

• Full 2-1/2" dial

- Color-coded quadruple calibrations with 0-300 psi, 21kg/cm², 21 Bar and 2100 kpa
- A 6" heavy-duty stem and 13" durable flexible hose included tune-up Tools
- The accurate compression, vacuum and pressure testers provide a handy work and high performance on engines and fuel systems.

AR020018 FLEX-DRIVE COMPRESSION TESTER

• Full 2-1/2" dial

- Color-coded quadruple calibrations with 0-300 psi, 21kg/cm², 21 Bar and 2100 kpa
- A long heavy-duty flexible hose with a 14mm/18mm adapter
- convenient pressure-holding, side release valve

AR020019

PROFESSIONAL VACUUM & FUEL PUMP TESTER

- Tests on worn or faulty parts in fuel pumps, vacuum systems and related lines
- Large 3-1/2" dial with color-coded scales
- A long, flexible, heavy duty rubber hose and manifold adapter


included.

ELECTRIC CIRCUIT TESTER

Voltage: 6-24 dcv

• Wire length: 4.5mt





- The best quality electrical tester available for checking 6 and 12 volt systems. Made to last a lifetime
- Has heavy duty ground clip and insulator. 5' of tough flexible rubber wire is retained in spring supported strain relief designed to withstand the most rugged use. Bulb is easily replaced.



AR030007 **CAR BATTERY & ALTERNATOR CHECKER**

- LED lights indicate car battery condition (engine stop) or output of alternator (engine running)
- Lights show poor, fair or good condition.
- Magnetic backboard keeps your hands free for checking.





- AR030013 BATTERY HYDROMETER
- Tests the battery in seconds.
- · Color-coded float for easy reading.



- Contents :
- 5.28 x 1.78 x 20pcs ; 6.07 x 1.78 x 20pcs ; 6.8 x 1.9 x 20pcs ; 7.65 x 1.78 x 20pcs; 7.8 x 1.9 x 20pcs; 8 x 2 x 20pcs; 8.8 x 1.9 x 20pcs ; 9.25 x 1.78 x 5pcs ; 9.8 x 1.9 x 15pcs ; 10.82 x 1.78 x 15pcs ; 11 x 2 x 10pcs ; 14 x 2 x 10pcs ; 12 x 2 x 15pcs ; 13 x 2 x 10pcs ; 13.8 x 1.9 x 10pcs ;
- 13.95 x 2.62 x 10pcs ; 14 x 2 x 10pcs ; 17 x 2 x 10pcs ; 17.17 x 1.78 x 10pcs
- Applicable : R-12/R-134
- Total : 270 pcs.







- Size : 5A, 7.5A, 10A, 15A, 20A, 25A, 30A
- Puller x 1 • Total : 106pcs
- AR040018
- · Designed for cleaning the battery terminals. You can use on both sides
























AUTOMOTIVE TOOL



HOSE CLAMP PLIERS AR060001

• A new design plier for all kinds of hose clamp. · Special design for narrow space.

• Tips and jaws swivel through 360 degrees.

AR060021 FLEXIBLE HOSE CLAMP

• For replacement of fule, oil and water hose.

• Hose clamp with flexible 630mm wire.

• Convenient for working hidden areas and long distance.

AR060015 7PCS DISCONNECT SET

 Includes six tools for disconnecting spring couplings on Ford. GM, and Chrysler air conditioning lines. Also works on fuel lines and can be used as push lock connectors on radiator and transmission lines. • 1/4", 5/16", 3/8", 1/2", 5/8", 3/4", 7/8"



RUBBER SPARK PLUG REMOVER AND INSTALLER

• Flexible shaft permits access from many angles. · Easily insert & remove hard-to-reach spark plugs with the flexible shaft

• Soft-stepped tip firmly grips terminal and porcelain. • Special design helps you avoid hot engine burns.

AR060032 A/C SPRING LOCKING COUPLING TOOL

• Release spring lock connector on air conditioning line. For separating For both and the second seco

 All the disconnect tools you need to work with quick connect fuel lines on FORD, CHRYSLER, and GM, and on the spring lock fuel line couplings on FORD's popular port fuel injection system.
Works on 5/16". 3/8" and 1/2" fuel lines.

3/8"(yellow) and 1/2"(green) : Releases spring lock connectors on fuel line. 5/16"(gray) and 3/8"(blue) : Releases quick connect fitting on fuel line. Transmission cooler line and fuel line quick.

Disconnect Tool

Removes push lock connectors found at both the radiator and transmission

FUEL & TRANSMISSION LINE DISCONNECT SET AR060035

Instructions

1. Choose the appropriate disconnect tool for the desired job. Make sure that you have chosen the tool for the correct pressure line diameter. Position the tool as per the illustration.
 Apply slight pressure toward the connector fitting pressing strong enough to depress the "connector fingers" that maintain the connection.

4. Remove the pressure line

5. To replace : place the pressure line fitting onto the desired fitting destination and apply pressure. A click sound signifies the re-connection of the pressure line.

186

U.S.A. pat. Applying TAIWAN pat. Applying






















ADJUSTABLE UNIVERSAL CAMSHAFT AI010030 PULLEY HOLDING TOOL

WRINKLE-BAND PISTON RING

COMPRESSOR

Adjustale band expands from 3" to 5" (76mm-127mm).

• For use on all kinds of engines.

AI010008


- · Designed with grooved pins which are designed hold the camshaft pulley stationary while loosening and tightening the center shaft bolt.
- While useful on most Asian overhead cam engines, it's most needed on transverse mounted V6 engines such as the VG30 used in Nissan
- maxima, as well as, the 3VZFE and 1MZFE engines used in TOYOTA CAMRYS. • The rear pulleys on these models are in very close proximity to the
- shock tower making removal and replacement difficult without this locking device.
- Application : BENZ, BMW, FORD, MITSUBISHI, HONDA, VW, AUDI, NISSAN, VOLVO, TOYOTA, ETC.
- Adjustable Distance : P.C.D 21mm~100mm





- · Replaces tapered split collets on recessed valve springs quickly and easily.
- The special spring loaded unit places collets in position on recessed heads instantly
- Includes magnet to retrieve collets.
- One valve spring is compressed, one end of the tool positions collets and magnet end picks up loose collets.





- Great stability with 5/8" width, 1-3/8" height and 20-1/2" length.
- · Convenient hanging hole and edge protector.
- . Use with feeler gauges to check for distortion in engine blocks, cylinder heads and flywheels.



- UNIVERSAL TWIN/4 CAM LOCK (GAS & AI010040 DIESEL ENGINES)
- Designed to lock TWIN CAMSHAFTS to timing marks during timing belt replacement. Fit onto sprockets and extends to lock in to sprocket teeth. Adjustable arms.
- · Fit various diameters and tooth pitch. Also suitable for locking between cam and diesel INJ.









JONNESVIAY.

UNIVERSAL ENGINE BELT TENSION AI010079 TESTER

• This tool can be used to confirm tension on the engine belt of cars. Simple to check the belt for proper tension. • Suitable for all common types of engine belt. Including timing . ribbed . tooth and V-belt.

AI010063 BELT GAUGE

• It can be used to adjust the tension on the cam belt where the movement of timing belt is mesured by load (NM). Suitable for use on cam belts various belt widths.

 Clear incremental marking with knurled knob for precise measurement

• Dual scale allows reading from top or bottom of tool.

AI010042

FLYWHEEL HOLDING TOOL SET

• Designed to prevent the crankshaft from rotating when removing the crnkshaft pulley for timing belt replacement.

• The pulley bolt has a high torque loading in which case the engine must be locked securely when releasing and tightening the bolt.

• Teeth-Like design allows the operator to engage the flywheel teeth and the tool is bolted to the transmission housing to prevent movement of the flywheel.

• Set supplied with 4 most popular tools.

• Ideal and essential for removing the crankshaft pulley when replacing the timing belt.

PETROL ENGINE TWIN CAM LOCKING/SETTING AI010041 TOOL AND FLYWHEEL HOLDING TOOL KIT

• The kit supplied with adequate tools to lock the camshafts on twin cam (multi-valve) engines in order to stop them rotating out of timed position when the timing belt is replaced and removed.

It also provides different camshaft locking pins that can cover specific crankshaft and flywheel locking applications.

• Allows the service easier and reduce the risk of incorrect valve timing from taking • Kit also supplied with two popular flywheel holding tools. They are ideal and

essential for removing the crankshaft pulley when replacing the timing belt.
 Suitable for a range of vehicles including : HONDA, LAND ROVER, ROVER, VW, RENAULT, CITROEN, PEUGEOT, FIAT and VAUXHALL/OPEL.

• 19 pc. kit contents : Camshaft locking tool x 10, Locking pins x 4

Setting and locking plate, Balancer pin, TDC location pin and Flywheel holding tool x 2


AI010078 **FAST CHECK WIRE-CLIP**





· Easy, rapid and convenient measuring checking. • It designed to check various electric wires. · Contents:black and red clips.

JONNESWAY.



6 PCS PLASTIC BRAKE HOSE AI010067 DISCONNECTOR

- Use for one touch type connector.
- To release hose from connector pushing ratanor by release tool than pull hose by hand.
- Use for most of the truck and bus.
- Size including:6.8.10.12.15.16 m/m.







AI010090A



COMPRESSION TESTER ADAPTOR (LONG AI010062 REACH)

- · Special design to extension the spark plug thread in the deep
- hole for easier testing.
- Length: 263mm, thread: 14mm.




AI010033 OXYGEN SENSOR WRENCH

- Put a slot in the side of this wrench to accommodate connectors on heated oxygen sensors, which usually won't fit in standard sensors wrenches. The extended and reinforced body removes the most stubborn sensors without rounding them off.
- Features 1/2 of the double square drive, 7/8" (22mm) hex.
- Flare nut for vacuum switch & oxygen sensor service on the computercontrolled engines.
- Applicable models : FORD, TOYOTA, NISSAN, BENZ, BMW and most of the European cars.


















• Larger design to use on the enging which valve spring exposed outside. With straight and bend jaws. • Applicable:12 V engine, Diesel engine..



AUTOMOTIVE TOOLS











188



JONNESWAY.

4PCS INJECTOR SOCKET SET AI010060

• 22mm (6pt), 22mm (12pt), 27mm (12pt), 28mm (12pt) • For Use On: ALFA ROMEO, CHRYSLER, BMW, FORD, VW, MERCEDES, AUDI, OPEL, VAUXHALL, SEAT, VOLVO, ROVER ALSO ON VOLVO, MAN2.5TD & SCANIA HGVS.

DIAMETER	DESCRIPTION	LENGTH
22MM	INJECTOR SOCKET(6PT)	110MM
22MM	INJECTOR SOCKET(12PT)	75MM
27MM	INJECTOR SOCKET(12PT)	78MM
28MM	INJECTOR SOCKET(12PT)	78MM

22PCS 1/2" DR. ALTERNATOR INSERT BIT SOCKET SET

- 1pc- M10 Spline Bit Soocket with 33T Nut: 110mm (L)
- 1pc- M10 Spline Bit Soocket with 31T Nut: 98mm (L)
- 1pc- M10 Spline Bit,14mm Hex.Drive: 57mm (L)
- 1pc- M10 Spline Bit Socket: 110mm (L) • 1pc- T50 Tx-Star Bit Socket with 33T Nut: 110mm (L)
- 2pc- 75mm (L), Spline Bit: M8, M10
- 2pc- 75mm (L), Tx-Star Bit: T40, T50
- 2pc- 75mm (L), Hexagon Bit: 8, 10mm
- 1pc-33Teeth Alternator Nut with 15mm Hex. Tip
- 1pc-33Teeth Alternator Nut with 17mm Hex. Tip
- 1pc-33Teeth Alternator Nut with 22mm Hex. Tip
- 1pc-17mm Hexagon Alternator Nut
- 1pc-22mm Hexagon Alternator Nut
- 1pc-28mm X 22mm Hexagon Alternator Nut • 1pc-28mm X 21mm Hexagon Alternator Nut
- 1pc-28mm X 19mm Hexagon Alternator Nut
- 1pc-4 Points Alternator Nut with 17mm Hex. Tip
- 1pc-3 Points Alternator Nut with 38mm Hex. Tip
- 1pc-1/2" Square Drive X 10mm Hex. Bit Holder

VALVE SPRING COMPRESSOR FOR AI020015 GENERAL CAR FOR SMALL ENGINE

Jaw opening Min : 2-5/16" Max : 4-3/4" Throat clearance : 6"

AI020016

VALVE SPRING COMPRESSOR FOR TOYOTA GENERAL CAR

• Compress valves on small overhead valve or I-head engines.

- Tool has a throat depth of 6-1/4" and jaw openings 3 to 5-3/8".

It's designed for light weight valve springs.
Compressor works on I-heads with manifolds removed and many industrial engines.

AI020017

VALVE SPRING COMPRESSOR FOR TRUCK







• Compress valve springs on overhead valve and L-head engines on cars, trucks and tractors. Tool has a 9-3/4" throat depth, and jaw openings 2-3/4

to 7-3/4" fit larger engine sizes. Jaws and plunger bar are easily adjusted. Plunger bar seats on both flat- and cup-shaped valve heads. Offset and Straight Jaws are included. Use these heat-treated jaws with 380 and 383 Valve Spring Compressors.





- For large engines & diesel engines.
- Unique direct action compressor lever gives improved visibility & ease of use in areas of difficult access.
- Collet release adapters : restricted access adapter, 25MM, 30MM.




AI020056A EXTRA LONG VALVE STEM SEAL PLIERS

- Long neck designed to reach into confined area of the seal to grip it for removal.
- Gripping serration allow to grasp both original equipment & aftermarket seals regardless of the configuration.



UNIVERSAL OVERHEAD CAM VALVE AI020049 SPRING COMPRESSOR

- For use on most foreign & domestic engines, including AUDI, CHRYSLER, INFINITI, HONDA, HYUNDAI, LEXUS, MAZDA, MITSUBISHI, NISSAN, PORSCHE, SATURN, TOYOTA, VOLVO & VOLKSWAGEN
- This is a kit included everything you need to remove & install the valve spring with the cylinder head on or off the OHV & OHC petrol or diesel engine. An ideal tool kit for most foreign & domestic engines. The multi-point adjustable base of this tool bolted security to the head while the adjustable lever mechanism pivots from the beam thus compressing the spring quickly by one hand operation, fast removal & installation of the spring retaining keepers is easily accomplished by hand through the large open on both sides of the compressing tube. This kit allows on car servicing.





Special spring steel

Heat-treated

Ratchet type complete with spanner

With safety adjusting screws





• Compression band stainless steel

Ratchet type complete with spanner

• With adjustable safety screws





190

AI020034-37 PISTON RING COMPRESSOR

ITEM NO.	HEIGHT	CAPACITY	Q'TY		N.W	G.W.	CUFT
		(MM)	Q'TY	Q'TY	kgs	kgs	
AI020034	3"	53-125	30	60	16	17.5	2.0'
AI020035	3"	90-175	30	60	18	19.5	2.0'
AI020037	6"	90-175	20	40	23.5	25	3.0'

AUTOMOTIVE TOOLS

200	20040-42 PISTON RING COMPRESSOR							
NO.	HEIGHT	CAPACITY (MM)	Q' INNER	TY CTN	N.W kgs	G.W. kgs	CUFT	
40	3"	90-175	30	60	18	19.5	2.0'	
41	4"	90-175	30	60	20.5	22	2.6'	
42	6"	90-175	20	40	23.5	25	3.0'	

VALVE SEAL REMOVAL & INSTALLER KIT AI020063

 Works on both valves steel seated or removed. Fine gripping serrated plier grasp both original equipment or aftermarket seals regardless of their configuration. Precision machined seal driving adapters guide the seal for proper setting.

- 1PC- Valve stem seal plier.
- IPC Drive handle 6" (150mm) long.

 2PCS Deep seal driving sockets for seals O.D. 10.8-14.8mm.

 7PCS Seal driving adapters fit seals 5,5.5,6,6,6,7,8, & 3/8".

- · Comprehensive test kit for both direct and indirect diesel injected cars.
- Simple & easy to use.
- For use on both direct or indirect injection engines.
- Checks engine compression under cranking conditions.
- Small profile, quick coupling adapters for speed & security.
- Built-in pressure relief valve enables repeat tests without dismantling.
- Flexible hose (355m) gives access to restricted plug & injector parts.
 Dual scale 80mm dia gauge 0-1000 lb / in² & 0-70 bar.



DIESEL ENGINE COMPRESSION TESTER AI020051 SET (CARS)

APPLICATIONS

BMW/MERCEDES-BENZ/CARBODIES/MITSUBISH/CITROEN/NISSAN/ DACIA/OPEL/DIAHATSU/PEUGEOT/FLAT/RENAULT/FORD/ROVER/ HOLDEN/SEAT/ISUZU/TOYOTA/LAND ROVER/VAUXHALL/LEYLAND / DAF/VOLKSWAGEN MAZDA/ VOLVO CONTENTS

DESCRIPTION	OVERALL LENGTH	GAUGE DIAMETER	SCALE
Gauge Assembly	560	83 THREAD	0-60 BAR OUTSIDE DIA
GLOWPLUG ADAPTER	73.5	M10 X 1.0	
GLOWPLUG ADAPTER	54	M12 X 1.25	
GLOWPLUG ADAPTER	72	M14 X 1.25	
DUMMY INJECTOR	114	N/A	21
STANDYNE DUMMY	112	N/A	19
GLOWPLUG ADAPTER	114.5	M10 X 1.0	
GLOWPLUG ADAPTER	119	M10 X 1.0	
DUMMY INJECTOR	78	M20 X 1.5	
REPLACEMENT SE	AL AND WASHER SE	Т:	
90° ELBOW			
-	ENGTH WIDT	H HOLE	
DIAMETER			
Clamp plate	63.5 25	17	



CONTENTS

- Compression Tester-General Purpose M14 & M18 Plug Ports M14 & M18 Thread Chaser, M10 & M12 Theread Chase
- M10 Extension M12 Extension M14 Extension
- M14 Extension,M18 Extension,Service Kit.
- Comprehensive kit is based on petrol compression tester for vehicles with M10,
- M12, M14, and M18 spark plug threads. Complete with extensions, thread chasers and service kit
- Easy to use.

- Checks condition of valves, piston rings, gaskets & cylinder heads.
 Used on cars, vans & motorcycles.
 Pressure relief valve enables repeated testing of a cylinder without removing the gauge.



Al020053	DIESEL ENG SET (C.V.S)	INE COMPRES	SION TESTER		
DESCRIPTION	OVERALL LENGTH	OVERALL LENGTH GAUGE DIAMETER			
Gauge	560	100	0-60 BAR		
Assembly	INT. THREAD	THREAD	EXT. THREAD		
Center Pillar Spacer Set	185	5/16 x 24 UNF	1/2 X 20 UNF		
	EXT. DIAMETER	LENGTH			
End Adapter	20.5	30			
End Adapter	23.6	32			
End Adapter	23.6	41			
REPLACEMENT SEAL AND WASHER SET :					
LENG	TH WIDTH	HOLE DI	AMETER		
Clamp plate 63.5	25	17			
Clamp plate 76.2	15	17			
90° ELBOW					





1300 mm ADAPTERS

PARTS LIST : 0~100 PSI low pressure gauge assembly x 1. 0~500 PSI high pressure gauge assembly x 1. Adapter hose 1/8-27 NPT x 1. Adapter 1/8-27 to 1/4-18 NPT x 1. Adapter 1/8-27 to 1/8-28 NPT x 1. Adapter 1/8-27 to 10-10 x 1. Fitting 1/8-27 90 steering elbow x 1. Fitting 1/8-27 nipple 2" long x 1. Fitting 1/8-27 coupling x 1. Adapter 1/8-27 to M8-1.0 x 1. Adapter 1/8-27 to M8-1.25 x 1. Adapter 1/8-27 to 5/16-24 NF x 1. Adapter 1/8-27 to 1/16-27 NPT x 1. Fitting 1/8-27 45 steering elbow x 1 Adapter 1/8-27 to VW AUDI x 1. • For all major manufacturer domestic and import vehicles. Pack in a plastic storage case.
Packing : 1Set/White box 6Set/Ctn N.W. 15.5kg G.W. : 16.5kg CUFT :3'





• Set contains two gauge assemblies for high and low pressure ranges.

Nine adapters to test a wide variety of domestic and import automatic

Four special fittings are also included for connection to hard-to reach

test parts in areas requiring a 45 to 90 angle.



AI020054 OIL PRESSURE TESTER SET

GAUGE ASSEMBLE : OVERALL LENGTH GAUGE DIAMETER SCALE 80mm

0-10 bar

THREAD,R1/8 DIN 2999,1/8 X 27 NPT,1/4 X 18 NPT, 3/8 X 20 UNF 1/2 X 20 UNF, M10 X 10, M12 X 1.5, M14 X 1.5, M16 X 1.5, M18 X 1.5, 90° ELBOW

• Helps to diagnose worn oil pumps and engines, faulty oil pressure switches and warning indicators. Easy to use.

Accurately tests oil pump pressure, switch & warning indicators.

Large clear dual scaled gauge.
Quick coupling adapters with shut-off valve for speed & security.

· Permanently oil primed, long, flexible hose

AI020061 TRANSMISSION PRESSURE GAUGE SET

PETROL & DIESEL ENGINE AI020138 **COMPRESSION AND LEAKAGE TEST KIT**

• This petrol & diesel engine compression and cylinder leakage test kits that cover the wide range of modern engines, including Hdi, TDCi and Pumpe Duse.

• Included clamp-on injector adaptors, 0-50 Bar (700PSI) gauge with rubber bumper, staright and right angled quick connect fitting and an extensive range of glow plug and injector adaptors enable this kit to cover the vast majority of car, van, truck, and bus, agricultural and marine diesel engines. Additional pressure gauge for references on incoming pressure during the operation (0-7bar).

• Glow Plug Adaptors: Wide range of Alfa, BMW, Chrusler, Daewoo, Fait, Ford, Hyuidi, Izusu, Land Rover, LDV, Mazda, Mercedes, Mitsubishi, Nissan, Opel, PSA, Renault, Saab, Suzuki, Toyota, VAG, Vauxhall, Volvo diesel engines.

• Spark plug size : 10 , 12 , 14 , 18mm.

• Injector: M20, M22, M24 & Ford Stanadyne injector plus clamp-on injector.

20141	DIESEL ENGINE COMPRESSION TESTER
	SET

• Comprehensive test kit for both direct and indirect diesel injected cars. • Simple & easy to use.

• For use on both direct or indirect injection engines.

• Checks engine compression under cranking conditions.

• Small profile, quick coupling adapters for speed & security.

• Built-in pressure relief valve enables repeat tests without dismantling. • Flexible hose(355MM) gives access to restricted plug & injector ports. Dual scale 80MM DIA gauge 0-1000 PSI& 0-70 kg/cm²





Q'TY	DESC.	Q'TY	DESC.
1	1/4x1/4 inch pipe plug		13 inch Ford adapter hose
2	5/16x1/4 inch NPT hose barb		bleed-off hose
2	1/4x1/4 inch NPT hose barb	1	bosch C.I.S. hose
1	0-50 PSI (0-3.5 bar) gauge	1	basic hose, 24 inch
1	0-100 PSI (0-7 bar) gauge		8mm-1.0 banjo bolt adapter
4	hose clamps	1	10mm-1.0 banjo bolt adapter
1	5/16 inch hose	1	12mm-1.25 banjo bolt adapter
1	1/4 inch hose	1	10mm-1.50 banjo bolt adapter
1	FORD spring lock adapter	1	HONDA adapter
1	1/4 inch NPT tee with valve	1	12mm-1.50malex10mm- 1.00femalex1-1/4"adapter
1	G.T T.B.I. adapter	1	12mm-1.50malex10mm- 1.00femalex1-1/4"adapter
1	G.M quick connect adapter	1	12mm-1.50malex8mm- 1.00femalex5/16"adapter
1	G.M 2.2L adapter	2	12mm-1.50malex8mm- 1.00maleadapter
1	FORD hair pin adapter	1	12mm-1.50malex8mm- 1.00malex3"adapter

• The fuel injection test kit tests fuel injection systems on vehicles on most makes and models.

Pinpoints problems in filters, lines and regulators.

AI020074

spark plugs.

 This kit comes complete with assorted hoses, hose barb fittings and hose clamps to adapt to earlier vehicle models, as well as current.

CYLINDER LEAK DETECTOR AND CRANK

STOPPER

• Kit allows easy identification of compression problems.

Detector measures exact leakage amount and locates leaks area.
Crank stopper locks engine harmonic balance pulleys and replacing







AI020103 DIESEL INJECTOR PULLER

- · Assists removal of stubborn bosch and lucas diesel injectors-saves time and money when injectors are difficult to remove.
- · With M8, M12, M14, adaptors.





SLIDE HAMMER TYPE INJECTOR AI020125 NOZZLE PULLER


- Can Use For Mercedes Cdi Engines Om 611, 612, 613,...etc. • Injection Nozeles That Do Not Fit Very Tightly Can Be Pulled Out Without.
- Needing To Take Them Apart Or Remove The Cylinder Block.
- The Specialty Design , The Puller Is Additionally Supported By The Steel Ball On The Valve Cover, Which Prevents The Puller From Tipping During The Removal Process.













JONNESWAY.



Precision machined tungsten carbide blades produce valve seats with: Accurate seat angle Superior seat surface True, flat seal · Seats concentric with valve guide Available in a wide range of cutter diameters and angles, Contents : cutter q46mm - q60mm45° and 30° cutter $\dot{\phi}44$ mm - $\dot{\phi}52$ mm75° and30° cutter q37mm - q46mm60° and45° cutter q37mm - q44mm75° and 30° cutter $\dot{\phi}28mm$ - $\dot{\phi}35mm75^\circ$ and 45° 5 pcs expandable pilot φ5.5mm - φ12.5mm "T" wrench handle

AI020027 VALVE SPRING COMPRESSOR

• Compresses overhead valve springs with rocker arm studs. • This tool can be used with the head either on or off the engine. • Jaws adjust to fit most domestic and import overhead valve engines. • Adjustable handle allows for clearance in tight areas, comes complete with stud adapter.

BANDING TOOL WITH CUTTER AI020043

· Operated by hand or 1/2" wrench.

• This tool is easily removed by sliding sideways after winding has been

020019	STANDARD PISTON RING EXPANDER CAPACITY : 4-1/2" TO 7" (115-180MM)
020020	STANDARD PISTON RING EXPANDER CAPACITY : 2-3/4" TO 4-1/4" (70-108MM)
020021	STANDARD PISTON RING EXPANDER CAPACITY : 2" TO 4" (50-100MM)

• Replace piston rings without the danger of breakage or destroy. • It doesn't need adjustment, and expands all ring styles whether square, diagonal or step - cut style.

AI030010 VALVE LAPPERS

Al030010 has 1-1/8" and 1-3/8" dia. Cup for Larger valves



12PCS DRAIN PLUG KEY SET AI030002

- Remove & install female drain plugs.
- All drain plug keys have 3/4" (19mm) hexagon body for use with socket or T-bar to drive.
- Chrome-Vanadium Steel heat-treated & black finish.






AI030014 MECHANICS STETHOSCOPE

- · Locates source of engine noise quickly.
- Listen for trouble by tracing sound of flowing water, oil, gas or steam.
- Identify piston slap, worn gears, faulty valves, water pump failure, damaged gaskets and defective bearing.
- Handle is shockproof.
- Disassembles for storage.





- Use on any application where securing a pulley is required.
- Especially useful in removing fan clutches
- Eliminates the need for multiple various sized holding wrenches.
- · Saves time and money.



6PCS PICK AND HOOK SET AI030027

- Straight, hook, combination
- Cotter key puller
- 45 & 90 degree large pick & hook
- Organizational tray
- Advanced tri-lobal ergonomic design handle increases torque and provides comfort while reducing fatigue.
- TPE (thermal plastic elastomer) over-mold ensures firm grip
- Resistant to acids, fluids and solvents
- Extra long 18" shaft for added reach
- Large 5/16" (8mm) shaft diameter for added strength
- Chrome-Vanadium steel shafts with high-polished chrome plated finish





 Removing & installing all types of lock rings. • Used in brakes, transmission, pedal shafts, clutches shaft. Deep serration jaws hold lock rings securely.









• 3 leg two way size : 65mm to 120mm, (2-1/2" to 4"). • 3/8" & 1/2" square drive with 19mm male hexagon adapter.

196

AUTOMOTIVE TOOLS



HEAVY-DUTY 10-1/2" REPLACEABLE TIP CIRCLIP PLIERS SET AI040017

Q'TY	TIP SIZE	TIP ANGLE
2	108	0°
2	108	15°
2	108	45°
2	108	90°
2	120	0°
2	120	15°
2	120	45°
2	120	90°

Replacement Tips

ncludes 2 Each 108 tips in 0°15°45°90°

ncludes 2 Each 120 tips in 0°15°45°90°

· Replaceable tips and have a spring ratchet locking mechanism to hold circlip securely against tension. Offset tips make it easier to facilitate circlip.

AI040008

VACUUM TESTING/BRAKE BLEEDING KIT

• The kit includes the vacuum pump, complete fittings and accessories for vacuum testing and brake bleeding, plus a detailed owners manual. • The vacuum pump is field repairable. Replace wron "o" ring, seals and valves with the vacuum pump repair kit.

DUAL VACUUM & PRESSURE PUMP AI040031 WITH BRAKE BLEEDER KIT

• Quality all metal construction vacuum & pressure pump creates and holds a metered vacuum and or pressure for testing a wide variety of automotive, marine, aircraft & agricultural equipment. Simply set the serrate control valve from vacuum to pressure for intended use. • There's infinite number of applications : air intake control valves, distributor vacuum advances, EGR valves, power brake boosters, transmission modulators, motorcycle carburetors, etc. Includes all adaptors and reservoir for brake bleeding & fluid transfer. • Gauge Diameter : 2"(50mm) Readings : 0 to 30in Hg (0 to -1 bar) Vacuum 0 to 60 psi (0 to 1.4 bar) pressure

OIL FILTER WRENCH 3-LEG, 2-WAY AI050002



ITEM NO.	SIZE MM	FLUTES	SUITABLE FOR MOTORCAR	ITEM NO.	SIZE MM	FLUTES	SUITABLE FOR MOTORCAR
HC-66/6	66 (2-19/32")	6	Flat (Punto, 1-2) Renault (Clio 1.2 Express, Kangoo, Rapid, Twingo)	HC-95/15	95 (3-6/8")	15	Toyota #15600-41010, Alfa, GM, Ford, ALFA, Chryster
HC-68/14	68 (2-11/16")	14	Fits Hastings. Mazda, Ford Escort, Capri, Subaru, Fran PH6607 (those Fram filters made in Korea). Motorcraft FL816	HC-96/18	96 (3-3/4")	18	Audi (A4. A6. Tdi), VW (Passat 97 Tdi) Renault (Laguna 2.2d. Safrane 2.2D Espace 2.2D. R19. Rapid. Megane. 1.9/2 1D. Tdi)
HC-73/14	73 (2-7/8")	14	Fits Toyota/Lexus	HC-100/15	100 (4")	15	Fits Fram, Motorcraft, Wix, Isuzu and Mitsubishi,
HC-76/12	76 (3")	12	Fiat (z.B. Ducato, Scudo, Ulysee), Renault,	HC-106/15	106 (4-11/64")	15	Fiat (Ducato 2.5D. Td)
HC-76/14	76 (3")	14	(Megane, Laguna, Espace 3) Fits Champion, Champ Lee, Purolator, Mopar, VW	HC-108/15	108 (4-8/32")	15	Volvo (C70. S70. V70.Tdi. TD) (Turbo. Diesel. 850 Tdi. Diesel) etc
	. ,		, Porsche, Mercedes, Benz, BMW, Audi, (I.B. A3TD) Opel.	HC-108/18	108 (4-8/32")	18	Renault (Espace, Laguna, Master, Safrane, Traffic 2.4, 2.5, 2.8D, TD)
HC-76/30	76 (3")	30	Fits Motorcraft only-FL400A, Ford		65 to 67mm		Fits same filters as made in Canada including
HC-76/8	76 (3")	8	Fiat (z.B. Marea), Lancia (z.B. Delta)	HC-65/67	(2-9/16" to 2-21/32")	14	PH4386. PH4967. PH6017. PH6018. Daihatsu.
HC-80/15	80 (3-9/64")	15	Fits Hastings. Fram, Purolator, Nissan, Honda, Motorcraft, Mazda, Isuzu, Subaru, Opel, Toyota.	HC-74/15	74mm	15	MF, Audi, #056-115-561G, gm. Rover. Chryster.
HC-86/16	86 (3-3/8")	16	Volvo (S40, S60, S70, S80)		(3-29/32")		
HC-86/18	86 (3-3/8")	18	VW. Golf (MK3. Tdi, passat Tdi.) Audi A6 Tdi, Renault (Clio, Rapid 1.9D Laguna, Safrane,	HC-74/76	74 to 76mm (3-29/32" to 3")	15	Fits Fram, Ac, Saturn
110 00/10	00 (0 0/0)	10	Espace 2.1D) Citroen, Peugeot, Renault		75 to 77mm	15	Fits VW, Audi. Castie. GM/AC, Hastings, Wix.
HC-90/15	90 (3-17/32")	15	Fits Honda Accord. Mitsubishi. Mopar. tsuzu	HC-75/77	(3-15/16" to3- 1/32")	10	NAPA Ford. Isuzu Mercedes, opel.
HC-92/10	92 (3-40/64")	10	Fiat, Cinquecento, Coupe, Croma, Fiat, Panda, Regata, Ritmo Fiat, Seicento, Tempra, Tipo,	HC-78/15	78mm (3-2/32")	15	Nissan #15208H8991, Ford, Toyota, Accord.
10-52/10 52 (5-40/04) 10		Lancia (Beta. Dedra. Kappa. Monte. Carlo. Prisma Thema. Trevi)	HC-80/82	80 to 82(3-9/ 64" to 3-7/32")	15	Fits Wix filters branded for mazda. Subaru. Toyota Honda. Acura. Nissan. NAPA.	
HC-93/15 93 (3-21/32")	1 1	Fits Casite, Champ, Champion, GM, Fram, Hastings. Opel, Mazda, Volvo, Mitsubishi,	HC-93/36	93mm (3-21/32")	36	Fits Motorcraft only FL1A, FLA1B, FL300, FL820, Ford	
10-33/13	HC-93/15 93 (3-21/32") 15		Purolator, Wix, Nissan, VW, Porsche, Renault Ford, Honda, Audi		Two Way Oil Filter Wrench 65-120mm		
HC-93/45	93 (3-21/32")	45	VW-Audi. (TDi 2.4, 2.6, 2.8L)	HC-9.5mm	M Adapter 1/2"(F) or 3/8"(M) Square drive tool		
	,				1		

	A
0	





















AI050007

PROFESSIONAL SWIVEL HANDLE OIL FILTER WRENCH

CAPACITY		
2-3/8" ~ 2-7/8" (60mm ~ 73mm)		
2-7/8" ~ 3-3/8" (73mm ~ 85mm)		
3-3/8" ~ 3-3/4" (85mm ~ 95mm)		
3-3/4" ~ 4-3/8" (95mm ~ 110mm)		

AI050043

OIL FILTER MASTER PLIERS

- Multi-purpose pliers 2-1/8" to 4-5/8" (53-118mm)
- Chrome Vanadium Steel
- Drop forged jaws with heat-treated, nickle plated
- Suitable for installing, removing and tightening objects of any shape.
- Locks onto the work with terrific grip.

050008

12" ADJUSTABLE OIL FILTER WRENCH SIZE : 60-115MM

AI050049

CHAIN WRENCH

• Size : 30-160mm • Handle 9" • Chain 23-3/8"

HEAVY DUTY OIL FILTER CHAIN AI050109 WRENCH

• Available for all type of oil filter • Flexible handle for narrow space • Size available: Ø 60~105m/m • Length of chain: 350 m/m


FILTER WRENCH (FROM 2-1/2" TO 3-1/8" 60MM~80MM) AI050030

Steel jaw grip filter is no slipping.
The large range enable to fit most standard size filters.
Use with 3/8" drive.


AI050024 4PCS PRY BAR SET

17/16" X 24" , 7/16" X 18", 3/8" X 12" , 1/4" X 8"

JONNESWAY.













200

JONNESVIAY.

WINDSHIELD INSTALLATION KIT AB010001

Specifications :

- A. Rope Insert Tool
 - Use this tool to insert the rope into rubber gasket.
 - The handle feeds rope through its stem as you pull it around the gasket.
- B. Assort Tip For Insert Tool :
 - For inserting locked strip into windshield seal.
- Different shaped heads interchange for most types of locking strip. C. Curved Hook Tool :
- Curved hook tool used for inserting and cleaning rubber gaskets. D. Straight hook tool used for inserting and cleaning rubber gaskets.
 - Designed for the removal of broken glass for the side runners without removing them.

AB010002 WINDSHIELD REMOVAL KIT

Specifications :

- Three strong galvanized steel wires are braided to from one wire. B. Wire Gripping Handles x2 pcs :
 - A & B Feed the wire through the hole in the wedge shaft.
 - Loop it through the hole at the top of the shaft.
 - Then back into the handle.
 - Pressing the wedge back into the handle, the wire is hold.
- C. Windshield Removal Tool : Cuts the butyl adhesive compound around windshield.
- D. Wire Feeder Tool
 - Designed for easy and flexible insertion of wire through
- polyurethand, allowing speedy removal of bonded windshield. E. Trim Pad Remover
 - Place the tool under the edge of the door upholstery panel and insert it into the fastener as far as possible, then simple pack pry up.
- F. Windshield Molding Release Tool :
 - Use for removal of Windshield molding.

AB010013 WINDSHIELD CUT-OUT WIRE

AB010026S 5 PCS HANDY REMOVER SET

- AB010026A : wedge set
- AB010026B : wedge set
- AB010026C : handy remover
- AB010026D : remover wide type
- AB010026E : remover pull type

BODY TOOLS





SUCTION LIFTER WITH TWO VACUUM AB020003

- Lever operated vacuums
- 2 x120mm diameter rubber suction cups
- Lifting action will not damage contact surface
- · For use on windscreens glass, tiles, plastic, or other smooth surfaced non-porous materials.

AB030038A LIFT SUPPORT FIXING CLAMP

- To fix the engine. For trunk and back door lift support
- To prevent the from slip.
- Place the tool on the lift rod next to the cylinder. After the work finished, tighten with the knob until it is secured on the lift rod.





- AIR INFLATE FOR UNLOCK DOOR AB030056 (VEHICLE)
- This inflate design easily and safely to separate the door frame from the vehicle body

IGNITION LOCK & RADIO & HOOK TOOL SET AB030024

- Ignition Lock Removal Tool Set
- Contains : 2 removal tools for Model W 126 ; 2 removal tools for Models W 124 & 201
- Pair of Hooks
- For removing instrument cluster. Applicable : Models W 107, 116, 123, 124, 126, 140 & 201
- Radio removal tool To radio removal on 1992 and newer MERCEDES.
- Applicable : Models 140, 129, 202 & 210




AB030028 CAR DOOR UPHOLSTERY REMOVER

- Removes upholstery clips in seconds.
- This perfectly balanced alloy forged tool is attached with plastic handle, with a bright plated blade.


AB030058 CLIP REMOVAL PLIERS (35 DEGREE)

- To remove trim pads & insulation
- To keep from breaking clips • To remove the "tough" clips




















AUTOMOTIVE TOOLS



AL010004 ANGLE ADJUSTER

 With 4pcs alignment plates. Hydraulic function.

• Suit for most car.

• NW : 31kgs GW : 32 kgs

• The purpose of wheel alignment is to reduce tire wear, improves fuel economy and handling, while increasing driving enjoyment and safety by proper adjusting the angles of the wheels, suspension system, and steering system.

• Used in conjunction with AG010119

DOUBLE WISHBONE ALIGNMENT TOOLS (IMPROVEMENT) AL010005

• Applicable : MERCEDES, MITSUBISHI, HONDAS, and all double wishbone suspension vechicles.

• Features : with two spacers to adjust the angle. On car maintenance without removing double wishbone. No damage to hub bearing. Fixed with c-type strong clamp, it works as 10 ton hydraulic press. Used on both front and rear suspension double wishbone. 10 ton two-speed hydraulic pump makes the maintenance easy and accurate. This is time, money, and labor saver. N.W. : 29.1 kgs G.W. :30 kgs

AN010227

WHEEL ALIGNMENT WITH DIGITAL PROTRACTOR

• Perform portable , no heavy turntable ! One person operation. • Displays camber ; caster ; KPI ; toe • Includes gauge and wheel mount (from 10" to 20") · Accurate, rugged and easy to use Saves time and money!







- Rear disc brake caliper tool.
- For rotating pistons back into the caliper to provide clearance for new pads.
- Includes 9 adapters (Available individually) for use in both 2 and 4-
- wheel rear disc rake assemblies of most domestic and import cars
- Tool may be used "on" or "off" the car. A real time saver that makes this tough job easy. Helps prevent damage to the piston and boot.













AN010070 REAR DISC BRAKE CALIPER TOOL

- · For rotating pistons back into the caliper to provide clearance for new pads.
- Includes 5 adapters for use in both 2 and 4-wheel
- rear disc brake assembles most of cars. • Tool may be used "ON" or "OFF" the car. A real time saver that
- makes this tough job easy helps prevent damage to the piston and boot. Contents use including
- Most HONDAS, MAZĎAS, DODGE, MITUBISHI, SUBARU, TOYOTA, FORD & GM etc.



AN010038 SEAL PULLER

- Removes oil & grease seals
- Two tips fit most application. • NW : 0.36 kg



- UNIVERSAL TRANSMISSION CLUTCH AN010183 SPRING COMPRESSOR
- · For removing and installing the transmission clutch piston snap ring.
- · Adjustable, for most models of European, Japanese and American cars and light trucks.
- · Accessory 01 can be used on BENZ transmission rear clutch piston snap rina...
- Accessory 02, the wide are plate, for use on all types and models of American and Japanese car automatic transmission clutch drums. For example: FORD. TOYOTA, MITSUBISHI....etc.
- Accessory 03, the middle are plate, for use on most models of American cars and light trucks.
- Accessory 04, small are plate, for use on BMW (4HP22, 5HP18...), VW, FORD, MONDEO (CD4E)....etc.
- · Accessory 05, the body of this tool: L300mm x W300mm x H330mm.













AUTOMOTIVE TOOLS



AN010145 4 IN 1 BALL JOINT SERVICE TOOLS SET

• For universal joints and anchor pins remove and install.

• Easy operate to the upper and lower ball joints on 1/2 and 3/4 ton pickups, Suburbans, and Yukons / Tahoes.

• Work on both original equipment and aftermarket ball joints.

AN010045 BALL JOINT SEPARATOR

- Placed between ball joint and steering knuckle and give a few sharp blows with a hammer
- Forged and heat treated 15/16" Opening Length : 12".

AN010091A INNER TIE ROD TOOL

- These tools are specially designed for the inner tie rods that are inaccessible to adjust.
- The long socket can be easily used with seven open-jaw drivers, size 1-3/16", 1-1/4", 1-5/16", 1-7/16" & 14mm, 17mm, 33.6mm, to most application.
- The inner tie rod can be easily removed and installed by slipping the long socket over tie rod end and connecting it to the open-jaw driver.

AN010092 MULTI-PURPOSE INNER TIE ROD TOOL

- The master tie rod tools easily replaces inner tie rod ends without removing the rack & pinion.
- Capacity : 33-42mm Patented.

AN010185 CV BOOT CLAMP PLIERS

FOR ALL EAR-TYPE CLAMPS

- APPLICATION: FOR AUDI, BMW, CHRYSLER, FORD, GM, HONDA, MAZDA, MERCEDES BENZ, NISSAN, OPEL/VAUXHALL, VW ETC.
- DESIGNED: TO USE WITH EXTENSION HANDLE OR TORQUE WRENCH



AN010008 BEARING RACE & SEAL DRIVER SET

- Collars : 9 sizes : 1.565", 1.750", 1.965", 2.325", 2.555", 2.470",
- 2.8230", 2.995", 3.180".
- 6 sizes fit most bearing race sizes #1 #6.
- Help reduce damage to both race and axle housing.

JONNESWAY.

AUTOMOTIVE TOOLS

206




AUTOMATIC TRANSMISSION CLUTCH AN010012A SPRING COMPRESSOR (IMPROVEMENT)

• For removing and istalling the transmission rear clutch piston snap ring... • Adjustable, for most models of American cars and light trucks. • NW : 3.2 kgs GW : 3.4 kgs



3PCS COMPOSITE HOSE PINCH TOOL AN010054A SET

- Special-radius jaws design will not damage internal hose lining.
- Lightweight, non-conductive, bright color 3 sizes for different application.





AN010085A SNAP IN TIRE VALVE INSTALLER


- Steel constructed tool with deep threaded head for positive sealing of all snap-in type passenger car tire valve stems.
- Rubber cover design to protect the rim.

• 3 position settled Patented.



AN010030A WHEEL WEIGHT BALANCE PLIERS

EXTERNAL & INTERNAL RESTORER



AN010072 EXTERNAL & INTERNAL RESTORER FILES	
 Restore tool for renewing damaged thread on any diameter bolt, stud, axle of shaft file both right and left hand threads. Design for in hide & narrow area usage. Description pitch sizes Metric file 0.80, 1.00, 1.25, 1.50, 1.75, 2.00, 3.00 	ſ

|--|

• Restore tool for renewing damaged thread on any diameter bolt, stud, axle or shaft file both right and left hand threads.


Description AN010072A Metric file AN010072B SAE file AN010072C SAE file


pitch sizes 0.75, 1.00, 1.25, 1.50, 1.75, 2.00, 2.50 3 0mm 11, 12, 13, 14, 16, 18, 20, 24 9, 10, 12, 16, 20, 27, 28, 32





















JONNESVIAY.

AN010188A TIRE LEVER WRENCH

• CHROME VANADIUM CARBON STEEL S45C MAT FINISHED

ITEM NO.	L	Т	WT
AN010188A	500	8.3	732

AN010064

OVERHEAD VALVE SPRING COMPRESSOR

• For use on a wide range of OHV, OHC and CVH engines not suitable for use on engines with deep seated valves.

Allow valve springs and valve stem oil seals to be replaced with the cylinder

· Feature a reversible jaw/adaptor and automatic cam-action locking to a predetermined setting.

AN010064A VALVE SPRING COMPRESSOR

• Compressor easily removes valve springs on most cars and light trucks, works with cylinder head on or off the engine.

Instructions :

• Remove valve cover.

• Place tool around valve spring as low as possible to fit spring coils.

• Screw down handle until spring is compressed sufficiently to remove keys and

A/C COMPRESSOR CLUTCH REMOVER AN010066 KIT

• Replace clutches found on FS6, C171, 6P & 148 computer. • Also GM R4 & A6, HR-6, DA-6 & V5 A/C compressors. • And compressors of Sanden SD505, 507, 508, 510, 575, 708 and 709. • 2 & 3 hole puller plate fits most clutches, the mechanical force does the pulling job.

AN020007 STANDARD ENGINE CYLINDER HONE

• 3 Leg 2" - 7" (51MM - 177MM)

PEUGEOT/CITROEN PENTAGON BRAKE AN040100 SOCKET (12.5MM)

Applicable: For use on bendix brakes on PEUGEOT and CITRONE vehicles.

AUTOMOTIVE TOOLS

208



PENTAGON SOCKET BIT FOR GIRLING AN040101 BRAKES(1/2" DR.)

· For use on most vehicles fitting with girling brake systems.

· Chrome vanadium bit holder, correctly hardened, tempered and chrome plated.

AN040042/43 45° FLARING, DOUBLE FLARING & CUTTING TOOL SET

Includes heavy duty tube cutter, standard 45 flaring tool and double flaring adapters set in custom carrying case. AN040042

Heavy duty tube cutter for 1/8" to 1-1/8" tubing; standard 45 flaring tool flares 7 sizes : 3/16", 1/4", 5/16", 3/8", 7/16", 1/2" and 5/8" O.D. tubing; five double flaring adapters cover 3/16", 1/4", 5/16", 3/8" and 1/2" O.D.

AN040043

Metric flaring, double flaring & cutting tool set flares seven metric sizes : 4mm, 4.75mm, 6mm, 8mm, 10mm, 12mm and 14mm O.D. tubing. Five double flaring adapters cover 4mm, 4.75mm, 6mm, 8mm and 10mm tubing.





• The new grip can keep your hands away from potential danger while striking.
















2

11






3

10

12



- for wheel hubs, half shafts, brake drums, etc • This set with the 4.3KG slide hammer can remove wheel hubs, half
- shafts, brake drums, drive shafts directly in the car.
- A mechanical spindle can press out drive shaft.
- Suitable for VW, Audi, Alfa Romeo, Ford, Citroen, BMW, Mazda, Fiat, M-Benz, Seat, Opel, Peugeot, Renault, Skoda, Porsche, etc
- Bolt size: M12*1.5
- M14*1.5 • Spindle Standard: Inner Thread: 2-1/4"-14uns Range: 90-130mm
- Outside Diameter: 160mm

HONDA LOWER CONTROL ARM BUSHES

REMOVER/ INSTALLER AN040087 (HYDRAULIC DRIVE)

Features:

- On car maintenance
- For replacement of bushes on HONDA cars.
- Easy to use. Save time and money.
 Applicable : HONDA CR-V (before 2001) , CIVIC K6 (1992) , CIVIC K8 (JC)(1996) · CIVIC K2 (carburetor) · CIVIC K3 (injection)
- General introduction for bush :
- A flexible bush has an elastomeric element enclosed between an outer sleeve and a centre axis to ensure better road grip and stability. Makes driving more comfortable



k6 lower control arm

k8 lower control arm k10 &CR-V lower control arm



JONNESWAY.

AG010138 1/2" IMPACT DRIVER W / 36MM 13 BITS

AG010140 MULTI - DOLLY (wideth: 37 mm)

• Auto body repairing D.I.Y & sheet metal working.

• Student crafts working.

Personal working studio.

• Made from carbon steel by hot forging & precision.

• Heat - treatment.

AG010055 PROFESSIONAL IMPACT DRIVER

Chrome molybdenum.

36L Phillips NO. 2, NO.3, 36L Slotted 8mm, 10mm.

AG010055A IMPACT DRIVER SET

• Chrome Vanadium steel • Bits. Material : S2. • Contents : 4Bits x 36mm : PHILLPS
 NO.2, NO.3 SLOTTED
Smm, 10mm 2Bits x 80mml : PHILLPS
 NO.2, NO.3

	M10110	PICK & FINISHING HAMMER (CROWNED FACE + ROUND POINT PICK)
J	 Crowned face. With hickory handle. 	
1		
	M10210B	STRAIGHT PEIN & FINISHING HAMMER

· With hickory handle.







AG010030	A	6PCS AUTO REPAIR TOOL SET
CONTENTS :		
AG010030A-2	1 F	PC Double End Hand Dolly.
AG010030A-3		PC Drip Moulding, Spoon.
AG010030A-1	1 F	PC Curved Dolly.
AG010030A-4	1 F	PC Toe Dolly.
M10110	1 F	PC Pick & Finishing Hammer.
M10401B	1 F	PC Light Shrinking Hammer (Flat Face).




AG010037	RECTANGULAR MAGNETIC TRAY (SIZE: 240 X 140 MM)
----------	---



AG010087 STEERING WHEEL PULLER

- Pulls steering wheels on most US and import cars.
- The floating swivel on the center screw prevents damage to the steering column.
- Zinc plated.
 2 sets of bolts.















JONNESWAY.

5PCS 8" FILE SET MF05S

1PC: Flat File
1PC: Round File
1PC: Half-Round File 1PC: Square File
1PC: Triangular File

Contents: A- Flat File B- Round File C- Half-Round File D- Square File E- Triangular File

AG010032 TELESCOPING INSPECTION MIRROR

TELESCOPING INSPECTION MIRROR AG010033

Size : 50 x 92mm

AG010034 MAGNETIC PICK-UP TOOL Heavy duty pocket. Capacity : 3.5 Lbs. L : 580 mm.

AG010035 3 IN 1 LIGHTED MAGNETIC MIRROR

Attach 25 x 50mm swivel inspection mirror and magnetic riveter. Heavy duty.





AUTOMOTIVE TOOLS

212



Specifications:

- A. LED Max power: 15W LED COB light
- B .Li-ion Rechargeable battery:3.7V 2200mAh C. Charger input: AC100~240V 50/60Hz
- D. Power output:5.0V 1000mAh
- E. Charge time:3.5-4 hours
- F. Battery life (active time): 2.5~10 hours
- G. Storage temperature: -20°C to 70°C
- H. Operation temperature: -5°C to 50°C
- I. Product Size: 375(L)x40(W)x30(H)mm



- AG010207 **15W COB LED WORKING LIGHT**
- Lumen adjustable
- Brightness: 410 LM
- Highest illuminance: 935 LUX for projecting distance of 50 cm
- Half illuminance: 300 LUX for projecting distance of 50 cm
- Fully charged battery allows 2.5 hours for full brightness, or 10 hours for half
- illuminance
- · With charging adaptor • Features:
- 1.Lumen tuning switch

AG010090A

Body Gun: Zinc & TPR

Operating Pressure: 90 PSI

• Air Flow 1.1 CFM At 100 PSI

• Gauge :2-1/2" Rubber Shroud Protection

• Pressure Gauge: PSI- Bar, Kgf/cm² - Kpa

Measuring Range From 0-200 PSI (Accuracy: +/- 1%)

• 360 Degree Hose Rotation & Clip Tip. (Hose 50cm)

Large LCD Display For Easy Reading

• Operation Temperature: -10°C~45°C

Supply Voltage: LED-9.0V

• Air Inlet: 1/4" Female (Air Inlet With 20 Mesh Screen)

Feature:

Function: • Fill Air. (Inflation) Release Air. (Deflating) • Gauge Pressure. (Measuring)

Specification:

- 2.Rotatable base with powerful magnet
- 3.Swivel hanging hook
- 4.Built-in 2200mAh LI-lon batter
- 5.Long battery life. It can support the highest illuminance for around 2.5 hours
- and half illuminance about 10 hours.
- 6.Short charge time: 3.5-4 hours Charging: red flash light/ blue light on/ yellow flash light

DIGITAL TIRE INFLATOR

7.USB charger & USB cable enclosed















AG010038AL PROFESSIONAL 3 FUNCTIONS TIRE GAUGE (L : 1600MM)




AG010042 HANDY TIRE GAUGE

CORRECT TIRE PRESSURE : 1. INCREASES GAS MILEAGE 2. INCREASES DRIVING SAFETY 3. REDUCES TIRE WEAR FEATURES: EASY TO READ PORTABLE ANSI GRADE B ACCURACY SHOCK RESISTANT WITH RELEASE BUTTON







JONNESVIAY.

160LB/IN² 270MM PROFESSIONAL TIRE

AG010047 380MM TIRE AIR CHUCK

16" PUSH & FOLDABLE CROSS - HANDLE SOCKET WRENCH AG010099

 Mat Finish Socket Size : 17, 19, 21 mm, 1/2" DR. (11/16", 3/4", 13/16", 1/2" DR.)

AG010169 2 WAY TRUCK WRENCH, CR-V 6140

AG010169 • Size: 32X33MM, DIA: 1" X16" • HRC38-45, CHREOME PLATED • W/DIA. 3/4" X600MM BAR, CR-MO, HRC38-45, CHROME PLATED

JONNESVIAY.

GENERAL TOOLS





FOR PASSENGER CAR & TRUCK






Use with 1/2" DR. commonly used for tightening head bolts and other bolts where a torque angle is required.

AG010119CS 2PCS MAGNETIC ADJUSTABLE CAMBER GAUGE

- Accurate camber measuring tool for use after repairs or replacement of struts, wheel assemblies etc. for cars and trucks.
- Vials housed in a durable non-magnetic casing with a magnetic head that attaches firmly to rotors or spindles.
- Gauge can be preset at any angle 0° to 90° before making adjustment. Range: 5° positive to 5° negative in 1/2° increments.






AG010049 5PCS SCREW EXTRACTOR SET

(Screw Extractor)

- Made of Chrome Molybdenum.
- Heat treated

AG010217

 Quick & easy way to remove broken screws, pipes, bolts & studs. Drill size : 5/64"(2mm), 9/64"(3.5mm), 5/32"(4mm), 1/4"(6mm), 19/64" (7.5mm).





PRODUCT DIMENSIONS	350MM(L) X 260MM(W) X 240MM(H)
LOAD CAPACITY	150KG
MATERIAL	STEEL
	INCLUDING BOTTLE RACK

MOBILE WORK CHAIR

MERCEDE REPAIR
AS PANE

214







• Types : 116/123/124/126/129/201/202/140 and 4-Matic includes. Advantage : Newly developed automatic 3-point safety interlock and automatic





NE320031	BENZ BALL JOINT INSTALLER W123/126/220
. Essencia hallisia	stinte steading langed

• For pressing ball joint into steering knuckle. Application : W123/W126/W220





- Suit for BENZ M111, M112
- Break loose the crank shaft pulley/harmonic balancer bolt. Designed to properly secure the pulley from rotating during R&R of crank bolt. The 50mm hex head armature slips past the lightest of spaces and slides right into the center slot on the pulley. Then slide the long bar onto the receiving end of the armature and lock it into position with the securing bolt.




ADJUSTABLE UNIVERSAL CRANKSHAFT AI010030A PULLEY HOLDING TOOL

- Adjustable distance: P.C.D. 30mm~150mm
- Material: SCM440 (Forging)
- This tool si designed for holding the crankshaft only.
 Applicable: BENZ S600, M137, M112, M113, M271, M642, CEFIRO A32, A33,
- and Most kinds of engine







- Spark plug socket 5/8" (16 mm) with retaining spring and joint, 3/8" square drive, outer diameter 22mm, length 93mm. • Applicable: M112, 113, 137, 155, 166, 271, 272, 273, 275, 902, 906.













MERCEDES BENZ REPAIR TOOLS





BENZ 7PCS NOZZLE INJECTOR PULLER FOR MERCEDES BENZ (SLIDE HAMER STYLE)

• For removing stubborn injectors on Mercedes Benz CDI engines and adapted tight common rail injectors without having to disassemble cylinder head. • The puller is additionally supported by the steel ball on the valve cover which prevents the puller from tipping during the removal process. Applicable: Mercedes CDI engines OM 611.612.613









AI050071

BENZ & BMW FAN SERVICE WRENCH KIT

• The hardest material, S45C & heat treated. • Shiny surface treatment, just like mirror. • The best quality in the field.

BENZ ENGINE OIL LEVEL GAUGE AI050069 (STRAIGHT)

NO. / NAME	MATERIAL NO.	ENGINE TYPE	REMARK
069 / BENZ ENGINE VEL GAUGE IGHT)	120589062100 103,943,984/985,104,111,119,120, ST 137,603,913/963/97,604,605,606, 611,612,613,628,612,965		STRAIGHT
RIPTION	dipstick for determining oil level and inspecting length of dipstick guide tube		

A11151111X/	BENZ ENGINE OIL LEVEL GAUGE (VOLUTE)			
NO. / NAME	MATERIAL NO.	MATERIAL NO. ENGINE TYPE REMARK		
AI050084 / BENZ ENGIN OIL LEVEL GAUGE (VOLUTE)	E 120589072100	112.113.646.647.648	VOLUTE	
DESCRIPTION	j .	measuring rod for measuring oil level and for checking length of oil pipe		

MERCEDES-BENZ V6 ENGINE SPARK AI050070 PLUG BOOT PULLER

• Special angle design with 17mm wrench to be a lever for removing and installing the wire easily. Applicable : BENZ V6 engine.




AI050083 BENZ (M111) OIL SEALING INSTALLER

• 210 589 00 15 00 drift punch for BENZ (M111) engine.

 Genuine stock no. : A111 016 0721 sealing ; no. : 210 5859 00 15 00 drift punch. • The seals get crack because they expand when hot and shrink when cold. · Easy and quick to install.





- Dimensions : 74mm x 14 flutes x 1/2" drive.
- Applicable : all MERCEDES models, AUDI (A3), BMW (E36), CITROEN, FIAT, FORD, LANCIA, MAZDA, NISSAN, OPEL, PEUGEOT, PORSCHE, RENAULT, TOYOTA, VW(GOLF IV), FORD METROSTART... etc.
- Caution : please use 27mm socket with a wrench to manipulated the tool while the torque value is over 25 NM, otherwise the tool will risk being broken. The torque value limit is 25 NM if the tool operated with a wrench.

AI050137 BENZ ML, BMW OIL FILTER WRENCH

• DR.1/2", 84 mm X 14 flutes

• 84mm Oil filter wrench with 14 points. •Applicable: 2007 Dodge Sprinter, 2007 MERCEDES-BENZ E 320 and the 2007



Jeep Cherokee with the 3.0L V6 CRD (Common Rail Diesel) engines. 3MW 658 103 008 0 PA66>GF35<7 521 353



BENZ (642) CRANKSHAFT HUB LOCKING

M-BENZ ML 67 402 17 429 MANN+HUMMEL 1 >PA 66-GF 35<

BENZ (M271) CRANKSHAFT HARMONIC AL010056 BALANCER PULLEY HOLDER

- · For removal and replacement of the crankshaft bolt.
- Applicable: Benz (M271)

TOOL

• Genuine stock No.: A 271 030 00 03

AL010057





No.	Chassis No	Model	Engine Type
1	W203. 020	C320 CD1	642. 91
2	W203. 220	C320 CD1	642. 91
3	W209. 320	CLK320 CD1	642. 91
4	W209. 420	CLK321 CDI Cabrio	642. 91
5	W219. 322	CLS320 CD	642. 92
6	W211.220	E280 CD1	642. 92
7	W211.020	E280 CD1	642. 92
8	W211.620	E280 CD1	642. 92
9	W211.022	E320 CD1	642. 92
10	W211.222	E320 CD1	642. 92
11	W211.024	E320 CD1 BLUETEC	642. 92
12	W211.084	E280 CDI 4 MATIC	642. 921
13	W211.284	E280 CDI 4 MATIC	642. 921
14	W211.089	E320 CDI 4 MATIC	642. 921
15	W211.289	E320 CDI 4 MATIC	642. 921
16	W204. 022	C320 CD1	642.96
17	W204. 089	C320 CDI 4MATIC	642. 961
18	W204. 289	C320 CDI 4MATIC	642. 961





















218

MERCEDES BENZ REPAIR TOOLS



BENZ AIR CONDITIONING COMPRESSOR AL010058 PULLEY HOLDING TOOL

• Counter holder for fixing in place and unfastening the belt pulley on the air condition compressor..

• Applicable : Benz Engine 112.113.272.273

BENZ (M112/M113/M137) CRANKSHAFT AL010061 HARMONIC BALANCER PULLEY HOLDER

 For remover and replacement of the crankshaft bolt, M112, M113 & M137, as found on E320, E430... etc.

BENZ TIMING LOCKING TOOL SET AL010076

- Suitable for a wide range of Benz, included in Petrol and Diesel engines. • The whole set includes:
- AI010099 BENZ FLYWHEEL RETAINING LOCK TOOL
- Applicable: BENZ ENGINE MODEL 112, 113, 137, 155, 156, 272/979, 273, 629, 642/992
- Genuine no.: 112 589 03 40 00 AI010118 BENZ FLYWHEEL LOCKING TOOL
- Applicable: BENZ ENGINE MODEL 102, 103, 104, 111, 601, 602.91/93/94/96/983, 603.91/93/96/97, 604, 605, 606, 611, 612/965/966, 613
- Genuine no.: 601 589 02 40 00
- AL010076-1 BENZ CAMSHAFT LOCKING PIN Applicable: BENZ ENGINE MODEL 111, 119, 604, 605, 606, 611/980, 612, 613, 628, 629, 640, 642/922, 612.965/966, 646, 647, 648
- Genuine no.: 111 589 03 15 00 • N M · 1 26




BENZ 722.6 TRANSMISSION OIL LEVEL AL010016 GAUGE

- Genuine stock no. : 140 589 15 21 00.
- The tool is designed for checking ATF level.
- Applicable : MECEDES models 1997 and newer with 722.6 transmission.

BENZ 722.7 TRANSMISSION OIL LEVEL AL010016A GAUGE

- The tool is designed to measure the oil level of transmission.
- Full length : 920mm
- Applicable : transmission type 722.7, 7.16.5



• Drift for unclipping the overflow pipe in the oil pan when draining the oil. • Applicable: BENZ 722.9 model transmission.






AN010119 BENZ ASSEMBLY FIXTURE

- Sleeve for installing reverse gear piston in front cover.
- Assembly device for brake band piston B1.
- Application : all MERCEDES models.
- Assembly fixture for circlip on spring retainer of clutch K1 and K2.





- For brake band piston B1.
- Application : All MERCEDES models 722.1, 722.3, 722.4, 722.5








BENZ SLEEVE, ASSEMBLY DEVICE & ASSEMBLY FIXTURE AN010123


- Genuine stock no. : 140 589 13 43 00.
- Sleeve for installing reverse gear piston in front cover.
- Assembly fixture for circlip on spring retainer of clutch k1 and k2.
- Applicable : transmission 722.6.
- NW : 5.2kgs GW : 5.4kgs
- Assembly tool; B1/2, K1/2 to compress clutch packs and allow installation of retaining ring (722.6).



AN	010124	BENZ TRANSMISSION SEAL ASSEMBLY SLEEVE								
1	Transmis	ssion measure tool (Ruler Type)								
2	Transmis	ssion measure tool (Plate)								
3	Piston oi	I seal installer								
4	Ki clutch									
5	Transmis	ssion O-ring sleeve								



Operation example: Assemble Wheel Bearing





PROFESSIONAL WHEEL BEARING TOOL AN010223 SET FOR MERCEDES

 Tool set for Mercedes set for e.g. 190 series (W201), A-Class (W168, W169), B-Class (W245), W124, C-Class (W202, W203), E-Class (W210), M-Class (W163, W164), S-Class (W140), V-Class (W639).

• This tool can safe, guick and professional replacement and removal of wheel bearing. minimum working effort – high time saving

simple and safe handing

CONTENTS:

AN010223-M.Benz	Description
AN010223-501	Clamping nut
AN010223-502	Pull spindle
AN010223-401	Bearing cover
AN010223-402	Housing
AN010223-402B	Housing
AN010223-405	Centring ring Ø80
AN010223-366	Pressure ring Ø66
AN010223-370	Pressure ring Ø70
AN010223-373	Pressure ring Ø73
AN010223-375	Pressure ring Ø75
AN010223-379	Pressure ring Ø79
AN010223-383	Pressure ring Ø83
AN010223-384	Pressure ring Ø84
AN010223-385	Pressure ring Ø85
AN010223-387	Pressure ring Ø87
AN010223-388	Pressure ring Ø88
AN010223-390	Pressure ring Ø90
AN010223-393	Pressure ring Ø93
AN010223-242	Centring ring Ø42
AN010223-245	Centring ring Ø45
AN010223-249	Centring ring Ø49
AN010223-250	Centring ring Ø50
AN010223-254	Centring ring Ø54
AN010223-260	Centring ring Ø60
AN010223-395	Centring ring
AN010223-101	Retainer adaptor for clamping nut and pressure spindle with O-ring
AN010223-102	Retainer adaptor for mecanical spindle

JONNESWAY.

UNDERCAR SERVICE TOOLS FOR MERCEDES BENZ



BENZ REPAIR TOOLS

MERCEDES



BENZ (W220/W211/W230) BALL-JOINT REMOVER/INSTALLER AN010182

- On car maintenance.
- Special design to remove & install the ball joint, without removing any parts. • Application: BENZ W220/W211/W230.



BENZ TRANSMISSION GAER LEVER RUBBER INSTALLER AN010213

- This pliers installs the nylon bushing used on all models of Mercedes BENZ automatic transmissions, and some Ford, BMW, VW, AUDI and many other makes using ZF transmissions.
- This tool easily and safely pushes tough nylon bushings into place on the shift shaft. Works on several different bushing sizes.
- Applicable: BENZ W124/W126/W140/W201/W202/W210...etc.









BENZ (W211/W220/W203) SUB-FRAME BUSH REMOVER / INSTALLER

W211 EXTRACT



BENZ AXLES WHEEL BEARING EXTRACTOR / INSTALLER AN040074

- A great tool used to replace front wheel bearings without removing the steering knuckle & strut assembly.
- As the spindle assembly isn't removed, there is no need to align front end after the job is done, saving a lot of time.
- Applicable : MERCEDES-BENZ, BMW, TOYOTA, VW, MARCH, FORD, VOLVO...etc.



1/2" DR. SPECIAL WHEEL LUG SOCKET 17MM X 88MM(L.) AG010204

- Material : CR-V with Manganese phosphated
 MS17 specially designed to loosen and tighten the new special wheel bolts found on Mercedes vehicles (17mm waf).
- Suitable for Mercedes M-class (W166), CL500(W216), S-Class (W221) and Maybach.

BMW REPAIR TOOLS





BMW REPAIR TOOLS


224



AI010084 BMW (M62) VANOS CAMSHAFT TOOLING

 Includes: AI010075 BMW V8(M60/M62) CAMSHAFT LOCKING FIXTURE AI010084B BMW(M62) VANOS CAMSHAFT TIMING TOOL AI010084C BMW(M62) VANOS TIMING HOOK AI010084D BMW(M62/M54) VANOS ELECTROMAGNETIC VALVE AI010084E BMW(M62) VANOS TENSIDNING BRACKET







- THIS TOOL IS SPECIFICALLY DESIGNED FOR HOLDING THE SPROCKET / CHAIN IN PLACE WHEN DISASSEMBLING THE VP44
- INJECTION PUMP AND HIGH PRESSURE PUMP. • COMMON RAIL FITTED TO BMW ENGINES: 318D/COMPACT(E46) 530D(E39)
- 320D/TD COMPACT(46) 530D(E60/E61) 535D(E60/E61) 330D(E46) 525D(E39) 730D(E38) 525D(E60/E61) X5 3.0D(E53)





	AI020068	BMW CAMSHAFT ALIGNMENT TOOL KIT
1		

- BMW Engine models M42 & M50 : includes 2 blocks swivel lock plate & locking pin for setting camshaft timing.
- Engine models M40 & M70 : includes plate & locking pin for setting camshaft timing.
- BMW Engine models M60 & M62 : includes 2 blocks swivel lock plate & locking pin for setting camshaft timing.



BMW (M60 / M62) CAMSHAFT AI020075 ALIGNMENT TOÓL

- Includes : 2 blocks swivel lock plate & locking pin for setting camshaft timing. • Applicable : BMW engine models M60 & M62. • NW : 4.1kgs







 Includes : 2 blocks swivel lock plate & locking pin for setting camshaft timing. • Applicable : BMW engine models M42 & M50. • NW : 2.2kgs





• Used to remover/install the front crankshaft seal. • Application: BMW (N40/N42/N45/N45T/N46/N46T/N52/N53/N54) • Genuine No.: BMW 119 220&119 230











JONNESVIAY.

BMW (M40 / M70) CAMSHAFT AI020077 ALIGNMENT TOOL

 Include : plate & locking pin for setting camshaft timing.
 Applicable : BMW engine models M40 & M70. • NW : 1.08kgs GW : 1.2kgs

AI040061

BMW (N40/N42/N45/N45T/N46/N46T/N52/ N53/N54) CRANKSHAFT FRONT OIL SEAL RÉMOVAL / INSTALL KIT

INSTALL



BMW (E31/E38/E39) WIPER LINKAGE **ASSEMBLY REMOVAL/INSTALLATION** SOCKET BIT (T80)

• Used to remove and install BMW (E31, E38, and E39) wiper linkage assembly. Used in conjunction with Al050082.
 Applicable : E12, E21, E23, E24, E28, E30, E30/C, WAGON E30, E31, E32,

E32/3, E34, WAGON E34, E36, E36/2, E36/3, E36/5, E36/7, E36/C, WAGON E36, E38, E38/3, E39, E39PL, WAGON E39, E46, E46/16, E46/2, E46/3, E46/5, E46/C, E52, E53, E60, E65, E66, E67, E85, RR1...ETC.

• Requirement windshield wiper arm removed. T80 (1/2" square drive expert draper tx star impact socket bit).

BMW (N42/N46) CAMSHAFT ALIGNMENT AL010025 TOOL

• This tool is a gauge for fixing the camshaft in TDC position used to dismantle and assemble intake and exhaust camshaft. • Applicable : BMW N42, N46.

(B)



(A)

(C)

(D)

BMW (M52TU/M54/M56) TIMING TOOL AL010020K

• This kit includes AL010020A/B/C/D/F

BMW M50-TU (M52/M54/M56) DOUBLE AL010020A VANOS SETUP BRACKET

• M52TU engine(1999-2000 323i, 328i, 528i/1999-2002 Z3). • M54 engine (2001-2005 325i, 330i, 525i, 530i, X5 3.0i/2001-2002 Z3 / 2003-2004 Z4 / 2004-2005 X3).

AL010020B SECONDARY CHAIN TENSIONER

- Locks chain tensioner during timing.
- Model: M50 , M52

AL010020C SECONDARY SPROCKET TOOL

• Application : M52TU, M54, M56

AL010020D PRIMARY CHAIN TENSIONER TOOL

• Application : M52, M52TU, M54, M56





AL010020E PULLER FOR CRANKSHAFT HUB

• Removes stuck vibration damper hub in conjunction with

VANOS COMPRESSED AIR FITTING AL010020F (U.S. STANDARD)

- Optional Accessory
- Fitting allows for functional testing of VANOS adjusting unit. Use to pressurize the single and double VANOS unit when checking or removing and rplacing.

Application : M50, M52, M52TU, M54, M56, N62















BMW REPAIR TOOLS



BMW (N62/N73) CAMSHAFT ALIGNMENT AL010027 TOOL

• AL010027-1 inlet camshaft gauge (genuine stock no. : 11 9 461). AL010027-3 bracket with bolt (genuine stock no. : 11 9 462). AL010027-2 exhaust camshaft gauge (genuine stock no. : 11 9 463). AL010027-4 BMW(N40, N42, N62, N73)camshaft alignment pin.

• Used to lock the camshaft on TDC position.

• Applicable : BMW N62, M73 engine.

· Accurate, easy to use, unique tool for maintenance.

• Best choice for engine overhaul on BMW (N62, N73) camshaft.

AL010030

BMW (M52/M54/M56) CRANKSHAFT HUB LOCKING TOOL

• Modes: M52TU, M54, M56

AL010036A BMW (N51/N52) TIMING TOOLS & PLUG MANDREL

• For locking flywheel in TDC position on BMW N51, N52, N52K, N53, N54. • Turns crankshaft to TDC position while central bolt moves. • Put AL010036A-3 into calibrate hole (arrow ahead) and fixed crankshaft. Attention

1. In the vehicle which carry special equipment SA205 (Automatic Transmission), there is a big hole make use of TDC position nearby calibrate hole. 2. When AL010036A-3 stayed in calibrate hole and locked flywheel, it is impossible to move engine through central bolt.

BMW(M47) DIESEL ENGINE CAMSHAFT ALIGNMENT TOOL AL010063

• Camshaft setting and flywheel locking tools to cover the latest range of BMW 2.0 and 3.0 litre common rail diesel engines used in BMW and other manufacturer's models.

• Applicable: BMW 2.0 (M47) and 3.0 (M57) Diesel Engines in BMW 3, 5 & 7 Series, X5, Land Rover Freelander, Range Rover, Rover 75

BMW (N62/N73) TIMING TOOLS AL010077

Includes AL010077-1, AL010077-2, AL010077-3, AL010077-4, AL010077-5, AL010077-6, AL010077-7, AL010077-8, AL010077-9, AL010077-10 and AL010077-11

BMW REPAIR TOOLS



BMW (N40/N45/N45T)PETROL ENGINE AL010078 TWIN CAMSHAFT SETTING / LOCKING **TOOL SET**

• Suitable for timing 1.6 Litre BMW N40, N45 and N45T chain driven petrol engines with Vanos units on the inlet and exhaust camshafts.

BMW MINI COOPER (N12)TIMING TOOL

 Engine Codes: N40, N45, N45T(B16) BMW: 116 1.6i E81/E87(03-09)

- 316 1.6i E46/E90(01-08) 316 1.6Ci E46/E90(01-06)
- 316 1.6ti E46(01-05)

SET

BMW MINI COOPER(N12) 2006~2007 R56

Applicable: BMW MINI COOPER(N12) 2007 R55

AL010079









- For timing the BMW N47/N47S 2.0 twin camshaft diesel chain drive engines, fitted in the 1 Series, 3 Series, 5 Series and X3.
- Applications: BMW; 1 Series, 118d (E81/E87)(06-09), 120d (E81/E82/E87)(06-09), 123d (E81/E82/E87)(07-09). 3 Series, 318d
- (E90/E91)(07-09), 320d (E90/E91/E92)(05-09) 5 Series, 520d (E60/E61) (06-08). X3, 2.0d (E83)(07-09)
- Engine Codes: N47, N47S(2007-2010)

Parts No.	Description	OEM No.
AL010102-1	Flywheel Plate Timing Pin	115 320
AL010102-2	Camshaft Alignment Tool	118 760
AL010102-3	Crankshaft Pulley Turning Tool	116 480
AL010102-4	High Pressure Pump Sprocket Removal Tool	118 740
AL010102-5	Tensioner Locking Pins X 2	113 340

Positioned crankshaft by AL010103-4 when rotating crankshaft in central bolt.

When repairing exhausted camshaft, install AL010103-1 on it and fixed tool by

• Install AL010103-2 to cylinder head cover fastened by AL010103-3-1. Put AL010103-1 on intake camshaft, and fixed tool by AL010103-3. Application: BMW MINI COOPER (N12/N14) 2007 R55

BMW MINI COOPER (N12/N14) TIMING





AL010025A BMW (N42/N46) PETROL TIMING TOOLS KIT

- Using with AL010025C. This kit includes AL010025-1, AL010025-2, AL010025-3, AL010025-4, AL010025-5, AL010025-6, AL010077-5.
- Timing, checking and adjusting the twin camshaft on petrol engine.
 Removing, installing and aligning of vanos unit.
 Applicable: BMW:

AL010103

AL010103-3.

E87(1 Series): 118i/120i N46 engine E46(3 Series): 316i/316Ti/318i/318Ti/(01-)N42/N46 engine E90/E91: 318i/320i N46 engine

TOOL SET

Note: Do not remove AL010103-4 while maintenance.


BMW MINI COOPER (N12/N14) 2006~2007 R56

- E85: Z4, 2.0L-N46 engine
- E83 N46 engine














228

JONNESVIAY.

BMW (N42/N46) CAMSHAFT CARRIER AL010025C BRACKET REMOVAL / INSTALLTION KIT

- Using with AL010025A. This kit includes AL010025-7, AL010025-8, AL010025-9, AL010025-11.
- Installation, removal and timing of variable camshaft timing unit/camshafts. • Checking and adjustment of camshaft timing.
- Applicable: BMW:
- E87(1 Series): 118i/120i N46 engine
- E46(3 Series): 316i/316Ti/318i/318Ti (01-)N42/N46 engine
- E90/E91: 318i/320i N46 engine
- E85: Z4, 2.0L-N46 engine
- E83 N46 engine



- This kit includes AL010036A-1, AL010036A-2, AL010036A-3, AL010036B and AL010077-5.
- Applicable: models:
- 128i. E82(07-08), 130i. E81/E87(05-08), 135iS. E82(07-08), 323i.
- E90/91/92/93(04-08), 325i/xi. E90/91/92/93(04-08), 328i/xi.
- E90/91/92/93(04-08), 330i/xi. E90/91/92/93(04-08), 335i/xi.
- E90/91/92/93(04-08), 523i/Li/xi. E60/61(04-08), 525i/Li/xi.
- E60/61(04-08), 528i/Li/xi. E60/61(06-08), 530i/Li/xi.
- E60/61(05-08), 535i/xi. E60/61(06-08), 630i.
- E63/64(04-08), 730i/Li. E65/66(04-08), X3 2.5/3.0.
- E83(06-08), X5 3.0. E70(06-08), Z4 2.5/3.0.
- E85/86(05-08)
- Engines: N51/N52/N52K Valvertronic, Direct Injection, Non-Valvetronic N53/N54

AL010085

BMW (N42 , N46) CAMSHAFT ALIGNMENT TOÓL

· Special design to fix the camshaft in TDC engine. Applicable : BMW N42 , N46

AL010080

BMW (N43) TIMING TOOL KIT



ENGINE / UNDERCAR SERVICE TOOLS FOR BMW

BMW









ENGINE TIMING TOOL SET FOR PROFESSIONAL ENGINE REPAIR FOR BMW DIESEL ENGINES M41/M51/M47 TU AL010099 M47 TU/T2, M57/TU/ T2:2.01/3.01; YEAR1998-2008

- Installation and removal of the camshaft / hydraulic chain tensioner
- · Checking and adjustment of camshaft timing
- · Easily accessible operating instructions including cross references to original
- part numbers Spare parts optionally available
- Clear arrangement of tools in high-quality plastic case with soft foam insert

E83:

E53/E70:

- 318tds/318tds Compact E36:
- Bj. 94-00/ 325td/ tds Bj.91-99
- E34/E39: 525td/tds Bj. 91-03
- 725tds Bj. 91-03 M47/M47TU/T2/M57TU/T2 E90/E91: 316i, 316ti, 318ci, 318ti, 320i E38: E87: 118d/ 120d
- 318d/ 318td Compact/ 320td E46:
- Compact/ 320d/ 330d
- E39: 520d/ 525d/ 530d
- E60/E61: 525d/ 530d/ 535d
- E63: 635d

Land Rover: 2.5DT Bj. 1994-2002 Land Rover: 3.0TD6 Bj. 2002-2006 Freelander. 2.0TD4 Bj. 2002-2006

X3, 2.01d/ 3.01d

X5, 3.01d

E38/E65/E66: 730d



VW, BMW SOCKET AN050014 (1/2"DR., 12 POINT, 21MM)

- For installing model and removing the front strut units on VW-GOLF II and JETTA since model 1987, GOLF III and VENTO since model 1993, PASSAT since 1988 and some Porsche.
- For loosing shock absorbers bolt on BMW E38, E39, E46, E52, E53, E60, E61,
- E63, E64, E65, E66, E83, E85, E86, E87, E90, E91, E92, E93, R50, R52, R53 • Drive 12.5=1/2"
- Chrome- Vanadium • Surface chrome- plated
- N.W.: 0.142 KGS



AE310178 BMW BALL JOINT PULLER (27&31MM)

- For quick and easy separate ball joint connections.
 AE310178-6 is particularly useful for control arms from steering knuckle. Special for E53, E83
- Applicable: BMW E38, E39, E52, E53, E60, E61, E70, E83, E90, E91, E92, R50, R52, R53, RR1, RR2, X5, W211








TOOLS

& AUDI REPAIR

VOLKSWAGEN

232



- Extra applicable: Alfa Romeo , Fiat , Citroen , Peugeot , Renault , Volkswagen A.Crankshaft locking pin
- B.Camshaft adjusting tool: 3/8" DR Nut. C.Tensioner retaining pins / 0.8mm,1.2mm,1.4mm,1.5mm,1.8mm,1.9mm D.Camshaft locking tools (Pair)

















AL010054

ENGINE TIMING TOOLS - VW & AUDI

• THIS NEW KIT OF TWELVE TOOLS IS REQUIRED FOR PETROL & DIESEL ENGINE SERVICE.

• INCLUDING TIMING BELT REPLACEMENT ON RECENT MODELS AND ALSO OLDER 1.9D MODELS FROM 1976.

• MODELS: AUDI A4, A6, A8, A11 YOAD (97-04), VW PASSAT (98-04).

AL010086

TIMING TOOL SET FOR VW AND AUDI FSI 2.0 LITRES / TURBO

• With camshaft tools , chain tensioner retainer, locking pins and tensioner bolt • For 2.0 FSI petrol engines since 2003 in : AUDI A3 2.0 FSI and FSI SOHC engines codes AWA , BHD , BMB VW GOLF 2.0 FSI and 2.0 FSI SOHC and Touran 2.0 FSI SOHC engine codes AWA [•] AXW OEM CODE DESCRIPION • T10250 CAMSHAFT CLAMP • T10020 PIN WRENCH T10092 TENSIONING BOLT • T40011 LOCKING PIN

 T10060A LOCKING PIN • 3366 CHAIN TENSIONER RETAINER

AI010069

VW CRANKSHAFT LOCKING SET

• Used to retain and lock the camshaft timing when replacing the timing belt or servicing engine parts.

• Suits VOLKSWAGEN BORA, GOLF, LUPO and POLO TDI'S.

AI010069A

CRANKSHAFT LOCKING TOOL

• For 2.0 Liter VOLKSWAGEN AUDI Engines-non Bored Out Engines.

AI010100B

VW AUDI TIMING PULLEY PULLER

• DIA. SPREAD:50-95MM

JONNESWAY.



234



VW, AUDI WATER PUMP PULLEY AI050067 LOCKING WRENCH

• Safe locking of the water-pump pulley. Easily loosing the stubborn bolts on the water-pump pulley.Over length : 298mm, width : 65mm

Applicable : VW, AUDI.

AI050090

TIMING ADJUSTABLE TOOL

Use for :

• VW : LUPO, POLO/CLASSIC, GOLF, BORA & CADDY. • ADUI : A2

AI050105 WINDSHIELD WIPER PULLER

The Wiper Puller is specially designed for use to remove the rear wiper arms with water jets included in the spindle of motorcars. For use with SKODA, AUDI, SEAT, VW and other.

• Always loosen the nut from the wiper arm BUT never totally remove the nut. • Removal of the nut may cause damage to the plastic arm of metal ferrule (where fitted).

· Locate the hole of the bolt over the spindle.

• Place the jaws of the tool under the wiper arm at the base of the spindle. Tighten with fingers first,

• Use 3/8" drive ratchet to 'dis-engage' arm from spindle.

· Lubrication maybe required.

VOLVO REPAIR TOOLS



Parts N AL01011 AL01011 AL01011 AL01011 AL01011 AL01011 AL01011

LAND ROVER , JAGUAR, VOLVO(T6) CAMSHAFT ALIGNMENT TOOL KIT AL010110

Special designed to align the engine camshaft and crankshaft position, and correct into the side cover.
Application: Land Rover, Jaguar, VOLVO S80, XC90, XC60, XC70 3.0T, 3.2 (T6 Engine) since 2007

s No.	Description	OEM no.	Q'ty
0110-1	CRANKSHAFT WRENCH	9997257	1
0110-2	CAMSHAFT ALIGNMENT TOOL	9997261	1
0110-3	COVER INSTALLER/ REMOVER	9997263	1
0110-4	COVER INSTALLER/ REMOVER	9997264	1
0110-5	1/2" Dr. T60 STAR SOCKET	9997272	1
0110-6	MOUNTING	9997271	1
0110-7	ENGINE COVER ALIGNMENT TOOL	9997266	1
0110-8	ENGINE COVER ALIGNMENT TOOL	9997267	1



TRUCK SERVICE TOOLS

JONNESWAY -





• The rear axles cover extractor socket • Size : 120mm, octagon. Applicable : BPW-16T





Inner:ø22mm Outer:ø28mm

JONNESWAY.

BPW TRUCK SOCKET TOOL (REAR WHEEL) AN040056

MAN (422,403), BENZ TRUCK DIESEL INJECTION VALVE SOCKET

The tool to remove and install diesel injection valve. Application : MAN (422.403) BENZ Truck, SCANIA



SAFETY INSTRUCTION

Jonnesway pneumatic tools aim to provide customer the industrial safety, excellent performance, vibration deduction and friendly services.

The following safety instructions cover all possible or conceivable conditions which may occur during operations. Before operating, please read the following safety instructions to avoid unnecessary hazards.

A. Wearing Protection Masks

Always wearing protection masks (such as safety goggle, ear mu and hand glove...etc) while operation pneumatic tools to avoid damage.

B. Avoid Damage Caused from Vibration or Repetitive Work Motion

Prolonged exposure to vibration or repetitive work motion may be harmful. If you feel tingling, numbness, discomfort or pain, please stop using tool and consult to a physician. Employees and operators should always follow the instructions as below:

- 1. Use hand grips with proper control to save energy while operating.
- 2. Keep your wrists as straight as possible.
- 3. Avoid very repetitive movements of the hands and wrists.
- 4. Keep hands and body warm and dry.
- 5. Avoid continuous vibration exposure.

C. Avoid Hazards from Compressed Air

Air under pressure can cause injury. Please aware the safety instructions as follows to ensure you a safer working environment.

- 1. Do not point the air hose at yourself or others. Always direct exhaust air away from yourself and others in the work area
- 2. Before operating, always check for damaged or loose hoses and fittings.
- 3. Always disconnect the tool with air compressor when not in use, before changing accessories, setting the torque. Or when making repairs.
- 4. Always keep air pressure in proper rate. Exceeding rated air pressure may shorten tool's life.
- 5. Do not connect air tools with electric power sources.
- 6. When using universal twist couplings, lock pins should always be installed to avoid accidental hose disconnection.


D. Avoid Additional Hazards

- 1. Slip, Trip, Fall is the major cause of injury and death! Beware of excess hose/cord left on the walking or work surface.
- 2. Operators and maintenance personnel must be physically fit to perform job tasks, and handle the bulk, weight and power of the tool. Debarring tools should be used to reduce risk of cuts and abrasions due to burrs.

WARNING!

- 1. Always stay cautious when using hand tools, and keep them away from children. Protective eyeware is recommended at all times.
- 2. Always unplug or disconnect the power source of any appliance or equipment before working on or near conductive surface as severe electrical shock may occur.
- 3. Select correct types and sizes of hand tool for the job purposes.

CAUTION:



The Air Tools Operation Manual and Six Basic Maintenance Elements

- 1. Through the tools' air inlet of air pressure, (not from the air pressure of air compressors the regular is 90PSI (6.2kg/cm2) which if it is too high ot too low will damage the tools' function and lifetime. Air inlet must have enough lubricating oil (oil#32~#46). In order to help the motor inside the air tool to get the enough lubrication. (Place the blank paper outside the air exhaust to see, it is the normal it there is the greasy dirt which means there is enough oil.) The air inlet must not contain the water. It will not be appropriate if the compressor not dry though the compressed air dryer.
- 2. Do not disassemble the tools' parts for operation, it will damage the tols and also affect the safety for the operator.
- checked immediately.
- 4. Regular checking (approximately once a week), maintain the tools add the grease to the rotating parts and add the lubricating oil (oil #32~#46) to the motor of the air tools are all necessary to assure the performance.
- 5. Using the tools must follow the safety regulations and its operation manual.
- 6. It is important to choose the right and appropriate tols to operate since if the tool is high power will easy to cause the damage of workplace and if the tool is low power will easy to cause the damage of tools.

JONNESVAY



Do not use hand sockets, universal ioint or other manual tools with air tools.



It is improper to use hammer or pipe to increase the torque on wrenches, torque wrenches, and ratchet handles.



Do not use screwdrivers as pry bar, punch or chisel.

3. Even the tools has small damage or not meet the original functions after using, it is not appropriate to continue use it which it has to be

	JONNESWAY.	INDEX	INDEX	JONNESWAY®
Delect 2 2 J. Telles 4 Delect 3 4 Delect 3 1 Delect 3 Delect 3	AB010001 201 AE310048 180 AG010207 212 AI020113 217	AL010025-5 230 AN010227 203 C-A8 34	D71P1150 112 DV13S5125 110 H08MT109S 122 JAG-0913R	148 JAT-6004K 160 M61125 127 P098 97
b b< b b b	AB010002 201 AE310049 180 AG010217 214 AI020125 194	AL010025A 228 AN020007 207 C-DBU3 34		148 JAT-6673B 159 M62102 127 P106 97
Section Ref All Market Ref Ref Ref Ref <th< td=""><td></td><td></td><td></td><td></td></th<>				
Aberbale 22 Aborde 10 Aborde 30 Aborde 30 Aborde 30 <th< td=""><td></td><td></td><td></td><td></td></th<>				
extender site Autors Autors Autors Autors Autors Autors Autors Autors				
Here Lag Lag <thlag< th=""> <thlag< th=""></thlag<></thlag<>				
Normal Cond Cond <thcond< th=""> Cond Cond <th< td=""><td>AB030038A 202 AE310095 180 AI010030 186 AI030010 195</td><td>AL010033 232 AN040074 222 D04P2100 115</td><td>D71P2250 112 H01SM209S 120 H10MB2100 123 JAG-6638</td><td>151 JAT-6959A 161 M63103 127 P2010SA 106</td></th<></thcond<>	AB030038A 202 AE310095 180 AI010030 186 AI030010 195	AL010033 232 AN040074 222 D04P2100 115	D71P2250 112 H01SM209S 120 H10MB2100 123 JAG-6638	151 JAT-6959A 161 M63103 127 P2010SA 106
A.S.B.C. 2 A.B.B.C. 2 A.B.B.C. 2 A.B.B.B. 2.2 A.B.B.B.B. 2.2 A.B.B.B.B. 2.2 A.B.B.B.B. 2.2 A.B.B.B.B				
Der Core 18. Carrolar Carrolar <				
Acc. 2010 154 AUBUSA 155 AUBUSA 156 AUBUSA 166 AUBUSA 166 AUBUSA 166 <				
Actional 10				
Altender Dis Altender Dis Altender Dis Dis </td <td></td> <td></td> <td></td> <td></td>				
All. Controls 11 All. Controls 12 All. Controls 23 All. Controls 24 All. Controls 24 All. Controls 24 All. Controls 24 All. Controls 23 All. Controls 24 All. Controls 23 All. Controls 24	AE030002 170 AE310178 230 AI010062 188 AI040017 197	AL010058 219 AN500001SV 10 D04S480 115	D71PP08SP 26 H03SA209S 119 H10MT08SP 31 JA-HVLP-40	
4 5 0				
Additional 121 Additional 22 Additional 22 Additional 22 Additional 23 Additi				
ALCHOME 127 ALCHOME 128				
Additional 16 Outrol 2:16 Additional 21 Additional 21 Additional 21 Microl 1:2 Microl 1:2 Microl 1:2 Micro 1:2 <td></td> <td></td> <td></td> <td></td>				
Actionals 12 Actionals 131 Autonals 131 Autonals 131 Autonals 135 A				
ALEJOND 124 ALEJOND 124 ALEJOND 124 MURANDE 123 MURANDE 124 MURANDE MURANDE		AL010076 219 AR020060 182 D3750T08S 116		
Accordia 112 Accordia 113 Maccordia 114 Outliss for 1 Parameters Pa				
Accompo 11 Accompo 12 Accompo 12 Accompo 13 Accompo 14 Distance 10 Dist				
Absolute 113 Autopano 124 Au				
Ar-2007 Y-17 AURONO 104 AURO				
Ac300187 J.3 Ac300188 J.9 AL00103 Z28 ARPANDE J.14 DTSR150 J.14				
AF300187 17.3 APDICADD 10.4 APDICAD				
A ABOINS 14 ADDIONS 14 DTISSO 11 DTISSO 11 DTISSO 12 MADBIONS 12 MADBIO				
A ABJ0002 14 ADJ0022 14 ADJ0022 12 AMC6001 23 AMC0001 20 AMC6001 23 AMC6001 20 AMC6001 20 AMC6001 20 AMC601				
A 620020 124 AC0020879 26 Alores 117 AND/0028 12 AND/0028 13 MOS/002 13 MOS/002 13 MOS/002 13 MOS/002 14 D1110 13 HOS/0028 14 HOS/0028 14 HOS/0028 14 HOS/0028 14 HOS/0028 14 <td></td> <td></td> <td></td> <td></td>				
AC310001 175 AC010032 211 AV020034 191 AV020034 201 AV020035 185 DPT11075 113 HOBM11085 122 JA-B3004 134 MU7016 125 MU7016 126 PA338 107 AE31000 17 AG010037 211 AI00043 211 AI001044 211 AI001044 211 AI00104 211 AI001044 211 AI001045 211 AI001045 211 AI001045 211 AI001045 21				
AE310001 175 AC6010033 211 AU200205 191 AU50080 200 AU50081 200 AU50081 200 AU50081 200 AU50081 200 AU50081 210 AU50081 211 AU50081 AU50081 AU50081 AU50081 <td>AE300213 174 AG010030A 210 AI020027 195 AI050070 217</td> <td>AN010012A 206 AR060032 185 D70S6150 114</td> <td>D71T10 113 H05SM280 121 JA-23S 168 JAR-6309A</td> <td>143 M06040 126 MTC408 129 P4314 107</td>	AE300213 174 AG010030A 210 AI020027 195 AI050070 217	AN010012A 206 AR060032 185 D70S6150 114	D71T10 113 H05SM280 121 JA-23S 168 JAR-6309A	143 M06040 126 MTC408 129 P4314 107
A E310005 175 A OB10034 211 AU20037 191 A DB5008 225 A N01004 205 A OP0025 218 A OB10035 211 A AB20003 121 A AB2003 123 AB2003 121 A AB2003 121 A AB2003 121 A AB2003 121 A AB2003 123 AB2003 121 A AB2003 121 A AB2003 123 AB2003 121 A AB2003 121 A AB2003 123 AB2003 121 A AB2003 123 AB2003 121 AB2003 123 AB2003 121 AB2003 123 AB2003 121 AB2003 123 AB2033 121 AB2033 123 AB2033 121 AB20333 123 AB20333				
AE310006 175 A6010035 211 A102004 191 A105008 226 A50406 230 7058200 114 D7172 113 H065115 121 JA-6111 165 JA-6312 144 M003024 125 M111105 128 P4336 107 AE31000 176 A60100384 214 A0030044 217 AN01064 207 C-30H20 33 D7059250 114 D7172 113 H065115 121 JA-6111 146 AM64303 26 M111105 128 P524104 102 A6310011 176 A00100384 212 A0020042 191 A0030080 20 C-30H220 33 D7059250 114 D71730 113 H065110 121 JA-611 45 M080030 26 M111105 138 H06516 121 JA-611 45 M080037 20 M11105 138 H06516 121 JA-611 45 M680037 20 M11105 138 H06516 121 JA-611 45 M520037 20 M11105 <				
A E310008 176 A 6021003 210 A 1000064 217 A 1001064 207 C-30H23 33 D70S9200 114 D71125 113 H06S120 121 A AB-3012 144 M08032 125 MTM1075 128 P5M10A 103 AC310013 176 AG010038 121 AU20043 139 AU00069 25 AU10006 207 C-30H262 33 D70S920 114 D71130 113 H06S120 121 JAB-2051 164 JAS-4019 157 M08030 128 P1M107 138 P5514 107 AC310017 177 AG010047 213 AU020042 192 AU010072 206 C-5DW1 113 P0115 13 H06S160 121 JAD-1015 15 JAS-107 H101 210 P0185 28 P5514 107 AC310018 177 AG010047 213 AU02072 206 C-5DW14 13 P0151 13 H06S160 121 JAD-1015 15 JAS-107 H114 JAS-207 H14 JAS-265				
AE310010 176 AG010038A. 212 AN020042 191 AN050085 218 AN010064 207 C-3DH262 33 D'15N05 113 D'1170 113 H065125 121 JAB-2051 146 JAB-3033 144 MM05085 26 PUI110 128 PSMI11 103 AE310013 177 AG010041 13 AN020047 190 AN05009 220 AN01007 206 C-5DW1 16 D'1TM0 113 H065130 121 JAB-703 146 JAS-1033 C PUI17 98 P54M10 103 AE310015 177 AG010042 213 AN020051 192 AN010072 206 C-5DM1 16 D'15N0 113 D'115 113 H065150 121 JAD-1051 145 JAS-1033-6H155 M03107 20 P5538 107 AE310024 178 AG010048 214 AN0200551 123 JAD-1021 JA JAS-1024 JA JAS-1024 JA JAS-1024 JA JAS-1024 JA JAS-534-6H54 MU1010 20 </td <td></td> <td></td> <td></td> <td></td>				
A E310013 177 A GRU1041 213 A DR20049 190 A DR20049 200 A N010070 204 C-SDW11 16 D71500 113 D71140 113 H06S140 121 JAB-7023 146 JAB-7003 157 M09500 126 P018 98 P5514 107 AE310015N 177 AG010042 212 Al020051 192 Al050093 200 AN010072 206 C-SDW1 19 D71500 113 D71150 113 H06S150 121 JAD-1021 144 JAS-1207-PHE354 M10102 20 P0185P 25 P5518 107 AE310024 178 AG010042 214 Al020051 192 Al051017 20 C-SDW1 17 D715N0 113 D71150 113 H06S120 121 JAD-1021 144 JAS-6542 157 M10108 126 P048 99 P5602 101 AE310025 178 AG010055 29 Al020054 193 Al050137 218 Al010072 20 C-7DW13 8 D				
AE310015N 177 AG010042 212 AI02005 190 AI050093 200 AN010072 206 C-5DW108 113 D71T45 113 H065150 121 JAD-1015 145 JAS-1033-6HE55 M09513SP 26 P018SP 25 P5536 107 AE310023 178 AG010048 214 Al020051 192 Al050102 206 C-6DA4 32 D71TN0 113 H065160 121 JAD-1021 144 JAS-2033-6HE154 M10101 210 P018SP1 25 P5536 107 AE310023 178 AG010055 29 Al020051 193 Al050109 193 Al01008 206 C-7DW136 18 D71TN1 113 H0652100 121 JAD-6246 145 JAS-6652 157 M11055 126 P046 99 P6006 99 A6010057 20 Al020061 133 Al020061 133 H065220 121 JAD-6246 145 JAS-6660 157				
AE310018 17 AG010047 213 A1020051 192 A105006 200 AN0100722 206 C-6DA4 32 D715N0 113 H06S160 121 JAD-1015K 145 JAS-1207-6HE154 M1010 210 P018SP1 25 P5536 107 AE310022 178 AG01048 214 A020053 192 A050107 206 C-7DW13 13 D715N1 113 H06S100 121 JAD-1021 144 JAS-634-6HE154 M104108 20 P028 98 P5602 101 AE310025 178 AG010055 209 A1020054 133 A0010072 206 C-7DW136 18 D715N11 113 D7117 113 H06S2105 121 JAD-6245 157 M11045 126 P066 99 P6006 99 A6310026 178 AG010087 21 JAD-6245 145 JAS-660-3 157 M11055 126 P066A 99 P6006 99 A6310026 178 AG010087 21 JAD-6245K 145 JAS-660-3 157				
AE310022 178 AG01048 214 Al02052 192 Al050104 200 AN010072B 206 C-6DA6 32 D715N0 113 D051D5 121 JAD-1021 144 JAS-1208-5HE54 M1021DB 210 P028 98 P5602 101 AE310023 178 AG010045 214 Al020055 109 Al050105 206 C-7DW130 17 D715N0 113 H065205 120 JAD-6233 144 JAS-6534-4HE54 M1041D8 210 P038 99 P5603 101 AE310025 178 AG010055 209 Al020561 193 Al050137 218 AN010092 205 C-7DW191V 8 D715N1 113 H065210 121 JAD-6246 145 JAS-6603 157 M1105 126 P06A 99 P6006 99 A6310027 178 A6010092 123 Al020641 JAS JAS-6603 157 M1105 126 P06A 99 P601055P 203 A631002 JAD-6246 JAS JAD-6246 JAS JAS-6607-HE55				
AE310023 178 AG010049 214 Al020053 192 Al050105 235 AN01072 206 C-7DW1 17 D715N10 113 D7176 113 H065209 120 JAD-6233 144 JAS-6534-6HE54 M104108 210 P038 99 P5603 101 AE310025 178 AG010057 209 Al020056 190 Al050102 200 AN010091A 205 C-7DW136 18 D715N11 113 D7177 113 H0652100 121 JAD-6234 144 JAS-6534-6HE54 M104108 210 P046 99 P6606 99 P6606 99 P6006 99 P6006 99 P6006 99 P6006 99 P6006 99 P6006 99 P601059 23 AG010094 214 AJ02064 144 JAS-6604 157 M11045 126 P0648 99 P6006 99 P601059 23 AG310025 134 AJ02064 144 JAS-6604 157 M11045 126 P0648 99 P601059 23 <td< td=""><td></td><td></td><td></td><td></td></td<>				
AE310025 178 AG010055A 209 Al020056A 190 Al050112 200 AN10091A 205 C-7DW191V 8 D715N12 113 D71T8 113 H065215 121 JAD-6246 145 JAS-6552 157 M11045 126 P060A 99 P600B 99 AE310027 178 AG010090 212 Al020063 191 Al050137 218 AN010092 205 C-7DW124V 5 D715N14 113 D71T8 113 H065220 121 JAD-6246K 145 JAS-6650 157 M11045 126 P060A 99 P600B 99 AE310027 178 AG010090 213 Al020064 191 Al050102 226 C-7DW7 16 D71FN4 113 D737134SV 20 H065250 121 JAD-6246 145 JAS-6697-6HE55 M60102 127 P0803F 25 P6105 P30 AE310021 180 AG0101182 214 Al02006F 195 Al10015F 226 C-7DW7 16 D71HE5 113 <				
AE310026 178 AG010087 210 Al020061 193 Al050137 218 AN01092 205 C-7DW224V 5 D715N13 113 D7179 113 H06S220 121 JAD-6246K 145 JAS-6600 157 M11055 126 P068 99 P60105SP 23 AE310027 178 AG010099 213 Al020064A 194 Al00005SV 21 AN01012 220 C-7DW5 17 D715N14 113 D7179 113 H06S220 121 JAD-6246K 145 JAS-660-3 157 M1105 126 P068 99 P6010SSP 23 AE31002 180 AG01011 213 Al020065 155 Al01012 220 C-7DW9 16 D71H82 113 DR0253S 117 H06S20 121 JAG-8660-3 157 M1105 126 P0608 99 P6010S 77 P081FL10SV 11 P6424 107 AE310031 180		AN010085A 206 C-7DW136 18 D715N11 113		
AE310027 178 AG010090A 212 Al02063 191 Al050143 225 AN01019 220 C-7DW5 17 D715N14 113 D737134SV 20 H06S225 121 JAD-6252A 144 JAS-6660-3 157 M11065 126 P068A 99 P60105SP 23 AE310029 180 AG010101 213 Al020064A 194 Al100006SV 21 AN01012 220 C-7DW7 16 D71FL20SV 11 DR0119S 117 H06S230 121 JAG-0806R 150 JAS-6697-5HE15 M60102 127 P0803SP 25 P6210 100 AE310031 180 AG010118A 214 Al02005R 22 AN01012 220 C-7DW551 17 D71HB25 113 DR0253S 117 H06S250 121 JAG-0806R 150 JAS-6698-5HE55 M60104 127 P086 97 P6436 107 AE310032 180 AG010119C 214 Al020075 224 Al01004 203 AN01018 220 C-8DW389V 2 <td< td=""><td></td><td></td><td></td><td></td></td<>				
AE310029 180 AG010099 213 Al020064A 194 Al100006SV 21 AN01012 220 C-7DW7 16 D71FL20SV 11 DR0119S 117 H06S230 121 JAG-6077 150 JAS-6697-5HE155 M60102 127 P0803SP 25 P6210 100 AE310030 180 AG01011 213 Al02006S 195 Al10002SP 28 AN01012 220 C-7DW9 16 D71HB2 113 DR019S 111 H06S240 121 JAG-6097-5HE155 M60103 127 P081FL10SV 11 P6424 107 AE310031 180 AG01011SS 214 Al02002F 28 AN01012 220 C-7DWB53 17 D71HB2 113 DV13P160 110 H06S260 121 JAG-6097-5HE155 M60105 127 P086 97 P6436 107 AE310032 180 AG010132 209 AN01012 222 C-8DW389V 2 D71HB4 113 </td <td></td> <td></td> <td></td> <td></td>				
A 8310030 180 A G010101 213 A 1020065 195 A 110001SP 29 A N010123 220 C-7DW9 16 D71HB2 113 DR0253S 117 H06S240 121 JAG-0806R 150 JAS-6697-6HE155 M60103 127 P081FL10SV 11 P6424 107 A 8310031 180 A G010118X 214 A 1020068 224 A 10000SP 28 A N010124 220 C-7DWB53 17 D71HB25 113 DV13P060 10 H06S250 121 JAG-0806RM 150 JAS-6698-6HE155 M60104 127 P086A 98 P7104 102 A 8310033 180 A G010140 209 A 1000035P 224 A 101004 203 A N010182 222 C-8DW389V 2 D71HB4 113 DV13P180 10 H06S280 121 JAG-0903RK 148 JAT-1010 158 M61110 127 P087A 98 P7602 101 A 8310034 180 A 6010147 214 A 020077 225 A 10100158 205 C-A13 34 D71HB5 <td></td> <td></td> <td></td> <td></td>				
AE310031 180 AG010118A 214 Al020068 224 Al10002SP 28 AN010124 220 C-7DWB53 17 D71HB25 113 DV13P060 110 H06S250 121 JAG-0806RM 150 JAS-6698-5HE55 M60104 127 P086 97 P6436 107 AE310032 180 AG010138 209 Al020074 194 Al10003SP 28 AN010145 205 C-8DW1162V 13 D71HB3 113 DV13P100 110 H06S260 121 JAG-0903RK 148 JAS-6698-6HE55 M60105 127 P086 97 P6436 107 AE310033 180 AG010138 209 Al020075 224 AL010004 203 AN010182 222 C-8DW389V 2 D71HB4 113 DV13P2100 110 H06S280 121 JAG-0903RK 148 JAT-1010 158 M61112 127 P087 97 P7601 101 AE310033 180 AG010147 214 Al020077 225 AL010015 219 AN010185 205 C-A13 34				
AE310033 180 AG010138 209 Al020075 224 AL010004 203 AN010182 222 C-8DW389V 2 D71HB4 113 AE310034 180 AG010140 209 Al020076 224 AL010005 203 AN010183 204 C-A11 34 D71HB5 113 DV13P2100 110 H06S280 121 JAG-0903RK 148 JAT-1010K 158 M61110 127 P087A 98 P7602 101 AE310035 180 AG010147 214 Al020077 225 AL010016 219 AN010185 205 C-A13 34 D71HB6 113 DV13P2100 110 H06SA209S 119 JAG-0903RK 148 JAT-1010K 158 M61113 127 P087A 98 P7602 101 AE310035 180 AG010147 214 Al020077 225 AL010016 219 AN010188 207 C-A3 34 D71HB8 113 DV13S275 110 H07M08SF 122 JAG-0906R 149 JAT-10T24 158 M61116 127 <td< td=""><td></td><td></td><td></td><td></td></td<>				
AE310034 180 AG010140 209 AI020076 224 AL010005 203 AN010183 204 C-A11 34 D71HB5 113 DV13P3150 110 H06SA109S 119 JAG-0903RM 148 JAT-1010K 158 M61112 127 P087A 98 P7602 101 AE310035 180 AG010147 214 AI020077 225 AL010016 219 AN010185 205 C-A13 34 D71HB6 113 DV13P9150 110 H06SA209S 119 JAG-0906F 149 JAT-10T18 158 M61113 127 P088A 97 P7603 101 AE310036 180 AG010150SP 27 AI020103 194 AL010016A 219 AN010188A 207 C-A3 34 D71HB8 113 DV13S275 110 H07M08SF 122 JAG-0906R 149 JAT-10T24 158 M61116 127 P088A 98 P7609 101 AE310037 180 AG010169 213 AI002007 234 AL010020K 226 AN010213 <td></td> <td></td> <td></td> <td></td>				
AE310035 180 AG010147 214 Al020077 225 AL010016 219 AN010185 205 C-A13 34 D71HB6 113 DV13PP07S 110 H06SA209S 119 JAG-0906F 149 JAT-10T18 158 M61113 127 P088 97 P7603 101 AE310036 180 AG010150SP 27 Al020103 194 AL010016A 219 AN010188A 207 C-A3 34 D71HB8 113 DV13S275 110 H07M08SF 122 JAG-0906R 149 JAT-10T24 158 M61116 127 P088A 98 P7609 101 AE310037 180 AG010169 213 Al020107 234 AL010020K 226 AN010213 222 C-A3B 34 D71P060 112 DV13S3100 110 H07M09S 122 JAG-0906RM 149 JAT-10T32 158 M61119 127 P097 97 P7719 100				
AE310036 180 AG010150SP 27 AI020103 194 AL010016A 219 AN010188A 207 C-A3 34 D71HB8 113 DV13S275 110 H07M08SF 122 JAG-0906R 149 JAT-10T24 158 M61116 127 P088A 98 P7609 101 AE310037 180 AG010169 213 AI020107 234 AL010020K 226 AN010213 222 C-A3B 34 D71P060 112 DV13S3100 110 H07M09S 122 JAG-0906RM 149 JAT-10T32 158 M61119 127 P097 97 P7719 100				
AE310037 180 AG010169 213 AI020107 234 AL010020K 226 AN010213 222 C-A3B 34 D71P060 112 DV13S3100 110 H07M09S 122 JAG-0906RM 149 JAT-10T32 158 M61119 127 P097 97 P7719 100				



Jonn	JE	SUIAY	®									IND	EX	INDEX										JON		ESW	AY.
P9920A	104	S03A401SP	24	S03A6123	90	S03A6248	91	S03AD6126	92	S04H4109	68	S04H6122	70	S04HD3118	67	S05H4814	72	S07H355	73	S09H305	75	S15H6109	78	S24H8400	79	S68H4118	63
P9920AS	104	S03A4108	88	S03A6124	90	S03A6249	91	S03AD6127	92	S04H4110	68	S04H6123	70	S04HD3119	67	S05H4815	72	S07H360	73	S09H3055	75	S15U43S	78	S27H2	79	S68H4119	63
P9920C	104	S03A4109	88	S03A6125	90	S03A6251	91	S03AD6128	92	S04H4111	68	S04H6124	70	S04HD3120	67	S05H4817	72	S07H4118SP	23	S09H306	75	S16A4506	94	S27H3	79	S68H4120	63
P9920CS	104	S03A4110	88	S03A6126	90	S03A6253	91 01	S03AD6129	92	S04H4112	68	S04H6125	70	S04HD3121	67	S05H4819	72 72	S07H420	73	S09H307	75 75	S16A4508	94 04	S27H4	79	S68H4121	63
PF-20 PF-30	163 163	S03A4111 S03A4111S	88 88	S03A6127 S03A6128	90 90	S03A6254 S03A6256	91 91	S03AD6130 S03AD6131	92 92	S04H4113 S04H4114	68 68	S04H6126 S04H6127	70 70	S04HD3122 S04HD3124	67 67	S05H4821 S05H4916S	72 86	S07H425 S07H427	73 73	S09H308 S09H310	75 75	S16A4510 S16A4512	94 97	S29H2133S S29H4140S	118 118	S68H4122 S68H4123	63 63
PF-40	163	S03A41113	88	S03A6129	90	S03A6257	91	S03AD6131	92	S04H4115	68	S04H6128	70	S04HD4108	68		72	S07H427	73	S09H312	75	S16A4512	94	S29H4140SP	24	S68H4124	63
PH-20	163	S03A4113	88	S03A6130	90	S03A6259	91	S03AD6133	92	S04H4116	68	S04H6129	70	S04HD4109	68	S05HD2106	72	S07H4320	73	S09H314	75	S16A4516	94	S40H108	80	S68H4125	63
PH-30	163	S03A4114	88	S03A6131	90	S03A6260	91	S03AD6134	92	S04H4117	68	S04H6130	70	S04HD4110	68		72	S07H4325	73	S09H404	75	S16A4518	94	S40H109	80	S68H4126	63
PH-40	163	S03A4115	88	S03A6132	90	S03A6263	91	S03AD6135	92	S04H4118	68	S04H6132	70	S04HD4111	68		72	S07H4327	73	S09H405	75	S16H1034	78	S40H110	80	S68H4127	63
PM-20	163	S03A4116	88 00	S03A6133	90	S03A6265	91 01	S03AD6136	92	S04H4119	68 68	S04H6133	/0 70	S04HD4112	68		72 72	S07H4330	/3	S09H406	75	S16H1234	78 70	S40H111	80	S68H4127S	
PM-30 PM-40	163 163	S03A4117 S03A4118	88 88	S03A6134 S03A6135	90 90	S03A6267 S03A6270	91 91	S03AD6137 S03AD6138	92 92	S04H4120 S04H4121	68 68	S04H6134 S04H6135	70 70	S04HD4113 S04HD4114	68 68	S05HD2110 S05HD2111	72 72	S07H4340 S07H4345	73 73	S09H407 S09H408	75 75	S16H1238 S16H1438		S40H112 S40H113	80 80	S68H4128 S68H4129	63 63
PV018	103	S03A4110 S03A4119	88	S03A6136	90	S03A6A4	92	S03AD6140	92	S04H4122	68	S04H6136	70	S04HD4114 S04HD4115	68		72	S07H4350	73	S09H410	75	S16H302		S40H113	80	S68H4130	63
PV0506	109	S03A4120	88	S03A6137	90	S03A6A8	92	S03AD6141	92	S04H4123	68	S04H6138	70	S04HD4116	68		72	S07H4355	73	S09H4118SP	23	S16H304		S60H4304S	79	S68H4132	63
PV0508	109	S03A4121	88	S03A6138	90	S03A6E04	92	S03AD6142	92	S04H4124	68	S04H6141	70	S04HD4117	68	S06A408S	94	S07H4360	73	S09H412	75	S16H3410	78	S64H4126S	87	S68H52341	.11S64
PV0510	109	S03A4122	88	S03A6139	90	S03A6E06	92	S03AD6143	92	S04H4125	68	S04H6146	70	S04HD4118	68		71	S07H4370	73	S09H414	75	S16H3412	78	S68H2103	62	SF-20	163
PV066	108	S03A4122SP		S03A6140	90	S03A6E07	92	S03AD6146	92	S04H4125S	81	S04H6150	70	S04HD4119	68		71	S07H440	73	S09H416	75	S16H3812	78 70	S68H2104	62	SF-20A	163
PV068 PV086	108 108	S03A4123 S03A4124	88 88	S03A6141 S03A6142	90 90	S03A6E08 S03A6E10	92 92	S03AD6149 S03AD6150	92 92	S04H4125SP S04H4126	30 68	S04H6419 S04H6421	70 70	S04HD4120 S04HD4121	68 68		71 71	S07H445 S07H450	73 73	S09H4304 S09H4305	75 75	S16H403 S17H4116	78 79	S68H21045 S68H2105	62 62	SF-30 SF-30A	163 163
PV087	108	S03A4124	88	S03A6142	90	S03A6E35	92	S03AD0130 S04H2104	52 66	S04H4120	68	S04H6422	70	S04HD4121 S04HD4122	68		71	S07H455	73	S09H4305	75	S17H4110 S17H4121	79	S68H21055		SF-40	163
PV088	108	S03A4126	88	S03A6144	90	S03A6U6	92	S04H21045	66	S04H4128	68	S04H6424	70	S04HD4123	68		71	S07H460	73	S09H4307	75	S17M3116	79	S68H2106	62	SH-20	163
PV106	109	S03A4127	88	S03A6145	90	S03A8226	93	S04H2105	66	S04H4129	68	S04H6426	70	S04HD4124	68	S06H310	71	S07H470	73	S09H4308	75	S17M3121	79	S68H21065	62	SH-20A	163
PV1106	108	S03A4128	88	S03A6146	90	S03A8229	93	S04H21055	66	S04H4130	68	S04H6427	70	S04HD4125	68		87	S07H4932S	87	S09H4310	75	S17M4116	79	S68H2107	62	SH-30	163
PV1118	108	S03A4129	88	S03A6147	90	S03A8235	93	S04H2106	66	S04H4132	68	S04H6429	70	S04HD4126	68		71	S08H206	74	S09H4312	75	S17M4121	79 05	S68H2108		SH-30A	163
PV156 PV2810	109 109	S03A4130	88 00	S03A6148	90	S03A8238	93 02	S04H2107	66 66	S04H4134	68 68	S04H6430 S04H6432	/0 70	S04HD4127	68		71	S08H207	74 74	S09H4314	75 75	S18A4117	95 95	S68H2109	62 62	SH-40 SM-20	163
R0602	109 41	S03A4131 S03A4132	88 88	S03A6149 S03A6150	90 90	S03A8241 S03A8A12	93 93	S04H2108 S04H2109	66 66	S04H4136 S04H4317SP	68 22	S04H6432 S04H6433	70	S04HD4128 S04HD4130	68 68	S06H314 S06H316	71 71	S08H208 S08H208S	74 118	S09H4316 S09H4930S	75 87	S18A4117M S18A4119	95 95	S68H2110 S68H2111	62 62	SM-20 SM-20A	163 163
R0603	41	S03A4208	88	S03A6151	90	S03A8A6	93	S04H2110	66	S04H458S	81	S04H6435	70	S04HD4710	69	S06H318	71	S08H209	74	S10H240	76	S18A4119M	95	S68H2112	62	SM-30	163
R1206	41	S03A4210	88	S03A6152	90	S03A8E04	93	S04H2111	66	S04H4724S	81	S04H6436	70	S04HD4711	69	S06H320	71	S08H210	74	S10H255	76	S18A4121	95	S68H2113	62	SM-30A	163
R2902	40	S03A4211	88	S03A6153	90	S03A8E06	93	S04H2112	66	S04H4908	69	S04H6438	70	S04HD4712	69	S06H410	71	S08H215	74	S10H270	76	S18A4121M	95	S68H2114	62	SM-40	163
R2903	40	S03A4213	88	S03A6154	90	S03A8E07	93	S04H2113	66	S04H4909	69 60	S04H6441	70	S04HD4713	69	S06H411	71	S08H220	74	S10H3100	76	S22H21150	80	S68H3106	62	T094602	38
R2904 R3602	40 40	S03A4214 S03A4216	88 00	S03A6155 S03A6156	90 90	S03A8E08 S03A8E10	93 93	S04H2118S S04H2125S	85 85	S04H4910	69 60	S04H6444	/0 70	S04HD4714 S04HD4715	69 69	S06H412 S06H414	71 71	S08H225 S08H227	74 74	S10H3120	76 76	S22H31200 S22H41375	80 80	S68H31065	62 62	T09682500 T21020F	
R3603		S03A4210 S03A4217	00 88	S03A6156 S03A6157	90 90	S03A8E10 S03A8E12	93 93	S04H2125SP		S04H4911 S04H4912	69 69	S04H6446 S04H6447	70	S04HD4715 S04HD4716	69		71	S08H227 S08H230		S10H340 S10H350	76	S22H41375	80 80	S68H3107 S68H3108	62	T21020P	36 36
R3604	40		88	S03A6158	90	S03A8E13	93	S04H2141S	85	S04H4913	69		70	S04HD4717	69		71	S08H240		S10H355	76	S22H41600	80	S68H3109		T21026N	36
R3702	40	S03A4221	88	S03A6159	90	S03A8U8	93	S04H3106	67	S04H4914	69	S04H6456	70	S04HD4718	69	S06H420	71	S08H2H8S	118	S10H360	76	S22H6500	80	S68H3110	62	T21035F	36
R3703	40	S03A4222	88	S03A6160	90	S03AD4110	89	S04H3107	67	S04H4915	69	S04HD2104		S04HD4719	69		71	S08H310	74	S10H370	76	S23H21130	80	S68H3111	62	T21076F	36
R3704	40	S03A4222SP		S03A6163	90	S03AD4111	89	S04H3108	67	S04H4916	69	S04HD21045		S04HD4720			71	S08H315	74	S10H380	76	S23H31200	80	S68H3112	62	T21250F	36
R3802 R3803	40 40	S03A4224 S03A4226	88 88	S03A6165 S03A6167	90 90	S03AD4111S S03AD4112	89 89	S04H3109 S04H3110	67 67	S04H4917 S04H4918	69 69	S04HD2105 S04HD21055		S04HD4721 S04HD4722	69 69		85 23	S08H320 S08H325	74 74	S11H200 S11H201	76 76	S23H41250 S23H41300	80 80	S68H3113 S68H3114	62 62	T27010N T27030N	37 37
R3803	40 40	S03A4220	88	S03A6107 S03A6170	90 90	S03AD4112 S03AD4113	89	S04H3110 S04H3111	67	S04H4918	69	S04HD21055		S04HD4723			23 73	S08H327	74 74	S11H201 S11H202	76	S23H6450	80 80	S68H3115	62	T27030N	37
R4202	40	S03A4229	88	S03A6217	91	S03AD4114	89	S04H3112	67	S04H4920	69		66	S04HD4724	69		73	S08H330		S11H203	76	S23H6500	80	S68H3116	62	T271000N	37
R4203	40	S03A4230	88	S03A6219	91	S03AD4116	89	S04H3113	67	S04H4921	69	S04HD2108	66	S04HFL36SV	12	S07H208	73	S08H340		S11H300	77	S23H8660	80	S68H3117	62	T271001N	37
R4204	40		88	S03A6221	91	S03AD4117	89	S04H3114	67	S04H4922		S04HD2109		S05A408S	94		73	S08H420		S11H301	77	S24H2100		S68H3118	62	T27100F	37
R4802	41	S03A4A3	89	S03A6222	91	S03AD4119	89	S04H3115	67	S04H4923	69 60			S05H2223S	86		73	S08H425	74	S11H302	77	S24H2150	79 70	S68H3119	62	T27100N	37
R4803 R4804	41 //1	S03A4A6 S03A4E10	89 89	S03A6224 S03A6226	91 91	S03AD4121 S03AD4124	89 89	S04H3116 S04H3117	67 67	S04H4924 S04H4925	69 69	S04HD2111 S04HD2112		S05H3808 S05H3809	72 72		73 73	S08H427 S08H430	74 74	S11H303 S11H304	77 77	S24H250 S24H275	79 79	S68H3120 S68H3121	62 62	T27150F T27200N	37 37
R4902	41	S03A4E10	89	S03A6220	91	S03AD4124 S03AD4303S			67	S04H4925	69	S04HD2112 S04HD2113		S05H3809	72		73	S0811430 S08H440		S12H200	77	S24H275	79	S68H3122	62	T27250F	37
R4903	41	S03A4E4	89	S03A6229	91	S03AD4317		S04H3119	67	S04H4927	69	S04HD3106		S05H3811	72		73	S08H445	74	S12H201	77	S24H3225		S68H3123	62	T27340N	37
R4904	41	S03A4E5	89	S03A6230	91	S03AD4319	95	S04H3120	67	S04H4928	69	S04HD3107	67	S05H3812	72	S07H230	73	S08H450	74	S12H202	77	S24H3300		S68H3124	62	T27500N	37
R5104	41	S03A4E6	89	S03A6232	91	S03AD4321	95	S04H3120S	84	S04H4929	69	S04HD3108		S05H3813		S07H240	73	S08H455	74	S12H203	77	S24H375		S68H4108	63	T27600F	37
R6602	39	S03A4E8	89	S03A6233	91	S03AD6117	92	S04H3121	67	S04H4930	69			S05H3814		S07H310	73	S08H460		S12H300	77	S24H4125		S68H4109		T27750F	37
R6603				S03A6235	91 01	S03AD6118	92	S04H3122	67 67	S04H4932	69	S04HD3110		S05H3815		S07H315	73 72	S08H470		S12H301	77 77	S24H4250		S68H4110	63 62	T27751F	37
R6604 RD01032S	39 117	S03A4U4 S03A6117	89 90	S03A6236 S03A6238	91 91	S03AD6119 S03AD6120	92 92	S04H3124 S04H3125S	67 84	S04H524127S S04H52460S		S04HD3111 S04HD3112		S05H3816 S05H3817	72	S07H320 S07H325	73 73	S09H203 S09H204		S12H302 S12H303	77 77	S24H450 S24H475		S68H4111 S68H4112	63 63	T27800N T30200NS	37 38
RD010323	117	S03A6117	90 90	S03A6240	91	S03AD0120 S03AD6121	92		84	S04H52482S		S04HD3112 S04HD3113		S05H3817	72		73	S09H204		S12H303	77	S24H475	79	S68H4112	63	V1001	105
RD0502	39	S03A6119	90	S03A6241	91	S03AD6122	92	S04H3157SP	30	S04H52494S		S04HD3114		S05H4238SP			73	S09H206		S14H310S	87	S24H6150	79	S68H4114	63	V1002	105
RD0503	39	S03A6120	90	S03A6243	91	S03AD6123	92		84	S04H6119	70	S04HD3115	67	S05H4810	72		73	S09H207		S15H240	78	S24H6200	79	S68H4115	63	V1004	105
RD05H2	39	S03A6121	90	S03A6244	91	S03AD6124	92	S04H3536SP		S04H6121	70	S04HD3116		S05H4812	72		73	S09H303		S15H356	78	S24H6400	79	S68H4116	63	V1310SP	29
RD05H22S	39	S03A6122	90	S03A6246	91	S03AD6125	92	S04H4108	68	S04H6121S	81	S04HD3117	67	S05H4813	72	S07H350	73	S09H304	75	S15H472	78	S24H8200	79	S68H4117	63	V1401	105



V1402	105	W26106	50	W26413PR	51	W26467	51	W43B111	54	W6511012	53	W72132	58
V1501	105	W26107	50	W26414	51	W26468	51	W43B112	54	W6511113	53	W72133	58
V1503	105	W26108	50	W26414PR	51	W26470	51	W43B113	54	W6511315	53	W72134	58
W03112SP	22	W26109	50	W26414S	52	W26470PR	51	W43B114	54	W6511417	53	W72135	58
W230607	46	W26110	50	W26415PR	51	W26FL34SV	12	W43B115	54	W6511618	53	W72136	58
W230809	46	W26111	50	W26416	51	W27AR10	55	W43B116	54	W6511922	53	W72138	58
W230810	46	W26112	50	W26416PR	51	W27AR8	55	W43B117	54	W66107S	45	W72140	58
W231011	46	W26112S	52	W26417	51	W27AS10	55	W43B118	54	W66108	45	W72141	58
W231012	46	W26113	50	W26417PR	51	W27AS12	55	W43B119	54	W66109	45	W72142	58
W23108S	46	W26114	50	W26418PR	51	W27AS15	55	W45107S	43	W66110	45	W72143	58
W23108SP	22	W26114S	52	W26419	51	W27AS18	55	W45108	43	W66111	45	W72144	58
W231113	46	W26115	50	W26419PR	51	W27AS4	55	W45109	43	W66112	45	W72145	58
W231213	46	W26116	50	W26420PR	51	W27AS6	55	W45110	43	W66113	45	W72146	58
W231214	46	W26116S	52	W26421	51	W27AS8	55	W45110S	44	W66114	45	W72147	58
W231415	46	W26116SP	31	W26421PR	51	W27AT10	55	W45111	43	W66115	45	W72148	58
W231617	46	W26117	50	W26422	51	W27AT12	55	W45112	43	W66117	45	W72150	58
W231719	46	W26118	50	W26422PR	51	W27AT15	55	W45112SP	22	W66119	45	W72152	58
W231819	46	W26119	50	W26423PR	51	W27AT4	55	W45113	43	W66207S	45	W72155	58
W231921	46	W26120	50	W26424	51	W27AT6	55	W45114	43	W67104S	46	W72160	58
W231922	46	W26121	50	W26424PR	51	W27AT8	55	W45115	43	W680809	45	W72165	58
W232022	46	W26122	50	W26425	51	W2808	57	W45116	43	W680810	45	W72170	58
W232123	46	W26123	50	W26425PR	51	W2810	57	W45117	43	W681011	45	W72175	58
W232427	46	W26124	50	W26426PR	51	W2812	57	W45117S	44	W681213	45	W72180	58
W233032	46	W26125	50	W26427	51	W2814	57	W45118	43	W681415	45	W72185	58
W240809	47	W26126	50	W26427PR	51	W2818	57	W45119	43	W681618	45	W72190	58
W240810	47	W26126S	52	W26428PR	51	W2824	57	W45121	43	W681719	45	W72195	58
W241011	47	W26127	50	W26429PR	51	W2836	57	W45122	43	W71106	49	W84106	60
W241012	47	W26128	50	W26430	51	W2848R	57	W45123	43	W71107	49	W84107	60
W24106S	47	W26129	50	W26430PR	51	W28A14	57	W45124	43	W71108	49	W84108	60
W241213	47	W26130	50	W26431	51	W28A18	57	W45208S	43	W71109	49	W84108S	60
W241214	47	W26132	50	W26432	51	W28A24	57	W45308SP	22	W71110	49	W84109	60
W241314	47	W26133	50	W26432PR	51	W28A36	57	W45508S	44	W71111	49	W84110	60
W241417	47	W26134	50	W26433	51	W28A48	57	W47108SP	22	W71112	49	W84111	60
W241617	47	W26135	50	W26434	51	W28HD10	56	W47708SP	22	W71113	49	W84112	60
W241719	47	W26136	50	W26434PR	51	W28HD12	56	W51108	44	W71114	49	W84113	60
W241922	47	W26138	50	W26435	51	W28HD14	56	W51109	44	W71115	49	W84114	60
W242123	47	W26141	50	W26436	51	W28HD8	56	W51110	44	W71116	49	W84115	60 60
W242224	47	W26143	50	W26436PR	51	W290608	48	W51111	44	W71117	49	W84116	60 60
W242427	47	W26145	50	W26437	51	W290711	48	W51112	44	W71118	49	W84117	60 60
W243032	47	W26146	50	W26438	51	W291012	48	W51113	44	W71119	49	W84118	60
W243236	47	W26148	50	W26438PR	51	W291418	48	W51114	44	W71120	49	W84119	60 60
W243641	47	W26150	50	W26441	51	W291622	48	W51115	44	W71121	49	W84120	60
W250607	48	W26155	50	W26441PR	51	W292024	48	W51116	44	W71122	49	W84121	60 60
W250809	48	W26160	50	W26443	51	W32206S	47 54	W51117	44	W71123	49	W84122	60 60
W250810	48	W26165 W26170	50 50	W26446 W26446PR	51 51	W43A0607	54 54	W51118 W51119	44	W71124 W71125	49 40	W84123 W84124	60 60
W251011	48				51 51	W43A0809	54 54		44 52	W71125 W71127	49 49		60 60
W251012 W25108S	48	W26406	51 51	W26448	51 51	W43A1011 W43A1012		W53216	52			W84125 W84126	60 60
	48	W26406PR	51 51	W26450	51 51		54 54	W53217	52 52	W71128	49 49		60 60
W251113	48	W26407PR W26408	51 51	W26450PR	51 51	W43A106S	54 24	W53219 W610810		W71130		W84127	60 60
W251213	48			W26452	51 51	W43A107SP	24		53 52	W71132	49 50	W84128	60 60
W251214	48	W26408PR	51 51	W26453	51 51	W43A1213	54 54	W611011	53 52	W721105	58 50	W84129	60 60
W251415	48 48	W26409PR	51 51	W26455 W26455PR	51 51	W43A1214	54 54	W611012	53 52	W721110	58 59	W84130	60 60
W251417 W251617	48 48	W26410	51 52		51 51	W43A1415	54 54	W61106S	53 52	W72122	58 58	W84132	60 61
W251617	48 48	W264108PRS		W26457	51 51	W43A1417	54 54	W611214	53 52	W72123	58 59	W86112S	61
W251819	48 48	W26410PR	51 51	W26459	51 51	W43A1617	54 54	W611315	53 52	W72124	58 50		
W251922	48 48	W26411	51 51	W26460	51 51	W43A1719	54 54	W611417 W611618	53 52	W72125	58 58		
W252022	48 48	W26411PR	51 52	W26460PR	51 51	W43A1819	54 54	W611618	53 52	W72126	58 59		
W252123	48 48	W26411PRS	52 52	W26462	51 51	W43A2022	54 54	W611719 W612224	53 52	W72127	58 58		
W252224	48 48	W26411SA W26412PR	52 51	W26463	51 51	W43B108		W612224	53 52	W72128 W72129	58 59		
W252427	48 48		51 51	W26465PR W26466	51 51	W43B109	54 54	W6510810	53 53		58 59		
W253032	48	W26413	51	WZ0400	51	W43B110	54	W6511011	53	W72130	58		

INDEX

JONNESWAY.

Authorised Agent/Distributor

